FCC/ISED RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.

FOR

Computer

ISSUED TO
Hexagon Metrology, Inc.

250 Circuit Drive North Kingstown RI US 02852



Report No.:	BL-EC2030005-601
EUT Name:	Computer
Model Name:	dCC (Digital Control Center) Wired Jogbox
Brand Name:	HEXAGON
Test Standard:	47 CFR Part 15 Subpart C RSS-Gen (Issue 5, March 2019) RSS-247 (Issue 2, February 2017)
FCC ID:	2AXRK-HEX02DCC
ISED Number:	26848-HEX02DCC
Test Conclusion:	Pass
Test Date:	Feb. 10, 2020 ~ Apr. 13, 2021
Date of Issue:	Apr. 15, 2021

Tested by: Ye Hongji
Date Apr. 15, 2021

Approved by: Wei Yanquan
(Chief Engineer)
Date Apr. 15, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055
TEL: +86-755-66850100, FAX: +86-755-61824271
Email: qc@baluntek.com
www.baluntek.com

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Mar. 16, 2021	Initial Issue
Rev. 02	Apr. 15, 2021	Update test data

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION) 5

1.1 Identification of the Testing Laboratory 5

1.2 Identification of the Responsible Testing Location 5

1.3 Laboratory Condition 5

1.4 Announce 5

2 PRODUCT INFORMATION 6

2.1 Applicant Information 6

2.2 Manufacturer Information 6

2.3 Factory Information 6

2.4 General Description for Equipment under Test (EUT) 6

2.5 Technical Information 7

3 SUMMARY OF TEST RESULTS 9

3.1 Test Standards 9

3.2 Verdict 9

4 GENERAL TEST CONFIGURATIONS 10

4.1 Test Environments 10

4.2 Test Equipment List 10

4.3 Measurement Uncertainty 11

4.4 Description of Test Setup 12

4.4.1 For Antenna Port Test 12

4.4.2 For AC Power Supply Port Test 12

4.4.3 For Radiated Test (Below 30 MHz) 13

4.4.4 For Radiated Test (30 MHz-1 GHz) 13

4.4.5 For Radiated Test (Above 1 GHz) 14

4.5 Measurement Results Explanation Example 15

4.5.1 For conducted test items: 15

4.5.2 For radiated band edges and spurious emission test: 15
5 TEST ITEMS 16
5.1 Antenna Requirements 16
5.1.1 Relevant Standards 16
5.1.2 Antenna Anti-Replacement Construction 16
5.1.3 Antenna Gain 16
5.2 Output Power 17
5.2.1 Test Limit 17
5.2.2 Test Setup 17
5.2.3 Test Procedure 17
5.2.4 Test Result 18
5.3 6dB Bandwidth 19
5.3.1 Limit 19
5.3.2 Test Setup 19
5.3.3 Test Procedure 19
5.3.4 Test Result 19
5.4 Conducted Spurious Emission 20
5.4.1 Limit 20
5.4.2 Test Setup 20
5.4.3 Test Procedure 20
5.4.4 Test Result 21
5.5 Band Edge (Authorized-band band-edge) 22
5.5.1 Limit 22
5.5.2 Test Setup 22
5.5.3 Test Procedure 22
5.5.4 Test Result 23
5.6 Conducted Emission 24
5.6.1 Limit 24
5.6.2 Test Setup 24
5.6.3 Test Procedure 24
5.6.4 Test Result 24
5.7 Radiated Spurious Emission 25

5.7.1 Limit 25
5.7.2 Test Setup 25
5.7.3 Test Procedure 25
5.7.4 Test Result 28
5.8 Band Edge (Restricted-band band-edge) 29
5.8.1 Limit 29
5.8.2 Test Setup 29
5.8.3 Test Procedure 29
5.8.4 Test Result 29
5.9 Power Spectral density (PSD) 30
5.9.1 Limit 30
5.9.2 Test Setup 30
5.9.3 Test Procedure 30
5.9.4 Test Result 30
ANNEX A TEST RESULT 31
A.1 Output Power 31
A.2 Bandwidth 34
A.3 Conducted Spurious Emissions 39
A.4 Band Edge (Authorized-band band-edge) 48
A.5 Conducted Emissions 52
A.6 Radiated Emission 54
A.7 Band Edge (Restricted-band band-edge) 80
A.8 Power Spectral Density (PSD) 84
ANNEX B TEST SETUP PHOTOS 87
ANNEX C EUT EXTERNAL PHOTOS 87
ANNEX D EUT INTERNAL PHOTOS 87

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20℃ to 25℃
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

(1) The test report reference to the report template version v6.4.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

(5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.

(6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Hexagon Metrology, Inc.
Address	250 Circuit Drive North Kingstown RI US 02852

2.2 Manufacturer Information

Manufacturer	Advantech Co., Ltd.
Address	NO.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan

2.3 Factory Information

Factory	Advantech Technology(CHINA) Co., LTD.
Address	NO.600, Hanpu-Road, Kunshan, Jiangsu. China

2.4 General Description for Equipment under Test (EUT)

EUT Type	Computer
Model Name Under Test	dCC (Digital Control Center) Wired Jogbox
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	KSE0516744
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth 4.0 Low Energy (BLE), WIFI 802.11a, 802.11b, 802.11g, 802.11n and 802.11ac

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz f_c = 2412 MHz + (N-1)*5 MHz, where - f_c = “Operating Frequency” in MHz, - N = “Channel Number” with the range from 1 to 11. 802.11n (40 MHz): 2.422 GHz - 2.452 GHz f_c = 2412 MHz + (N-1)*5 MHz, where - f_c = “Operating Frequency” in MHz, - N = “Channel Number” with the range from 3 to 9.
Modulation Type	DSSS, OFDM
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PIFA Antenna
Antenna Gain	3.14 dBi
About the Product	Only the WIFI 802.11b, 802.11g, 802.11n (HT20/40) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM (802.11n-40MHz)	BPSK	13.5/15
	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
6dB Bandwidth	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
3	RSS-Gen (Issue 5, Mar. 2019)	General Requirements for Compliance of Radio Apparatus
4	RSS-247 (Issue 2, February 2017)	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
5	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC PART No.	ISED Part No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	RSS-247, 5.4 (6)	N/A	Pass[Note 1]
2	Output Power	15.247(b)	RSS-247, 5.4 (4)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	RSS-GEN, 6.6; RSS-247, 5.2 (1)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.209; 15.247(d)	RSS-GEN, 8.9; RSS-247, 5.5	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (2)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	RSS-Gen, 7.1.2	N/A	N/A [Note 2]

Note [1]: Please refer to section 5.1.

Note [2]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	10.8 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2020.06.08	2021.06.07
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2020.06.08	2021.06.07
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2020.06.09	2021.06.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2020.06.09	2021.06.08
LISN	SCHWARZBECK	NSLK 8127	8127-687	2020.06.09	2021.06.08
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2020.06.08	2021.06.07
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2020.06.08	2021.06.07
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2020.06.08	2021.06.07
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
Temperature Chamber	AHK	SP20	1412	2020.06.10	2021.06.09
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2021.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2021.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2021.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2020.06.08	2021.06.07
Power Amplifier	OPHIR RF	5225F	1037	2021.02.18	2022.02.17
Power Amplifier	OPHIR RF	5273F	1016	2021.02.18	2022.12.17
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Sound Level Meter	B&K	NL-20	00844023	2020.10.23	2021.10.22
Ear Simulator	B&K	4192-L-001	3038758	2021.01.15	2022.01.14

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Audio analyzer	B&K	UPL 16	100129	2021.02.26	2022.02.25

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.4.2 For AC Power Supply Port Test



(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (d)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed

using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.

2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.

3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a

factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as

described in Section 6.0.

c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding 10log (1/x), where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 6dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

<u>Reference level measurement</u>

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ⩾ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW ⩾ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW ⩾ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle ⩾ 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ⩾ 3 x RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

<u>General Procedure for conducted measurements in restricted bands</u>

a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)

c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).

d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).

e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

E = EIRP – 20log D + 104.8

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

f) Compare the resultant electric field strength level to the applicable limit.

g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 1.

b) VBW ≥ 3 x RBW.

c) Detector = Peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

a) The EUT shall be configured to operate at the maximum achievable duty cycle.

b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

c) RBW = 1 MHz (unless otherwise specified).

d) VBW ≥ 3 x RBW.

e) Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

f) Averaging type = power (i.e., RMS).

1) As an alternative, the detector and averaging type may be set for linear voltage averaging.

2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

g) Sweep time = auto.

h) Perform a trace average of at least 100 traces.

i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is 10 log(1/x), where x is the duty cycle.

2) If linear voltage averaging mode was used in step f), then the applicable correction factor is 20 log(1/x), where x is the duty cycle.

3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz ⩽ RBW ⩽ 100 kHz.

Set the VBW ⩾ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	Duty Cycle	T (ms)	1/T(kHz)
802.11b	0.976	12.320	0.081
802.11g	0.968	2.027	0.493
802.11n-20 MHz	0.973	1.907	0.524
802.11n-40 MHz	0.928	0.904	1.106

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.66	92.47	30	1000	Pass
Middle	20.65	116.14			Pass
High	19.45	88.10			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.86	96.83	30	1000	Pass
Middle	23.98	250.03			Pass
High	19.71	93.54			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.40	109.65	30	1000	Pass
Middle	23.83	241.55			Pass
High	19.53	89.74			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.37	86.50	30	1000	Pass
Middle	21.86	153.46			Pass
High	19.94	98.63			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	16.55	45.19	30	1000	Pass
Middle	16.68	46.56			Pass
High	16.27	42.36			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	14.78	30.06	30	1000	Pass
Middle	18.55	71.61			Pass
High	14.57	28.64			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.21	33.19	30	1000	Pass
Middle	18.65	73.28			Pass
High	14.47	27.99			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	14.29	26.85	30	1000	Pass
Middle	16.66	46.34			Pass
High	14.36	27.29			Pass

E.I.R.P Test Data (For ISED)

802.11b Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	19.69	93.11	36	4	Pass
Middle	19.82	95.94			Pass
High	19.41	87.30			Pass

802.11g Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	17.92	61.94	36	4	Pass
Middle	21.69	147.57			Pass
High	17.71	59.02			Pass

802.11n-20 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	18.35	68.39	36	4	Pass
Middle	21.79	151.01			Pass
High	17.61	57.68			Pass

802.11n-40 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	17.43	55.34	36	4	Pass
Middle	19.80	95.50			Pass
High	17.50	56.23			Pass

A.2 Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	8.110107	12.54162	⩾500
Middle	8.1604	12.88566	⩾500
High	7.659668	12.61918	⩾500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	13.266602	16.91488	⩾500
Middle	15.769775	17.24764	⩾500
High	15.469238	16.84805	⩾500

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	13.867187	17.82643	⩾500
Middle	16.120117	18.19845	⩾500
High	16.02002	17.7766	⩾500

802.11n-40MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	21.41333	35.07616	⩾500
Middle	35.82251	36.54247	⩾500
High	35.121826	35.9981	⩾500

Test plots

6 dB Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



99% Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-51.46	9.17	-10.83	Pass
Middle	-50.06	9.22	-10.78	Pass
High	-49.24	9.50	-10.50	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-50.41	5.62	-14.38	Pass
Middle	-50.35	7.16	-12.84	Pass
High	-49.69	6.59	-14.41	Pass

802.11n-20MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-50.49	5.40	-14.60	Pass
Middle	-50.01	7.26	-12.74	Pass
High	-48.93	4.94	-15.06	Pass

802.11n-40MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-50.57	3.25	-16.75	Pass
Middle	-49.29	5.78	-14.22	Pass
High	-48.74	2.33	-17.67	Pass

Test Plots

802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11b MIDDLE CHANNEL CARRIER LEVEL



802.11b MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11b MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11b HIGH CHANNEL CARRIER LEVEL



802.11b HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11b HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g LOW CHANNEL CARRIER LEVEL



802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g MIDDLE CHANNEL CARRIER LEVEL



802.11g MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g HIGH CHANNEL CARRIER LEVEL



802.11g HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-20 LOW CHANNEL CARRIER LEVEL



802.11n-20 LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-20 LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-20 MIDDLE CHANNEL CARRIER LEVEL



802.11n-20 MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-20 MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-20 HIGH CHANNEL CARRIER LEVEL



802.11n-20 HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-20 HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-40 LOW CHANNEL CARRIER LEVEL



802.11n-40 LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-40 LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-40 MIDDLE CHANNEL CARRIER LEVEL



802.11n-40 MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-40 MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-40 HIGH CHANNEL CARRIER LEVEL



802.11n-40 HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-40 HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

802.11b Mode：

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-45.79	9.17	-10.83	Pass
High Channel	-50.08	9.50	-10.50	Pass

802.11g Mode：

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-34.21	5.62	-14.38	Pass
High Channel	-48.94	6.59	-14.41	Pass

802.11n-20 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-34.40	5.40	-14.60	Pass
High Channel	-46.78	4.94	-15.06	Pass

802.11n-40 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-34.87	3.25	-16.75	Pass
High Channel	-39.25	2.33	-17.67	Pass

Test Plots

802.11b LOW CHANNEL, Carrier level



802.11b LOW CHANNEL, Reference level



802.11b HIGH CHANNEL, Carrier level



802.11b HIGH CHANNEL, Reference level



802.11g LOW CHANNEL, Carrier level



802.11g LOW CHANNEL, Reference level



802.11g HIGH CHANNEL, Carrier level



802.11g HIGH CHANNEL, Reference level



802.11n-20 MHz LOW CHANNEL, Carrier level



802.11n-20 MHz LOW CHANNEL, Reference level



802.11n-20 MHz HIGH CHANNEL, Carrier level



802.11n-20 MHz HIGH CHANNEL, Reference level



802.11n-40 MHz LOW CHANNEL, Carrier level



802.11n-40 MHz LOW CHANNEL, Reference level



802.11n-40 MHz HIGH CHANNEL, Carrier level



802.11n-40 MHz HIGH CHANNEL, Reference level



A.5 Conducted Emissions

Note [1]: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.
Note [2]: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.168	52.33	11.08	65.06	-12.73	Peak	L	Pass
1**	0.168	26.56	11.08	55.06	-28.50	AV	L	Pass
2	0.430	44.21	11.40	57.25	-13.04	Peak	L	Pass
2**	0.430	27.32	11.40	47.25	-19.93	AV	L	Pass
3	1.124	35.80	11.25	56.00	-20.20	Peak	L	Pass
3**	1.124	21.90	11.25	46.00	-24.10	AV	L	Pass
4	9.528	43.64	10.99	60.00	-16.36	Peak	L	Pass
4**	9.528	32.92	10.99	50.00	-17.08	AV	L	Pass
5	16.012	46.66	11.39	60.00	-13.34	Peak	L	Pass
5**	16.012	35.35	11.39	50.00	-14.65	AV	L	Pass
6	25.296	44.74	11.29	60.00	-15.26	Peak	L	Pass
6**	25.296	35.83	11.29	50.00	-14.17	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	40.63	11.16	66.00	-25.37	Peak	N	Pass
1**	0.150	28.88	11.16	56.00	-27.12	AV	N	Pass
2	0.424	44.48	11.40	57.37	-12.89	Peak	N	Pass
2**	0.424	31.88	11.40	47.37	-15.49	AV	N	Pass
3	1.104	37.83	11.23	56.00	-18.17	Peak	N	Pass
3**	1.104	25.22	11.23	46.00	-20.78	AV	N	Pass
4	9.600	44.24	11.05	60.00	-15.76	Peak	N	Pass
4**	9.600	32.33	11.05	50.00	-17.67	AV	N	Pass
5	16.104	47.78	11.39	60.00	-12.22	Peak	N	Pass
5**	16.104	35.16	11.39	50.00	-14.84	AV	N	Pass
6	25.256	46.35	11.25	60.00	-13.65	Peak	N	Pass
6**	25.256	35.82	11.25	50.00	-14.18	AV	N	Pass

A.6 Radiated Emission

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz，According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note [4]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Test Data and Plots

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	42.367	29.03	-24.53	40.0	-10.97	Peak	294.00	100	Vertical	Pass
2	151.735	30.53	-28.67	43.5	-12.97	Peak	232.00	100	Vertical	Pass
3	321.970	34.59	-23.16	46.0	-11.41	Peak	10.00	200	Vertical	Pass
4	386.475	36.30	-21.53	46.0	-9.70	Peak	113.00	100	Vertical	Pass
5	515.485	34.91	-18.61	46.0	-11.09	Peak	3.00	100	Vertical	Pass
6	995.878	42.19	-9.63	54.0	-11.81	Peak	274.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	52.068	19.55	-24.21	40.0	-20.45	Peak	82.00	100	Horizontal	Pass
2	151.492	30.92	-28.74	43.5	-12.58	Peak	182.00	200	Horizontal	Pass
3	321.728	36.50	-23.10	46.0	-9.50	Peak	97.00	100	Horizontal	Pass
4	386.718	39.04	-21.54	46.0	-6.96	Peak	230.00	100	Horizontal	Pass
5	515.242	33.09	-18.72	46.0	-12.91	Peak	30.00	200	Horizontal	Pass
6	1000.000	35.77	-9.41	54.0	-18.23	Peak	186.00	200	Horizontal	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

1 GHz to 18 GHz, ANT V 802.11b Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1018.000	39.06	-15.91	74.0	-34.94	Peak	267.00	100	Vertical	Pass
1**	1018.000	23.33	-15.91	54.0	-30.67	AV	267.00	100	Vertical	Pass
2	2412.000	88.84	-11.92	74.0	14.84	Peak	47.00	100	Vertical	N/A
2**	2412.000	82.27	-11.92	54.0	28.27	AV	47.00	100	Vertical	N/A
3	3245.000	42.30	-7.01	74.0	-31.70	Peak	78.00	100	Vertical	Pass
3**	3245.000	31.51	-7.01	54.0	-22.49	AV	78.00	100	Vertical	Pass
4	4745.000	46.94	-5.06	74.0	-27.06	Peak	268.00	100	Vertical	Pass
4**	4745.000	34.69	-5.06	54.0	-19.31	AV	268.00	100	Vertical	Pass
5	10076.500	50.86	1.86	74.0	-23.14	Peak	310.00	100	Vertical	Pass
5**	10076.500	39.90	1.86	54.0	-14.10	AV	310.00	100	Vertical	Pass
6	13844.750	52.65	9.29	74.0	-21.35	Peak	326.00	100	Vertical	Pass
6**	13844.750	41.72	9.29	54.0	-12.28	AV	326.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.000	38.83	-16.21	74.0	-35.17	Peak	237.00	100	Horizontal	Pass
1**	1599.000	23.72	-16.21	54.0	-30.28	AV	237.00	100	Horizontal	Pass
2	2413.000	100.30	-11.74	74.0	26.30	Peak	166.00	100	Horizontal	N/A
2**	2413.000	97.47	-11.74	54.0	43.47	AV	166.00	100	Horizontal	N/A
3	3193.000	47.05	-7.46	74.0	-26.95	Peak	100.00	100	Horizontal	Pass
3**	3193.000	29.89	-7.46	54.0	-24.11	AV	100.00	100	Horizontal	Pass
4	4824.000	53.14	-2.62	74.0	-20.86	Peak	319.00	100	Horizontal	Pass
4**	4824.000	40.14	-2.62	54.0	-13.86	AV	319.00	100	Horizontal	Pass
5	10742.750	49.69	7.03	74.0	-24.31	Peak	340.00	100	Horizontal	Pass
5**	10742.750	38.92	7.03	54.0	-15.08	AV	340.00	100	Horizontal	Pass
6	14581.750	53.04	12.24	74.0	-20.96	Peak	340.00	100	Horizontal	Pass
6**	14581.750	42.93	12.24	54.0	-11.07	AV	340.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.500	41.53	-16.61	74.0	-32.47	Peak	334.00	100	Vertical	Pass
1**	1596.500	28.35	-16.61	54.0	-25.65	AV	334.00	100	Vertical	Pass
2	2438.000	96.26	-12.47	74.0	22.26	Peak	20.00	100	Vertical	N/A
2**	2438.000	93.26	-12.47	54.0	39.26	AV	20.00	100	Vertical	N/A
3	3195.000	52.18	-6.81	74.0	-21.82	Peak	345.00	100	Vertical	Pass
3**	3195.000	34.50	-6.81	54.0	-19.50	AV	345.00	100	Vertical	Pass
4	4874.000	48.95	-2.47	74.0	-25.05	Peak	35.00	100	Vertical	Pass
4**	4874.000	36.22	-2.47	54.0	-17.78	AV	35.00	100	Vertical	Pass
5	5991.000	51.66	-0.28	74.0	-22.34	Peak	115.00	100	Vertical	Pass
5**	5991.000	38.20	-0.28	54.0	-15.80	AV	115.00	100	Vertical	Pass
6	14653.250	51.58	11.71	74.0	-22.42	Peak	119.00	100	Vertical	Pass
6**	14653.250	41.88	11.71	54.0	-12.12	AV	119.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1594.500	40.11	-16.54	74.0	-33.89	Peak	238.00	100	Horizontal	Pass
1**	1594.500	24.20	-16.54	54.0	-29.80	AV	238.00	100	Horizontal	Pass
2	2438.000	99.21	-12.47	74.0	25.21	Peak	209.00	100	Horizontal	N/A
2**	2438.000	96.52	-12.47	54.0	42.52	AV	209.00	100	Horizontal	N/A
3	3249.000	47.78	-7.46	74.0	-26.22	Peak	210.00	100	Horizontal	Pass
3**	3249.000	30.74	-7.46	54.0	-23.26	AV	210.00	100	Horizontal	Pass
4	4874.000	51.19	-2.47	74.0	-22.81	Peak	329.00	100	Horizontal	Pass
4**	4874.000	38.93	-2.47	54.0	-15.07	AV	329.00	100	Horizontal	Pass
5	10847.250	50.12	7.37	74.0	-23.88	Peak	350.00	100	Horizontal	Pass
5**	10847.250	38.93	7.37	54.0	-15.07	AV	350.00	100	Horizontal	Pass
6	17628.750	55.52	15.48	74.0	-18.48	Peak	283.00	100	Horizontal	Pass
6**	17628.750	42.35	15.48	54.0	-11.65	AV	283.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1033.000	37.95	-17.16	74.0	-36.05	Peak	186.00	100	Vertical	Pass
1**	1033.000	31.48	-17.16	54.0	-22.52	AV	186.00	100	Vertical	Pass
2	1604.000	37.24	-16.23	74.0	-36.76	Peak	324.00	100	Vertical	Pass
2**	1604.000	22.95	-16.23	54.0	-31.05	AV	324.00	100	Vertical	Pass
3	2462.000	79.15	-11.62	74.0	5.15	Peak	26.00	100	Vertical	N/A
3**	2462.000	76.65	-11.62	54.0	22.65	AV	26.00	100	Vertical	N/A
4	4392.000	45.10	-3.84	74.0	-28.90	Peak	229.00	100	Vertical	Pass
4**	4392.000	32.76	-3.84	54.0	-21.24	AV	229.00	100	Vertical	Pass
5	6765.000	51.00	2.53	74.0	-23.00	Peak	47.00	100	Vertical	Pass
5**	6765.000	38.36	2.53	54.0	-15.64	AV	47.00	100	Vertical	Pass
6	11878.500	48.46	5.60	74.0	-25.54	Peak	302.00	100	Vertical	Pass
6**	11878.500	38.54	5.60	54.0	-15.46	AV	302.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1911.000	38.34	-14.44	74.0	-35.66	Peak	360.00	100	Horizontal	Pass
1**	1911.000	24.40	-14.44	54.0	-29.60	AV	360.00	100	Horizontal	Pass
2	2462.500	78.32	-11.51	74.0	4.32	Peak	246.00	100	Horizontal	N/A
2**	2462.500	76.14	-11.51	54.0	22.14	AV	246.00	100	Horizontal	N/A
3	4140.000	44.43	-3.66	74.0	-29.57	Peak	113.00	100	Horizontal	Pass
3**	4140.000	33.31	-3.66	54.0	-20.69	AV	113.00	100	Horizontal	Pass
4	6873.000	51.15	2.49	74.0	-22.85	Peak	279.00	100	Horizontal	Pass
4**	6873.000	38.00	2.49	54.0	-16.00	AV	279.00	100	Horizontal	Pass
5	8831.500	46.24	3.25	74.0	-27.76	Peak	228.00	100	Horizontal	Pass
5**	8831.500	37.12	3.25	54.0	-16.88	AV	228.00	100	Horizontal	Pass
6	14458.000	50.40	11.09	74.0	-23.60	Peak	0.00	100	Horizontal	Pass
6**	14458.000	39.71	11.09	54.0	-14.29	AV	0.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1005.500	32.61	-16.77	74.0	-41.39	Peak	0.00	100	Vertical	Pass
1**	1005.500	22.00	-16.77	54.0	-32.00	AV	0.00	100	Vertical	Pass
2	1985.000	39.08	-14.11	74.0	-34.92	Peak	271.00	100	Vertical	Pass
2**	1985.000	24.65	-14.11	54.0	-29.35	AV	271.00	100	Vertical	Pass
3	2412.000	80.74	-11.56	74.0	6.74	Peak	328.00	100	Vertical	N/A
3**	2412.000	74.07	-11.56	54.0	20.07	AV	328.00	100	Vertical	N/A
4	4684.000	46.71	-2.57	74.0	-27.29	Peak	239.00	100	Vertical	Pass
4**	4684.000	34.92	-2.57	54.0	-19.08	AV	239.00	100	Vertical	Pass
5	6587.000	51.49	1.69	74.0	-22.51	Peak	127.00	100	Vertical	Pass
5**	6587.000	39.17	1.69	54.0	-14.83	AV	127.00	100	Vertical	Pass
6	14587.250	51.32	12.38	74.0	-22.68	Peak	229.00	100	Vertical	Pass
6**	14587.250	41.71	12.38	54.0	-12.29	AV	229.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1249.000	36.34	-16.19	74.0	-37.66	Peak	336.00	100	Horizontal	Pass
1**	1249.000	24.17	-16.19	54.0	-29.83	AV	336.00	100	Horizontal	Pass
2	2412.500	77.86	-11.98	74.0	3.86	Peak	228.00	100	Horizontal	N/A
2**	2412.500	71.52	-11.98	54.0	17.52	AV	228.00	100	Horizontal	N/A
3	2479.500	43.96	-11.57	74.0	-30.04	Peak	17.00	100	Horizontal	Pass
3**	2479.500	24.00	-11.57	54.0	-30.00	AV	17.00	100	Horizontal	Pass
4	4725.000	46.40	-2.86	74.0	-27.60	Peak	9.00	100	Horizontal	Pass
4**	4725.000	34.25	-2.86	54.0	-19.75	AV	9.00	100	Horizontal	Pass
5	9931.500	48.47	5.63	74.0	-25.53	Peak	262.00	100	Horizontal	Pass
5**	9931.500	38.64	5.63	54.0	-15.36	AV	262.00	100	Horizontal	Pass
6	14675.250	51.41	11.53	74.0	-22.59	Peak	186.00	100	Horizontal	Pass
6**	14675.250	39.45	11.53	54.0	-14.55	AV	186.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1031.000	38.69	-17.05	74.0	-35.31	Peak	179.00	100	Vertical	Pass
1**	1031.000	32.04	-17.05	54.0	-21.96	AV	179.00	100	Vertical	Pass
2	1441.500	37.69	-16.08	74.0	-36.31	Peak	310.00	100	Vertical	Pass
2**	1441.500	23.06	-16.08	54.0	-30.94	AV	310.00	100	Vertical	Pass
3	2437.000	89.86	-12.23	74.0	15.86	Peak	327.00	100	Vertical	N/A
3**	2437.000	82.93	-12.23	54.0	28.93	AV	327.00	100	Vertical	N/A
4	4745.000	46.52	-2.53	74.0	-27.48	Peak	69.00	100	Vertical	Pass
4**	4745.000	34.94	-2.53	54.0	-19.06	AV	69.00	100	Vertical	Pass
5	9901.250	47.83	5.77	74.0	-26.17	Peak	318.00	100	Vertical	Pass
5**	9901.250	37.26	5.77	54.0	-16.74	AV	318.00	100	Vertical	Pass
6	14606.500	50.97	12.32	74.0	-23.03	Peak	121.00	100	Vertical	Pass
6**	14606.500	39.95	12.32	54.0	-14.05	AV	121.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1378.000	36.71	-16.14	74.0	-37.29	Peak	285.00	100	Horizontal	Pass
1**	1378.000	23.87	-16.14	54.0	-30.13	AV	285.00	100	Horizontal	Pass
2	2437.000	86.70	-12.23	74.0	12.70	Peak	302.00	100	Horizontal	N/A
2**	2437.000	79.67	-12.23	54.0	25.67	AV	302.00	100	Horizontal	N/A
3	3250.000	43.16	-7.20	74.0	-30.84	Peak	214.00	100	Horizontal	Pass
3**	3250.000	30.33	-7.20	54.0	-23.67	AV	214.00	100	Horizontal	Pass
4	5953.000	48.16	0.54	74.0	-25.84	Peak	360.00	100	Horizontal	Pass
4**	5953.000	37.49	0.54	54.0	-16.51	AV	360.00	100	Horizontal	Pass
5	10283.500	47.71	7.21	74.0	-26.29	Peak	8.00	100	Horizontal	Pass
5**	10283.500	38.77	7.21	54.0	-15.23	AV	8.00	100	Horizontal	Pass
6	14581.750	50.42	12.24	74.0	-23.58	Peak	341.00	100	Horizontal	Pass
6**	14581.750	41.70	12.24	54.0	-12.30	AV	341.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1020.000	31.61	-17.21	74.0	-42.39	Peak	289.00	100	Vertical	Pass
1**	1020.000	20.98	-17.21	54.0	-33.02	AV	289.00	100	Vertical	Pass
2	2461.500	83.27	-11.87	74.0	9.27	Peak	333.00	100	Vertical	N/A
2**	2461.500	76.90	-11.87	54.0	22.90	AV	333.00	100	Vertical	N/A
3	4326.000	45.40	-3.72	74.0	-28.60	Peak	303.00	100	Vertical	Pass
3**	4326.000	33.21	-3.72	54.0	-20.79	AV	303.00	100	Vertical	Pass
4	6615.000	50.52	2.65	74.0	-23.48	Peak	28.00	100	Vertical	Pass
4**	6615.000	38.88	2.65	54.0	-15.12	AV	28.00	100	Vertical	Pass
5	11257.000	49.07	6.76	74.0	-24.93	Peak	14.00	100	Vertical	Pass
5**	11257.000	39.44	6.76	54.0	-14.56	AV	14.00	100	Vertical	Pass
6	14590.000	50.24	12.45	74.0	-23.76	Peak	48.00	100	Vertical	Pass
6**	14590.000	40.13	12.45	54.0	-13.87	AV	48.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1025.000	31.15	-17.28	74.0	-42.85	Peak	259.00	100	Horizontal	Pass
1**	1025.000	21.57	-17.28	54.0	-32.43	AV	259.00	100	Horizontal	Pass
2	1591.500	35.92	-16.50	74.0	-38.08	Peak	325.00	100	Horizontal	Pass
2**	1591.500	22.55	-16.50	54.0	-31.45	AV	325.00	100	Horizontal	Pass
3	2461.500	80.49	-11.88	74.0	6.49	Peak	206.00	100	Horizontal	N/A
3**	2461.500	73.54	-11.88	54.0	19.54	AV	206.00	100	Horizontal	N/A
4	5758.000	48.03	-0.47	74.0	-25.97	Peak	184.00	100	Horizontal	Pass
4**	5758.000	36.65	-0.47	54.0	-17.35	AV	184.00	100	Horizontal	Pass
5	9282.500	46.92	3.84	74.0	-27.08	Peak	0.00	100	Horizontal	Pass
5**	9282.500	38.11	3.84	54.0	-15.89	AV	0.00	100	Horizontal	Pass
6	14592.750	50.32	12.45	74.0	-23.68	Peak	310.00	100	Horizontal	Pass
6**	14592.750	39.49	12.45	54.0	-14.51	AV	310.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1020.000	32.70	-17.21	74.0	-41.30	Peak	154.00	100	Vertical	Pass
1**	1020.000	21.76	-17.21	54.0	-32.24	AV	154.00	100	Vertical	Pass
2	2412.500	81.66	-11.84	74.0	7.66	Peak	325.00	100	Vertical	N/A
2**	2412.500	75.18	-11.84	54.0	21.18	AV	325.00	100	Vertical	N/A
3	3028.000	43.09	-7.99	74.0	-30.91	Peak	0.00	100	Vertical	Pass
3**	3028.000	31.71	-7.99	54.0	-22.29	AV	0.00	100	Vertical	Pass
4	4758.000	46.19	-2.80	74.0	-27.81	Peak	324.00	100	Vertical	Pass
4**	4758.000	34.77	-2.80	54.0	-19.23	AV	324.00	100	Vertical	Pass
5	9268.750	47.61	3.55	74.0	-26.39	Peak	360.00	100	Vertical	Pass
5**	9268.750	38.31	3.55	54.0	-15.69	AV	360.00	100	Vertical	Pass
6	14570.750	51.99	11.86	74.0	-22.01	Peak	299.00	100	Vertical	Pass
6**	14570.750	41.91	11.86	54.0	-12.09	AV	299.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1358.500	36.61	-16.00	74.0	-37.39	Peak	246.00	100	Horizontal	Pass
1**	1358.500	23.54	-16.00	54.0	-30.46	AV	246.00	100	Horizontal	Pass
2	2412.500	77.32	-11.84	74.0	3.32	Peak	229.00	100	Horizontal	N/A
2**	2412.500	71.01	-11.84	54.0	17.01	AV	229.00	100	Horizontal	N/A
3	3280.000	43.40	-7.27	74.0	-30.60	Peak	62.00	100	Horizontal	Pass
3**	3280.000	30.16	-7.27	54.0	-23.84	AV	62.00	100	Horizontal	Pass
4	4382.000	45.15	-3.91	74.0	-28.85	Peak	282.00	100	Horizontal	Pass
4**	4382.000	32.92	-3.91	54.0	-21.08	AV	282.00	100	Horizontal	Pass
5	6579.000	51.32	1.55	74.0	-22.68	Peak	299.00	100	Horizontal	Pass
5**	6579.000	39.57	1.55	54.0	-14.43	AV	299.00	100	Horizontal	Pass
6	10528.250	49.21	7.45	74.0	-24.79	Peak	345.00	100	Horizontal	Pass
6**	10528.250	38.13	7.45	54.0	-15.87	AV	345.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1021.500	31.99	-17.04	74.0	-42.01	Peak	132.00	100	Vertical	Pass
1**	1021.500	22.19	-17.04	54.0	-31.81	AV	132.00	100	Vertical	Pass
2	2437.000	85.00	-12.31	74.0	11.00	Peak	330.00	100	Vertical	N/A
2**	2437.000	77.96	-12.31	54.0	23.96	AV	330.00	100	Vertical	N/A
3	3690.000	43.15	-5.39	74.0	-30.85	Peak	83.00	100	Vertical	Pass
3**	3690.000	31.09	-5.39	54.0	-22.91	AV	83.00	100	Vertical	Pass
4	4689.000	46.50	-2.89	74.0	-27.50	Peak	57.00	100	Vertical	Pass
4**	4689.000	34.58	-2.89	54.0	-19.42	AV	57.00	100	Vertical	Pass
5	9310.000	47.34	4.64	74.0	-26.66	Peak	323.00	100	Vertical	Pass
5**	9310.000	38.13	4.64	54.0	-15.87	AV	323.00	100	Vertical	Pass
6	14471.750	52.32	11.53	74.0	-21.68	Peak	138.00	100	Vertical	Pass
6**	14471.750	42.92	11.53	54.0	-11.08	AV	138.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1994.000	39.41	-13.75	74.0	-34.59	Peak	217.00	100	Horizontal	Pass
1**	1994.000	25.28	-13.75	54.0	-28.72	AV	217.00	100	Horizontal	Pass
2	2437.000	80.66	-12.31	74.0	6.66	Peak	200.00	100	Horizontal	N/A
2**	2437.000	73.73	-12.31	54.0	19.73	AV	200.00	100	Horizontal	N/A
3	2479.500	49.10	-11.57	74.0	-24.90	Peak	13.00	100	Horizontal	Pass
3**	2479.500	30.18	-11.57	54.0	-23.82	AV	13.00	100	Horizontal	Pass
4	4710.000	46.63	-3.45	74.0	-27.37	Peak	0.00	100	Horizontal	Pass
4**	4710.000	34.32	-3.45	54.0	-19.68	AV	0.00	100	Horizontal	Pass
5	11399.999	49.63	7.19	74.0	-24.37	Peak	338.00	100	Horizontal	Pass
5**	11399.999	40.46	7.19	54.0	-13.54	AV	338.00	100	Horizontal	Pass
6	14598.250	51.96	12.46	74.0	-22.04	Peak	311.00	100	Horizontal	Pass
6**	14598.250	42.76	12.46	54.0	-11.24	AV	311.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1009.500	32.59	-16.91	74.0	-41.41	Peak	275.00	100	Vertical	Pass
1**	1009.500	21.56	-16.91	54.0	-32.44	AV	275.00	100	Vertical	Pass
2	1776.500	37.51	-15.10	74.0	-36.49	Peak	37.00	100	Vertical	Pass
2**	1776.500	23.42	-15.10	54.0	-30.58	AV	37.00	100	Vertical	Pass
3	2458.000	81.55	-11.79	74.0	7.55	Peak	339.00	100	Vertical	N/A
3**	2458.000	75.37	-11.79	54.0	21.37	AV	339.00	100	Vertical	N/A
4	6594.000	51.25	1.83	74.0	-22.75	Peak	356.00	100	Vertical	Pass
4**	6594.000	39.19	1.83	54.0	-14.81	AV	356.00	100	Vertical	Pass
5	9296.250	48.26	4.32	74.0	-25.74	Peak	282.00	100	Vertical	Pass
5**	9296.250	38.66	4.32	54.0	-15.34	AV	282.00	100	Vertical	Pass
6	14584.500	52.50	12.31	74.0	-21.50	Peak	123.00	100	Vertical	Pass
6**	14584.500	42.45	12.31	54.0	-11.55	AV	123.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1740.000	37.89	-15.71	74.0	-36.11	Peak	351.00	100	Horizontal	Pass
1**	1740.000	23.96	-15.71	54.0	-30.04	AV	351.00	100	Horizontal	Pass
2	2459.000	78.07	-11.79	74.0	4.07	Peak	229.00	100	Horizontal	N/A
2**	2459.000	70.86	-11.79	54.0	16.86	AV	229.00	100	Horizontal	N/A
3	3838.000	43.54	-5.93	74.0	-30.46	Peak	34.00	100	Horizontal	Pass
3**	3838.000	31.21	-5.93	54.0	-22.79	AV	34.00	100	Horizontal	Pass
4	6730.000	50.90	2.19	74.0	-23.10	Peak	149.00	100	Horizontal	Pass
4**	6730.000	39.71	2.19	54.0	-14.29	AV	149.00	100	Horizontal	Pass
5	9307.250	47.32	4.59	74.0	-26.68	Peak	349.00	100	Horizontal	Pass
5**	9307.250	39.79	4.59	54.0	-14.21	AV	349.00	100	Horizontal	Pass
6	16696.500	52.69	12.81	74.0	-21.31	Peak	147.00	100	Horizontal	Pass
6**	16696.500	40.67	12.81	54.0	-13.33	AV	147.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1020.500	30.79	-17.32	74.0	-43.21	Peak	165.00	100	Vertical	Pass
1**	1020.500	21.47	-17.32	54.0	-32.53	AV	165.00	100	Vertical	Pass
2	2422.500	82.79	-12.33	74.0	8.79	Peak	334.00	100	Vertical	N/A
2**	2422.500	75.57	-12.33	54.0	21.57	AV	334.00	100	Vertical	N/A
3	4261.000	44.92	-3.80	74.0	-29.08	Peak	250.00	100	Vertical	Pass
3**	4261.000	32.96	-3.80	54.0	-21.04	AV	250.00	100	Vertical	Pass
4	5063.000	46.83	-2.10	74.0	-27.17	Peak	80.00	100	Vertical	Pass
4**	5063.000	34.83	-2.10	54.0	-19.17	AV	80.00	100	Vertical	Pass
5	9312.750	48.94	4.58	74.0	-25.06	Peak	311.00	100	Vertical	Pass
5**	9312.750	39.02	4.58	54.0	-14.98	AV	311.00	100	Vertical	Pass
6	14631.250	53.30	12.01	74.0	-20.70	Peak	279.00	100	Vertical	Pass
6**	14631.250	42.82	12.01	54.0	-11.18	AV	279.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1267.000	36.23	-16.33	74.0	-37.77	Peak	146.00	100	Horizontal	Pass
1**	1267.000	23.76	-16.33	54.0	-30.24	AV	146.00	100	Horizontal	Pass
2	2422.000	79.31	-12.47	74.0	5.31	Peak	340.00	100	Horizontal	N/A
2**	2422.000	71.92	-12.47	54.0	17.92	AV	340.00	100	Horizontal	N/A
3	4305.000	45.22	-4.02	74.0	-28.78	Peak	233.00	100	Horizontal	Pass
3**	4305.000	33.62	-4.02	54.0	-20.38	AV	233.00	100	Horizontal	Pass
4	6438.000	50.84	1.44	74.0	-23.16	Peak	102.00	100	Horizontal	Pass
4**	6438.000	38.39	1.44	54.0	-15.61	AV	102.00	100	Horizontal	Pass
5	10074.500	49.03	6.47	74.0	-24.97	Peak	61.00	100	Horizontal	Pass
5**	10074.500	37.96	6.47	54.0	-16.04	AV	61.00	100	Horizontal	Pass
6	14141.750	52.87	10.90	74.0	-21.13	Peak	214.00	100	Horizontal	Pass
6**	14141.750	42.67	10.90	54.0	-11.33	AV	214.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1007.000	32.03	-16.60	74.0	-41.97	Peak	232.00	100	Vertical	Pass
1**	1007.000	21.47	-16.60	54.0	-32.53	AV	232.00	100	Vertical	Pass
2	2438.000	82.55	-12.37	74.0	8.55	Peak	331.00	100	Vertical	N/A
2**	2438.000	75.57	-12.37	54.0	21.57	AV	331.00	100	Vertical	N/A
3	3790.000	42.86	-5.92	74.0	-31.14	Peak	184.00	100	Vertical	Pass
3**	3790.000	31.32	-5.92	54.0	-22.68	AV	184.00	100	Vertical	Pass
4	5953.000	47.86	0.54	74.0	-26.14	Peak	195.00	100	Vertical	Pass
4**	5953.000	36.86	0.54	54.0	-17.14	AV	195.00	100	Vertical	Pass
5	10621.750	47.49	7.20	74.0	-26.51	Peak	198.00	100	Vertical	Pass
5**	10621.750	38.65	7.20	54.0	-15.35	AV	198.00	100	Vertical	Pass
6	14636.750	49.76	12.01	74.0	-24.24	Peak	220.00	100	Vertical	Pass
6**	14636.750	36.98	12.01	54.0	-17.02	AV	220.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1161.500	35.28	-16.86	74.0	-38.72	Peak	244.00	100	Horizontal	Pass
1**	1161.500	25.52	-16.86	54.0	-28.48	AV	244.00	100	Horizontal	Pass
2	2056.500	38.69	-14.13	74.0	-35.31	Peak	311.00	100	Horizontal	Pass
2**	2056.500	22.79	-14.13	54.0	-31.21	AV	311.00	100	Horizontal	Pass
3	2438.500	78.61	-12.41	74.0	4.61	Peak	187.00	100	Horizontal	N/A
3**	2438.500	71.07	-12.41	54.0	17.07	AV	187.00	100	Horizontal	N/A
4	4647.000	45.60	-3.20	74.0	-28.40	Peak	105.00	100	Horizontal	Pass
4**	4647.000	33.05	-3.20	54.0	-20.95	AV	105.00	100	Horizontal	Pass
5	9315.500	46.78	4.53	74.0	-27.22	Peak	97.00	100	Horizontal	Pass
5**	9315.500	38.52	4.53	54.0	-15.48	AV	97.00	100	Horizontal	Pass
6	14598.250	48.85	12.46	74.0	-25.15	Peak	154.00	100	Horizontal	Pass
6**	14598.250	37.02	12.46	54.0	-16.98	AV	154.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1022.500	31.56	-17.25	74.0	-42.44	Peak	90.00	100	Vertical	Pass
1**	1022.500	21.20	-17.25	54.0	-32.80	AV	90.00	100	Vertical	Pass
2	2459.500	83.48	-11.67	74.0	9.48	Peak	330.00	100	Vertical	N/A
2**	2459.500	74.11	-11.67	54.0	20.11	AV	330.00	100	Vertical	N/A
3	2901.500	41.80	-9.39	74.0	-32.20	Peak	56.00	100	Vertical	Pass
3**	2901.500	25.23	-9.39	54.0	-28.77	AV	56.00	100	Vertical	Pass
4	4500.000	45.31	-2.74	74.0	-28.69	Peak	295.00	100	Vertical	Pass
4**	4500.000	32.10	-2.74	54.0	-21.90	AV	295.00	100	Vertical	Pass
5	10126.750	47.85	6.46	74.0	-26.15	Peak	306.00	100	Vertical	Pass
5**	10126.750	37.04	6.46	54.0	-16.96	AV	306.00	100	Vertical	Pass
6	14455.250	48.93	11.00	74.0	-25.07	Peak	306.00	100	Vertical	Pass
6**	14455.250	36.90	11.00	54.0	-17.10	AV	306.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 High Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1160.000	35.02	-17.00	74.0	-38.98	Peak	112.00	100	Horizontal	Pass
1**	1160.000	24.38	-17.00	54.0	-29.62	AV	112.00	100	Horizontal	Pass
2	2450.500	79.93	-12.09	74.0	5.93	Peak	205.00	100	Horizontal	N/A
2**	2450.500	72.82	-12.09	54.0	18.82	AV	205.00	100	Horizontal	N/A
3	3482.000	43.40	-6.70	74.0	-30.60	Peak	59.00	100	Horizontal	Pass
3**	3482.000	30.09	-6.70	54.0	-23.91	AV	59.00	100	Horizontal	Pass
4	4929.000	45.43	-2.19	74.0	-28.57	Peak	360.00	100	Horizontal	Pass
4**	4929.000	34.00	-2.19	54.0	-20.00	AV	360.00	100	Horizontal	Pass
5	9315.500	46.89	4.53	74.0	-27.11	Peak	360.00	100	Horizontal	Pass
5**	9315.500	37.28	4.53	54.0	-16.72	AV	360.00	100	Horizontal	Pass
6	14141.750	49.28	10.90	74.0	-24.72	Peak	173.00	100	Horizontal	Pass
6**	14141.750	38.81	10.90	54.0	-15.19	AV	173.00	100	Horizontal	Pass

A.7 Band Edge (Restricted-band band-edge)

Test Data

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
802.11b	Low	2390	52.261	32	74	21.739	PEAK	Pass
		2390	44.968	32	54	9.032	AVERAGE	Pass
	HIGH	2483.5	62.618	32	74	11.382	PEAK	Pass
		2483.5	46.551	32	54	7.449	AVERAGE	Pass
802.11g	Low	2390	62.348	32	74	11.652	PEAK	Pass
		2390	47.411	32	54	6.589	AVERAGE	Pass
	HIGH	2483.5	68.537	32	74	5.463	PEAK	Pass
		2483.5	48.977	32	54	5.023	AVERAGE	Pass
802.11n20	Low	2390	70.792	32	74	3.208	PEAK	Pass
		2390	51.353	32	54	2.647	AVERAGE	Pass
	HIGH	2483.5	67.753	32	74	6.247	PEAK	Pass
		2483.5	47.647	32	54	6.353	AVERAGE	Pass
802.11n40	Low	2390	62.381	32	74	11.619	PEAK	Pass
		2390	46.258	32	54	7.742	AVERAGE	Pass
	HIGH	2483.5	69.918	32	74	4.082	PEAK	Pass
		2483.5	50.270	32	54	3.730	AVERAGE	Pass

Test plots

802.11b Mode：

LOW CHANNEL, PEAK

LOW CHANNEL, AV



HIGH CHANNEL, PEAK

HIGH CHANNEL, AV



802.11g Mode：

LOW CHANNEL, PEAK

LOW CHANNEL, AV



HIGH CHANNEL, PEAK

HIGH CHANNEL, AV



802.11n-20 MHz Mode：

LOW CHANNEL, PEAK

LOW CHANNEL, AV



HIGH CHANNEL, PEAK

HIGH CHANNEL, AV



802.11n-40 MHz Mode：

LOW CHANNEL, PEAK

LOW CHANNEL, AV



HIGH CHANNEL, PEAK

HIGH CHANNEL, AV



A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-5.55	8
Middle	-5.12	8
High	-5.66	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-8.95	8
Middle	-6.44	8
High	-9.50	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-9.78	8
Middle	-7.71	8
High	-10.71	8

802.11n-40 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-13.55	8
Middle	-9.49	8
High	-12.57	8

Test plots

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-EC2030005-AR.pdf”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-EC2030005-AW.pdf”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-EC2030005-AI.pdf”.

--END OF REPORT--