

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-22T0071


Page (105) of (214)

Mode: 802.11ac_HT20
Band: UNII-1
Distance of measurement: 3 meter
Channel: 44

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.75	49.31	Peak	H	-9.44	-	39.87	74.00	34.13
1 005.25	52.71	Peak	V	-9.44	-	43.27	74.00	30.73
1 079.74	51.49	Peak	H	-9.36	-	42.13	74.00	31.87
1 158.23	51.11	Peak	V	-9.28	-	41.83	74.00	32.17
1 191.73	49.93	Peak	H	-9.24	-	40.69	74.00	33.31
1 288.22	51.30	Peak	V	-9.11	-	42.19	74.00	31.81
1 409.21	51.30	Peak	V	-8.96	-	42.34	74.00	31.66

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.


1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: 802.11ac_HT20
 Band: UNII-1
 Distance of measurement: 3 meter
 Channel: 48

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	53.38	Peak	V	-9.44	-	43.94	74.00	30.06
1 080.24	51.58	Peak	H	-9.37	-	42.21	74.00	31.79
1 185.23	51.86	Peak	V	-9.25	-	42.61	74.00	31.39
1 187.73	50.59	Peak	H	-9.25	-	41.34	74.00	32.66
1 288.72	51.27	Peak	V	-9.11		42.16	74.00	31.84
1 386.71	51.42	Peak	V	-8.98		42.44	74.00	31.56

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11an_HT40
 Band: UNII-1
 Distance of measurement: 3 meter
 Channel: 38

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.75	53.02	Peak	V	-9.44	-	43.58	74.00	30.42
1 005.75	49.94	Peak	H	-9.43	-	40.51	74.00	33.49
1 080.74	52.95	Peak	H	-9.36	-	43.59	74.00	30.41
1 183.73	50.18	Peak	V	-9.26	-	40.92	74.00	33.08
1 188.23	50.17	Peak	H	-9.25	-	40.92	74.00	33.08
1 410.71	51.30	Peak	V	-8.96	-	42.34	74.00	31.66

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4 598.15	39.27	Peak	V	5.63	-	44.90	74.00	29.10
5 146.36	44.26	Peak	H	7.94	-	52.20	74.00	21.80



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11an_HT40
Band: UNII-1
Distance of measurement: 3 meter
Channel: 46

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 004.25	52.88	Peak	V	-9.44	-	43.44	74.00	30.56
1 007.75	49.72	Peak	H	-9.44	-	40.28	74.00	33.72
1 080.24	52.26	Peak	H	-9.37	-	42.89	74.00	31.11
1 161.23	51.45	Peak	V	-9.28	-	42.17	74.00	31.83
1 179.73	50.32	Peak	H	-9.26	-	41.06	74.00	32.94
1 288.72	50.90	Peak	V	-9.11	-	41.79	74.00	32.21
1 397.21	50.91	Peak	V	-8.97	-	41.94	74.00	32.06

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5350.87	39.04	Peak	H	7.25	-	46.29	74.00	27.71
5399.98	35.58	Peak	V	7.11	-	42.69	74.00	31.31



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr




Mode: 802.11ac_HT40
 Band: UNII-1
 Distance of measurement: 3 meter
 Channel: 38

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	53.08	Peak	V	-9.44	-	43.64	74.00	30.36
1 000.75	50.10	Peak	H	-9.44	-	40.66	74.00	33.34
1 080.74	51.66	Peak	H	-9.36	-	42.30	74.00	31.70
1 160.23	51.36	Peak	V	-9.28	-	42.08	74.00	31.92
1 286.72	51.89	Peak	V	-9.12	-	42.77	74.00	31.23
1 288.72	50.15	Peak	H	-9.11	-	41.04	74.00	32.96
1 396.71	51.47	Peak	V	-8.97	-	42.50	74.00	31.50

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4634.80	38.96	Peak	V	5.79	-	44.75	74.00	29.25
5148.81	45.45	Peak	H	7.92	-	53.37	74.00	20.63



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11ac_HT40
Band: UNII-1
Distance of measurement: 3 meter
Channel: 46

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.75	52.69	Peak	V	-9.44	-	43.25	74.00	30.75
1 004.25	49.29	Peak	H	-9.44	-	39.85	74.00	34.15
1 080.74	52.01	Peak	H	-9.36	-	42.65	74.00	31.35
1 188.23	51.77	Peak	V	-9.25	-	42.52	74.00	31.48
1 188.73	50.21	Peak	H	-9.25	-	40.96	74.00	33.04
1 286.22	51.91	Peak	V	-9.12	-	42.79	74.00	31.21
1 398.21	51.29	Peak	V	-8.97	-	42.32	74.00	31.68
1 604.19	50.53	Peak	H	-4.89	-	45.64	74.00	28.36

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5351.19	39.45	Peak	H	7.25	-	46.70	74.00	27.30
5360.68	35.82	Peak	V	7.22	-	43.04	74.00	30.96



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11ac_HT80
Band: UNII-1
Distance of measurement: 3 meter
Channel: 42

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	50.11	Peak	H	-9.44	-	40.67	74.00	33.33
1 002.25	53.25	Peak	V	-9.44	-	43.81	74.00	30.19
1 080.24	51.65	Peak	H	-9.37	-	42.28	74.00	31.72
1 182.22	49.74	Peak	H	-9.26	-	40.48	74.00	33.52
1 188.73	51.49	Peak	V	-9.25	-	42.24	74.00	31.76
1 416.71	50.62	Peak	V	-8.96	-	41.66	74.00	32.34

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 149.20	37.80	Peak	H	7.92	-	45.72	74.00	28.28
4 753.53	38.84	Peak	V	6.30	-	45.14	74.00	28.86



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-22T0071


Page (119) of (214)

Mode: 802.11a
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 52

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 001.25	48.89	Peak	H	-9.44	-	39.45	74.00	34.55
1 001.25	52.02	Peak	V	-9.44	-	42.58	74.00	31.42
1 080.74	51.61	Peak	H	-9.36	-	42.25	74.00	31.75
1 162.73	50.96	Peak	V	-9.27	-	41.69	74.00	32.31
1 181.23	49.56	Peak	H	-9.26	-	40.30	74.00	33.70
1 413.71	51.44	Peak	V	-8.96	-	42.48	74.00	31.52
1 545.20	49.10	Peak	V	-5.85	-	43.25	74.00	30.75

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-22T0071


Page (121) of (214)

Mode: 802.11a
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 60

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 000.25	52.67	Peak	V	-9.44	-	43.23	74.00	30.77
1 004.75	49.03	Peak	H	-9.44	-	39.59	74.00	34.41
1 080.24	52.27	Peak	H	-9.37	-	42.90	74.00	31.10
1 159.23	51.75	Peak	V	-9.28	-	42.47	74.00	31.53
1 179.73	49.09	Peak	H	-9.26	-	39.83	74.00	34.17
1 289.22	52.74	Peak	V	-9.12	-	43.62	74.00	30.38
1 422.71	50.87	Peak	V	-8.97	-	41.90	74.00	32.10

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11a
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 64

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	51.97	Peak	V	-9.44	-	42.53	74.00	31.47
1 000.75	48.70	Peak	H	-9.44	-	39.26	74.00	34.74
1 080.24	51.80	Peak	H	-9.37	-	42.43	74.00	31.57
1 154.73	51.79	Peak	V	-9.29	-	42.50	74.00	31.50
1 186.23	50.24	Peak	H	-9.25	-	40.99	74.00	33.01
1 288.72	51.08	Peak	V	-9.11	-	41.97	74.00	32.03
1 390.21	50.99	Peak	V	-8.98	-	42.01	74.00	31.99

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 350.95	39.98	Peak	H	7.25	-	47.23	74.00	26.77
5 351.65	40.67	Peak	V	7.25	-	47.92	74.00	26.08



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: 802.11an_HT20
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 52

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	49.86	Peak	H	-9.44	-	40.42	74.00	33.58
1 000.75	52.69	Peak	V	-9.44	-	43.25	74.00	30.75
1 080.24	53.40	Peak	H	-9.37	-	44.03	74.00	29.97
1 173.23	51.19	Peak	V	-9.26	-	41.93	74.00	32.07
1 189.73	50.11	Peak	H	-9.25	-	40.86	74.00	33.14
1 282.22	49.74	Peak	V	-9.13	-	40.61	74.00	33.39
1 288.22	51.38	Peak	V	-9.11	-	42.27	74.00	31.73
1 415.21	51.12	Peak	V	-8.97	-	42.15	74.00	31.85

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-22T0071


Page (127) of (214)

Mode: 802.11an_HT20
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 60

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.75	53.20	Peak	V	-9.44	-	43.76	74.00	30.24
1 080.74	51.61	Peak	H	-9.36	-	42.25	74.00	31.75
1 164.73	51.31	Peak	V	-9.28	-	42.03	74.00	31.97
1 194.23	49.80	Peak	H	-9.25	-	40.55	74.00	33.45
1 274.22	49.32	Peak	H	-9.13	-	40.19	74.00	33.81
1 288.72	52.20	Peak	V	-9.11	-	43.09	74.00	30.91

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11an_HT20
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 64

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	53.31	Peak	V	-9.44	-	43.87	74.00	30.13
1 000.25	49.95	Peak	H	-9.44	-	40.51	74.00	33.49
1 080.24	52.23	Peak	H	-9.37	-	42.86	74.00	31.14
1 190.23	52.12	Peak	V	-9.25	-	42.87	74.00	31.13
1 275.72	49.95	Peak	H	-9.14	-	40.81	74.00	33.19
1 314.72	51.10	Peak	V	-9.08	-	42.02	74.00	31.98
1 396.21	50.90	Peak	V	-8.97	-	41.93	74.00	32.07

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 351.04	39.93	Peak	H	7.25	-	47.18	74.00	26.82
5 352.31	39.12	Peak	V	7.25	-	46.37	74.00	27.63



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.


1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: 802.11ac_HT20
 Band: UNII-2A
 Distance of measurement: 3 meter
 Channel: 52

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	49.57	Peak	H	-9.44	-	40.13	74.00	33.87
1 000.25	52.22	Peak	V	-9.44	-	42.78	74.00	31.22
1 080.24	52.25	Peak	H	-9.37	-	42.88	74.00	31.12
1 166.73	51.11	Peak	V	-9.27	-	41.84	74.00	32.16
1 179.73	50.03	Peak	H	-9.26	-	40.77	74.00	33.23
1 423.71	50.67	Peak	V	-8.96	-	41.71	74.00	32.29

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: 802.11ac_HT20
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 60

- **Spurious**

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1000.75	49.67	Peak	H	-9.44	-	40.23	74.00	33.77
1002.25	52.10	Peak	V	-9.44	-	42.66	74.00	31.34
1080.74	51.66	Peak	H	-9.36	-	42.30	74.00	31.70
1179.73	49.34	Peak	H	-9.26	-	40.08	74.00	33.92
1187.23	51.74	Peak	V	-9.26	-	42.48	74.00	31.52
1287.72	51.07	Peak	V	-9.11	-	41.96	74.00	32.04
1390.21	51.21	Peak	V	-8.98	-	42.23	74.00	31.77

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: 802.11ac_HT20
Band: UNII-2A
Distance of measurement: 3 meter
Channel: 64

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.25	49.83	Peak	H	-9.44	-	40.39	74.00	33.61
1 003.25	52.52	Peak	V	-9.44	-	43.08	74.00	30.92
1 080.24	52.23	Peak	H	-9.37	-	42.86	74.00	31.14
1 167.23	50.84	Peak	V	-9.27	-	41.57	74.00	32.43
1 187.73	49.16	Peak	H	-9.25	-	39.91	74.00	34.09
1 289.22	52.23	Peak	V	-9.12	-	43.11	74.00	30.89
1 411.21	50.42	Peak	V	-8.96	-	41.46	74.00	32.54

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 350.72	43.22	Peak	H	7.25	-	50.47	74.00	23.53
5 352.39	39.66	Peak	V	7.25	-	46.91	74.00	27.09



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.


1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: 802.11an_HT40
 Band: UNII-2A
 Distance of measurement: 3 meter
 Channel: 54

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 002.75	52.87	Peak	V	-9.44	-	43.43	74.00	30.57
1 080.74	52.30	Peak	H	-9.36	-	42.94	74.00	31.06
1 160.73	51.79	Peak	V	-9.28	-	42.51	74.00	31.49
1 186.73	50.52	Peak	H	-9.26	-	41.26	74.00	32.74
1 288.22	49.78	Peak	H	-9.11	-	40.67	74.00	33.33
1 421.21	50.84	Peak	V	-8.96	-	41.88	74.00	32.12
1 536.70	50.62	Peak	V	-5.98	-	44.64	74.00	29.36

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 6 GHz.
2. Average test would be performed if the peak result were greater than the average limit.