FCC RADIO TEST REPORT
FCC ID: 2AXTFMAS1227

Product: Automation Rugged Windows Mobile Tablet PC

Trade Mark: MACTRON GROUP

Model No.: MAS1227

Family Model: N/A

Report No.: S21102603702003

Issue Date: Nov 17. 2021

Prepared for

MACTRON GROUP CO.,LTD.

2F, No. 86, Xinhu 1st Rd., Neihu Dist, Taipei City , Taiwan (R.O.C.)

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website:http://www.ntek.org.cn

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION 4

2 SUMMARY OF TEST RESULTS 5

3 FACILITIES AND ACCREDITATIONS 6

3.1 FACILITIES 6
3.2 LABORATORY ACCREDITATIONS AND LISTINGS 6
3.3 MEASUREMENT UNCERTAINTY 6

4 GENERAL DESCRIPTION OF EUT 7

5 DESCRIPTION OF TEST MODES 9

6 SETUP OF EQUIPMENT UNDER TEST 11

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 11
6.2 SUPPORT EQUIPMENT 12
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 13

7 TEST REQUIREMENTS 15

7.1 CONDUCTED EMISSIONS TEST 15
7.1.1 Applicable Standard 15
7.1.2 Conformance Limit 15
7.1.3 Measuring Instruments 15
7.1.4 Test Configuration 15
7.1.5 Test Procedure 15
7.1.6 Test Results 16
7.2 RADIATED SPURIOUS EMISSION 18
7.2.1 Applicable Standard 18
7.2.2 Conformance Limit 18
7.2.3 Measuring Instruments 19
7.2.4 Test Configuration 19
7.2.5 Test Procedure 20
7.2.6 Test Results 21
7.3 6DB BANDWIDTH 27
7.3.1 Applicable Standard 27
7.3.2 Conformance Limit 27
7.3.3 Measuring Instruments 27
7.3.4 Test Setup 27
7.3.5 Test Procedure 27
7.3.6 Test Results 28
7.4 DUTY CYCLE 29
7.4.1 Applicable Standard 29
7.4.2 Conformance Limit 29
7.4.3 Measuring Instruments 29
7.4.4 Test Setup 29
7.4.5 Test Procedure 29
7.4.6 Test Results 30
7.5 MAXIMUM OUTPUT POWER 31
7.5.1 Applicable Standard 31
7.5.2 Conformance Limit 31
7.5.3 Measuring Instruments 31
7.5.4 Test Setup 31
7.5.5 Test Procedure 31
7.5.6 EUT operation during Test 31
7.5.7 Test Results 32
7.6 POWER SPECTRAL DENSITY 33

7.6.1 Applicable Standard 33
7.6.2 Conformance Limit 33
7.6.3 Measuring Instruments 33
7.6.4 Test Setup 33
7.6.5 Test Procedure 33
7.6.6 Test Results 34
7.7 CONDUCTED BAND EDGE MEASUREMENT 35
7.7.1 Applicable Standard 35
7.7.2 Conformance Limit 35
7.7.3 Measuring Instruments 35
7.7.4 Test Setup 35
7.7.5 Test Procedure 35
7.7.6 Test Results 36
7.8 SPURIOUS RF CONDUCTED EMISSIONS 37
7.8.1 Conformance Limit 37
7.8.2 Measuring Instruments 37
7.8.3 Test Setup 37
7.8.4 Test Procedure 37
7.8.5 Test Results 37
7.9 ANTENNA APPLICATION 38
7.9.1 Antenna Requirement 38
7.9.2 Result 38

8 TEST RESULTS 39

2.4G WIFI: 39
8.1.1 DUTY CYCLE 39
8.1.2 MAXIMUM CONDUCTED OUTPUT POWER 52
8.1.3 OCCUPIED CHANNEL BANDWIDTH 53
8.1.4 MAXIMUM POWER SPECTRAL DENSITY LEVEL 78
8.1.5 BAND EDGE 91
8.1.6 CONDUCTED RF SPURIOUS EMISSION 108
MIMO 2.4G: 133
8.1.7 MAXIMUM CONDUCTED OUTPUT POWER 133
8.1.8 MAXIMUM POWER SPECTRAL DENSITY LEVEL 134
8.1.9 BAND EDGE 141
8.1.10 CONDUCTED RF SPURIOUS EMISSION 150

1 TEST RESULT CERTIFICATION

Applicant's name.....:	MACTRON GROUP CO.,LTD.
Address.....:	2F, No. 86, Xinhu 1st Rd., Neihu Dist, Taipei City , Taiwan (R.O.C.)
Manufacturer's Name.....:	MACTRON GROUP CO.,LTD.
Address.....:	2F, No. 86, Xinhu 1st Rd., Neihu Dist, Taipei City , Taiwan (R.O.C.)
Product description	
Product name.....:	Automation Rugged Windows Mobile Tablet PC
Model and/or type reference .....:	MAS1227
Family Model.....:	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C FCC KDB 662911 D01 Multiple Transmitter Output v02r01 ANSI C63.10-2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Date of Test : Oct 28. 2021 ~ Nov 16. 2021

Testing Engineer : Allen Liu
(Allen Liu)

Authorized Signatory : Alex
(Alex Li)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	**Test Item**	**Verdict**	**Remark**
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Maximum Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District Shenzhen, Guangdong, China

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	All emissions, radiated(9KHz~30MHz)	±6dB

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Automation Rugged Windows Mobile Tablet PC
Trade Mark	MACTRON GROUP
FCC ID	2AXTFMAS1227
Model No.	MAS1227
Family Model	N/A
Model Difference	N/A
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20); 2422-2452MHz for 802.11n(HT40)
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Number of Channels	11 channels for 802.11b/g/11n(HT20); 7 channels for 802.11n(HT40);
Antenna Type	Antenna 1: FPC Antenna Antenna 2: FPC Antenna
Smart system	☒SISO for 802.11b/g ☒ MIMO for 802.11n20/n40
Antenna Gain	Antenna 1: 1dBi Antenna 2: 1dBi
Power supply	☒DC supply: DC 7.4V, 6300mAh from battery or DC 12V from Adapter.
	☒Adapter supply: Model: FJ-SW20171204000 Input: 100-240V~50/60Hz 1.5A Max Output: 12.0V⎓4.0A 48.0W
HW Version	MTG MAS1227 MB PCB
SW Version	Windows 10
Firmware version	EC25AFFDR07A08M4G

Note: 1.Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Revision History

Report No.	Version	Description	Issued Date
S21102603702003	Rev.01	Initial issue of report	Nov 17. 2021

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.
The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.
The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20/HT40):

Channel	Frequency(MHz)
1	2412
2	2417
…	…
5	2432
6	2437
…	…
10	2457
11	2462

Note: fc=2412MHz+(k-1)×5MHz k=1 to 11

AC power line Conducted Emission was tested under maximum output power.

The module for 2.4G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11b/g	1TX, 1RX
802.11n	1TX/2TX, 1RX/2RX

For power measurements: Directional gain=G_{ANT} + Array Gain=1dBi + 0 = 1dBi
For power spectral density (PSD) measurements: Directional gain=G_{ANT} + Array Gain=1dBi + 3.01 = 4.01dBi

Note: G_{ANT} means antenna gain for the same gain in dBi.
For power spectral density (PSD) measurements: Array Gain = $10\log(N_{ANT}/N_{ss})$dB.

For power measurements:
Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT};
Array Gain = 5 log(N_{ANT}/N_{SS}) dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

N_{ANT} = number of transmit antennas and
N_{SS} = number of spatial streams. (Assume N_{SS} = *1* unless you have specific information to the contrary.)

Test Mode:

Test Items	Mode	Data Rate	Channel	Ant
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1/2
	11g/BPSK	6 Mbps	1/6/11	1/2
	11n HT20	MCS0	1/6/11	1/2
	11n HT40	MCS7	3/6/9	1/2
Power Spectral Density				
	11b/CCK	1 Mbps	1/6/11	1/2
	11g/BPSK	6 Mbps	1/6/11	1/2
	11n HT20	MCS0	1/6/11	1/2
	11n HT40	MCS7	3/6/9	1/2
6dB Spectrum Bandwidth				
	11b/CCK	1 Mbps	1/6/11	1/2
	11g/BPSK	6 Mbps	1/6/11	1/2
	11n HT20	MCS0	1/6/11	1/2
	11n HT40	MCS7	3/6/9	1/2
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz				
	11b/CCK	1 Mbps	1/6/11	1/2
	11g/BPSK	6 Mbps	1/6/11	1/2
	11n HT20	MCS0	1/6/11	1/2
	11n HT40	MCS7	3/6/9	1/2
Band Edge Emissions				
	11b/CCK	1 Mbps	1/6/11	1/2
	11g/BPSK	6 Mbps	1/6/11	1/2
	11n HT20	MCS0	1/6/11	1/2
	11n HT40	MCS7	3/6/9	1/2

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	FJ-SW20171204000	N/A	Peripherals
AE-2	Monitor	N/A	N/A	N/A	Peripherals
AE-3	Earphone	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.2m
C-2	HDMI Cable	YES	NO	1.0m
C-3	Earphone Cable	NO	NO	1.2m
C-4	RF Cable	YES	NO	0.1m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.
(4) During the battery power test, the battery is fully charged.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Aglient	E4407B	MY45108040	2021.04.27	2022.04.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.04.27	2022.04.26	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2021.04.27	2022.04.26	1 year
4	Test Receiver	R&S	ESPI7	101318	2021.04.27	2022.04.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29	2022.03.28	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.29	2022.03.28	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2020.11.20	2021.11.19	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01	2022.06.30	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2020.11.20	2021.11.19	1 year
11	Power Meter	DARE	RPR3006W	15I00041SNO84	2020.11.20	2021.11.19	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	Filter	TRILTHIC	2400MHz	29	2020.11.20	2021.11.19	1 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2021.04.27	2022.04.26	1 year
2	LISN	R&S	ENV216	101313	2021.04.27	2022.04.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2021.04.27	2022.04.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.6 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name :	MAS1227
Temperature:	24 ℃	Relative Humidity:	48%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode:	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	44.51	9.71	54.22	65.56	-11.34	QP
0.1580	37.16	9.71	46.87	55.56	-8.69	AVG
0.2700	35.33	9.63	44.96	61.12	-16.16	QP
0.2700	24.62	9.63	34.25	51.12	-16.87	AVG
0.3220	31.96	9.63	41.59	59.65	-18.06	QP
0.3220	21.62	9.63	31.25	49.65	-18.40	AVG
3.2659	23.18	9.71	32.89	56.00	-23.11	QP
3.2659	12.87	9.71	22.58	46.00	-23.42	AVG
13.5419	28.27	9.79	38.06	60.00	-21.94	QP
13.5419	19.56	9.79	29.35	50.00	-20.65	AVG
24.3538	26.72	9.86	36.58	60.00	-23.42	QP
24.3538	18.16	9.86	28.02	50.00	-21.98	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature：	24 ℃	Relative Humidity：	48%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 12V from Adapter AC 120V/60Hz	Test Mode：	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	47.24	9.63	56.87	65.56	-8.69	QP
0.1580	37.39	9.63	47.02	55.56	-8.54	AVG
0.2059	39.00	9.63	48.63	63.37	-14.74	QP
0.2059	28.95	9.63	38.58	53.37	-14.79	AVG
0.2939	34.97	9.66	44.63	60.41	-15.78	QP
0.2939	25.59	9.66	35.25	50.41	-15.16	AVG
2.9820	24.40	9.72	34.12	56.00	-21.88	QP
2.9820	14.93	9.72	24.65	46.00	-21.35	AVG
13.6179	22.56	9.75	32.31	60.00	-27.69	QP
13.6179	12.75	9.75	22.50	50.00	-27.50	AVG
24.3219	25.86	9.80	35.66	60.00	-24.34	QP
24.3219	16.55	9.80	26.35	50.00	-23.65	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz:
Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz:
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and frequencies above 1GHz,
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
g For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:
For peak measurement:
Set RBW=100 kHz for f < 1 GHz; VBW=120KHz; Sweep = auto; Detector function = peak; Trace = max hold;
Set RBW = 1 MHz, VBW= 3MHz for f≥1 GHz
For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT：	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature：	26 ℃	Relative Humidity：	54%
Test Mode:	Mode2/Mode3/Mode4/Mode5	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT：	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature：	22 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Test Mode：	Normal Link
Test Voltage ：	DC 7.4V		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	46.9947	17.40	16.17	33.57	40.00	-6.43	QP
V	63.0915	22.33	11.76	34.09	40.00	-5.91	QP
V	92.1388	19.99	16.37	36.36	43.50	-7.14	QP
V	135.0319	13.34	18.74	32.08	43.50	-11.42	QP
V	663.4728	9.52	30.60	40.12	46.00	-5.88	QP
V	884.5027	8.92	33.52	42.44	46.00	-3.56	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level- Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	67.4381	15.64	12.47	28.11	40.00	-11.89	QP
H	96.0986	14.07	16.59	30.66	43.50	-12.84	QP
H	176.2684	15.12	17.16	32.28	43.50	-11.22	QP
H	269.4284	15.59	21.81	37.40	46.00	-8.60	QP
H	387.9920	13.79	24.62	38.41	46.00	-7.59	QP
H	526.3967	12.09	27.25	39.34	46.00	-6.66	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level- Limit



Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

All the modulation modes have been tested, only shown the worst data as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2422 MHz)(802.11n40 MIMO)--Above 1G									
4844.265	63.06	5.21	35.59	44.30	59.56	74.00	-14.44	Pk	Vertical
4844.265	40.27	5.21	35.59	44.30	36.77	54.00	-17.23	AV	Vertical
7266.296	60.16	6.48	36.27	44.60	58.31	74.00	-15.69	Pk	Vertical
7266.296	44.17	6.48	36.27	44.60	42.32	54.00	-11.68	AV	Vertical
4844.255	61.38	5.21	35.55	44.30	57.84	74.00	-16.16	Pk	Horizontal
4844.255	43.10	5.21	35.55	44.30	39.56	54.00	-14.44	AV	Horizontal
7266.017	62.89	6.48	36.27	44.52	61.12	74.00	-12.88	Pk	Horizontal
7266.017	46.57	6.48	36.27	44.52	44.80	54.00	-9.20	AV	Horizontal
Mid Channel (2437 MHz)(802.11n40 MIMO)--Above 1G									
4874.312	62.50	5.21	35.66	44.20	59.17	74.00	-14.83	Pk	Vertical
4874.312	43.05	5.21	35.66	44.20	39.72	54.00	-14.28	AV	Vertical
7311.227	60.07	7.10	36.50	44.43	59.24	74.00	-14.76	Pk	Vertical
7311.227	46.96	7.10	36.50	44.43	46.13	54.00	-7.87	AV	Vertical
4874.529	61.30	5.21	35.66	44.20	57.97	74.00	-16.03	Pk	Horizontal
4874.529	47.96	5.21	35.66	44.20	44.63	54.00	-9.37	AV	Horizontal
7311.313	59.27	7.10	36.50	44.43	58.44	74.00	-15.56	Pk	Horizontal
7311.313	42.10	7.10	36.50	44.43	41.27	54.00	-12.73	AV	Horizontal
High Channel (2452 MHz)(802.11n40 MIMO)--Above 1G									
4904.178	66.10	5.21	35.52	44.21	62.62	74.00	-11.38	Pk	Vertical
4904.178	42.63	5.21	35.52	44.21	39.15	54.00	-14.85	AV	Vertical
7356.018	60.89	7.10	36.53	44.60	59.92	74.00	-14.08	Pk	Vertical
7356.018	44.59	7.10	36.53	44.60	43.62	54.00	-10.38	AV	Vertical
4904.447	67.04	5.21	35.52	44.21	63.56	74.00	-10.44	Pk	Horizontal
4904.447	46.76	5.21	35.52	44.21	43.28	54.00	-10.72	AV	Horizontal
7356.226	60.51	7.10	36.53	44.60	59.54	74.00	-14.46	Pk	Horizontal
7356.226	44.65	7.10	36.53	44.60	43.68	54.00	-10.32	AV	Horizontal

Note:

(1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(3)"802.11n40" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

Spurious Emission in Restricted Band 2310MHz -18000MHz
All the modulation modes have been tested, only shown the worst data as below:

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11b									
2310.00	58.29	2.97	27.80	43.80	45.26	74	-28.74	Pk	Horizontal
2310.00	43.09	2.97	27.80	43.80	30.06	54	-23.94	AV	Horizontal
2310.00	58.74	2.97	27.80	43.80	45.71	74	-28.29	Pk	Vertical
2310.00	42.17	2.97	27.80	43.80	29.14	54	-24.86	AV	Vertical
2390.00	58.21	3.14	27.21	43.80	44.76	74	-29.24	Pk	Vertical
2390.00	42.32	3.14	27.21	43.80	28.87	54	-25.13	AV	Vertical
2390.00	56.75	3.14	27.21	43.80	43.30	74	-30.70	Pk	Horizontal
2390.00	41.21	3.14	27.21	43.80	27.76	54	-26.24	AV	Horizontal
2483.50	57.83	3.58	27.70	44.00	45.11	74	-28.89	Pk	Vertical
2483.50	42.95	3.58	27.70	44.00	30.23	54	-23.77	AV	Vertical
2483.50	59.01	3.58	27.70	44.00	46.29	74	-27.71	Pk	Horizontal
2483.50	42.05	3.58	27.70	44.00	29.33	54	-24.67	AV	Horizontal
802.11g									
2310.00	58.28	2.97	27.80	43.80	45.25	74	-28.75	Pk	Horizontal
2310.00	44.52	2.97	27.80	43.80	31.49	54	-22.51	AV	Horizontal
2310.00	57.10	2.97	27.80	43.80	44.07	74	-29.93	Pk	Vertical
2310.00	42.98	2.97	27.80	43.80	29.95	54	-24.05	AV	Vertical
2390.00	57.40	3.14	27.21	43.80	43.95	74	-30.05	Pk	Vertical
2390.00	42.22	3.14	27.21	43.80	28.77	54	-25.23	AV	Vertical
2390.00	58.46	3.14	27.21	43.80	45.01	74	-28.99	Pk	Horizontal
2390.00	44.09	3.14	27.21	43.80	30.64	54	-23.36	AV	Horizontal
2483.50	58.45	3.58	27.70	44.00	45.73	74	-28.27	Pk	Vertical
2483.50	44.28	3.58	27.70	44.00	31.56	54	-22.44	AV	Vertical
2483.50	59.11	3.58	27.70	44.00	46.39	74	-27.61	Pk	Horizontal
2483.50	41.79	3.58	27.70	44.00	29.07	54	-24.93	AV	Horizontal
802.11n20									
2310.00	58.01	2.97	27.80	43.80	44.98	74	-29.02	Pk	Horizontal
2310.00	43.84	2.97	27.80	43.80	30.81	54	-23.19	AV	Horizontal
2310.00	58.36	2.97	27.80	43.80	45.33	74	-28.67	Pk	Vertical
2310.00	42.05	2.97	27.80	43.80	29.02	54	-24.98	AV	Vertical
2390.00	57.96	3.14	27.21	43.80	44.51	74	-29.49	Pk	Vertical
2390.00	42.43	3.14	27.21	43.80	28.98	54	-25.02	AV	Vertical
2390.00	57.18	3.14	27.21	43.80	43.73	74	-30.27	Pk	Horizontal
2390.00	42.38	3.14	27.21	43.80	28.93	54	-25.07	AV	Horizontal
2483.50	57.70	3.58	27.70	44.00	44.98	74	-29.02	Pk	Vertical
2483.50	42.41	3.58	27.70	44.00	29.69	54	-24.31	AV	Vertical
2483.50	59.27	3.58	27.70	44.00	46.55	74	-27.45	Pk	Horizontal
2483.50	42.10	3.58	27.70	44.00	29.38	54	-24.62	AV	Horizontal

802.11n40									
2310.00	59.62	2.97	27.80	43.80	46.59	74	-27.41	Pk	Horizontal
2310.00	44.83	2.97	27.80	43.80	31.80	54	-22.20	AV	Horizontal
2310.00	56.74	2.97	27.80	43.80	43.71	74	-30.29	Pk	Vertical
2310.00	43.33	2.97	27.80	43.80	30.30	54	-23.70	AV	Vertical
2390.00	57.57	3.14	27.21	43.80	44.12	74	-29.88	Pk	Vertical
2390.00	41.77	3.14	27.21	43.80	28.32	54	-25.68	AV	Vertical
2390.00	57.97	3.14	27.21	43.80	44.52	74	-29.48	Pk	Horizontal
2390.00	44.13	3.14	27.21	43.80	30.68	54	-23.32	AV	Horizontal
2483.50	58.52	3.58	27.70	44.00	45.80	74	-28.20	Pk	Vertical
2483.50	44.61	3.58	27.70	44.00	31.89	54	-22.11	AV	Vertical
2483.50	58.52	3.58	27.70	44.00	45.80	74	-28.20	Pk	Horizontal
2483.50	42.23	3.58	27.70	44.00	29.51	54	-24.49	AV	Horizontal

Spurious Emission in Restricted Bands 3260MHz- 18000MHz
All the modulation modes have been tested, only shown the worst data as below:

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	60.28	4.04	29.57	44.70	49.19	74	-24.81	Pk	Vertical
3260	55.95	4.04	29.57	44.70	44.86	54	-9.14	AV	Vertical
3260	61.80	4.04	29.57	44.70	50.71	74	-23.29	Pk	Horizontal
3260	56.48	4.04	29.57	44.70	45.39	54	-8.61	AV	Horizontal
3332	64.79	4.26	29.87	44.40	54.52	74	-19.48	Pk	Vertical
3332	53.49	4.26	29.87	44.40	43.22	54	-10.78	AV	Vertical
3332	62.99	4.26	29.87	44.40	52.72	74	-21.28	Pk	Horizontal
3332	52.93	4.26	29.87	44.40	42.66	54	-11.34	AV	Horizontal
17797	43.50	10.99	43.95	43.50	54.94	74	-19.06	Pk	Vertical
17797	32.74	10.99	43.95	43.50	44.18	54	-9.82	AV	Vertical
17788	43.37	11.81	43.69	44.60	54.27	74	-19.73	Pk	Horizontal
17788	32.09	11.81	43.69	44.60	42.99	54	-11.01	AV	Horizontal

“802.11b” mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW = 100KHz
VBW ≥ 3*RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.3.6 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.4 DUTY CYCLE

7.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 6.

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 10MHz(the largest available value)
VBW = 10MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure T_{total} and T_{on}
Calculate Duty Cycle = T_{on} / T_{total}

7.4.6 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.5 MAXIMUM OUTPUT POWER

7.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 8.3.2.3.

7.5.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.5.3 Measuring Instruments

The following table is the setting of the power meter.

Power meter parameter	Setting
Detector	Peak

7.5.4 Test Setup



7.5.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.9.1.3 of ANSI C63.10

7.5.6 EUT operation during Test

The EUT was programmed to be in continuously transmitting mode.

7.5.7 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Note: The module for 2.4G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
11b, 11g	1Tx, 1Rx
11n(HT20/HT40)	1Tx, 1Rx ,2Tx, 2Rx

Note: For 802.11n has MIMO mode. Directional gain= 1dbi
1dbi<6.0 dbi so power limit= 30.00dBm

Test data reference attachment.

7.6 POWER SPECTRAL DENSITY

7.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 8.4.

7.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10
This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 *RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.6 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

The module for 2.4G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
11b, 11g	1Tx, 1Rx
11n(HT20/HT40)	1Tx, 1Rx ,2Tx, 2Rx

Note: For 802.11n has MIMO mode. Directional gain=4.01dbi
4.01db<6.0 dbi so power spectral density = 8dBm

Test data reference attachment.

7.7 CONDUCTED BAND EDGE MEASUREMENT

7.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 8.7.

7.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance D01V05r02 Section 8.7.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

7.7.6 Test Results

EUT:	Automation Rugged Windows Mobile Tablet PC	Model Name ：	MAS1227
Temperature:	26 ℃	Relative Humidity：	54%
Test Mode:	802.11b/g/n20/n40	Test By:	Allen Liu

Test data reference attachment.

7.8 SPURIOUS RF CONDUCTED EMISSIONS

7.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.3 Test Setup

Please refer to Section 6.1 of this test report.

7.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 26.5GHz.

7.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The module for 2.4G WIFI has two antennas, and different modes support different transmit mode what describe as Following form:

Mode	Tx/Rx
802.11b/g	1TX, 1RX
802.11n	1TX/2TX, 1RX/2RX

It complies with the standard requirement.

8 TEST RESULTS

2.4G WIFI:

8.1.1 DUTY CYCLE

Antenna	Condition	Mode	Frequency (MHz)	Duty Cycle (%)
Ant 1	NVNT	802.11b	2412	99.78
Ant 1	NVNT	802.11b	2437	99.66
Ant 1	NVNT	802.11b	2462	99.56
Ant 2	NVNT	802.11b	2412	99.78
Ant 2	NVNT	802.11b	2437	99.67
Ant 2	NVNT	802.11b	2462	99.62
Ant 1	NVNT	802.11g	2412	99.18
Ant 1	NVNT	802.11g	2437	99.02
Ant 1	NVNT	802.11g	2462	99.28
Ant 2	NVNT	802.11g	2412	99.28
Ant 2	NVNT	802.11g	2437	99.26
Ant 2	NVNT	802.11g	2462	99.27
Ant 1	NVNT	802.11n(HT20)	2412	99.22
Ant 1	NVNT	802.11n(HT20)	2437	99.22
Ant 1	NVNT	802.11n(HT20)	2462	98.96
Ant 2	NVNT	802.11n(HT20)	2412	99.15
Ant 2	NVNT	802.11n(HT20)	2437	99.19
Ant 2	NVNT	802.11n(HT20)	2462	99.15
Ant 1	NVNT	802.11n(HT40)	2422	98.22
Ant 1	NVNT	802.11n(HT40)	2437	98.24
Ant 1	NVNT	802.11n(HT40)	2452	98.23
Ant 2	NVNT	802.11n(HT40)	2422	98.23
Ant 2	NVNT	802.11n(HT40)	2437	98.21
Ant 2	NVNT	802.11n(HT40)	2452	98.22

Duty Cycle NVNT 802.11b 2412MHz Ant 1



Duty Cycle NVNT 802.11b 2437MHz Ant 1



Duty Cycle NVNT 802.11b 2462MHz Ant 1



Duty Cycle NVNT 802.11b 2412MHz Ant 2



Duty Cycle NVNT 802.11b 2437MHz Ant 2



Duty Cycle NVNT 802.11b 2462MHz Ant 2



Duty Cycle NVNT 802.11g 2412MHz Ant 1



Duty Cycle NVNT 802.11g 2437MHz Ant 1



Duty Cycle NVNT 802.11g 2462MHz Ant 1



Duty Cycle NVNT 802.11g 2412MHz Ant 2



Duty Cycle NVNT 802.11g 2437MHz Ant 2



Duty Cycle NVNT 802.11g 2462MHz Ant 2



Duty Cycle NVNT 802.11n(HT20) 2412MHz Ant 1



Duty Cycle NVNT 802.11n(HT20) 2437MHz Ant 1



Duty Cycle NVNT 802.11n(HT20) 2462MHz Ant 1



Duty Cycle NVNT 802.11n(HT20) 2412MHz Ant 2



Duty Cycle NVNT 802.11n(HT20) 2437MHz Ant 2



Duty Cycle NVNT 802.11n(HT20) 2462MHz Ant 2



Duty Cycle NVNT 802.11n(HT40) 2422MHz Ant 1



Duty Cycle NVNT 802.11n(HT40) 2437MHz Ant 1



Duty Cycle NVNT 802.11n(HT40) 2452MHz Ant 1



Duty Cycle NVNT 802.11n(HT40) 2422MHz Ant 2



Duty Cycle NVNT 802.11n(HT40) 2437MHz Ant 2



Duty Cycle NVNT 802.11n(HT40) 2452MHz Ant 2



8.1.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	802.11b	2412	Ant 1	13.65	30	Pass
NVNT	802.11b	2437	Ant 1	14	30	Pass
NVNT	802.11b	2462	Ant 1	13.47	30	Pass
NVNT	802.11b	2412	Ant 2	13.11	30	Pass
NVNT	802.11b	2437	Ant 2	13.36	30	Pass
NVNT	802.11b	2462	Ant 2	13.77	30	Pass
NVNT	802.11g	2412	Ant 1	12.71	30	Pass
NVNT	802.11g	2437	Ant 1	13.42	30	Pass
NVNT	802.11g	2456	Ant 1	13.08	30	Pass
NVNT	802.11g	2412	Ant 2	11.84	30	Pass
NVNT	802.11g	2437	Ant 2	12.45	30	Pass
NVNT	802.11g	2456	Ant 2	11.9	30	Pass
NVNT	802.11n(HT20)	2412	Ant 1	12.61	30	Pass
NVNT	802.11n(HT20)	2437	Ant 1	13.35	30	Pass
NVNT	802.11n(HT20)	2462	Ant 1	13.42	30	Pass
NVNT	802.11n(HT20)	2412	Ant 2	11.33	30	Pass
NVNT	802.11n(HT20)	2437	Ant 2	12.56	30	Pass
NVNT	802.11n(HT20)	2462	Ant 2	11.69	30	Pass
NVNT	802.11n(HT40)	2422	Ant 1	11.92	30	Pass
NVNT	802.11n(HT40)	2437	Ant 1	12.25	30	Pass
NVNT	802.11n(HT40)	2452	Ant 1	11.74	30	Pass
NVNT	802.11n(HT40)	2422	Ant 2	11.08	30	Pass
NVNT	802.11n(HT40)	2437	Ant 2	11.21	30	Pass
NVNT	802.11n(HT40)	2452	Ant 2	10.68	30	Pass

8.1.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	802.11b	2412	Ant 1	12.9071	9.12	0.5	Pass
NVNT	802.11b	2437	Ant 1	12.8272	9.52	0.5	Pass
NVNT	802.11b	2462	Ant 1	12.6673	9.56	0.5	Pass
NVNT	802.11b	2412	Ant 2	12.7073	9.88	0.5	Pass
NVNT	802.11b	2437	Ant 2	12.5075	9.6	0.5	Pass
NVNT	802.11b	2462	Ant 2	12.6274	9.6	0.5	Pass
NVNT	802.11g	2412	Ant 1	16.7033	14.04	0.5	Pass
NVNT	802.11g	2437	Ant 1	16.7033	14.64	0.5	Pass
NVNT	802.11g	2462	Ant 1	16.5035	15.4	0.5	Pass
NVNT	802.11g	2412	Ant 2	16.5834	16.32	0.5	Pass
NVNT	802.11g	2437	Ant 2	16.5834	13.2	0.5	Pass
NVNT	802.11g	2462	Ant 2	16.5834	12.56	0.5	Pass
NVNT	802.11n(HT20)	2412	Ant 1	17.7822	16.04	0.5	Pass
NVNT	802.11n(HT20)	2437	Ant 1	18.022	15.08	0.5	Pass
NVNT	802.11n(HT20)	2462	Ant 1	17.6623	17.6	0.5	Pass
NVNT	802.11n(HT20)	2412	Ant 2	17.8621	17.56	0.5	Pass
NVNT	802.11n(HT20)	2437	Ant 2	17.7822	14.68	0.5	Pass
NVNT	802.11n(HT20)	2462	Ant 2	17.6623	13.8	0.5	Pass
NVNT	802.11n(HT40)	2422	Ant 1	36.3636	30	0.5	Pass
NVNT	802.11n(HT40)	2437	Ant 1	36.3636	33.92	0.5	Pass
NVNT	802.11n(HT40)	2452	Ant 1	36.4436	27.52	0.5	Pass
NVNT	802.11n(HT40)	2422	Ant 2	36.3636	31.28	0.5	Pass
NVNT	802.11n(HT40)	2437	Ant 2	36.1239	33.84	0.5	Pass
NVNT	802.11n(HT40)	2452	Ant 2	35.8841	34.4	0.5	Pass

OBW NVNT 802.11b 2412MHz Ant 1



-6 dB BW NVNT 802.11b 2412MHz Ant 1



OBW NVNT 802.11b 2437MHz Ant 1



-6 dB BW NVNT 802.11b 2437MHz Ant 1



OBW NVNT 802.11b 2462MHz Ant 1



-6 dB BW NVNT 802.11b 2462MHz Ant 1



OBW NVNT 802.11b 2412MHz Ant 2



-6 dB BW NVNT 802.11b 2412MHz Ant 2



OBW NVNT 802.11b 2437MHz Ant 2



-6 dB BW NVNT 802.11b 2437MHz Ant 2



OBW NVNT 802.11b 2462MHz Ant 2



-6 dB BW NVNT 802.11b 2462MHz Ant 2



OBW NVNT 802.11g 2412MHz Ant 1

-6 dB BW NVNT 802.11g 2412MHz Ant 1



OBW NVNT 802.11g 2437MHz Ant 1

-6 dB BW NVNT 802.11g 2437MHz Ant 1



OBW NVNT 802.11g 2462MHz Ant 1



-6 dB BW NVNT 802.11g 2462MHz Ant 1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.466955 GHz	-5.70 dBm		
M2		1	2.45472 GHz	-11.69 dBm		
M3		1	2.47012 GHz	-11.51 dBm		

OBW NVNT 802.11g 2412MHz Ant 2

-6 dB BW NVNT 802.11g 2412MHz Ant 2



OBW NVNT 802.11g 2437MHz Ant 2



-6 dB BW NVNT 802.11g 2437MHz Ant 2



OBW NVNT 802.11g 2462MHz Ant 2

-6 dB BW NVNT 802.11g 2462MHz Ant 2



OBW NVNT 802.11n(HT20) 2412MHz Ant 1



-6 dB BW NVNT 802.11n(HT20) 2412MHz Ant 1



OBW NVNT 802.11n(HT20) 2437MHz Ant 1



-6 dB BW NVNT 802.11n(HT20) 2437MHz Ant 1



OBW NVNT 802.11n(HT20) 2462MHz Ant 1



-6 dB BW NVNT 802.11n(HT20) 2462MHz Ant 1



OBW NVNT 802.11n(HT20) 2412MHz Ant 2



-6 dB BW NVNT 802.11n(HT20) 2412MHz Ant 2



OBW NVNT 802.11n(HT20) 2437MHz Ant 2



-6 dB BW NVNT 802.11n(HT20) 2437MHz Ant 2



OBW NVNT 802.11n(HT20) 2462MHz Ant 2



-6 dB BW NVNT 802.11n(HT20) 2462MHz Ant 2



OBW NVNT 802.11n(HT40) 2422MHz Ant 1



-6 dB BW NVNT 802.11n(HT40) 2422MHz Ant 1



OBW NVNT 802.11n(HT40) 2437MHz Ant 1

-6 dB BW NVNT 802.11n(HT40) 2437MHz Ant 1



OBW NVNT 802.11n(HT40) 2452MHz Ant 1



-6 dB BW NVNT 802.11n(HT40) 2452MHz Ant 1



OBW NVNT 802.11n(HT40) 2422MHz Ant 2



-6 dB BW NVNT 802.11n(HT40) 2422MHz Ant 2



OBW NVNT 802.11n(HT40) 2437MHz Ant 2



-6 dB BW NVNT 802.11n(HT40) 2437MHz Ant 2



OBW NVNT 802.11n(HT40) 2452MHz Ant 2



-6 dB BW NVNT 802.11n(HT40) 2452MHz Ant 2



8.1.4 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	802.11b	2412	Ant 1	-10.893	8	Pass
NVNT	802.11b	2437	Ant 1	-10.35	8	Pass
NVNT	802.11b	2462	Ant 1	-11.052	8	Pass
NVNT	802.11b	2412	Ant 2	-11.499	8	Pass
NVNT	802.11b	2437	Ant 2	-10.49	8	Pass
NVNT	802.11b	2462	Ant 2	-10.666	8	Pass
NVNT	802.11g	2412	Ant 1	-11.493	8	Pass
NVNT	802.11g	2437	Ant 1	-9.447	8	Pass
NVNT	802.11g	2462	Ant 1	-11.191	8	Pass
NVNT	802.11g	2412	Ant 2	-12.374	8	Pass
NVNT	802.11g	2437	Ant 2	-10.986	8	Pass
NVNT	802.11g	2462	Ant 2	-11.484	8	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-11.582	8	Pass
NVNT	802.11n(HT20)	2437	Ant 1	-10.036	8	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-10.211	8	Pass
NVNT	802.11n(HT20)	2412	Ant 2	-12.053	8	Pass
NVNT	802.11n(HT20)	2437	Ant 2	-10.839	8	Pass
NVNT	802.11n(HT20)	2462	Ant 2	-10.504	8	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-14.346	8	Pass
NVNT	802.11n(HT40)	2437	Ant 1	-13.981	8	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-14.441	8	Pass
NVNT	802.11n(HT40)	2422	Ant 2	-15.867	8	Pass
NVNT	802.11n(HT40)	2437	Ant 2	-14.849	8	Pass
NVNT	802.11n(HT40)	2452	Ant 2	-14.79	8	Pass

PSD NVNT 802.11b 2412MHz Ant 1



PSD NVNT 802.11b 2437MHz Ant 1



PSD NVNT 802.11b 2462MHz Ant 1



PSD NVNT 802.11b 2412MHz Ant 2



PSD NVNT 802.11b 2437MHz Ant 2



PSD NVNT 802.11b 2462MHz Ant 2



PSD NVNT 802.11g 2412MHz Ant 1



PSD NVNT 802.11g 2437MHz Ant 1



PSD NVNT 802.11g 2462MHz Ant 1



PSD NVNT 802.11g 2412MHz Ant 2



PSD NVNT 802.11g 2437MHz Ant 2



PSD NVNT 802.11g 2462MHz Ant 2



PSD NVNT 802.11n(HT20) 2412MHz Ant 1



PSD NVNT 802.11n(HT20) 2437MHz Ant 1



PSD NVNT 802.11n(HT20) 2462MHz Ant 1



PSD NVNT 802.11n(HT20) 2412MHz Ant 2



PSD NVNT 802.11n(HT20) 2437MHz Ant 2



PSD NVNT 802.11n(HT20) 2462MHz Ant 2



PSD NVNT 802.11n(HT40) 2422MHz Ant 1



PSD NVNT 802.11n(HT40) 2437MHz Ant 1



PSD NVNT 802.11n(HT40) 2452MHz Ant 1



PSD NVNT 802.11n(HT40) 2422MHz Ant 2



PSD NVNT 802.11n(HT40) 2437MHz Ant 2



PSD NVNT 802.11n(HT40) 2452MHz Ant 2



8.1.5 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	802.11b	2412	Ant 1	-51.81	-20	Pass
NVNT	802.11b	2462	Ant 1	-54.71	-20	Pass
NVNT	802.11b	2412	Ant 2	-54.41	-20	Pass
NVNT	802.11b	2462	Ant 2	-55.68	-20	Pass
NVNT	802.11g	2412	Ant 1	-42	-20	Pass
NVNT	802.11g	2462	Ant 1	-42.21	-20	Pass
NVNT	802.11g	2412	Ant 2	-43.28	-20	Pass
NVNT	802.11g	2462	Ant 2	-51.34	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-42.32	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-42.54	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 2	-42.18	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 2	-47.68	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-32	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-28.58	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 2	-34.13	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 2	-45.5	-20	Pass

Band Edge NVNT 802.11b 2412MHz Ant 1 Ref



Band Edge NVNT 802.11b 2412MHz Ant 1 Emission

Band Edge NVNT 802.11b 2462MHz Ant 1 Ref



Band Edge NVNT 802.11b 2462MHz Ant 1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.46253 GHz	3.38 dBm		
M2		1	2.4835 GHz	-53.88 dBm		
M3		1	2.5 GHz	-53.23 dBm		
M4		1	2.4882 GHz	-51.10 dBm		

Band Edge NVNT 802.11b 2412MHz Ant 2 Ref



Band Edge NVNT 802.11b 2412MHz Ant 2 Emission



Band Edge NVNT 802.11b 2462MHz Ant 2 Ref



Band Edge NVNT 802.11b 2462MHz Ant 2 Emission



Band Edge NVNT 802.11g 2412MHz Ant 1 Ref



Band Edge NVNT 802.11g 2412MHz Ant 1 Emission



Band Edge NVNT 802.11g 2462MHz Ant 1 Ref



Band Edge NVNT 802.11g 2462MHz Ant 1 Emission



Band Edge NVNT 802.11g 2412MHz Ant 2 Ref



Band Edge NVNT 802.11g 2412MHz Ant 2 Emission



Band Edge NVNT 802.11g 2462MHz Ant 2 Ref



Band Edge NVNT 802.11g 2462MHz Ant 2 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.46423 GHz	-0.30 dBm		
M2		1	2.4835 GHz	-49.00 dBm		
M3		1	2.5 GHz	-52.36 dBm		
M4		1	2.4844 GHz	-48.86 dBm		

Band Edge NVNT 802.11n(HT20) 2412MHz Ant 1 Ref



Band Edge NVNT 802.11n(HT20) 2412MHz Ant 1 Emission



Band Edge NVNT 802.11n(HT20) 2462MHz Ant 1 Ref



Band Edge NVNT 802.11n(HT20) 2462MHz Ant 1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.46613 GHz	0.38 dBm		
M2		1	2.4835 GHz	-40.80 dBm		
M3		1	2.5 GHz	-52.88 dBm		
M4		1	2.4839 GHz	-39.76 dBm		

Band Edge NVNT 802.11n(HT20) 2412MHz Ant 2 Ref



Band Edge NVNT 802.11n(HT20) 2412MHz Ant 2 Emission



Band Edge NVNT 802.11n(HT20) 2462MHz Ant 2 Ref



Band Edge NVNT 802.11n(HT20) 2462MHz Ant 2 Emission



Band Edge NVNT 802.11n(HT40) 2422MHz Ant 1 Ref



Band Edge NVNT 802.11n(HT40) 2422MHz Ant 1 Emission



Band Edge NVNT 802.11n(HT40) 2452MHz Ant 1 Ref



Band Edge NVNT 802.11n(HT40) 2452MHz Ant 1 Emission



Band Edge NVNT 802.11n(HT40) 2422MHz Ant 2 Ref



Band Edge NVNT 802.11n(HT40) 2422MHz Ant 2 Emission



Band Edge NVNT 802.11n(HT40) 2452MHz Ant 2 Ref



Band Edge NVNT 802.11n(HT40) 2452MHz Ant 2 Emission



8.1.6 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	802.11b	2412	Ant 1	-48.99	-20	Pass
NVNT	802.11b	2437	Ant 1	-49.78	-20	Pass
NVNT	802.11b	2462	Ant 1	-48.47	-20	Pass
NVNT	802.11b	2412	Ant 2	-48.96	-20	Pass
NVNT	802.11b	2437	Ant 2	-49.28	-20	Pass
NVNT	802.11b	2462	Ant 2	-50.22	-20	Pass
NVNT	802.11g	2412	Ant 1	-45.82	-20	Pass
NVNT	802.11g	2437	Ant 1	-47.39	-20	Pass
NVNT	802.11g	2462	Ant 1	-45.86	-20	Pass
NVNT	802.11g	2412	Ant 2	-43.86	-20	Pass
NVNT	802.11g	2437	Ant 2	-46.72	-20	Pass
NVNT	802.11g	2462	Ant 2	-45.54	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-47.02	-20	Pass
NVNT	802.11n(HT20)	2437	Ant 1	-47.71	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-48.38	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 2	-45.49	-20	Pass
NVNT	802.11n(HT20)	2437	Ant 2	-47.4	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 2	-44.6	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-45.25	-20	Pass
NVNT	802.11n(HT40)	2437	Ant 1	-45.58	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-44.01	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 2	-43.8	-20	Pass
NVNT	802.11n(HT40)	2437	Ant 2	-45.14	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 2	-44.94	-20	Pass

Tx. Spurious NVNT 802.11b 2412MHz Ant 1 Ref

Tx. Spurious NVNT 802.11b 2412MHz Ant 1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.41331 GHz	3.95 dBm		
M2		1	16.704134 GHz	-45.91 dBm		
M3		1	4.907473 GHz	-50.45 dBm		
M4		1	7.05739 GHz	-49.35 dBm		
M5		1	9.640953 GHz	-49.61 dBm		

Tx. Spurious NVNT 802.11b 2437MHz Ant 1 Ref



Tx. Spurious NVNT 802.11b 2437MHz Ant 1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.43661 GHz	3.91 dBm		
M2		1	16.785702 GHz	-45.93 dBm		
M3		1	5.045641 GHz	-49.40 dBm		
M4		1	7.464401 GHz	-49.97 dBm		
M5		1	9.745827 GHz	-49.62 dBm		

Tx. Spurious NVNT 802.11b 2462MHz Ant 1 Ref