



FCC Test Report

Report No: FCS202511069W01

Issued for

Applicant:	Shenzhen Caibo Technology Co.,Ltd
Address:	F4, Building 30, Fifth Industrial Zone,Huaide Cuigang Industrial Park, Fu Yong,Bao'an District, Shenzhen,China
Product Name:	15W Manual Press Wireless Car Charging Holder
Brand Name:	N/A
Model Name:	H6
Series Model:	H6L, Y-H100, Y-H101, Y-H102 ,T240-F, T241-F
FCC ID:	2AXTH-H6
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.fcs-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name.....: Shenzhen Caibo Technology Co.,Ltd

Address.....: F4, Building 30, Fifth Industrial Zone,Huaide Cuigang Industrial Park, Fu Yong,Bao'an District, Shenzhen,China

Manufacture's Name.....: Shenzhen Caibo Technology Co.,Ltd

Address.....: F4, Building 30, Fifth Industrial Zone,Huaide Cuigang Industrial Park, Fu Yong,Bao'an District, Shenzhen,China

Product Description

Product Name.....: 15W Manual Press Wireless Car Charging Holder

Brand Name: N/A

Model Name.....: H6

Series Model.....: Please refer to the first page of the report

Test Standards.....: FCC Rules and Regulations Part 15 Subpart C, Section 209

Test Procedure.....: ANSI C63.10:2020

This device described above has been tested FCS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of FCS, this document may be altered or revised by FCS, personal only, and shall be noted in the revision of the document..

Date of Test.....:

Date (s) of performance of tests.: November 05, 2025 ~ November 21, 2025

Date of Issue.....: November 21, 2025

Test Result.....: Pass

Tested by : Mike Tan
(Mike Tan)

Reviewed by : Nels wang
(Nels Wang)

Approved by : Jack Wang
(Jack Wang)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	9
2.4 EQUIPMENTS LIST	10
3 CONDUCTED EMISSION MEASUREMENT	11
3.1 LIMIT	11
3.2 TEST PROCEDURE	11
3.3 TEST SETUP	12
3.4 TEST RESULTS	13
4. RADIATED EMISSION MEASUREMENT	15
4.1 LIMIT	15
4.2 TEST PROCEDURE	16
4.3 TEST SETUP	17
4.4 TEST RESULTS	18
(30MHZ-1000MHZ)	19
5. 20 DB BANDWIDTH TEST	21
5.1 LIMIT	21
5.2 TEST PROCEDURE	21
5.3 TEST SETUP	21
5.4 TEST RESULTS	22
6. ANTENNA REQUIREMENT	23
6.1 STANDARD REQUIREMENT	23
6.2 EUT ANTENNA	23

**Revision History**

Rev.	Issue Date	Effect Page	Contents
00	November 21, 2025	N/A	N/A

1. SUMMARY OF TEST RESULTS

FCC Rules and Regulations Part 15 Subpart C, Section 209			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.209(a) (f)	Radiated Spurious Emission	PASS	--
15.215(c)	20dB Bandwidth	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2020

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
Laboray Accreditations:	
FCC Test Firm Registration Number:	514908
CNAS Number:	L15566
Designation number:	CN0127
A2LA accreditation number:	5545.01
ISED Number:	25801
CAB ID:	CN0097

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	± 0.71 dB
2	Unwanted Emissions, conducted	± 2.98 dB
3	Conducted Emission (9KHz-150KHz)	± 4.13 dB
4	Conducted Emission (150KHz-30MHz)	± 4.74 dB
5	All emissions,radiated (9KHz -30MHz)	± 3.1 dB
6	All emissions,radiated(<1G) 30MHz-1000MHz	± 3.2 dB
7	All emissions,radiated (1GHz -18GHz)	± 3.66 dB
8	All emissions,radiated (18GHz -40GHz)	± 4.31 dB
9	Occupied bandwidth	± 0.3 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	15W Manual Press Wireless Car Charging Holder
Trade Name	N/A
Model Name	H6
Series Model	Please refer to the first page of the report
Model Difference	PCB board, structure and internal of these model(s) are the same, only differing in Model name and color. So no additional models were tested
Channel List	Please refer to the Note 2.
Operation frequency	115-205kHz
Modulation Type	MSK
Antenna Type	Inductive Loop Antenna with 1.0dBi
Power Supply	Input voltage: 5V2A,9V2.2A,12V2A Output power: 5W/7.5W/10W/15W
Rated voltage	DC 12V by adapter
Test voltage	DC 12V by adapter
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Operation frequency:115KHz~205KHz

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Inductive Loop Antenna	N/A	0.0dBi	Antenna

2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test software: Test manually using a fixed-frequency prototype

The fixed-frequency prototype is used to manually control the EUT to work in continuous TX mode, select the test channel, and the wireless mode is shown in the following table

1. The Mode 1/2/3 product supports 115-205KHz

Tested mode, Description	
Mode	Description
Mode 1	Null Load
Mode 2	Half Load-7.5W
Mode 3	Full Load -15W

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1	electronic load	YBZ	Intelligent wireless charging full function test module	N/A	This is for testing only in report.
2	Adapter	Xiaomi	AD652G	N/A	This is for testing only in report.

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2025.08.25	2026.08.24
Signal Analyzer	R&S	FSV40-N	FCS-E012	2025.08.25	2026.08.24
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2025.08.25	2026.08.24
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2025.08.25	2026.08.24
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2025.08.25	2026.08.24
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2025.08.25	2026.08.24
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2025.08.25	2026.08.24
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2025.08.25	2026.08.24
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E005	2025.08.25	2026.08.24
Testing Software	EZ-EMC(Ver.03A1 CE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2025.08.25	2026.08.24
LISN	R&S	ENV216	FCS-E007	2025.08.25	2026.08.24
LISN	ETS	3810/2NM	FCS-E009	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E008	2025.08.25	2026.08.24
Testing Software	EZ-EMC(Ver.03A1 CE)				

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
Spectrum Analyzer	Keysight	N9020A	FCS-E015	2025.08.25	2026.08.24
Spectrum Analyzer	Agilent	E4447A	MY50180039	2025.08.25	2026.08.24
Spectrum Analyzer	R&S	FSV-40	101499	2025.08.25	2026.08.24
Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)				

3 CONDUCTED EMISSION MEASUREMENT

3.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


3.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP




- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 TEST RESULTS

Temperature:	24.5℃	Relative Humidity:	50%
Test Mode:	Mode 3(Worst)	Test Voltage:	DC 12V from adapter AC 120V/60Hz
Result:	Pass		


L-line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1	*	0.1500	46.71	9.99	56.70	66.00	9.30	peak
2		0.1500	14.96	9.99	24.95	56.00	31.05	AVG
3		0.2310	35.44	9.89	45.33	62.41	17.08	peak
4		0.2310	18.07	9.89	27.96	52.41	24.45	AVG
5		0.5594	21.58	9.92	31.50	56.00	24.50	peak
6		0.5594	13.25	9.92	23.17	46.00	22.83	AVG
7		1.1174	24.55	10.00	34.55	56.00	21.45	peak
8		1.1174	21.46	10.00	31.46	46.00	14.54	AVG
9		3.5700	27.42	10.06	37.48	56.00	18.52	peak
10		3.5700	26.38	10.06	36.44	46.00	9.56	AVG
11		8.0295	29.14	10.08	39.22	60.00	20.78	peak
12		8.0295	27.91	10.08	37.99	50.00	12.01	AVG

Temperature:	24.5°C	Relative Humidity:	50%
Test Mode:	Mode 3(Worst)	Test Voltage:	DC 12V from adapter AC 120V/60Hz
Result:	Pass		

N-line



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
1		0.1500	46.62	9.91	56.53	66.00	9.47	peak
2		0.1500	17.87	9.91	27.78	56.00	28.22	AVG
3		0.2130	36.44	9.83	46.27	63.09	16.82	peak
4		0.2130	22.57	9.83	32.40	53.09	20.69	AVG
5		0.5595	25.38	9.92	35.30	56.00	20.70	peak
6		0.5595	20.21	9.92	30.13	46.00	15.87	AVG
7		1.1174	26.07	9.97	36.04	56.00	19.96	peak
8		1.1174	21.96	9.97	31.93	46.00	14.07	AVG
9		3.5700	27.95	10.07	38.02	56.00	17.98	peak
10	*	3.5700	26.90	10.07	36.97	46.00	9.03	AVG
11		8.0295	28.56	10.10	38.66	60.00	21.34	peak
12		8.0295	27.60	10.10	37.70	50.00	12.30	AVG

Remark:

- 1.All readings are Quasi-Peak.
- 2.Margin = Result (Result =Reading + Factor) - Limit
- 3.Factor= Cable Loss +Antenna Factor-Amplifier Gain

4. RADIATED EMISSION MEASUREMENT

4.1 LIMIT

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009mhz - 1000mhz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- (5) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz




4.4 TEST RESULTS

For spurious emission

(9KHz-30MHz)

Temperature:	24.7°C	Relative Humidity:	61%
Test Voltage:	DC 12V from adapter AC 120V/60Hz	Phase:	Coaxial
Test Mode:	Mode 3(Worst)		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.0142	49.56	10.12	59.68	124.56	-64.88	AV
2	0.0430	39.43	10.22	49.65	114.95	-65.30	AV
3	0.1268	58.53	10.30	68.83	105.84	-37.01	AV
4*	0.1301	69.12	10.39	79.51	105.63	-26.12	AV
5	0.1313	57.57	10.45	68.02	105.35	-37.33	AV
6	0.1736	36.15	12.86	49.01	102.82	-53.81	AV

Remarks:

1. Final Level =Receiver Read level + Factor

2.The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these three bands are based on measurements employing an average detector

Note:Coaxial and Coplanar have both conducted tests, and the report only reflects the worst polarity data

(30MHZ-1000MHZ)

Temperature:	23.7°C	Relative Humidity:	61%
Test Voltage:	DC 12V from adapter AC 120V/60Hz	Phase:	Horizontal
Test Mode:	Mode 3(Worst)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	32.1795	33.27	-8.69	24.58	40.00	-15.42	peak
2	79.5209	52.14	-32.26	19.88	40.00	-20.12	peak
3 *	141.8262	66.51	-32.30	34.21	43.50	-9.29	peak
4	305.6800	64.84	-32.29	32.55	46.00	-13.45	peak
5	541.3725	55.36	-32.10	23.26	46.00	-22.74	peak
6	986.0717	61.20	-31.80	29.40	54.00	-24.60	peak

Remarks:

1. Final Level =Receiver Read level + Factor

Temperature:	22.7°C	Relative Humidity:	61%
Test Voltage:	DC 12V from adapter AC 120V/60Hz	Phase:	Vertical
Test Mode:	Mode 3(Worst)		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	32.4059	43.65	-8.83	34.82	40.00	-5.18	peak
2	77.3212	64.01	-32.25	31.76	40.00	-8.24	peak
3	135.5062	68.52	-32.30	36.22	43.50	-7.28	peak
4	287.9904	54.32	-32.30	22.02	46.00	-23.98	peak
5	609.9217	60.75	-32.09	28.66	46.00	-17.34	peak
6	1000.0000	60.46	-31.80	28.66	54.00	-25.34	peak

Remarks:

1. Final Level =Receiver Read level + Factor

5. 20 DB BANDWIDTH TEST

5.1 LIMIT

According to 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation

5.2 TEST PROCEDURE


- Check the calibration of the measuring instrument using either an internal calibrator or a
 - a. known signal from an external generator
 - b. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
 - c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

5.3 TEST SETUP



5.4 TEST RESULTS

Temperature:	24.5°C	Relative Humidity:	50%
Test Mode:	Mode 3(Worst)	Test Voltage:	DC 12V from adapter AC 120V/60Hz
Frequency (KHz)	130.00	20dB Bandwidth (Hz)	2749
		Result	PASS



6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The antennas used for this product is Inductive Loop Antenna and no other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 0.0dBi.

*****END OF THE REPORT*****