

Radio frequency radiation exposure evaluation: portable devices

RESULT :

Pass

Test Specification

Test item	: 2.4GHz remote control car
Identification / Type No.	: G03094R, G5002R, G5005R, G5006R, G03094R01, G03094R02, G03094R03, G03094R04, G03094R05, G03094R06, G03094R07, G03094R08
FCC ID	: 2AXV4-G03094R
Test standard	: CFR47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 D04

Calculation Method according to KDB 447498 D04

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

For 2.4G SRD

$$E.I.R.P = 86.67 - 95.2 = -8.53\text{dBm}$$

$$ERP = -8.53 - 2.15 = -10.68\text{dBm}$$

FCC Measurement Record:

Test Mode	Conducted Power (dBm)	Conducted Power (mW)	ERP (dBm)	ERP (mW)	Minimum Separation Distances (mm)	Limit (mW)
2.4GHz SRD	----	----	-10.68	0.085	5	2.72

Hence the EUT is excluded from SAR evaluation if the distance between the antenna and the human body is equal or above one of the minimum distances depicted in the tables above, depending on the wireless protocol in use, in accordance with FCC KDB Publication 447498 D04.