

TEST REPORT

Product Name : Azzaro Royale Headphone S27 DDP, Azzaro
Royale Headphone S27 FCA
Model Number : LH072400/DDP, LH072401/FCA
FCC ID : 2AXWJ-LH0724

Prepared for : ADM Promotions (Shanghai) Co., Ltd.
Address : Room 1205B, SOHO Donghai Plaza, Tongren Road,
Jing' an District, Shanghai

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : 1&2/F., Building 2, Zone A, Zhongda Marine
Biotechnology Research and Development Base,
No.9, Xincheng Avenue, Songshanhu High-technology
Industrial Development Zone, Dongguan, Guangdong,
China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2606220045E00202R
Date of sample receipt : June 22, 2026
Date(s) of Tests : June 22, 2026 to July 08, 2026
Date of issue : July 08, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : ADM Promotions (Shanghai) Co., Ltd.
Address : Room 1205B, SOHO Donghai Plaza, Tongren Road, Jing' an District, Shanghai
Manufacturer : ADM Promotions (Shanghai) Co., Ltd.
Address : Room 1205B, SOHO Donghai Plaza, Tongren Road, Jing' an District, Shanghai
EUT : Azzaro Royale Headphone S27 DDP, Azzaro Royale Headphone S27 FCA
Model Name : LH072400/DDP, LH072401/FCA
Trademark : AZZARO

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1091	PASS

The above equipment was tested by EMTEK (DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1091.

The test results of this report relate only to the tested sample identified in this report

Date of Test : June 22, 2026 to July 08, 2026


Prepared by :


Jessica Zhang /Editor

Reviewer :


Warren Deng /Supervisor

Approve & Authorized Signer :


Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2606220045E00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Azzaro Royale Headphone S27 DDP, Azzaro Royale Headphone S27 FCA
Model Number:	LH072400/DDP, LH072401/FCA Note: All models are identical, with the sole distinction being the model name. Model LH072400/DDP was chosen to complete all testing.
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	-3.19 dBm(0.000480 W)
Antenna Gain:	0 dBi
Power supply:	DC 5V from USB DC 3.7V from battery
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 0 dBi

When a single module works, the measurement results are as follows:

BT1

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	E.I.R.P (dBm)	Tune upPower (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK	-4.21	-4.21	-5±1	-4	0.1234004	3
2441	GFSK	-4.65	-4.65	-5±1	-4	0.1243981	3
2480	GFSK	-4.67	-4.67	-5±1	-4	0.1253880	3
2402	Π/4-DQPSK	-3.71	-3.71	-4±1	-3	0.1553519	3
2441	Π/4-DQPSK	-3.90	-3.90	-4±1	-3	0.1566080	3
2480	Π/4-DQPSK	-3.97	-3.97	-4±1	-3	0.1578541	3
2402	8-DPSK	-3.19	-3.19	-4±1	-3	0.1553519	3
2441	8-DPSK	-3.68	-3.68	-4±1	-3	0.1566080	3
2480	8-DPSK	-3.64	-3.64	-4±1	-3	0.1578541	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***