











11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup



11.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


11.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.9.21
Test Power Supply:	DC 12V	Sample Number:	S26090213-002


Mode	Freq. (MHz)	Verdict
GFSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
π /4-DQPSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass

11.5. Test graphs







DH5_Ant1_2441_0~Reference




DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500




DH5_Ant1_2480_0~Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500




2DH5_Ant1_2402_0~Reference





2DH5_Ant1_2402_30~1000




2DH5_Ant1_2402_1000~26500









3DH5_Ant1_2402_0~Reference




3DH5_Ant1_2402_30~1000




3DH5_Ant1_2402_1000~26500







3DH5_Ant1_2480_0~Reference



3DH5_Ant1_2480_30~1000




3DH5_Ant1_2480_1000~26500



12. Duty cycle

12.1. Block diagram of test setup



12.2. Limit

Just for Report.

12.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
$$\text{Duty cycle} = \text{Pulse's on time} / \text{Burst cycle}$$


12.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.9.21
Test Power Supply:	DC 12V	Sample Number:	S26090213-002


Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
DH5	Ant1	2402	2.90	3.76	77.13	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.90	3.75	77.33	1.12
2DH5	Ant1	2402	2.89	3.75	77.07	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.89	3.75	77.07	1.13
3DH5	Ant1	2402	2.89	3.75	77.07	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.89	3.75	77.07	1.13

12.5. Test graphs







2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


14. Radiated Emission


14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2027/09/13
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2027/09/13
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2027/09/13
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2027/09/14
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2027/09/14
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-5M	DDT-ZC03800	2027/09/14
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2027/07/08
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2027/07/10
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2027/07/10
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2027/07/10
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04

PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2027/09/14
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/

14.2. Block diagram of test setup





14.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9 kHz to 30 MHz, so below final test was performed with frequency range from 30 MHz to 25 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz, so the final test was performed with frequency range from 30 MHz to 25 GHz and recorded in below.

(10) 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

(12) The worst simultaneous case and was recorded.

14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-17

Tested By:

Zhang Yibo

Test Mode:

TX DH5 Mode

Power Supply:

DC 12V

Condition:

Temp:21.1°C;Humi:48.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26090213-1E\FCC BELOW 1G\1

Memo:

Sample Number:S26090213-002



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	32.633	35.26	10.70	3.82	17.48	40.00	22.52	QP	Horizontal
2	36.662	32.6	11.93	3.87	16.10	40.00	23.90	QP	Horizontal
3	55.798	29.38	12.96	4.03	14.07	40.00	25.93	QP	Horizontal
4	239.888	34.19	12.20	5.04	19.03	46.00	26.97	QP	Horizontal
5	287.860	30.42	13.16	5.23	16.41	46.00	29.59	QP	Horizontal
6	359.764	30.25	14.80	5.54	18.13	46.00	27.87	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-17

Tested By:

Zhang Yibo

Test Mode:

TX DH5 Mode

Power Supply:

DC 12V

Condition:

Temp:21.1°C;Humi:48.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26090213-1E\FCC BELOW 1G\2

Memo:

Sample Number:S26090213-002



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.491	37.07	10.85	3.83	19.45	40.00	20.55	QP	Vertical
2	36.431	32.67	11.82	3.87	16.06	40.00	23.94	QP	Vertical
3	46.109	32.15	13.79	3.96	17.60	40.00	22.40	QP	Vertical
4	65.978	29.19	11.11	4.13	12.13	40.00	27.87	QP	Vertical
5	104.290	27.01	11.73	4.32	10.76	43.50	32.74	QP	Vertical
6	239.888	29.3	12.20	5.04	14.14	46.00	31.86	QP	Vertical

Note:


1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2402MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\1
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3886.600	49.84	31.57	-40.83	40.58	74.00	33.42	PK	Horizontal
2	4802.900	58.91	33.21	-41.30	50.82	74.00	23.18	PK	Horizontal
3	7364.800	48.82	37.34	-39.71	46.45	74.00	27.55	PK	Horizontal
4	8410.300	48.37	38.14	-38.99	47.52	74.00	26.48	PK	Horizontal
5	10707.000	46.98	40.00	-35.71	51.27	74.00	22.73	PK	Horizontal
6	12118.000	45.81	39.90	-34.81	50.90	74.00	23.10	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4802.900	56.75	33.21	-41.30	48.66	54.00	5.34	AV	Horizontal
2	10707.000	33.75	40.00	-35.71	38.04	54.00	15.96	AV	Horizontal
3	12118.000	33.99	39.90	-34.81	39.08	54.00	14.92	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2402MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT12
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3861.100	50.20	31.52	-40.88	40.84	74.00	33.16	PK	Vertical
2	4804.600	59.11	33.22	-41.30	51.03	74.00	22.97	PK	Vertical
3	7380.100	49.45	37.28	-39.72	47.01	74.00	26.99	PK	Vertical
4	8396.700	48.21	38.09	-39.01	47.29	74.00	26.71	PK	Vertical
5	10773.300	45.98	40.00	-35.45	50.53	74.00	23.47	PK	Vertical
6	12106.100	46.11	39.90	-34.74	51.27	74.00	22.73	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4803.943	56.87	33.22	-41.30	48.79	54.00	5.21	AV	Vertical
2	10773.300	34.61	40.00	-35.45	39.16	54.00	14.84	AV	Vertical
3	12106.100	34.38	39.90	-34.74	39.54	54.00	14.46	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2441MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\3
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3862.800	50.24	31.53	-40.88	40.89	74.00	33.11	PK	Horizontal
2	4882.800	56.10	33.47	-41.27	48.30	74.00	25.70	PK	Horizontal
3	7609.600	48.98	37.22	-39.81	46.39	74.00	27.61	PK	Horizontal
4	8269.200	48.86	37.94	-39.11	47.69	74.00	26.31	PK	Horizontal
5	11159.200	46.39	39.82	-35.14	51.07	74.00	22.93	PK	Horizontal
6	12366.200	46.59	39.73	-34.61	51.71	74.00	22.29	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4882.800	54.09	33.47	-41.27	46.29	54.00	7.71	AV	Horizontal
2	11159.200	34.61	39.82	-35.14	39.29	54.00	14.71	AV	Horizontal
3	12366.200	34.09	39.73	-34.61	39.21	54.00	14.79	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2441MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT4
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3818.600	50.40	31.31	-40.97	40.74	74.00	33.26	PK	Vertical
2	4882.800	54.34	33.47	-41.27	46.54	74.00	27.46	PK	Vertical
3	7324.000	50.04	37.56	-39.68	47.92	74.00	26.08	PK	Vertical
4	8410.300	48.13	38.14	-38.99	47.28	74.00	26.72	PK	Vertical
5	10691.700	47.62	39.98	-35.76	51.84	74.00	22.16	PK	Vertical
6	12316.900	45.90	39.78	-35.00	50.68	74.00	23.32	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10691.700	35.51	39.98	-35.76	39.73	54.00	14.27	AV	Vertical
2	12316.900	35.37	39.78	-35.00	40.15	54.00	13.85	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2480MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\5
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3942.700	49.75	31.69	-41.08	40.36	74.00	33.64	PK	Horizontal
2	4938.900	49.45	33.66	-41.01	42.10	74.00	31.90	PK	Horizontal
3	7414.100	49.56	37.17	-39.77	46.96	74.00	27.04	PK	Horizontal
4	8296.400	49.11	37.99	-39.09	48.01	74.00	25.99	PK	Horizontal
5	10603.300	46.22	39.81	-35.93	50.10	74.00	23.90	PK	Horizontal
6	12420.600	45.90	39.72	-34.52	51.10	74.00	22.90	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8296.400	36.91	37.99	-39.09	35.81	54.00	18.19	AV	Horizontal
2	10603.300	35.17	39.81	-35.93	39.05	54.00	14.95	AV	Horizontal
3	12420.600	35.10	39.72	-34.52	40.30	54.00	13.70	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-17 **Tested By:** Cao Jie
Test Mode: TX DH5 2480MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\6
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3854.300	50.75	31.51	-40.90	41.36	74.00	32.64	PK	Vertical
2	4959.300	51.40	33.74	-40.89	44.25	74.00	29.75	PK	Vertical
3	7439.600	50.13	37.12	-39.84	47.41	74.00	26.59	PK	Vertical
4	8124.700	48.64	37.90	-39.17	47.37	74.00	26.63	PK	Vertical
5	10781.800	46.33	40.00	-35.42	50.91	74.00	23.09	PK	Vertical
6	12129.900	45.51	39.90	-34.89	50.52	74.00	23.48	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10781.800	34.60	40.00	-35.42	39.18	54.00	14.82	AV	Vertical
2	12129.900	34.35	39.90	-34.89	39.36	54.00	14.64	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-19 **Tested By:** Cao Jie
Test Mode: TX DH5 2402MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\19
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	21445.977	50.42	38.44	3.87	41.88	74.00	32.12	PK	Horizontal
2	23476.499	51.23	39.20	4.69	44.30	74.00	29.70	PK	Horizontal
3	24875.839	50.90	39.54	4.72	45.28	74.00	28.72	PK	Horizontal
4	32761.568	47.17	41.50	5.26	46.01	74.00	27.99	PK	Horizontal
5	37015.993	49.45	42.92	6.01	49.04	74.00	24.96	PK	Horizontal
6	39164.693	47.50	46.03	6.61	49.95	74.00	24.05	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	37015.993	42.43	42.92	6.01	42.02	54.00	11.98	AV	Horizontal
2	39164.693	41.51	46.03	6.61	43.96	54.00	10.04	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-19 **Tested By:** Cao Jie
Test Mode: TX DH5 2402MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.2°C;Humi:52.4% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\20
Memo: Sample Number:S26090213-002 Power Setting:6

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	20637.529	48.93	38.29	3.80	40.81	74.00	33.19	PK	Vertical
2	23387.865	51.27	39.22	4.66	44.21	74.00	29.79	PK	Vertical
3	25238.432	50.26	39.53	4.81	44.71	74.00	29.29	PK	Vertical
4	32844.830	47.00	41.54	5.29	45.91	74.00	28.09	PK	Vertical
5	36819.924	49.03	42.88	6.19	48.80	74.00	25.20	PK	Vertical
6	39511.171	47.20	46.31	6.64	49.44	74.00	24.56	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36819.924	42.37	42.88	6.19	42.14	54.00	11.86	AV	Vertical
2	39511.171	41.59	46.31	6.64	43.83	54.00	10.17	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15. Band Edge Compliance

15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2027/09/13
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2027/09/13
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2027/09/13
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2027/09/14
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2027/09/14
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-5M	DDT-ZC03800	2027/09/14
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2027/07/08
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2027/07/10
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2027/07/10
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2027/07/10
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209 limits, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

15.6. Test result

PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\21

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2377.720	44.69	28.16	-26.14	46.71	74.00	27.29	PK	Horizontal
2	2390.000	42.10	28.18	-26.15	44.13	74.00	29.87	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\22

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2361.750	43.72	28.12	-26.14	45.70	74.00	28.30	PK	Vertical
2	2390.000	41.02	28.18	-26.15	43.05	74.00	30.95	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\23

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2372.740	44.09	28.15	-26.14	46.10	74.00	27.90	PK	Horizontal
2	2390.000	42.77	28.18	-26.15	44.80	74.00	29.20	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\24

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2379.430	44.19	28.16	-26.14	46.21	74.00	27.79	PK	Vertical
2	2390.000	40.59	28.18	-26.15	42.62	74.00	31.38	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\25

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2378.350	44.10	28.16	-26.14	46.12	74.00	27.88	PK	Horizontal
2	2390.000	41.20	28.18	-26.15	43.23	74.00	30.77	PK	Horizontal

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\26

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2358.950	43.90	28.12	-26.14	45.88	74.00	28.12	PK	Vertical
2	2390.000	41.01	28.18	-26.15	43.04	74.00	30.96	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\27

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.43	28.60	-26.14	43.89	74.00	30.11	PK	Horizontal
2	2490.187	43.90	28.64	-26.14	46.40	74.00	27.60	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\28

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.66	28.60	-26.14	44.12	74.00	29.88	PK	Vertical
2	2486.857	44.21	28.62	-26.14	46.69	74.00	27.31	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\29

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.40	28.60	-26.14	43.86	74.00	30.14	PK	Horizontal
2	2488.708	44.08	28.63	-26.14	46.57	74.00	27.43	PK	Horizontal

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\30

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.58	28.60	-26.14	44.04	74.00	29.96	PK	Vertical
2	2484.790	45.55	28.61	-26.14	48.02	74.00	25.98	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\31

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.26	28.60	-26.14	43.72	74.00	30.28	PK	Horizontal
2	2489.251	44.43	28.64	-26.14	46.93	74.00	27.07	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-20

Tested By:

Liang Rijing

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.2°C;Humi:52.4%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q26090213-1E\FCC ABOVE 1G BT\32

Memo:

Sample Number:S26090213-002 Power Setting:6



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	41.37	28.60	-26.14	43.83	74.00	30.17	PK	Vertical
2	2488.255	44.18	28.63	-26.14	46.67	74.00	27.33	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

16. Power Line Conducted Emissions

16.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
/	/	/	/	/

16.2. Block diagram of test setup



16.3. Limits

Frequency	Quasi-Peak Level dB(uV)	Average Level dB(uV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

16.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

16.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “---” means Peak detection; “---” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

16.7. Test data

Not applicable. EUT is DC powered.

18. Photos of the EUT

Please refer to DDT-Q26090213-1E appendix I

-----End Report-----