

# SAR Test Report

Report No.: AGC10211210904FH01

**FCC ID** : 2AXX5BS101S

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Tablet PC

**BRAND NAME** : Brightside

**MODEL NAME** : BS101, BS102, BS103, BS104, BS105, BS106, BS107, BS108, BS109

**APPLICANT** : Shenzhen Jinhengzhi Technology Co., Ltd.

**DATE OF ISSUE** : Oct. 26, 2021

**STANDARD(S)** : IEEE Std. 1528:2013  
FCC 47 CFR Part 2&2.1093:2013  
IEEE Std C95.1™-2005  
IEC 62209-1: 2016

**REPORT VERSION** : V1.0

Attestation of Global Compliance(Shenzhen) Co., Ltd.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



### Report Revise Record

| Report Version | Revise Time | Issued Date   | Valid Version | Notes           |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0           | /           | Oct. 26, 2021 | Valid         | Initial Release |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## Test Report

|                       |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| Applicant Name        | Shenzhen Jinhengzhi Technology Co., Ltd.                                                          |
| Applicant Address     | 3307, TOWER A, WORLD TRADE PLAZA, FUTIAN, SHENZHEN                                                |
| Manufacturer Name     | Shenzhen Jinhengzhi Technology Co., Ltd.                                                          |
| Manufacturer Address  | 3307, TOWER A, WORLD TRADE PLAZA, FUTIAN, SHENZHEN                                                |
| Factory Name          | Shenzhen Jinhengzhi Technology Co., Ltd.                                                          |
| Factory Address       | 3307, TOWER A, WORLD TRADE PLAZA, FUTIAN, SHENZHEN                                                |
| Product Designation   | Tablet PC                                                                                         |
| Brand Name            | Brightside                                                                                        |
| Model Name            | BS101, BS102, BS103, BS104, BS105, BS106, BS107, BS108, BS109                                     |
| Different Description | All the models are the same, only different in model names.                                       |
| EUT Voltage           | DC 3.85V by battery                                                                               |
| Applicable Standard   | IEEE Std. 1528:2013<br>FCC 47 CFR Part 2§2.1093:2013<br>IEEE Std C95.1™-2005<br>IEC 62209-1: 2016 |
| Test Date             | Oct. 12, 2021 to Oct. 14, 2021                                                                    |
| Report Template       | AGCRT-US-3G3/SAR (2021-04-20)                                                                     |

Note: The results of testing in this report apply to the product/system which was tested only.

*Thea Huang*

Prepared By

Thea Huang (Project Engineer)

Oct. 14, 2021

*Calvin Liu*

Reviewed By

Calvin Liu (Reviewer)

Oct. 26, 2021

*Max Zhang*

Approved By

Max Zhang (Authorized Officer)

Oct. 26, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## TABLE OF CONTENTS

|                                                                                               |           |
|-----------------------------------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF MAXIMUM SAR VALUE .....</b>                                                  | <b>5</b>  |
| <b>2. GENERAL INFORMATION.....</b>                                                            | <b>6</b>  |
| 2.1. EUT DESCRIPTION.....                                                                     | 6         |
| <b>3. SAR MEASUREMENT SYSTEM.....</b>                                                         | <b>8</b>  |
| 3.1. THE SATIMO SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS ..... | 8         |
| 3.2. COMOSAR E-FIELD PROBE .....                                                              | 9         |
| 3.3. ROBOT.....                                                                               | 9         |
| 3.4. VIDEO POSITIONING SYSTEM .....                                                           | 10        |
| 3.5. DEVICE HOLDER .....                                                                      | 10        |
| 3.6. SAM TWIN PHANTOM.....                                                                    | 11        |
| <b>4. SAR MEASUREMENT PROCEDURE.....</b>                                                      | <b>12</b> |
| 4.1. SPECIFIC ABSORPTION RATE (SAR).....                                                      | 12        |
| 4.2. SAR MEASUREMENT PROCEDURE .....                                                          | 13        |
| 4.3. RF EXPOSURE CONDITIONS .....                                                             | 15        |
| <b>5. TISSUE SIMULATING LIQUID.....</b>                                                       | <b>18</b> |
| 5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID.....                                     | 18        |
| 5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS .....                            | 18        |
| 5.3. TISSUE CALIBRATION RESULT .....                                                          | 19        |
| <b>6. SAR SYSTEM CHECK PROCEDURE .....</b>                                                    | <b>20</b> |
| 6.1. SAR SYSTEM CHECK PROCEDURES .....                                                        | 20        |
| 6.2. SAR SYSTEM CHECK.....                                                                    | 21        |
| <b>7. EUT TEST POSITION.....</b>                                                              | <b>22</b> |
| 7.1. BODY WORN POSITION .....                                                                 | 22        |
| <b>8. SAR EXPOSURE LIMITS .....</b>                                                           | <b>23</b> |
| <b>9. TEST FACILITY .....</b>                                                                 | <b>24</b> |
| <b>10. TEST EQUIPMENT LIST .....</b>                                                          | <b>25</b> |
| <b>11. MEASUREMENT UNCERTAINTY .....</b>                                                      | <b>26</b> |
| <b>12. CONDUCTED POWER MEASUREMENT.....</b>                                                   | <b>29</b> |
| <b>13. TEST RESULTS.....</b>                                                                  | <b>37</b> |
| 13.1. SAR TEST RESULTS SUMMARY.....                                                           | 37        |
| <b>APPENDIX A. SAR SYSTEM CHECK DATA .....</b>                                                | <b>47</b> |
| <b>APPENDIX B. SAR MEASUREMENT DATA.....</b>                                                  | <b>53</b> |
| <b>APPENDIX C. TEST SETUP PHOTOGRAPHS.....</b>                                                | <b>65</b> |
| <b>APPENDIX D. CALIBRATION DATA .....</b>                                                     | <b>68</b> |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



## 1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

| Frequency Band            | Highest Reported 1g-SAR(W/kg)  |                              | SAR Test Limit (W/kg) |
|---------------------------|--------------------------------|------------------------------|-----------------------|
|                           | Body-worn(with 0mm separation) | Hotspot(with 0mm separation) |                       |
| GSM 850                   | 0.361                          | 0.361                        | 1.6                   |
| PCS 1900                  | 0.047                          | 0.047                        |                       |
| UMTS Band II              | 0.353                          | 0.353                        |                       |
| UMTS Band V               | 0.903                          | 0.903                        |                       |
| WIFI 2.4G                 | 0.675                          | 0.675                        |                       |
| Simultaneous Reported SAR | 1.578                          |                              |                       |
| SAR Test Result           | PASS                           |                              |                       |

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/kg) specified in IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:2005 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 648474 D04 Handset SAR v01r03
- KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04
- KDB 941225 D01 3G SAR Procedures v03r01
- KDB 941225 D06 Hotspot Mode v02r01
- KDB 248227 D01 802 11 Wi-Fi SAR v02r02
- KDB 616217 D04 SAR evaluation requirements for laptop, notebook, notebook and tablet computers

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 2. GENERAL INFORMATION

### 2.1. EUT Description

| General Information     |                                                                                                                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Designation     | Tablet PC                                                                                                                                                                                        |
| Test Model              | BS101                                                                                                                                                                                            |
| Hardware Version        | ZL80_MB_V5.3                                                                                                                                                                                     |
| Software Version        | ZL80V5.3G_JH08_O_V0.1_20210915                                                                                                                                                                   |
| Device Category         | Portable                                                                                                                                                                                         |
| RF Exposure Environment | Uncontrolled                                                                                                                                                                                     |
| Antenna Type            | Internal                                                                                                                                                                                         |
| GSM and GPRS            |                                                                                                                                                                                                  |
| Support Band            | <input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 <input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800                |
| GPRS Type               | Class B                                                                                                                                                                                          |
| GPRS Class              | Class 12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)                                                                                                                                                     |
| TX Frequency Range      | GSM 850 : 820-850MHz;; PCS 1900: 1850-1910MHz;                                                                                                                                                   |
| RX Frequency Range      | GSM 850 : 869~894MHz; PCS 1900: 1930~1990MHz                                                                                                                                                     |
| Release Version         | R99                                                                                                                                                                                              |
| Type of modulation      | GMSK for GSM/GPRS                                                                                                                                                                                |
| Antenna Gain            | GSM850: 0.7dBi ;PCS1900: 0.85dBi                                                                                                                                                                 |
| Max. Average Power      | GSM850: 32.27dBm ;PCS1900: 30.20dBm                                                                                                                                                              |
| WCDMA                   |                                                                                                                                                                                                  |
| Support Band            | <input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V<br><input type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band VIII |
| HS Type                 | HSPA(HSUPA/HSDPA)                                                                                                                                                                                |
| TX Frequency Range      | WCDMA FDD Band II: 1850-1910MHz; WCDMA FDD Band V: 824-849MHz                                                                                                                                    |
| RX Frequency Range      | WCDMA FDD Band II: 1930-1990MHz; WCDMA FDD Band V: 869-894MHz                                                                                                                                    |
| Release Version         | Rel-6                                                                                                                                                                                            |
| Type of modulation      | HSDPA:QPSK/16QAM; HSUPA:BPSK; WCDMA:QPSK                                                                                                                                                         |
| Antenna Gain            | Band II: 0.85dBi; Band V: 0.7dBi                                                                                                                                                                 |
| Max. Average Power      | Band II: 22.55dBm; Band V: 22.59dBm                                                                                                                                                              |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



### EUT Description (Continue)

|                     |                                                                                                                                                                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Bluetooth</b>    |                                                                                                                                                                                                                                     |
| Bluetooth Version   | <input type="checkbox"/> V2.0 <input type="checkbox"/> V2.1 <input type="checkbox"/> V2.1+EDR <input type="checkbox"/> V3.0 <input type="checkbox"/> V3.0+HS <input checked="" type="checkbox"/> V4.0 <input type="checkbox"/> V4.1 |
| Operation Frequency | 2402~2480MHz                                                                                                                                                                                                                        |
| Type of modulation  | BR <input checked="" type="checkbox"/> GFSK, EDR <input checked="" type="checkbox"/> π/4-DQPSK, <input checked="" type="checkbox"/> 8DPSK<br>BLE <input checked="" type="checkbox"/> GFSK 1Mbps <input type="checkbox"/> GFSK 2Mbps |
| Avg. Burst Power    | BR&EDR: 3.74dBm; BLE: 4.20dBm                                                                                                                                                                                                       |
| Antenna Gain        | 0.42dBi                                                                                                                                                                                                                             |
| <b>WIFI</b>         |                                                                                                                                                                                                                                     |
| WIFI Specification  | <input type="checkbox"/> 802.11a <input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20) <input checked="" type="checkbox"/> 802.11n(40)            |
| Operation Frequency | 2412~2462MHz                                                                                                                                                                                                                        |
| Avg. Burst Power    | 11b:15.14dBm,11g:10.73dBm,11n(20):9.58dBm,11n(40):6.60dBm                                                                                                                                                                           |
| Antenna Gain        | 0.42dBi                                                                                                                                                                                                                             |
| <b>Accessories</b>  |                                                                                                                                                                                                                                     |
| Battery             | Brand name: N/A<br>Model No. : 3368145<br>Voltage and Capacitance: 3.85V & 5000mAh                                                                                                                                                  |
| Earphone            | Brand name: N/A<br>Model No. : N/A                                                                                                                                                                                                  |

- Note: 1. CMU200 can measure the average power and Peak power at the same time  
2. The sample used for testing is end product.  
3. The test sample has no any deviation to the test method of standard mentioned in page 1.


|         |                                                                                                  |
|---------|--------------------------------------------------------------------------------------------------|
| Product | Type                                                                                             |
|         | <input checked="" type="checkbox"/> Production unit <input type="checkbox"/> Identical Prototype |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



### 3. SAR MEASUREMENT SYSTEM

#### 3.1. The SATIMO system used for performing compliance tests consists of following items



The COMOSAR system for performing compliance tests consists of the following items:

- The PC. It controls most of the bench devices and stores measurement data. A computer running WinXP and the Opensar software.
- The E-Field probe. The probe is a 3-axis system made of 3 distinct dipoles. Each dipole returns a voltage in function of the ambient electric field.
- The Keithley multimeter measures each probe dipole voltages.
- The SAM phantom simulates a human head. The measurement of the electric field is made inside the phantom.
- The liquids simulate the dielectric properties of the human head tissues.
- The network emulator controls the mobile phone under test.
- The validation dipoles are used to measure a reference SAR. They are used to periodically check the bench to make sure that there is no drift of the system characteristics over time.
- The phantom, the device holder and other accessories according to the targeted measurement.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



### 3.2. COMOSAR E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SATIMO. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SATIMO conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528 and relevant KDB files.) The calibration data are in Appendix D.

#### Isotropic E-Field Probe Specification

|                           |                                                                                                                                                                                                            |                                                                                      |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>              | SSE5                                                                                                                                                                                                       |  |
| <b>Manufacture</b>        | MVG                                                                                                                                                                                                        |                                                                                      |
| <b>Identification No.</b> | SN 03/18 EP327                                                                                                                                                                                             |                                                                                      |
| <b>Frequency</b>          | 0.15GHz-3GHz<br>Linearity:±0.08dB(150MHz-3GHz)                                                                                                                                                             |                                                                                      |
| <b>Dynamic Range</b>      | 0.01W/kg-100W/kg<br>Linearity:±0.08dB                                                                                                                                                                      |                                                                                      |
| <b>Dimensions</b>         | Overall length:330mm<br>Length of individual dipoles:4.5mm<br>Maximum external diameter:8mm<br>Probe Tip external diameter:5mm<br>Distance between dipoles/ probe extremity:2.7mm                          |                                                                                      |
| <b>Application</b>        | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%. |                                                                                      |

### 3.3. Robot

The COMOSAR system uses the KUKA robot from SATIMO SA (France).For the 6-axis controller COMOSAR system, the KUKA robot controller version from SATIMO is used.

The XL robot series have many features that are important for our application:

- ☐ High precision (repeatability 0.02 mm)
- ☐ High reliability (industrial design)
- ☐ Jerk-free straight movements
- ☐ Low ELF interference (the closed metallic construction shields against motor control fields)
- ☐ 6-axis controller




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




### 3.4. Video Positioning System

The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts. The camera is piloted by the main computer with firewire link. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip. The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



### 3.5. Device Holder

The COMOSAR device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles. The COMOSAR device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon_r = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



### 3.6. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- ☐ Left head
- ☐ Right head
- ☐ Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### ELLI39 Phantom

The Flat phantom is a fiberglass shellphantom with 2mm+/- 0.2 mm shell thickness. It has only one measurement area for Flat phantom



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 4. SAR MEASUREMENT PROCEDURE

### 4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element(dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

Where

|                |                                                                                      |
|----------------|--------------------------------------------------------------------------------------|
| SAR            | is the specific absorption rate in watts per kilogram;                               |
| E              | is the r.m.s. value of the electric field strength in the tissue in volts per meter; |
| σ              | is the conductivity of the tissue in siemens per metre;                              |
| ρ              | is the density of the tissue in kilograms per cubic metre;                           |
| c <sub>h</sub> | is the heat capacity of the tissue in joules per kilogram and Kelvin;                |

$\left. \frac{dT}{dt} \right|_{t=0}$  is the initial time derivative of temperature in the tissue in kelvins per second

## 4.2. SAR Measurement Procedure

### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties,

### Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in SATIMO software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

|                                                                                                        | $\leq 3 \text{ GHz}$                                                                                                                                                                                                                                                   | $> 3 \text{ GHz}$                                                                  |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | $5 \pm 1 \text{ mm}$                                                                                                                                                                                                                                                   | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$                         |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                                             |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$                 | $\leq 2 \text{ GHz}: \leq 15 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 12 \text{ mm}$                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 12 \text{ mm}$<br>$4 - 6 \text{ GHz}: \leq 10 \text{ mm}$ |
|                                                                                                        | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                                    |

### Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g and 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                           |                                                                                             |                                                                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$                                                                                                                                                                                                                                                                                                                                                                                                             |                                           | $\leq 2 \text{ GHz}: \leq 8 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$         | $3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$<br>$4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$                                          |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                                                                                                                                                                                                                    | uniform grid: $\Delta z_{\text{Zoom}}(n)$ | $\leq 5 \text{ mm}$                                                                         | $3 - 4 \text{ GHz}: \leq 4 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 3 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$    |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | graded grid                               | $\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $3 - 4 \text{ GHz}: \leq 3 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                           | $\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$                                                                                  |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | x, y, z                                   | $\geq 30 \text{ mm}$                                                                        | $3 - 4 \text{ GHz}: \geq 28 \text{ mm}$<br>$4 - 5 \text{ GHz}: \geq 25 \text{ mm}$<br>$5 - 6 \text{ GHz}: \geq 22 \text{ mm}$ |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.<br>* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$ , $\leq 8 \text{ mm}$ , $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                           |                                                                                             |                                                                                                                               |

## Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### 4.3. RF Exposure Conditions


Test Configuration and setting:

The EUT is a model of GSM/WCDMA Portable Mobile Station (MS). It supports GSM/GPRS, WCDMA/HSPA, BT, WIFI, and support hot spot mode.

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator were established by air link. The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the emulator antenna is at least 30db smaller than the output power of EUT.

For WLAN testing, the EUT is configured with the WLAN continuous TX tool through engineering command.

#### Antenna Location: (the back view)



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### SAR Test Exclusion Consideration for Adjacent Edges

Per KDB 447498 D01 cl. 4.3.1:

a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR.

b) For 100 MHz to 6 GHz and test separation distances  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

1)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz

2)  $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

| 1-g SAR test exclusion thresholds for WWAN |                                   |              |                |                |               |
|--------------------------------------------|-----------------------------------|--------------|----------------|----------------|---------------|
| Test position                              |                                   | Edge 1 (5mm) | Edge 2 (162mm) | Edge 3 (145mm) | Edge 4 (27mm) |
| Test Mode                                  |                                   |              |                |                |               |
| GSM850                                     | SAR test exclusion thresholds(mW) | <b>16.28</b> | <b>796.58</b>  | <b>700.39</b>  | <b>87.92</b>  |
|                                            | SAR Max. Avg. Burst Power(mW)     | 326.59       | 326.59         | 326.59         | 326.59        |
|                                            | SAR required (Yes/No)             | Yes          | No             | No             | Yes           |
| PCS1900                                    | SAR test exclusion thresholds(mW) | <b>11.03</b> | <b>1230.28</b> | <b>1060.28</b> | <b>59.55</b>  |
|                                            | SAR Max. Avg. Burst Power(mW)     | 188.36       | 188.36         | 188.36         | 188.36        |
|                                            | SAR required (Yes/No)             | Yes          | No             | No             | Yes           |
| WCDMA Band II                              | SAR test exclusion thresholds(mW) | <b>11.02</b> | <b>1230.21</b> | <b>1060.21</b> | <b>59.51</b>  |
|                                            | SAR Max. Avg. Burst Power(mW)     | 179.89       | 179.89         | 179.89         | 179.89        |
|                                            | SAR required (Yes/No)             | Yes          | No             | No             | Yes           |
| WCDMA Band V                               | SAR test exclusion thresholds(mW) | <b>16.50</b> | <b>782.05</b>  | <b>688.39</b>  | <b>89.10</b>  |
|                                            | SAR Max. Avg. Burst Power(mW)     | 181.55       | 181.55         | 181.55         | 181.55        |
|                                            | SAR required (Yes/No)             | Yes          | No             | No             | Yes           |

| 1-g SAR test exclusion thresholds for WWAN |                                   |              |               |                |                |
|--------------------------------------------|-----------------------------------|--------------|---------------|----------------|----------------|
| Test position                              |                                   | Edge 1 (2mm) | Edge 2 (52mm) | Edge 3 (156mm) | Edge 4 (161mm) |
| Test Mode                                  |                                   |              |               |                |                |
| 2.4G WIFI                                  | SAR test exclusion thresholds(mW) | <b>3.82</b>  | <b>115.60</b> | <b>1155.60</b> | <b>1205.60</b> |
|                                            | SAR Max. Avg. Burst Power(mW)     | 32.66        | 32.66         | 32.66          | 32.66          |
|                                            | SAR required (Yes/No)             | Yes          | No            | No             | No             |

**BT:**

**BR&EDR:**

$P_t=3.74\text{dBm}=2.37\text{mW}$

The result for RF exposure evaluation  $\text{SAR}=(2.37\text{mW}/5\text{mm}) \cdot [\sqrt{2.441(\text{GHz})}]=0.74<3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

**BLE:**

$P_t=4.20\text{dBm}=2.63\text{mW}$

The result for RF exposure evaluation  $\text{SAR}=(2.63\text{mW}/5\text{mm}) \cdot [\sqrt{2.402(\text{GHz})}]=0.82<3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### CONCLUSION

The SAR evaluation of BT is not required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>



## 5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10% are listed in 6.2

### 5.1. The composition of the tissue simulating liquid

| Ingredient<br>(% Weight)<br>Frequency<br>(MHz) | Water | Nacl | Polysorbate 20 | DGBE  | 1,2<br>Propanediol | Triton<br>X-100 |
|------------------------------------------------|-------|------|----------------|-------|--------------------|-----------------|
| 835 Head                                       | 50.36 | 1.25 | 48.39          | 0.0   | 0.0                | 0.0             |
| 1900 Head                                      | 54.9  | 0.18 | 0.0            | 44.92 | 0.0                | 0.0             |
| 2450 Head                                      | 71.88 | 0.16 | 0.0            | 7.99  | 0.0                | 19.97           |

### 5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1 have been incorporated in the following table. The body tissue dielectric parameters recommended by the IEC 62209-2 have been incorporated in the following table.

| Target Frequency<br>(MHz) | head         |                | body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 300                       | 45.3         | 0.87           | 45.3         | 0.87           |
| 450                       | 43.5         | 0.87           | 43.5         | 0.87           |
| <b>835</b>                | <b>41.5</b>  | <b>0.90</b>    | <b>41.5</b>  | <b>0.90</b>    |
| 900                       | 41.5         | 0.97           | 41.5         | 0.97           |
| 915                       | 41.5         | 1.01           | 41.5         | 1.01           |
| 1450                      | 40.5         | 1.20           | 40.5         | 1.20           |
| 1610                      | 40.3         | 1.29           | 40.3         | 1.29           |
| <b>1800 – 2000</b>        | <b>40.0</b>  | <b>1.40</b>    | <b>40.0</b>  | <b>1.40</b>    |
| <b>2450</b>               | <b>39.2</b>  | <b>1.80</b>    | <b>39.2</b>  | <b>1.80</b>    |
| 3000                      | 38.5         | 2.40           | 38.5         | 2.40           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### 5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using SATIMO Dielectric Probe Kit and R&S Network Analyzer ZVL6.

| Tissue Stimulant Measurement for 835MHz |              |                              |                        |                        |               |
|-----------------------------------------|--------------|------------------------------|------------------------|------------------------|---------------|
| Head                                    | Fr.<br>(MHz) | Dielectric Parameters (±10%) |                        | Tissue<br>Temp<br>[°C] | Test time     |
|                                         |              | εr 41.5 (37.35-45.65)        | δ[s/m] 0.90(0.81-0.99) |                        |               |
|                                         | 824.2        | 42.41                        | 0.89                   | 21.4                   | Oct. 12, 2021 |
|                                         | 826.4        | 41.85                        | 0.90                   |                        |               |
|                                         | 835          | 41.62                        | 0.91                   |                        |               |
|                                         | 836.6        | 41.23                        | 0.92                   |                        |               |
|                                         | 846.6        | 41.03                        | 0.93                   |                        |               |
|                                         | 848.8        | 40.96                        | 0.94                   |                        |               |

| Tissue Stimulant Measurement for 1900MHz |              |                              |                       |                        |               |
|------------------------------------------|--------------|------------------------------|-----------------------|------------------------|---------------|
| Head                                     | Fr.<br>(MHz) | Dielectric Parameters (±10%) |                       | Tissue<br>Temp<br>[°C] | Test time     |
|                                          |              | εr40.00(36.00-44.00)         | δ[s/m]1.40(1.26-1.54) |                        |               |
|                                          | 1850.2       | 40.21                        | 1.34                  | 21.0                   | Oct. 13, 2021 |
|                                          | 1852.4       | 39.94                        | 1.35                  |                        |               |
|                                          | 1880         | 39.78                        | 1.36                  |                        |               |
|                                          | 1900         | 39.56                        | 1.37                  |                        |               |
|                                          | 1907.6       | 39.32                        | 1.38                  |                        |               |
|                                          | 1909.8       | 39.10                        | 1.39                  |                        |               |
|                                          |              |                              |                       |                        |               |

| Tissue Stimulant Measurement for 2450MHz |              |                              |                       |                        |               |
|------------------------------------------|--------------|------------------------------|-----------------------|------------------------|---------------|
| Head                                     | Fr.<br>(MHz) | Dielectric Parameters (±10%) |                       | Tissue<br>Temp<br>[°C] | Test time     |
|                                          |              | εr39.2(35.28-43.12)          | δ[s/m]1.80(1.62-1.98) |                        |               |
|                                          | 2412         | 39.54                        | 1.72                  | 21.8                   | Oct. 14, 2021 |
|                                          | 2437         | 39.26                        | 1.73                  |                        |               |
|                                          | 2450         | 39.00                        | 1.74                  |                        |               |
|                                          | 2462         | 38.86                        | 1.75                  |                        |               |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




## 6. SAR SYSTEM CHECK PROCEDURE

### 6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

Each SATIMO system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the SATIMO software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 6.2. SAR System Check

### 6.2.1. Dipoles

|                                                                                   |                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>The dipoles used are based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of IEEE. the table below provides details for the mechanical and electrical specifications for the dipoles.</p> |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| Frequency | L (mm) | h (mm) | d (mm) |
|-----------|--------|--------|--------|
| 835MHz    | 161.0  | 89.8   | 3.6    |
| 1900MHz   | 68     | 39.5   | 3.6    |
| 2450MHz   | 51.5   | 30.4   | 3.6    |

### 6.2.2. System Check Result

| System Performance Check at 835 MHz &1900MHz & 2450MHz for Body                      |                    |       |                                 |               |                    |       |                   |               |
|--------------------------------------------------------------------------------------|--------------------|-------|---------------------------------|---------------|--------------------|-------|-------------------|---------------|
| Validation Kit: SN29/15 DIP 0G835-383& SN 46/11 DIP 1G900-187& SN46/11 DIP 2G450-189 |                    |       |                                 |               |                    |       |                   |               |
| Frequency [MHz]                                                                      | Target Value(W/kg) |       | Reference Result ( $\pm 10\%$ ) |               | Tested Value(W/kg) |       | Tissue Temp. [°C] | Test time     |
|                                                                                      | 1g                 | 10g   | 1g                              | 10g           | 1g                 | 10g   |                   |               |
| 835                                                                                  | 9.95               | 6.50  | 8.955-10.945                    | 5.85-7.15     | 9.41               | 5.89  | 21.4              | Oct. 12, 2021 |
| 1900                                                                                 | 40.82              | 20.99 | 36.738-44.902                   | 18.891-23.089 | 40.27              | 19.74 | 21.0              | Oct. 13, 2021 |
| 2450                                                                                 | 54.45              | 24.16 | 49.005-59.895                   | 21.744-26.576 | 49.58              | 22.24 | 21.8              | Oct. 14, 2021 |

Note:

(1) We use a CW signal of 18dBm for system check, and then all SAR values are normalized to 1W forward power. The result must be within  $\pm 10\%$  of target value.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 7. EUT TEST POSITION

This EUT was tested in **Body back, Edge1 and Edge 4.**

### 7.1. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to **0mm.**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>



## 8. SAR EXPOSURE LIMITS

### Limits for General Population/Uncontrolled Exposure (W/kg)

| Type Exposure                                       | Uncontrolled Environment Limit (W/kg) |
|-----------------------------------------------------|---------------------------------------|
| Spatial Peak SAR (1g cube tissue for brain or body) | 1.60                                  |
| Spatial Average SAR (Whole body)                    | 0.08                                  |
| Spatial Peak SAR (Limbs)                            | 4.0                                   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## 9. TEST FACILITY

|                                          |                                                                                                                                          |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Site</b>                         | Attestation of Global Compliance (Shenzhen) Co., Ltd                                                                                     |
| <b>Location</b>                          | 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| <b>Designation Number</b>                | CN1259                                                                                                                                   |
| <b>FCC Test Firm Registration Number</b> | 975832                                                                                                                                   |
| <b>A2LA Cert. No.</b>                    | 5054.02                                                                                                                                  |
| <b>Description</b>                       | Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA                                                                |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## 10. TEST EQUIPMENT LIST

| Equipment description | Manufacturer/ Model     | Identification No.     | Current calibration date    | Next calibration date       |
|-----------------------|-------------------------|------------------------|-----------------------------|-----------------------------|
| SAR Probe             | MVG                     | SN 03/18 EP327         | Dec. 17,2020                | Dec. 16,2021                |
| Phantom               | SATIMO                  | SN_2316_ELLI39         | Validated. No cal required. | Validated. No cal required. |
| Liquid                | SATIMO                  | -                      | Validated. No cal required. | Validated. No cal required. |
| Comm Tester           | Agilent-8960            | GB46310822             | Aug. 18,2021                | Aug. 17,2022                |
| Multimeter            | Keithley 2000           | 4114939                | Aug. 18,2021                | Aug. 17,2022                |
| SAR Software          | MVG-OpenSAR             | OpenSAR V4_02_35       | N/A                         | N/A                         |
| Dipole                | SATIMO SID835           | SN29/15 DIP 0G835-383  | Apr. 26,2019                | Apr. 25,2022                |
| Dipole                | SATIMO SID1900          | SN 46/11 DIP 1G900-187 | Apr. 26,2019                | Apr. 25,2022                |
| Dipole                | SATIMO SID2450          | SN 46/11 DIP 2G450-189 | Apr. 26,2019                | Apr. 25,2022                |
| Signal Generator      | Agilent-E4438C          | US41461365             | Aug. 18,2021                | Aug. 17,2022                |
| Vector Analyzer       | Agilent / E4440A        | MY44303916             | Mar. 21,2021                | Mar. 20,2022                |
| Network Analyzer      | Rhode & Schwarz ZVL6    | SN101443               | Oct. 16,2020                | Oct. 15,2021                |
| Attenuator            | Warison /WATT-6SR1211   | S/N:WRJ34AYM2F1        | June 09,2021                | June 08,2022                |
| Attenuator            | Mini-circuits / VAT-10+ | 31405                  | June 09,2021                | June 08,2022                |
| Amplifier             | AS0104-55_55            | 1004793                | June 10,2021                | June 09,2022                |
| Directional Couple    | Werlatone/ C5571-10     | SN99463                | May 15,2020                 | May 14,2022                 |
| Directional Couple    | Werlatone/ C6026-10     | SN99482                | May 15,2020                 | May 14,2022                 |
| Power Sensor          | NRP-Z21                 | 1137.6000.02           | Sep. 07,2021                | Sep. 06,2022                |
| Power Sensor          | NRP-Z23                 | 100323                 | Feb. 17,2021                | Feb. 16,2022                |
| Power Viewer          | R&S                     | V2.3.1.0               | N/A                         | N/A                         |

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 11. MEASUREMENT UNCERTAINTY

| SATIMO Uncertainty- SN 03/18 EP327<br>Measurement uncertainty for DUT averaged over 1 gram / 10 gram. |       |              |                |            |              |              |                |                 |    |
|-------------------------------------------------------------------------------------------------------|-------|--------------|----------------|------------|--------------|--------------|----------------|-----------------|----|
| Uncertainty Component                                                                                 | Sec.  | Tol<br>(+-%) | Prob.<br>Dist. | Div.       | Ci (1g)      | Ci (10g)     | 1g Ui<br>(+-%) | 10g Ui<br>(+-%) | vi |
| <b>Measurement System</b>                                                                             |       |              |                |            |              |              |                |                 |    |
| Probe calibration                                                                                     | E.2.1 | 7.000        | N              | 1          | 1            | 1            | 7.000          | 7.000           | ∞  |
| Axial Isotropy                                                                                        | E.2.2 | 0.075        | R              | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 0.031          | 0.031           | ∞  |
| Hemispherical Isotropy                                                                                | E.2.2 | 0.075        | R              | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 0.031          | 0.031           | ∞  |
| Boundary effect                                                                                       | E.2.3 | 1.000        | R              | $\sqrt{3}$ | 1            | 1            | 0.577          | 0.577           | ∞  |
| Linearity                                                                                             | E.2.4 | 0.870        | R              | $\sqrt{3}$ | 1            | 1            | 0.502          | 0.502           | ∞  |
| System detection limits                                                                               | E.2.4 | 1.000        | R              | $\sqrt{3}$ | 1            | 1            | 0.577          | 0.577           | ∞  |
| Modulation response                                                                                   | E.2.5 | 3.000        | R              | $\sqrt{3}$ | 1            | 1            | 1.732          | 1.732           | ∞  |
| Readout Electronics                                                                                   | E.2.6 | 0.021        | N              | 1          | 1            | 1            | 0.021          | 0.021           | ∞  |
| Response Time                                                                                         | E.2.7 | 0.000        | R              | $\sqrt{3}$ | 1            | 1            | 0.000          | 0.000           | ∞  |
| Integration Time                                                                                      | E.2.8 | 1.400        | R              | $\sqrt{3}$ | 1            | 1            | 0.808          | 0.808           | ∞  |
| RF ambient conditions-Noise                                                                           | E.6.1 | 3.000        | R              | $\sqrt{3}$ | 1            | 1            | 1.732          | 1.732           | ∞  |
| RF ambient conditions-reflections                                                                     | E.6.1 | 3.000        | R              | $\sqrt{3}$ | 1            | 1            | 1.732          | 1.732           | ∞  |
| Probe positioner mechanical tolerance                                                                 | E.6.2 | 1.400        | R              | $\sqrt{3}$ | 1            | 1            | 0.808          | 0.808           | ∞  |
| Probe positioning with respect to phantom shell                                                       | E.6.3 | 1.400        | R              | $\sqrt{3}$ | 1            | 1            | 0.808          | 0.808           | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation                     | E.5   | 2.300        | R              | $\sqrt{3}$ | 1            | 1            | 1.328          | 1.328           | ∞  |
| <b>Test sample Related</b>                                                                            |       |              |                |            |              |              |                |                 |    |
| Test sample positioning                                                                               | E.4.2 | 2.6          | N              | 1          | 1            | 1            | 2.600          | 2.600           | ∞  |
| Device holder uncertainty                                                                             | E.4.1 | 3            | N              | 1          | 1            | 1            | 3.000          | 3.000           | ∞  |
| Output power variation—SAR drift measurement                                                          | E.2.9 | 5            | R              | $\sqrt{3}$ | 1            | 1            | 2.887          | 2.887           | ∞  |
| SAR scaling                                                                                           | E.6.5 | 5            | R              | $\sqrt{3}$ | 1            | 1            | 2.887          | 2.887           | ∞  |
| <b>Phantom and tissue parameters</b>                                                                  |       |              |                |            |              |              |                |                 |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                                          | E.3.1 | 4            | R              | $\sqrt{3}$ | 1            | 1            | 2.309          | 2.309           | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity                         | E.3.2 | 1.9          | N              | 1          | 1            | 0.84         | 1.900          | 1.596           | ∞  |
| Liquid conductivity measurement                                                                       | E.3.3 | 2.5          | R              | $\sqrt{3}$ | 0.78         | 0.71         | 1.126          | 1.025           | ∞  |
| Liquid permittivity measurement                                                                       | E.3.3 | 4            | N              | 1          | 0.78         | 0.71         | 3.120          | 2.840           | M  |
| Liquid conductivity—temperature uncertainty                                                           | E.3.4 | 2.5          | R              | $\sqrt{3}$ | 0.23         | 0.26         | 0.332          | 0.375           | ∞  |
| Liquid permittivity—temperature uncertainty                                                           | E.3.4 | 5            | N              | 1          | 0.23         | 0.26         | 1.150          | 1.300           | M  |
| Combined Standard Uncertainty                                                                         |       |              | RSS            |            |              |              | 10.525         | 10.341          |    |
| Expanded Uncertainty (95% Confidence interval)                                                        |       |              | K=2            |            |              |              | 21.051         | 20.681          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SATIMO Uncertainty- SN 03/18 EP327<br>System Validation uncertainty for DUT averaged over 1 gram / 10 gram. |         |              |                |            |         |          |                |                 |    |
|-------------------------------------------------------------------------------------------------------------|---------|--------------|----------------|------------|---------|----------|----------------|-----------------|----|
| Uncertainty Component                                                                                       | Sec.    | Tol<br>(+-%) | Prob.<br>Dist. | Div.       | Ci (1g) | Ci (10g) | 1g Ui<br>(+-%) | 10g Ui<br>(+-%) | vi |
| <b>Measurement System</b>                                                                                   |         |              |                |            |         |          |                |                 |    |
| Probe calibration                                                                                           | E.2.1   | 7.000        | N              | 1          | 1       | 1        | 7.000          | 7.000           | ∞  |
| Axial Isotropy                                                                                              | E.2.2   | 0.075        | R              | $\sqrt{3}$ | 1       | 1        | 0.043          | 0.043           | ∞  |
| Hemispherical Isotropy                                                                                      | E.2.2   | 0.075        | R              | $\sqrt{3}$ | 0       | 0        | 0.000          | 0.000           | ∞  |
| Boundary effect                                                                                             | E.2.3   | 1.000        | R              | $\sqrt{3}$ | 1       | 1        | 0.577          | 0.577           | ∞  |
| Linearity                                                                                                   | E.2.4   | 0.870        | R              | $\sqrt{3}$ | 1       | 1        | 0.502          | 0.502           | ∞  |
| System detection limits                                                                                     | E.2.4   | 1.0          | R              | $\sqrt{3}$ | 1       | 1        | 0.58           | 0.58            | ∞  |
| Modulation response                                                                                         | E.2.5   | 3.0          | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Readout Electronics                                                                                         | E.2.6   | 0.021        | N              | 1          | 1       | 1        | 0.021          | 0.021           | ∞  |
| Response Time                                                                                               | E.2.7   | 0.0          | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Integration Time                                                                                            | E.2.8   | 1.4          | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| RF ambient conditions-Noise                                                                                 | E.6.1   | 3.0          | R              | $\sqrt{3}$ | 1       | 1        | 1.73           | 1.73            | ∞  |
| RF ambient conditions-reflections                                                                           | E.6.1   | 3.0          | R              | $\sqrt{3}$ | 1       | 1        | 1.73           | 1.73            | ∞  |
| Probe positioner mechanical tolerance                                                                       | E.6.2   | 1.4          | R              | $\sqrt{3}$ | 1       | 1        | 0.81           | 0.81            | ∞  |
| Probe positioning with respect to phantom shell                                                             | E.6.3   | 1.4          | R              | $\sqrt{3}$ | 1       | 1        | 0.81           | 0.81            | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation                           | E.5     | 2.3          | R              | $\sqrt{3}$ | 1       | 1        | 1.33           | 1.33            | ∞  |
| <b>System validation source</b>                                                                             |         |              |                |            |         |          |                |                 |    |
| Deviation of experimental dipole from numerical dipole                                                      | E.6.4   | 5.0          | N              | 1          | 1       | 1        | 5.00           | 5.00            | ∞  |
| Input power and SAR drift measurement                                                                       | 8,6.6.4 | 5.0          | R              | $\sqrt{3}$ | 1       | 1        | 2.89           | 2.89            | ∞  |
| Dipole axis to liquid distance                                                                              | 8,E.6.6 | 2.0          | R              | $\sqrt{3}$ | 1       | 1        | 1.15           | 1.15            | ∞  |
| <b>Phantom and set-up</b>                                                                                   |         |              |                |            |         |          |                |                 |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                                                | E.3.1   | 4.0          | R              | $\sqrt{3}$ | 1       | 1        | 2.31           | 2.31            | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity                               | E.3.2   | 1.9          | N              | 1          | 1       | 0.84     | 1.90           | 1.60            | ∞  |
| Liquid conductivity (temperature uncertainty)                                                               | E.3.3   | 2.5          | R              | $\sqrt{3}$ | 0.78    | 0.71     | 1.13           | 1.02            | ∞  |
| Liquid conductivity (measured)                                                                              | E.3.3   | 4            | N              | 1          | 0.78    | 0.71     | 3.12           | 2.84            | M  |
| Liquid permittivity (temperature uncertainty)                                                               | E.3.4   | 2.5          | R              | $\sqrt{3}$ | 0.23    | 0.26     | 0.33           | 0.38            | ∞  |
| Liquid permittivity (measured)                                                                              | E.3.4   | 5            | N              | 1          | 0.23    | 0.26     | 1.15           | 1.30            | M  |
| Combined Standard Uncertainty                                                                               |         |              | RSS            |            |         |          | 10.458         | 10.272          |    |
| Expanded Uncertainty (95% Confidence interval)                                                              |         |              | K=2            |            |         |          | 20.916         | 20.543          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SATIMO Uncertainty- SN 03/18 EP327                                                |         |               |                |            |         |          |                |                 |    |
|-----------------------------------------------------------------------------------|---------|---------------|----------------|------------|---------|----------|----------------|-----------------|----|
| System Check uncertainty for DUT averaged over 1 gram / 10 gram.                  |         |               |                |            |         |          |                |                 |    |
| Uncertainty Component                                                             | Sec.    | Tol<br>(+- %) | Prob.<br>Dist. | Div.       | Ci (1g) | Ci (10g) | 1g Ui<br>(+-%) | 10g Ui<br>(+-%) | vi |
| <b>Measurement System</b>                                                         |         |               |                |            |         |          |                |                 |    |
| Probe calibration drift                                                           | E.2.1.3 | 0.5           | N              | 1          | 1       | 1        | 0.50           | 0.50            | ∞  |
| Axial Isotropy                                                                    | E.2.2   | 0.075         | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Hemispherical Isotropy                                                            | E.2.2   | 0.075         | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Boundary effect                                                                   | E.2.3   | 1.000         | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Linearity                                                                         | E.2.4   | 0.870         | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| System detection limits                                                           | E.2.4   | 1.0           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Modulation response                                                               | E.2.5   | 3.0           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Readout Electronics                                                               | E.2.6   | 0.021         | N              | 1          | 0       | 0        | 0.00           | 0.00            | ∞  |
| Response Time                                                                     | E.2.7   | 0             | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Integration Time                                                                  | E.2.8   | 1.4           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| RF ambient conditions-Noise                                                       | E.6.1   | 3.0           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| RF ambient conditions-reflections                                                 | E.6.1   | 3.0           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| Probe positioner mechanical tolerance                                             | E.6.2   | 1.4           | R              | $\sqrt{3}$ | 1       | 1        | 0.81           | 0.81            | ∞  |
| Probe positioning with respect to phantom shell                                   | E.6.3   | 1.4           | R              | $\sqrt{3}$ | 1       | 1        | 0.81           | 0.81            | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation | E.5     | 2.3           | R              | $\sqrt{3}$ | 0       | 0        | 0.00           | 0.00            | ∞  |
| <b>System check source (dipole)</b>                                               |         |               |                |            |         |          |                |                 |    |
| Deviation of experimental dipoles                                                 | E.6.4   | 2.0           | N              | 1          | 1       | 1        | 2.00           | 2.00            | ∞  |
| Input power and SAR drift measurement                                             | 8,6.6.4 | 5.0           | R              | $\sqrt{3}$ | 1       | 1        | 2.89           | 2.89            | ∞  |
| Dipole axis to liquid distance                                                    | 8,E.6.6 | 2.0           | R              | $\sqrt{3}$ | 1       | 1        | 1.15           | 1.15            | ∞  |
| <b>Phantom and tissue parameters</b>                                              |         |               |                |            |         |          |                |                 |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                      | E.3.1   | 4             | R              | $\sqrt{3}$ | 1       | 1        | 2.31           | 2.31            | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity     | E.3.2   | 1.9           | N              | 1          | 1       | 0.84     | 1.90           | 1.60            | ∞  |
| Liquid conductivity measurement                                                   | E.3.3   | 2.5           | R              | $\sqrt{3}$ | 0.78    | 0.71     | 1.13           | 1.02            | ∞  |
| Liquid permittivity measurement                                                   | E.3.3   | 4             | N              | 1          | 0.78    | 0.71     | 3.12           | 2.84            | M  |
| Liquid conductivity—temperature uncertainty                                       | E.3.4   | 2.5           | R              | $\sqrt{3}$ | 0.23    | 0.26     | 0.33           | 0.38            | ∞  |
| Liquid permittivity—temperature uncertainty                                       | E.3.4   | 5             | N              | 1          | 0.23    | 0.26     | 1.15           | 1.30            | M  |
| Combined Standard Uncertainty                                                     |         |               | RSS            |            |         |          | 5.562          | 5.203           |    |
| Expanded Uncertainty (95% Confidence interval)                                    |         |               | K=2            |            |         |          | 11.124         | 10.406          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## 12. CONDUCTED POWER MEASUREMENT

### GSM BAND

| Mode                 | Frequency(MHz) | Avg. Burst Power(dBm) | Duty cycle Factor(dBm) | Frame Power(dBm) |
|----------------------|----------------|-----------------------|------------------------|------------------|
| Maximum Power <1>    |                |                       |                        |                  |
| GSM 850              | 824.2          | 32.17                 | -9                     | 23.17            |
|                      | 836.6          | <b>32.27</b>          | -9                     | 23.27            |
|                      | 848.8          | 32.04                 | -9                     | 23.04            |
| GPRS 850<br>(1 Slot) | 824.2          | 31.75                 | -9                     | 22.75            |
|                      | 836.6          | 31.84                 | -9                     | 22.84            |
|                      | 848.8          | 31.58                 | -9                     | 22.58            |
| GPRS 850<br>(2 Slot) | 824.2          | 30.31                 | -6                     | 24.31            |
|                      | 836.6          | 30.36                 | -6                     | 24.36            |
|                      | 848.8          | 30.16                 | -6                     | 24.16            |
| GPRS 850<br>(3 Slot) | 824.2          | 29.34                 | -4.26                  | 25.08            |
|                      | 836.6          | 29.07                 | -4.26                  | 24.81            |
|                      | 848.8          | 29.40                 | -4.26                  | <b>25.14</b>     |
| GPRS 850<br>(4 Slot) | 824.2          | 27.08                 | -3                     | 24.08            |
|                      | 836.6          | 27.47                 | -3                     | 24.47            |
|                      | 848.8          | 27.04                 | -3                     | 24.04            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



# GSM BAND CONTINUE

| Mode              | Frequency(MHz) | Avg. Burst Power(dBm) | Duty cycle Factor(dBm) | Frame Power(dBm) |
|-------------------|----------------|-----------------------|------------------------|------------------|
| Maximum Power <1> |                |                       |                        |                  |
| PCS1900           | 1850.2         | 30.12                 | -9                     | 21.12            |
|                   | 1880           | <b>30.20</b>          | -9                     | 21.20            |
|                   | 1909.8         | 30.06                 | -9                     | 21.06            |
| GPRS1900 (1 Slot) | 1850.2         | 29.65                 | -9                     | 20.65            |
|                   | 1880           | 29.79                 | -9                     | 20.79            |
|                   | 1909.8         | 29.76                 | -9                     | 20.76            |
| GPRS1900 (2 Slot) | 1850.2         | 27.66                 | -6                     | 21.66            |
|                   | 1880           | 27.73                 | -6                     | 21.73            |
|                   | 1909.8         | 27.94                 | -6                     | 21.94            |
| GPRS1900 (3 Slot) | 1850.2         | 26.91                 | -4.26                  | 22.65            |
|                   | 1880           | 26.94                 | -4.26                  | 22.68            |
|                   | 1909.8         | 26.76                 | -4.26                  | 22.50            |
| GPRS1900 (4 Slot) | 1850.2         | 25.75                 | -3                     | <b>22.75</b>     |
|                   | 1880           | 25.52                 | -3                     | 22.52            |
|                   | 1909.8         | 25.66                 | -3                     | 22.66            |

## Note 1:

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) – 9 dB

Frame Power = Max burst power (2 Up Slot) – 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) – 3 dB

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## UMTS BAND HSDPA Setup Configuration:

- The EUT was connected to Base Station Agilent-8960 referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Based Station with following setting:
  - (1) Set Gain Factors( $\beta_c$  and  $\beta_d$ ) parameters set according to each
  - (2) Set RMC 12.2Kbps+HSDPA mode.
  - (3) Set Cell Power=-86dBm
  - (4) Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - (5) Select HSDPA Uplink Parameters
  - (6) Set Delta ACK, Delta NACK and Delta CQI=8
  - (7) Set Ack - Nack Repetition Factor to 3
  - (8) Set CQI Feedback Cycle (k) to 4ms
  - (9) Set CQI Repetition Factor to 2
  - (10) Power Ctrl Mode=All Up bits
- The transmitted maximum output power was recorded.

Table C.10.2.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH

| Sub-test | $\beta_c$ (Note5) | $\beta_d$     | $\beta_d$ (SF) | $\beta_c/\beta_d$ | $\beta_{HS}$ (Note1, Note 2) | CM (dB) (Note 3) | MPR (dB) (Note 3) |
|----------|-------------------|---------------|----------------|-------------------|------------------------------|------------------|-------------------|
| 1        | 2/15              | 15/15         | 64             | 2/15              | 4/15                         | 0.0              | 0.0               |
| 2        | 12/15(Note 4)     | 15/15(Note 4) | 64             | 12/15(Note 4)     | 24/15                        | 1.0              | 0.0               |
| 3        | 15/15             | 8/15          | 64             | 15/8              | 30/15                        | 1.5              | 0.5               |
| 4        | 15/15             | 4/15          | 64             | 15/4              | 30/15                        | 1.5              | 0.5               |

Note 1:  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta ACK$  and  $\Delta NACK = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ , and  $\Delta CQI = 24/15$  with  $\beta_{hs} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $hs/c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $c/d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $c = 11/15$  and  $d = 15/15$ .

### HSUPA Setup Configuration:

- The EUT was connected to Base Station Agilent-8960 referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Base Station with following setting \* :
  - (1) Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - (2) Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - (3) Set Cell Power = -86 dBm
  - (4) Set Channel Type = 12.2k + HSPA
  - (5) Set UE Target Power
  - (6) Power Ctrl Mode= Alternating bits
  - (7) Set and observe the E-TFCI
  - (8) Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- The transmitted maximum output power was recorded.

Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH

| Sub-test | $\beta_c$      | $\beta_d$      | $\beta_d$ (SF) | $\beta_c/\beta_d$ | $\beta_{HS}$ (Note 1) | $\beta_{ec}$ | $\beta_{ed}$ (Note 4) (Note 5)                 | $\beta_{ed}$ (SF) | $\beta_{ed}$ (Code s) | CM (dB) (Note 2) | MPR (dB) (Note 2) (Note 6) | AG Index (Note 5) | E-TF CI |
|----------|----------------|----------------|----------------|-------------------|-----------------------|--------------|------------------------------------------------|-------------------|-----------------------|------------------|----------------------------|-------------------|---------|
| 1        | 11/15 (Note 3) | 15/15 (Note 3) | 64             | 11/15 (Note 3)    | 22/15                 | 209/225      | 1309/225                                       | 4                 | 1                     | 1.0              | 0.0                        | 20                | 75      |
| 2        | 6/15           | 15/15          | 64             | 6/15              | 12/15                 | 12/15        | 94/75                                          | 4                 | 1                     | 3.0              | 2.0                        | 12                | 67      |
| 3        | 15/15          | 9/15           | 64             | 15/9              | 30/15                 | 30/15        | $\beta_{ed1}$ : 47/15<br>$\beta_{ed2}$ : 47/15 | 4<br>4            | 2                     | 2.0              | 1.0                        | 15                | 92      |
| 4        | 2/15           | 15/15          | 64             | 2/15              | 4/15                  | 2/15         | 56/75                                          | 4                 | 1                     | 3.0              | 2.0                        | 17                | 71      |
| 5        | 15/15          | 0              | -              | -                 | 5/15                  | 5/15         | 47/15                                          | 4                 | 1                     | 1.0              | 0.0                        | 12                | 67      |

Note 1: For sub-test 1 to 4,  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ . For sub-test 5,  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 5/15$  with  $\beta_{hs} = 5/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $hs/c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $c/d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $c = 10/15$  and  $d = 15/15$ .

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5:  $\beta_{ed}$  cannot be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

**UMTS BAND II**

| Mode               | Frequency<br>(MHz) | Avg. Burst Power<br>(dBm) |
|--------------------|--------------------|---------------------------|
| WCDMA 1900<br>RMC  | 1852.4             | <b>22.55</b>              |
|                    | 1880               | 21.85                     |
|                    | 1907.6             | 22.14                     |
| WCDMA 1900<br>AMR  | 1852.4             | 22.04                     |
|                    | 1880               | 22.17                     |
|                    | 1907.6             | 21.91                     |
| HSDPA<br>Subtest 1 | 1852.4             | 21.11                     |
|                    | 1880               | 20.83                     |
|                    | 1907.6             | 20.63                     |
| HSDPA<br>Subtest 2 | 1852.4             | 20.07                     |
|                    | 1880               | 19.98                     |
|                    | 1907.6             | 20.50                     |
| HSDPA<br>Subtest 3 | 1852.4             | 20.01                     |
|                    | 1880               | 19.84                     |
|                    | 1907.6             | 20.29                     |
| HSDPA<br>Subtest 4 | 1852.4             | 20.16                     |
|                    | 1880               | 20.31                     |
|                    | 1907.6             | 20.57                     |
| HSUPA<br>Subtest 1 | 1852.4             | 20.74                     |
|                    | 1880               | 20.20                     |
|                    | 1907.6             | 20.23                     |
| HSUPA<br>Subtest 2 | 1852.4             | 21.53                     |
|                    | 1880               | 21.86                     |
|                    | 1907.6             | 21.48                     |
| HSUPA<br>Subtest 3 | 1852.4             | 21.30                     |
|                    | 1880               | 21.13                     |
|                    | 1907.6             | 21.16                     |
| HSUPA<br>Subtest 4 | 1852.4             | 21.09                     |
|                    | 1880               | 22.05                     |
|                    | 1907.6             | 22.35                     |
| HSUPA<br>Subtest 5 | 1852.4             | 21.01                     |
|                    | 1880               | 21.76                     |
|                    | 1907.6             | 21.78                     |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



**UMTS BAND V**

| Mode               | Frequency<br>(MHz) | Avg. Burst Power<br>(dBm) |
|--------------------|--------------------|---------------------------|
| WCDMA 850<br>RMC   | 826.4              | <b>22.59</b>              |
|                    | 836.6              | 21.87                     |
|                    | 846.6              | 21.96                     |
| WCDMA 850<br>AMR   | 826.4              | 22.06                     |
|                    | 836.6              | 22.13                     |
|                    | 846.6              | 22.03                     |
| HSDPA<br>Subtest 1 | 826.4              | 21.29                     |
|                    | 836.6              | 20.98                     |
|                    | 846.6              | 20.91                     |
| HSDPA<br>Subtest 2 | 826.4              | 20.41                     |
|                    | 836.6              | 20.10                     |
|                    | 846.6              | 20.60                     |
| HSDPA<br>Subtest 3 | 826.4              | 20.18                     |
|                    | 836.6              | 19.74                     |
|                    | 846.6              | 20.25                     |
| HSDPA<br>Subtest 4 | 826.4              | 20.25                     |
|                    | 836.6              | 20.66                     |
|                    | 846.6              | 20.80                     |
| HSUPA<br>Subtest 1 | 826.4              | 20.78                     |
|                    | 836.6              | 20.16                     |
|                    | 846.6              | 20.29                     |
| HSUPA<br>Subtest 2 | 826.4              | 21.54                     |
|                    | 836.6              | 21.74                     |
|                    | 846.6              | 21.22                     |
| HSUPA<br>Subtest 3 | 826.4              | 21.21                     |
|                    | 836.6              | 21.07                     |
|                    | 846.6              | 21.21                     |
| HSUPA<br>Subtest 4 | 826.4              | 21.14                     |
|                    | 836.6              | 22.06                     |
|                    | 846.6              | 22.23                     |
| HSUPA<br>Subtest 5 | 826.4              | 20.98                     |
|                    | 836.6              | 21.70                     |
|                    | 846.6              | 21.93                     |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

| UE Transmit Channel Configuration                                    | CM(db)               | MPR(db)       |
|----------------------------------------------------------------------|----------------------|---------------|
| For all combinations of ,DPDCH,DPCCH<br>HS-DPDCH,E-DPDCH and E-DPCCH | $0 \leq CM \leq 3.5$ | $MAX(CM-1,0)$ |

Note: CM=1 for  $\beta_c/\beta_d=12/15$ ,  $\beta_{hs}/\beta_c=24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX\_AG\_C in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### WIFI

| Mode        | Data Rate (Mbps) | Channel | Frequency(MHz) | Avg. Burst Power(dBm) |
|-------------|------------------|---------|----------------|-----------------------|
| 802.11b     | 1                | 01      | 2412           | 14.33                 |
|             |                  | 06      | 2437           | 14.49                 |
|             |                  | 11      | 2462           | <b>15.14</b>          |
| 802.11g     | 6                | 01      | 2412           | 10.73                 |
|             |                  | 06      | 2437           | 9.10                  |
|             |                  | 11      | 2462           | 9.60                  |
| 802.11n(20) | 6.5              | 01      | 2412           | 8.74                  |
|             |                  | 06      | 2437           | 8.83                  |
|             |                  | 11      | 2462           | 9.58                  |
| 802.11n(40) | 13.5             | 03      | 2422           | 5.92                  |
|             |                  | 06      | 2437           | 6.17                  |
|             |                  | 09      | 2452           | 6.60                  |

### Bluetooth\_V4.0

| Modulation     | Channel | Frequency(MHz) | Peak Power (dBm) |
|----------------|---------|----------------|------------------|
| GFSK           | 0       | 2402           | 3.69             |
|                | 39      | 2441           | 3.32             |
|                | 78      | 2480           | 3.17             |
| $\pi/4$ -DQPSK | 0       | 2402           | 3.45             |
|                | 39      | 2441           | 2.91             |
|                | 78      | 2480           | 2.76             |
| 8-DPSK         | 0       | 2402           | 3.30             |
|                | 39      | 2441           | <b>3.74</b>      |
|                | 78      | 2480           | 3.47             |

### Bluetooth\_V4.0

| Modulation | Channel | Frequency(MHz) | Peak Power (dBm) |
|------------|---------|----------------|------------------|
| GFSK       | 0       | 2402           | <b>4.20</b>      |
|            | 19      | 2440           | 3.85             |
|            | 39      | 2480           | 3.67             |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



## 13. TEST RESULTS

### 13.1. SAR Test Results Summary

#### 13.1.1. Test position and configuration

Body-worn and 4 Edges SAR was performed with the device 0mm from the phantom.

#### 13.1.2. Operation Mode

1. Per KDB 447498 D01 v06 ,for each exposure position, if the highest 1-g SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional.
2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is  $\geq 0.8$ W/kg, testing for repeated SAR measurement is required , that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
  - (1) When the original highest measured SAR is  $\geq 0.8$ W/kg, repeat that measurement once.
  - (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $>1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg.
  - (3) Perform a third repeated measurement only if the original, first and second repeated measurement is  $\geq 1.5$  W/kg and ratio of largest to smallest SAR for the original, first and second measurement is  $\geq 1.20$ .
3. Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
4. Per KDB 648474 D04 v01r03,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$ W/kg, SAR testing with a headset connected is not required.
5. Per KDB 248227 D01v02r02,for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$ W/kg.
6. Per KDB 941225 D06 V02r01, When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations.
7. Per KDB616217 D04 v01r02, The antennas in tablets are typically located near the back (bottom) surface and/or along the edges of the devices; therefore, SAR evaluation is required for these configurations. Exposures from antennas through the front (top) surface of the display section of a full-size tablet, away from the edges, are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary, except for tablets that are designed to require continuous operations with the hand(s) next to the antenna(s).
8. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:  
Maximum Scaling SAR =tested SAR (Max.)  $\times$  [maximum turn-up power (mw)/ maximum measurement output power(mw) ]
9. Proximity sensor, just for avoiding the wrong operation in the phone screen when call, and has no influence on output power or SAR result

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



### 13.1.3. Test Result

| SAR MEASUREMENT                        |             |     |           |                    |                             |                          |                          |                   |              |
|----------------------------------------|-------------|-----|-----------|--------------------|-----------------------------|--------------------------|--------------------------|-------------------|--------------|
| Depth of Liquid (cm):>15               |             |     |           |                    | Relative Humidity (%): 48.3 |                          |                          |                   |              |
| Product: Tablet PC                     |             |     |           |                    |                             |                          |                          |                   |              |
| Test Mode: GSM850 with GMSK modulation |             |     |           |                    |                             |                          |                          |                   |              |
| Position                               | Mode        | Ch. | Fr. (MHz) | Power Drift (<±5%) | SAR (1g) (W/kg)             | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit (W/kg) |
| SIM 1 Card                             |             |     |           |                    |                             |                          |                          |                   |              |
| Body back                              | GPRS-3 slot | 190 | 836.6     | -0.08              | 0.335                       | 29.40                    | 29.07                    | 0.361             | 1.6          |
| Edge 1 (Top)                           | GPRS-3 slot | 190 | 836.6     | 0.05               | 0.143                       | 29.40                    | 29.07                    | 0.154             | 1.6          |
| Edge 4(Left)                           | GPRS-3 slot | 190 | 836.6     | -0.03              | 0.024                       | 29.40                    | 29.07                    | 0.026             | 1.6          |

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back and edge is 0mm of all above table.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SAR MEASUREMENT                         |             |     |           |                             |                 |                          |                          |                   |              |
|-----------------------------------------|-------------|-----|-----------|-----------------------------|-----------------|--------------------------|--------------------------|-------------------|--------------|
| Depth of Liquid (cm):>15                |             |     |           | Relative Humidity (%): 46.3 |                 |                          |                          |                   |              |
| Product: Tablet PC                      |             |     |           |                             |                 |                          |                          |                   |              |
| Test Mode: PCS1900 with GMSK modulation |             |     |           |                             |                 |                          |                          |                   |              |
| Position                                | Mode        | Ch. | Fr. (MHz) | Power Drift (<±5%)          | SAR (1g) (W/kg) | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit (W/kg) |
| SIM 1 Card                              |             |     |           |                             |                 |                          |                          |                   |              |
| Body back                               | GPRS-4 slot | 661 | 1880.0    | 0.13                        | 0.032           | 25.80                    | 25.52                    | 0.034             | 1.6          |
| Edge 1 (Top)                            | GPRS-4 slot | 661 | 1880.0    | -0.09                       | 0.044           | 25.80                    | 25.52                    | 0.047             | 1.6          |
| Edge 4(Left)                            | GPRS-4 slot | 661 | 1880.0    | 0.12                        | 0.006           | 25.80                    | 25.52                    | 0.006             | 1.6          |

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back and edge is 0mm of all above table.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SAR MEASUREMENT                               |              |      |           |                    |                             |                          |                          |                   |              |
|-----------------------------------------------|--------------|------|-----------|--------------------|-----------------------------|--------------------------|--------------------------|-------------------|--------------|
| Depth of Liquid (cm):>15                      |              |      |           |                    | Relative Humidity (%): 46.3 |                          |                          |                   |              |
| Product: Tablet PC                            |              |      |           |                    |                             |                          |                          |                   |              |
| Test Mode: WCDMA Band II with QPSK modulation |              |      |           |                    |                             |                          |                          |                   |              |
| Position                                      | Mode         | Ch.  | Fr. (MHz) | Power Drift (<±5%) | SAR (1g) (W/kg)             | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit (W/kg) |
| Body back                                     | RMC 12.2kbps | 9400 | 1880      | -0.15              | 0.231                       | 22.60                    | 21.85                    | 0.275             | 1.6          |
| Edge 1 (Top)                                  | RMC 12.2kbps | 9400 | 1880      | 0.12               | <b>0.297</b>                | 22.60                    | 21.85                    | <b>0.353</b>      | 1.6          |
| Edge 4(Left)                                  | RMC 12.2kbps | 9400 | 1880      | -0.18              | 0.036                       | 22.60                    | 21.85                    | 0.043             | 1.6          |

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back and edge is 0mm of all above table.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SAR MEASUREMENT                              |              |      |           |                    |                             |                          |                          |                   |              |
|----------------------------------------------|--------------|------|-----------|--------------------|-----------------------------|--------------------------|--------------------------|-------------------|--------------|
| Depth of Liquid (cm):>15                     |              |      |           |                    | Relative Humidity (%): 48.3 |                          |                          |                   |              |
| Product: Tablet PC                           |              |      |           |                    |                             |                          |                          |                   |              |
| Test Mode: WCDMA Band V with QPSK modulation |              |      |           |                    |                             |                          |                          |                   |              |
| Position                                     | Mode         | Ch.  | Fr. (MHz) | Power Drift (<±5%) | SAR (1g) (W/kg)             | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit (W/kg) |
| Body back                                    | RMC 12.2kbps | 4132 | 826.4     | 0.06               | 0.893                       | 22.60                    | 22.59                    | 0.895             | 1.6          |
| Body back                                    | RMC 12.2kbps | 4183 | 836.6     | -0.02              | 0.857                       | 22.00                    | 21.87                    | 0.883             | 1.6          |
| Body back                                    | RMC 12.2kbps | 4233 | 846.6     | 0.08               | <b>0.895</b>                | 22.00                    | 21.96                    | <b>0.903</b>      | 1.6          |
| Edge 1 (Top)                                 | RMC 12.2kbps | 4183 | 836.6     | -0.07              | 0.214                       | 22.00                    | 21.87                    | 0.221             | 1.6          |
| Edge 4(Left)                                 | RMC 12.2kbps | 4183 | 836.6     | -0.04              | 0.039                       | 22.00                    | 21.87                    | 0.040             | 1.6          |

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back and edge is 0mm of all above table.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| SAR MEASUREMENT          |      |     |           |                             |                 |                          |                          |                   |              |
|--------------------------|------|-----|-----------|-----------------------------|-----------------|--------------------------|--------------------------|-------------------|--------------|
| Depth of Liquid (cm):>15 |      |     |           | Relative Humidity (%): 51.0 |                 |                          |                          |                   |              |
| Product: Tablet PC       |      |     |           |                             |                 |                          |                          |                   |              |
| Test Mode:802.11b        |      |     |           |                             |                 |                          |                          |                   |              |
| Position                 | Mode | Ch. | Fr. (MHz) | Power Drift (<±5%)          | SAR (1g) (W/kg) | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit (W/kg) |
| Body back                | DTS  | 6   | 2437      | -0.05                       | 0.573           | 15.20                    | 14.49                    | 0.675             | 1.6          |
| Edge 1 (Top)             | DTS  | 6   | 2437      | 0.12                        | 0.323           | 15.20                    | 14.49                    | 0.380             | 1.6          |

Note:

- According to KDB248227, SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a/b channels.
- All of above "DTS" means data transmitters.
- The test separation for body back and edge is 0mm of all above table.

| Repeated SAR            |              |      |           |                    |                      |                    |                       |                    |                       |              |
|-------------------------|--------------|------|-----------|--------------------|----------------------|--------------------|-----------------------|--------------------|-----------------------|--------------|
| Product: Tablet PC      |              |      |           |                    |                      |                    |                       |                    |                       |              |
| Test Mode: WCDMA Band V |              |      |           |                    |                      |                    |                       |                    |                       |              |
| Position                | Mode         | Ch.  | Fr. (MHz) | Power Drift (<±5%) | Once SAR (1g) (W/kg) | Power Drift (<±5%) | Twice SAR (1g) (W/kg) | Power Drift (<±5%) | Third SAR (1g) (W/kg) | Limit (W/kg) |
| Body back               | RMC 12.2kbps | 4233 | 846.6     | 0.06               | <b>0.745</b>         | --                 | --                    | --                 | --                    | 1.6          |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## Simultaneous Multi-band Transmission Evaluation:

### Application Simultaneous Transmission information:

| NO | Simultaneous state              | Portable Handset |           |         |
|----|---------------------------------|------------------|-----------|---------|
|    |                                 | Head             | Body-worn | Hotspot |
| 1  | GSM (Data) + WLAN 2.4GHz (data) | -                | Yes       | Yes     |
| 2  | GSM (Data) + Bluetooth(data)    | -                | Yes       | Yes     |
| 3  | WCDMA+WLAN 2.4GHz (data)        | -                | Yes       | Yes     |
| 4  | WCDMA+Bluetooth(data)           | -                | Yes       | Yes     |

#### NOTE:

1. WIFI and BT share the same antenna, and cannot transmit simultaneously.
2. Simultaneous with every transmitter must be the same test position.
3. KDB 447498 D01, BT SAR is excluded as below table.
4. KDB 447498 D01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR and 0mm for body-worn SAR.
5. According to KDB 447498 D01 4.3.1, Standalone SAR test exclusion is as follow:  
For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:  

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR<sup>30</sup>, where
  - f(GHz) is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
  - The result is rounded to one decimal place for comparison
  - The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below
The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.
6. If the test separation distance is  $< 5$ mm, 5mm is used for excluded SAR calculation.
7. According to KDB 447498 D01 4.3.2, simultaneous transmission SAR test exclusion is as follow:
  - (1) Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.
  - (2) Any transmitters and antennas should be considered when calculating simultaneous mode.
  - (3) For mobile phone and PC, it's the sum of all transmitters and antennas at the same mode with same position in each applicable exposure condition
  - (4) When the standalone SAR test exclusion of section 4.3.2 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to det
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$$
for test separation distances  $\leq 50$  mm;  
where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



8. When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion. The ratio is determined by  $(SAR1 + SAR2)1.5/R_i$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

| Estimated SAR |      | Max Power including Tune-up Tolerance |      | Separation Distance (mm) | Estimated SAR (W/kg) |
|---------------|------|---------------------------------------|------|--------------------------|----------------------|
|               |      | dBm                                   | mW   |                          |                      |
| <b>BT</b>     | Body | 5                                     | 3.16 | 0                        | 0.13                 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



#### Sum of the SAR for GSM 850 & Wi-Fi & BT:

| RF Exposure Conditions | Test Position | Simultaneous Transmission Scenario |                |           | $\Sigma$ 1-g SAR (W/kg) | SPLSR (Yes/No) |
|------------------------|---------------|------------------------------------|----------------|-----------|-------------------------|----------------|
|                        |               | GSM 850                            | Wi-Fi DTS Band | Bluetooth |                         |                |
| Body-worn (Data)       | Rear          | 0.361                              | 0.675          |           | 1.036                   | No             |
|                        |               | 0.361                              |                | 0.13      | 0.491                   | No             |
| Body-worn (Hotspot)    | Edge 1        | 0.154                              | 0.380          |           | 0.534                   | No             |
|                        | Edge 1        | 0.154                              |                | 0.13      | 0.284                   | No             |

#### Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio"

#### Sum of the SAR for PCS 1900 & Wi-Fi & BT:

| RF Exposure Conditions | Test Position | Simultaneous Transmission Scenario |                |           | $\Sigma$ 1-g SAR (W/kg) | SPLSR (Yes/No) |
|------------------------|---------------|------------------------------------|----------------|-----------|-------------------------|----------------|
|                        |               | GSM 1900                           | Wi-Fi DTS Band | Bluetooth |                         |                |
| Body-worn (Data)       | Rear          | 0.034                              | 0.675          |           | 0.709                   | No             |
|                        |               | 0.034                              |                | 0.13      | 0.164                   | No             |
| Body-worn (Hotspot)    | Edge 1        | 0.047                              | 0.380          |           | 0.427                   | No             |
|                        | Edge 1        | 0.047                              |                | 0.13      | 0.177                   | No             |

#### Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio"

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



**Sum of the SAR for WCDMA Band II & Wi-Fi & BT:**

| RF Exposure Conditions | Test Position | Simultaneous Transmission Scenario |                |           | $\Sigma$ 1-g SAR (W/kg) | SPLSR (Yes/No) |
|------------------------|---------------|------------------------------------|----------------|-----------|-------------------------|----------------|
|                        |               | WCDMA Band II                      | Wi-Fi DTS Band | Bluetooth |                         |                |
| Body-worn              | Rear          | 0.275                              | 0.675          |           | 0.950                   | No             |
|                        | Edge 1        | 0.353                              | 0.380          |           | 0.733                   | No             |
|                        | Rear          | 0.275                              |                | 0.13      | 0.405                   | No             |
|                        | Edge 1        | 0.353                              |                | 0.13      | 0.483                   | No             |

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/kg, SPLSR assessment is not required.
- SPLSR mean is “The SAR to Peak Location Separation Ratio “

**Sum of the SAR for WCDMA Band V & Wi-Fi & BT:**

| RF Exposure Conditions | Test Position | Simultaneous Transmission Scenario |                |           | $\Sigma$ 1-g SAR (W/kg) | SPLSR (Yes/No) |
|------------------------|---------------|------------------------------------|----------------|-----------|-------------------------|----------------|
|                        |               | WCDMA Band V                       | Wi-Fi DTS Band | Bluetooth |                         |                |
| Body-worn              | Rear          | 0.903                              | 0.675          |           | 1.578                   | No             |
|                        | Edge 1        | 0.221                              | 0.380          |           | 0.601                   | No             |
|                        | Rear          | 0.903                              |                | 0.13      | 1.033                   | No             |
|                        | Edge 1        | 0.221                              |                | 0.13      | 0.351                   | No             |

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/kg, SPLSR assessment is not required.
- SPLSR mean is “The SAR to Peak Location Separation Ratio “

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab

Date: Oct. 12, 2021

System Check Head 835 MHz

DUT: Dipole 835 MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1; Conv.F=5.24

Frequency: 835 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 41.62$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Flat Section; Input Power=18dBm


Ambient temperature (°C):21.6, Liquid temperature (°C): 21.4

### SATIMO Configuration

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/System Check 835MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/System Check 835MHz Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=-2.00, Y=1.00

SAR Peak: 0.88 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.371852 |
| SAR 1g (W/Kg)  | 0.593843 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



**Test Laboratory: AGC Lab**  
**System Check Head 1900MHz**  
**DUT: Dipole 1900 MHz; Type: SID 1900**

**Date: Oct. 13, 2021**


Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=4.48  
Frequency: 1900 MHz; Medium parameters used:  $f = 1800\text{MHz}$ ;  $\sigma = 1.37 \text{ mho/m}$ ;  $\epsilon_r = 39.56$ ;  $\rho = 1000 \text{ kg/m}^3$  ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature ( $^{\circ}\text{C}$ ):21.2, Liquid temperature ( $^{\circ}\text{C}$ ): 21.0

SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

**Configuration/System Check 1900MHz Head/Area Scan:** Measurement grid: dx=8mm, dy=8mm

**Configuration/System Check 1900MHz Head/Zoom Scan:** Measurement grid: dx=8mm,dy=8mm, dz=5mm



**Maximum location: X=5.00, Y=-1.00**

**SAR Peak: 4.34 W/kg**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 1.245824 |
| <b>SAR 1g (W/Kg)</b>  | 2.540637 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



Test Laboratory: AGC Lab

Date: Oct. 14, 2021

System Check Head 2450 MHz

DUT: Dipole 2450 MHz Type: SID 2450

Communication System CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1; Conv.F=4.32

Frequency: 2450 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.74$  mho/m;  $\epsilon_r = 39.00$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Flat Section; Input Power=18dBm


Ambient temperature (°C):22.1, Liquid temperature (°C): 21.8

SATIMO Configuration

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/System Check 2450MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/System Check 2450MHz Head/Zoom Scan: Measurement grid: dx=5mm,dy=5mm, dz=5mm



Maximum location: X=-1.00, Y=0.00

SAR Peak: 5.41 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 1.403044 |
| SAR 1g (W/Kg)  | 3.128517 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## APPENDIX B. SAR MEASUREMENT DATA

Test Laboratory: AGC Lab  
GPRS 850 Mid- Body- Back (3up)  
DUT: Tablet PC; Type: BS101

Date: Oct. 12, 2021

Communication System: GPRS-3 Slot; Communication System Band: GSM 850; Duty Cycle: 1:2.7; Conv.F=5.24;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.23$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.6, Liquid temperature (°C): 21.4


SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/GPRS 850 Mid-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/GPRS 850 Mid-Body-Back/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

|                 |                                     |
|-----------------|-------------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm       |
| Zoom Scan       | 5x5x7,dx=8mm dy=8mm dz=5mm,Complete |
| Phantom         | ELLI                                |
| Device Position | Body Back                           |
| Band            | GSM 850                             |
| Channels        | Middle                              |
| Signal          | TDMA (Crest factor: 2.7)            |



Maximum location: X=-25.00, Y=57.00

SAR Peak: 0.50 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.220818 |
| SAR 1g (W/Kg)  | 0.335198 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  | 24.00  | 29.00  |
|------------|--------|--------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.4957 | 0.3414 | 0.2231 | 0.1671 | 0.1210 | 0.0892 | 0.0646 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



Test Laboratory: AGC Lab  
GPRS 1900 Mid-Edge 1 (4up)  
DUT: Tablet PC; Type: BS101

Date: Oct. 13, 2021


Communication System: GPRS-4Slot; Communication System Band: PCS 1900; Duty Cycle: 1:2.1; Conv.F=4.48;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1800\text{MHz}$ ;  $\sigma = 1.36\text{ mho/m}$ ;  $\epsilon_r = 39.78$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom section: Flat Section  
Ambient temperature ( $^{\circ}\text{C}$ ): 21.2, Liquid temperature ( $^{\circ}\text{C}$ ): 21.0

SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/GPRS1900 Mid-Edge 1/Area Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$   
Configuration/GPRS1900 Mid-Edge 1/Zoom Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ ;

|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm                                     |
| Zoom Scan       | 5x5x7, $dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$ , Complete |
| Phantom         | ELLI                                                              |
| Device Position | Edge 1                                                            |
| Band            | PCS 1900                                                          |
| Channels        | Middle                                                            |
| Signal          | TDMA (Crest factor: 2.0)                                          |





Maximum location: X=3.00, Y=64.00  
SAR Peak: 0.08 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.021194 |
| SAR 1g (W/Kg)  | 0.044066 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



Test Laboratory: AGC Lab  
WCDMA Band II Mid-Edge 1(RMC)  
DUT: Tablet PC; Type: BS101

Date: Oct. 13, 2021


Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.48  
Frequency: 1880 MHz; Medium parameters used:  $f = 1800\text{MHz}$ ;  $\sigma = 1.36\text{ mho/m}$ ;  $\epsilon_r = 39.78$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom section: Flat Section  
Ambient temperature ( $^{\circ}\text{C}$ ): 21.2, Liquid temperature ( $^{\circ}\text{C}$ ): 21.0

SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/ WCDMA band II Mid-Edge 1/Area Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$   
Configuration/ WCDMA band II Mid-Edge 1/Zoom Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ ;

|                 |                                     |
|-----------------|-------------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm       |
| Zoom Scan       | 5x5x7,dx=8mm dy=8mm dz=5mm,Complete |
| Phantom         | ELLI                                |
| Device Position | Edge 1                              |
| Band            | WCDMA band II                       |
| Channels        | Middle                              |
| Signal          | CDMA (Crest factor: 1.0)            |



Maximum location: X=-1.00, Y=64.00



SAR Peak: 0.52 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.142352 |
| SAR 1g (W/Kg)  | 0.296988 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



Test Laboratory: AGC Lab  
WCDMA Band V High-Body-Towards Grounds (RMC)  
DUT: Tablet PC; Type: BS101

Date: Oct. 12, 2021

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD; Duty Cycle:1: 1; Conv.F=5.24;  
Frequency: 846.6 MHz; Medium parameters used:  $f = 835\text{MHz}$ ;  $\sigma = 0.93\text{ mho/m}$ ;  $\epsilon_r = 41.03$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom section: Flat Section  
Ambient temperature ( $^{\circ}\text{C}$ ): 21.6, Liquid temperature ( $^{\circ}\text{C}$ ): 21.4


SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

Configuration/ WCDMA Band V High-Body-Back/Area Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$

Configuration/ WCDMA Band V High-Body-Back/Zoom Scan: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ ;

|                 |                                     |
|-----------------|-------------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm       |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Complete |
| Phantom         | ELLI                                |
| Device Position | Body Back                           |
| Band            | WCDMA Band V                        |
| Channels        | High                                |
| Signal          | CDMA (Crest factor: 1.0)            |



Maximum location: X=-18.00, Y=55.00

SAR Peak: 1.53 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.520696 |
| SAR 1g (W/Kg)  | 0.894923 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  | 24.00  | 29.00  |
|------------|--------|--------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.5560 | 0.9136 | 0.4774 | 0.3159 | 0.2179 | 0.1551 | 0.1103 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## WIFI MODE

Test Laboratory: AGC Lab  
802.11b Mid-Body-Worn- Back (DTS)  
DUT: Tablet PC; Type: BS101

Date: Oct. 14, 2021


Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.32;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.73$  mho/m;  $\epsilon_r = 39.26$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):22.1, Liquid temperature (°C): 21.8

### SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

**Configuration/802.11b Mid- Body- Back /Area Scan:** Measurement grid: dx=8mm, dy=8mm  
**Configuration/802.11b Mid- Body- Back /Zoom Scan:** Measurement grid: dx=5mm,dy=5mm, dz=5mm;

|                 |                               |
|-----------------|-------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm |
| ZoomScan        | 7x7x7,dx=5mm dy=5mm dz=5mm    |
| Phantom         | ELLI                          |
| Device Position | Body Back                     |
| Band            | 2450MHz                       |
| Channels        | Middle                        |
| Signal          | Crest factor: 1.0             |



**Maximum location: X=-35.00, Y=-24.00**



**SAR Peak: 1.20 W/kg**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.217034 |
| <b>SAR 1g (W/Kg)</b>  | 0.572677 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## Repeated SAR

Test Laboratory: AGC Lab

Date: Oct. 12, 2021

WCDMA Band V High-Body-Towards Grounds (RMC)

DUT: Tablet PC; Type: BS101


Communication System: UMTS; Communication System Band: BAND V UTRA/FDD; Duty Cycle:1: 1; Conv.F=5.24;  
Frequency: 846.6 MHz; Medium parameters used:  $f = 835\text{MHz}$ ;  $\sigma = 0.93\text{ mho/m}$ ;  $\epsilon_r = 41.03$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom section: Flat Section  
Ambient temperature ( $^{\circ}\text{C}$ ): 21.6, Liquid temperature ( $^{\circ}\text{C}$ ): 21.4

## SATIMO Configuration:

- Probe: SSE5; Calibrated: Dec. 17,2020; Serial No.: SN 03/18 EP327
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4\_02\_35

**Configuration/ WCDMA Band V High-Body-Back/Area Scan:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ 
**Configuration/ WCDMA Band V High-Body-Back/Zoom Scan:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ ;

|                 |                                     |
|-----------------|-------------------------------------|
| Area Scan       | surf_sam_plan.txt, h= 5.00 mm       |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Complete |
| Phantom         | ELLI                                |
| Device Position | Body Back                           |
| Band            | WCDMA Band V                        |
| Channels        | High                                |
| Signal          | CDMA (Crest factor: 1.0)            |



Maximum location: X=-17.00, Y=56.00

SAR Peak: 1.14 W/kg

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.472125 |
| SAR 1g (W/Kg)  | 0.745454 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>




## APPENDIX C. TEST SETUP PHOTOGRAPHS

Body Back 0mm



Edge 1(Top) 0mm



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



Edge 4(Left) 0mm




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN

Note : The position used in the measurement were according to IEEE 1528-2013



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



## APPENDIX D. CALIBRATION DATA

Refer to Attached files.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>





## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

