FCC Radio Test Report

FCC ID: 2AXXD-MLBT2101

The report concerns: Original Grant

Report Reference No.....:	20EFCS12046 0021
Date Sample(s) Received.....:	2020-12-10
Date of Tested.....:	From 2020-12-17 to 2021-01-04
Date of issue.....:	2021-01-05
Testing Laboratory .....:	DongGuan ShuoXin Electronic Technology Co., Ltd.
Address .....:	Zone A, 1F, No. 6, XinGang Road YuanGang Street, XinAn District, ChangAn Town, DongGuan City, GuangDong, China
Applicant's name .....:	Musilab Electronic (DongGuan) Co., Ltd
Address .....:	No.5 Huanwei Street,Fugang,Qingxi Town, Dongguan,Guangdong,China
Manufacturer.....:	Musilab Electronic (DongGuan) Co., Ltd
Equipment.....:	BT Wireless HiFi speaker
Trade Mark .....:	**Musilab® Audio**
Model .....:	BT210,BT210T, BT208,BT208T,BT218,BT218T, SOLO 4,SOLO 4T
Ratings .....:	I/P: AC100-240V 50/60Hz O/P: Speaker Power Output: 36 Watts Rms

Test Engineer: Blue Qiu

Responsible Engineer : Smile Wang

Authorized Signatory: King Wang

Table of Contents Page

1 . TEST REPORT DECLARE 5

2 . SUMMARY OF TEST RESULTS 6

2.1 MEASUREMENT UNCERTAINTY 7

3 . GENERAL INFORMATION 8

3.1 GENERAL DESCRIPTION OF EUT 8

3.2 DESCRIPTION OF TEST MODES 10

3.3 PARAMETERS OF TEST SOFTWARE 11

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 11

3.5 SUPPORT UNITS 11

3.6 TEST ENVIRONMENT CONDITIONS 12

4 . AC POWER LINE CONDUCTED EMISSIONS TEST 13

4.1 LIMIT 13

4.2 TEST PROCEDURE 13

4.3 MEASUREMENT INSTRUMENTS LIST 13

4.4 TESTSETUP 14

4.5 EUT OPERATING CONDITIONS 14

4.6 TEST RESULTS 15

5 . RADIATED EMISSION TEST 17

5.1 LIMIT 17

5.2 TEST PROCEDURE AND SETTING 18

5.3 MEASUREMENT INSTRUMENTS LIST 19

5.4 TESTSETUP 19

5.5 EUT OPERATING CONDITIONS 20

5.6 TEST RESULTS - 9 KHZ TO 30MHZ 21

5.7 TEST RESULTS- 30 MHZ TO 1000MHZ 22

5.8 TEST RESULTS - ABOVE 1000MHZ(BAND EDGE) 24

5.9 TEST RESULTS - ABOVE 1000MHZ(HARMONIC) 32

6 . NUMBER OF HOPPING FREQUENCY 44

6.1 LIMIT 44

6.2 TEST PROCEDURE AND SETTING 44

6.3 MEASUREMENT INSTRUMENTS LIST 44

6.4 TEST SETUP 44

Table of Contents Page

6.5 EUT OPERATION CONDITIONS 44
6.6 TEST RESULTS 45
7 . AVERAGE TIME OF OCCUPANCY 46
7.1 LIMIT 46
7.2 TEST PROCEDURE AND SETTING 46
7.3 MEASUREMENT INSTRUMENTS LIST 46
7.4 TEST SETUP 46
7.5 EUT OPERATION CONDITIONS 46
7.6 TEST RESULTS 47
8 . HOPPING CHANNEL SEPARATION MEASUREMENT 49
8.1 LIMIT 49
8.2 TEST PROCEDURE AND SETTING 49
8.3 MEASUREMENT INSTRUMENTS LIST 49
8.4 TEST SETUP 49
8.5 EUT OPERATION CONDITIONS 49
8.6 TEST RESULTS 50
9 . BANDWIDTH TEST 52
9.1 LIMIT 52
9.2 TEST PROCEDURE AND SETTING 52
9.3 MEASUREMENT INSTRUMENTS LIST 52
9.4 TEST SETUP 52
9.5 EUT OPERATION CONDITIONS 52
9.6 TEST RESULTS 53
10 . MAXIMUM OUTPUT POWER 55
10.1 LIMIT 55
10.2 TEST PROCEDURE AND SETTING 55
10.3 MEASUREMENT INSTRUMENTS LIST 55
10.4 TEST SETUP 55
10.5 EUT OPERATION CONDITIONS 55
10.6 TEST RESULTS 56
11 . CONDUCTED SPURIOUS EMISSION 57
11.1 LIMIT 57
11.2 TEST PROCEDURE AND SETTING 57
11.3 MEASUREMENT INSTRUMENTS LIST 57

Table of Contents **Page**

11.4 TEST SETUP **57**
11.5 EUT OPERATION CONDITIONS **57**
11.6 TEST RESULTS **58**

1. TEST REPORT DECLARE

Applicant	Musilab Electronic (DongGuan) Co., Ltd
Address	No.5 Huanwei Street,Fugang,Qingxi Town, Dongguan,Guangdong,China
Manufacturer	Musilab Electronic (DongGuan) Co., Ltd
Address	No.5 Huanwei Street,Fugang,Qingxi Town, Dongguan,Guangdong,China
Factory	Musilab Electronic (DongGuan) Co., Ltd
Address	No.5 Huanwei Street,Fugang,Qingxi Town, Dongguan,Guangdong,China
Equipment	BT Wireless HiFi speaker
Model No.	BT210,BT210T, BT208,BT208T,BT218,BT218T,SOLO 4,SOLO 4T
Trade Mark	Musilab® Audio
Standard	FCC Part15, Subpart C (15.247) ANSI C63.10-2013

We Declare:

The equipment described above is tested by DongGuanShuoXin Electronic Technology Co., Ltd(ATT). and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and DongGuanShuoXin Electronic Technology Co., Ltd.(ATT) is assumed of full responsibility for the accuracy and completeness of these tests.

ATT is not responsible for the sampling stage, so the results only apply to the sample as received.

ATT's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. ATT shall have no liability for any declarations, inferences or generalizations drawn by the client or others from ATT issued reports.

2. SUMMARY OF TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below:

Standard(s) Section		Test Item	Judgment	Remark
FCC	ISED			
15.207	-	AC Power Line Conducted Emissions	PASS	------
15.247(d) 15.205(a) 15.209(a)	-	Radiated Emission	PASS	------
15.247(a)(1)(iii)	-	Number of Hopping Frequency	PASS	------
15.247(a)(1)(iii)	-	Average Time Of Occupancy	PASS	------
15.247(a)(1)	-	Hopping Channel Separation	PASS	------
15.247(a)(1)	-	Bandwidth	PASS	------
15.247(a)(1)	-	Maximum Output Power	PASS	------
15.247(d)	-	Conducted Spurious Emission	PASS	------
-	-	Frequency Stability	PASS	------
15.203	-	Antenna Requirement	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable in this test report

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

2.1MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Uncertainty for Conductionemission test (9kHz-150kHz)	3.7 dB
Uncertainty for Conduction emission test (150kHz-30MHz)	3.3 dB
Uncertainty for Radiation Emission test (30MHz-200MHz)	4.60 dB (Polarize: V)
	4.60 dB (Polarize: H)
Uncertainty for Radiation Emission test (200MHz-1GHz)	6.10 dB (Polarize: V)
	5.08 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz-6GHz)	5.01 dB (Polarize: V)
	5.01 dB (Polarize: H)
Uncertainty for Radiation Emission test (6GHz-18GHz)	5.26 dB (Polarize: V)
	5.26 dB (Polarize: H)
Uncertainty for Radiation Emission test (18GHz-40GHz)	5.06 dB (Polarize: V)
	5.06 dB (Polarize: H)
Uncertainty for radio frequency	±0.048kHz
Uncertainty for conducted RF Power	±0.32dB

Note:

This uncertainty represents an expanded uncertainty expressed at approximately the 95%confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	BT Wireless HiFi speaker	
Brand Name	Musilab® Audio	
Test Model	BT210,BT210T, BT208,BT208T,BT218,BT218T,SOLO 4,SOLO 4T	
Series Model	N/A	
Model Difference(s)	N/A	
Hardware Version	V1.0	
Software Version	V1.0	
PowerSource	Supplied from AC.	
Power Rating	I/P: AC100-240V 50/60Hz O/P: Speaker Power Output: 36 Watts Rms	
Operation Frequency	2402 MHz ~ 2480 MHz	
Modulation Technology	GFSK, π/4-DQPSK	
Bit Rate of Transmitter	1Mbps /2Mbps	
Antenna Information	Antenna Type:PCB	Maximum Peak Gain:1.2dBi
Max. Output Power	1Mbps: -2.093dBm (0.000618W) 2Mbps:-1.440dBm (0.000718W)	

Note:

1. For a more detailed features description, please refer to the manufacturer’s specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode**NOTE (1)**
Mode 2	TX Mode Channel 78 _2Mbps

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 2	TX Mode Channel 78 _2Mbps

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 2	TX Mode Channel 78 _2Mbps

Radiated emissions test - Above 1GHz	
Final Test Mode	Description
Mode 1	TXMode **NOTE (1)**

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode**NOTE (1)**

Note:

(1) The measurements are performed at the high, middle, low available channels.

3.3PARAMETERS OF TEST SOFTWARE

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software	692FCC_assist		
Frequency (MHz)	2402	2441	2480
Parameters(1Mbps)	10	10	10
Parameters(2Mbps)	10	10	10

3.4BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED



3.5SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
AE	Notebook	ACER	MS2367	32807810766

Item	Cable Type	Shielded Type	Ferrite Core	Length
C1	DC Cable	NO	NO	0.8m

3.6TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage
AC Power Line Conducted Emissions	25°C	53%	AC 120V
Radiated Emissions-9K-30MHz	25°C	60%	AC 120V
Radiated Emissions-30 MHz to 1GHz	24°C	68%	AC 120V
Radiated Emissions-Above 1000 MHz	24°C	68%	AC 120V
Number of Hopping Frequency	24.8°C	40.9%	AC 120V
Average Time Of Occupancy	24.8°C	40.9%	AC 120V
Hopping Channel Separation	24.8°C	40.9%	AC 120V
Bandwidth	24.8°C	40.9%	AC 120V
Maximum Output Power	24.8°C	40.9%	AC 120V
Conducted Spurious Emission	24.8°C	40.9%	AC 120V

4.AC POWER LINE CONDUCTED EMISSIONS TEST

4.1LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56*	56 to 46*
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.2TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipmentpowered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

4.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Pulse Limiter	MTS-systemtechnik	MTS-IMP-136	261115-010-0024	12/11/2021
2	EMI Test Receiver	R&S	ESCI	101308	12/11/2021
3	LISN	AFJ	LS16	16011103219	06/09/2021
4	LISN	Schwarzbeck	NSLK 8127	8127-432	12/11/2021
5	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

4.4TESTSETUP



4.5EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuouslytransmitting data or hopping on mode.

4.6TEST RESULTS

Test Mode:	TX Mode Channel 78 _2Mbps

Line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1980	38.68	11.20	49.88	63.69	-13.81	QP
2	0.1980	33.57	11.20	44.77	53.69	-8.92	AVG
3	0.3300	32.55	10.48	43.03	59.45	-16.42	QP
4	0.3300	30.49	10.48	40.97	49.45	-8.48	AVG
5	0.3940	31.73	10.41	42.14	57.98	-15.84	QP
6	0.3940	29.22	10.41	39.63	47.98	-8.35	AVG
7	0.4620	32.54	10.33	42.87	56.66	-13.79	QP
8	0.4620	28.80	10.33	39.13	46.66	-7.53	AVG
9	0.5299	31.15	10.28	41.43	56.00	-14.57	QP
10	0.5299	27.32	10.28	37.60	46.00	-8.40	AVG
11	29.6140	37.47	10.21	47.68	60.00	-12.32	QP
12	29.6140	30.70	10.21	40.91	50.00	-9.09	AVG

Remarks:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _2Mbps

Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1980	38.65	11.20	49.85	63.69	-13.84	QP
2	0.1980	33.16	11.20	44.36	53.69	-9.33	AVG
3	0.2660	31.41	10.74	42.15	61.24	-19.09	QP
4	0.2660	25.96	10.74	36.70	51.24	-14.54	AVG
5	0.3300	33.64	10.48	44.12	59.45	-15.33	QP
6	0.3300	28.33	10.48	38.81	49.45	-10.64	AVG
7	0.5299	29.60	10.28	39.88	56.00	-16.12	QP
8	0.5299	24.26	10.28	34.54	46.00	-11.46	AVG
9	19.2619	35.90	10.22	46.12	60.00	-13.88	QP
10	19.2619	31.46	10.22	41.68	50.00	-8.32	AVG
11	29.2220	40.53	10.21	50.74	60.00	-9.26	QP
12	29.2220	33.05	10.21	43.26	50.00	-6.74	AVG

Remarks:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

5. RADIATED EMISSION TEST

5.1LIMIT

In case the emission fall within the restricted band specified on15.205(a) &RSS-Gen 8.10, then the 15.209(a) &RSS-Gen 8.9 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-30 MHz)

Frequency (MHz)	Magnetic field strength (H-Field) (μA/m)	Measurement Distance (meters)
0.009-0.490	6.37/F(kHz)	300
0.490-1.705	6.37/F(kHz)	30
1.705-30.0	0.08	30

LIMITS OF RADIATED EMISSION MEASUREMENT (30 MHz-1000MHz)

Frequency (MHz)	Field Strength (μV/m at 3m)
30-88	100
88-216	150
216-960	200
Above 960	500

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The limit for radiated test was performed according to FCC PART 15C and RSS-247.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2TEST PROCEDURE AND SETTING

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn‘t perform. (below 1GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn‘t perform. (above 1GHz)
i. The test result is calculated as the following:
   (1) Result = Reading + Correct Factor
   (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
   (3) Margin = Result - Limit

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	RBW 1MHz VBW 3MHz peak detector for Pk value RMS detector for AV value

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

5.3MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	101307	12/12/2021
2	Spectrum Analyzer	Agilent	E4407B	US40240708	11/17/2021
3	Loop antenna	SCHWARZBECK K	FMZB1519	1519-062	12/14/2021
4	Broadband antenna	SCHWARZBECK	VULB9168	VULB9168-192	03/22/2021
5	HORN ANTENNA	SCHWARZBECK	BBHA9120D	9120D 1065	04/21/2021
6	Preamplifier Amplifier	HP	8447F	3113A05680	12/11/2021
7	PRE-AMPLIFIER	CY	EMC011830	980136	12/11/2021
8	RF Cable	R&S	Test Cable 4	4	12/11/2021
9	RF Cable	R&S	Test Cable 5	5	12/11/2021
10	RF Cable	R&S	Test Cable 9	9	04/22/2021
11	RF Cable	R&S	Test Cable 10	10	12/11/2021
12	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

5.4TESTSETUP

9 kHz-30 MHz



30 MHz to 1 GHz



Above 1 GHz



5.5EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6TEST RESULTS - 9 kHz TO 30MHz

Test Mode:	TX Mode Channel 78 _2Mbps

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =20 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor

5.7TEST RESULTS- 30 MHz TO 1000MHz

Test Mode:	TX Mode Channel 78 _2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9618	35.22	-11.62	23.60	40.00	-16.40	QP
2	38.6160	33.18	-13.02	20.16	40.00	-19.84	QP
3	78.1389	35.58	-15.22	20.36	40.00	-19.64	QP
4	222.1698	33.34	-9.89	23.45	46.00	-22.55	QP
5	248.5518	34.38	-8.78	25.60	46.00	-20.40	QP
6	330.1949	39.58	-8.17	31.41	46.00	-14.59	QP

Test Mode:	TX Mode Channel 78 _2Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	74.3955	33.63	-16.59	17.04	40.00	-22.96	QP
2	192.4186	35.09	-9.53	25.56	43.50	-17.94	QP
3	210.7860	37.37	-8.89	28.48	43.50	-15.02	QP
4	222.1698	35.36	-8.32	27.04	46.00	-18.96	QP
5	254.7284	36.10	-6.00	30.10	46.00	-15.90	QP
6	343.1800	36.18	-7.90	28.28	46.00	-17.72	QP

5.8TEST RESULTS - ABOVE 1000MHz(BAND EDGE)

Test Mode:	TX 2402 MHz_CH00_1Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	21.10	30.06	51.16	74.00	-22.84	peak
2	2390.000	10.01	30.06	40.07	54.00	-13.93	AVG
3	2401.850	57.52	30.10	87.62	/	/	peak
4	2402.050	25.23	30.10	55.33	/	/	AVG

Test Mode:	TX 2402 MHz_CH00_1Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	21.94	30.06	52.00	74.00	-22.00	peak
2	2390.000	10.02	30.06	40.08	54.00	-13.92	AVG
3	2401.900	26.24	30.10	56.34	/	/	AVG
4	2402.000	64.93	30.10	95.03	/	/	peak

Test Mode:	TX 2480 MHz_CH78_1Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.800	25.03	30.32	55.35	/	/	AVG
2	2479.850	58.31	30.32	88.63	/	/	peak
3	2483.500	22.83	30.33	53.16	74.00	-20.84	peak
4	2483.500	10.44	30.33	40.77	54.00	-13.23	AVG

Test Mode:	TX 2480 MHz_CH78_1Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.750	67.50	30.32	97.82	/	/	peak
2	2480.100	26.79	30.32	57.11	/	/	AVG
3	2483.500	23.73	30.33	54.06	74.00	-19.94	peak
4	2483.500	11.04	30.33	41.37	54.00	-12.63	AVG

Test Mode:	TX 2402 MHz_CH00_2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	21.28	30.06	51.34	74.00	-22.66	peak
2	2390.000	9.99	30.06	40.05	54.00	-13.95	AVG
3	2401.850	58.75	30.10	88.85	/	/	peak
4	2401.850	24.80	30.10	54.90	/	/	AVG

Test Mode:	TX 2402 MHz_CH00_2Mbps

Horizontal



.

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	21.50	30.06	51.56	74.00	-22.44	peak
2	2390.000	9.98	30.06	40.04	54.00	-13.96	AVG
3	2402.000	60.92	30.10	91.02	/	/	peak
4	2402.000	25.73	30.10	55.83	/	/	AVG

Test Mode:	TX 2480 MHz_CH78_2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.800	58.17	30.32	88.49	/	/	peak
2	2479.900	24.89	30.32	55.21	/	/	AVG
3	2483.500	21.55	30.33	51.88	74.00	-22.12	peak
4	2483.500	10.42	30.33	40.75	54.00	-13.25	AVG

Test Mode:	TX 2480 MHz_CH78_2Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.850	64.14	30.32	94.46	/	/	peak
2	2480.000	25.88	30.32	56.20	/	/	AVG
3	2483.500	24.12	30.33	54.45	74.00	-19.55	peak
4	2483.500	10.94	30.33	41.27	54.00	-12.73	AVG

5.9TEST RESULTS - ABOVE 1000MHz(HARMONIC)

Test Mode:	TX 2402 MHz_CH00_1Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	48.92	-7.53	41.39	74.00	-32.61	peak
2	4804.000	40.55	-7.53	33.02	54.00	-20.98	AVG

Test Mode:	TX 2402 MHz_CH00_1Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	49.22	-7.53	41.69	74.00	-32.31	peak
2	4804.000	40.05	-7.53	32.52	54.00	-21.48	AVG

Test Mode:	TX 2441 MHz_CH39_1Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.500	47.08	-7.31	39.77	74.00	-34.23	peak
2	4882.500	38.72	-7.31	31.41	54.00	-22.59	AVG

Test Mode:	TX 2441 MHz_CH39_1Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.500	48.98	-7.31	41.67	74.00	-32.33	peak
2	4882.500	39.33	-7.31	32.02	54.00	-21.98	AVG

Test Mode:	TX 2480 MHz_CH78_1Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	49.09	-7.09	42.00	74.00	-32.00	peak
2	4960.000	39.14	-7.09	32.05	54.00	-21.95	AVG

Test Mode:	TX 2480 MHz_CH78_1Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.250	49.82	-7.09	42.73	74.00	-31.27	peak
2	4960.250	40.71	-7.09	33.62	54.00	-20.38	AVG

Test Mode:	TX 2402 MHz_CH00_2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	48.92	-7.53	41.39	74.00	-32.61	peak
2	4804.000	39.68	-7.53	32.15	54.00	-21.85	AVG

Test Mode:	TX 2402 MHz_CH00_2Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	49.22	-7.53	41.69	74.00	-32.31	peak
2	4804.000	37.73	-7.53	30.20	54.00	-23.80	AVG

Test Mode:	TX 2441 MHz_CH39_2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.100	47.08	-7.31	39.77	74.00	-34.23	peak
2	4882.100	38.56	-7.31	31.25	54.00	-22.75	AVG

Test Mode:	TX 2441 MHz_CH39_2Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.000	48.98	-7.31	41.67	74.00	-32.33	peak
2	4882.000	39.36	-7.31	32.05	54.00	-21.95	AVG

Test Mode:	TX 2480 MHz_CH78_2Mbps

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.200	49.09	-7.09	42.00	74.00	-32.00	peak
2	4960.200	40.62	-7.09	33.53	54.00	-20.47	AVG

Test Mode:	TX 2480 MHz_CH78_2Mbps

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.200	49.82	-7.09	42.73	74.00	-31.27	peak
2	4960.200	41.24	-7.09	34.15	54.00	-19.85	AVG

6.NUMBER OF HOPPING FREQUENCY

6.1LIMIT

FCC Part15, Subpart C (15.247)	
Section	Test Item
15.247(a)(1)(iii)	Number of Hopping Frequency

6.2TEST PROCEDURE AND SETTING

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW=100 kHz, VBW=300 kHz, Sweep time = Auto.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100kHz
VBW	300kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

6.4TEST SETUP



6.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Hopping Mode_1Mbps		
Number of Hopping Frequency	Measurement result(CH)	Limit(CH)
	79	≥15



Hopping Mode_2Mbps		
Number of Hopping Frequency	Measurement result(CH)	Limit(CH)
	79	≥15



7.AVERAGE TIME OF OCCUPANCY

7.1LIMIT

FCC Part15, Subpart C (15.247)		
Section	Test Item	Limit
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec

7.2TEST PROCEDURE AND SETTING

a. The transmitter output (antenna port) was connected to the spectrum analyzer
b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz
c. Use a video trigger with the trigger level set to enabletriggering only on full pulses
d. Sweep Time is more than once pulse time
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span
f. Measure the maximum time duration of one single pulse
g. Set the EUT for DH1, DH3 and DH5 packet transmitting
h. Measure the maximum time duration of one single pulse
i. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX).So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds
j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slotsTX, 1 time slot RX).So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds
k. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slotsTX, 1 time slot RX).So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

7.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

7.4TEST SETUP

7.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

TX Mode_1Mbps				
Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.380	121.6	400
DH3	2441	1.638	262.1	400
DH5	2441	2.885	307.7	400

DH1



DH3



DH5



TX Mode_2Mbps				
Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.391	125.1	400
DH3	2441	1.643	262.9	400
DH5	2441	2.893	308.6	400

DH1



DH3

DH5



8.HOPPING CHANNEL SEPARATION MEASUREMENT

8.1LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

8.2TEST PROCEDURE AND SETTING

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
Video (or Average) Bandwidth (VBW) ≥ RBW
Sweep = Auto
Detector function = Peak
Trace = Max Hold

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	10 kHz
VBW	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

8.4TEST SETUP

8.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
CH00	2402	1.002	>(25KHz or 2/3*20dB Bandwidth)	PASS
CH39	2441	0.992	>(25KHz or 2/3*20dB Bandwidth)	PASS
CH78	2480	0.996	>(25KHz or 2/3*20dB Bandwidth)	PASS

2402 MHz

2441 MHz

2480 MHz



TX Mode_2Mbps				
Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
CH00	2402	1.006	>(25KHz or 2/3*20dB Bandwidth)	PASS
CH39	2441	0.994	>(25KHz or 2/3*20dB Bandwidth)	PASS
CH78	2480	0.992	>(25KHz or 2/3*20dB Bandwidth)	PASS

2402 MHz

2441 MHz

2480 MHz

9.BANDWIDTH TEST

9.1LIMIT

FCC Part15, Subpart C (15.247)	
Section	Test Item
15.247(a)(1)	Bandwidth

9.2TEST PROCEDURE AND SETTING

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 30 kHz, VBW=100 kHz, Sweep Time = Auto.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth
RBW	30kHz
VBW	100kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

9.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

9.4TEST SETUP

9.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	20dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)	Result
CH00	2402	0.879	0.819	PASS
CH39	2441	0.881	0.822	PASS
CH78	2480	0.879	0.823	PASS

2402MHz



2441MHz



2480MHz



TX Mode_2Mbps				
Channel	Frequency (MHz)	20dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)	Result
CH00	2402	1.282	1.172	PASS
CH39	2441	1.284	1.172	PASS
CH78	2480	1.280	1.171	PASS

2402MHz



2441MHz



2480MHz



10.MAXIMUM OUTPUT POWER

10.1LIMIT

FCC Part15 , Subpart C (15.247)		
Section	Test Item	Limit
15.247(a)(1)	Maximum Output Power	0.125Watt or 21dBm

Note:
Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB band width of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

10.2TEST PROCEDURE AND SETTING

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

10.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

10.4TEST SETUP



10.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

10.6 TEST RESULTS

TX Mode_1Mbps				
Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Result
CH00	2402	-3.409	0.000456	PASS
CH39	2441	-3.419	0.000455	PASS
CH78	2480	-2.093	0.000618	PASS
Limit	21dBm /0.125W			

CH00



CH39



CH78



TX Mode_2Mbps				
Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Result
CH00	2402	-2.672	0.000541	PASS
CH39	2441	-2.405	0.000575	PASS
CH78	2480	-1.440	0.000718	PASS
Limit	21dBm /0.125W			

CH00



CH39



CH78



11.CONDUCTED SPURIOUS EMISSION

11.1LIMIT

For FCC

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

For ISED

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

11.2TEST PROCEDURE AND SETTING

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 100 kHz, VBW=300 kHz, Sweep time = Auto.

11.3MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2021/05/24
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

11.4TEST SETUP



11.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

11.6TEST RESULTS

TX Mode_1Mbps

Bandedge- CH00 (Lower)



Bandedge CH78 (Upper)



Bandedge- Hopping on (Lower)



Bandedge Hopping on (Upper)



10th Harmonic of the fundamental frequency

CH00



CH39



CH78



TX Mode_2Mbps

Bandedge- CH00 (Lower)



Bandedge CH78 (Upper)



Bandedge- Hopping on (Lower)



Bandedge- Hopping on (Upper)



10th Harmonic of the fundamental frequency

CH00



CH39



CH78



END OF TEST REPORT