

# TEST REPORT

**FCC ID: 2AXYP-OPN-371-R****Product: Open-Ear True Wireless Earbuds****Model No.: OPN-371****Trade Mark: oriamo****Report No.: WSCT-ANAB-R&E260200021A-BT****Issued Date: 17 March 2026****Issued for:****ORIAMO TECHNOLOGY LIMITED****FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI  
STREET FOTAN NT HONGKONG****Issued By:****World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.  
Building A-B,Baoli'an Industrial Park,No.58 and 60,Tangtou Avenue, Shiyan  
Street, Bao'an District, Shenzhen City, Guangdong Province, China****TEL: +86-755-26996192****FAX: +86-755-86376605**

**Note:** This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



## TABLE OF CONTENTS

|                                                     |    |
|-----------------------------------------------------|----|
| 1. Test Certification .....                         | 3  |
| 2. Test Result Summary .....                        | 4  |
| 3. EUT Description .....                            | 5  |
| 4. General Information .....                        | 7  |
| 4.1. TEST ENVIRONMENT AND MODE .....                | 7  |
| 4.2. DESCRIPTION OF SUPPORT UNITS .....             | 7  |
| 5. Facilities and Accreditations .....              | 8  |
| 5.1. FACILITIES .....                               | 8  |
| 5.2. ACCREDITATIONS .....                           | 8  |
| 5.3. MEASUREMENT UNCERTAINTY .....                  | 9  |
| 5.4. MEASUREMENT INSTRUMENTS .....                  | 10 |
| 6. Test Results and Measurement Data .....          | 11 |
| 6.1. ANTENNA REQUIREMENT .....                      | 11 |
| 6.2. CONDUCTED EMISSION .....                       | 12 |
| 6.3. CONDUCTED OUTPUT POWER .....                   | 16 |
| 6.4. 20dB OCCUPY BANDWIDTH .....                    | 23 |
| 6.5. CARRIER FREQUENCIES SEPARATION .....           | 30 |
| 6.6. HOPPING CHANNEL NUMBER .....                   | 37 |
| 6.7. DWELL TIME .....                               | 41 |
| 6.8. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....  | 52 |
| 6.9. CONDUCTED BAND EDGE MEASUREMENT .....          | 53 |
| 6.10. CONDUCTED SPURIOUS EMISSION MEASUREMENT ..... | 56 |
| 6.11. RADIATED SPURIOUS EMISSION MEASUREMENT .....  | 66 |
| 7. Test Setup Photographs .....                     | 78 |

Report No.: WSCT-ANAB-R&amp;E260200021A-BT Issued Date: 17 March 2026

## 1. Test Certification

**Product:** Open-Ear True Wireless Earbuds

**Model No.:** OPN-371

**Trade Mark:** oriamo

**Applicant:** ORIAMO TECHNOLOGY LIMITED  
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN  
MEI STREET FOTAN NT HONGKONG

**Manufacturer:** ORIAMO TECHNOLOGY LIMITED  
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN  
MEI STREET FOTAN NT HONGKONG

**Date of Test:** 02 February 2026 to 17 March 2026

**Applicable Standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Wang Xiang

(Wang Xiang)

Checked By:

Qin ShuiQuan

(Qin ShuiQuan)

Approved By:

Li Huaibi

(Li Huaibi)

Date:

17 March 2026

## 2. Test Result Summary

| Requirement                      | CFR 47 Section                      | Result |
|----------------------------------|-------------------------------------|--------|
| Antenna Requirement              | §15.203/§15.247 (c)                 | PASS   |
| AC Power Line Conducted Emission | §15.207                             | PASS   |
| Maximum conducted output power   | §15.247 (b)(1)<br>§2.1046           | PASS   |
| 20dB Occupied Bandwidth          | §15.247 (a)(1)<br>§2.1049           | PASS   |
| Carrier Frequencies Separation   | §15.247 (a)(1)                      | PASS   |
| Hopping Channel Number           | §15.247 (a)(1)                      | PASS   |
| Dwell Time                       | §15.247 (a)(1)                      | PASS   |
| Radiated Emission                | §15.205/§15.209<br>§2.1053, §2.1057 | PASS   |
| Band Edge                        | §15.247(d)<br>§2.1051, §2.1057      | PASS   |

### Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

|                             |                                                                                                                     |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Product Name:</b>        | Open-Ear True Wireless Earbuds                                                                                      |
| <b>Model :</b>              | OPN-371                                                                                                             |
| <b>Trade Mark:</b>          | oriamo                                                                                                              |
| <b>Operation Frequency:</b> | 2402MHz~2480MHz                                                                                                     |
| <b>Channel Separation:</b>  | 1MHz                                                                                                                |
| <b>Number of Channel:</b>   | 79                                                                                                                  |
| <b>Modulation Type:</b>     | GFSK, $\pi/4$ -DQPSK, 8-DPSK                                                                                        |
| <b>Antenna Type:</b>        | Chip Antenna                                                                                                        |
| <b>Antenna Gain:</b>        | -0.86dBi                                                                                                            |
| <b>Operating Voltage:</b>   | Rechargeable Li-ion Polymer Battery: 451012<br>0.1295Wh<br>3.7V 35mAh<br>Charging Box: 802040<br>3.7V 600mAh 2.22Wh |
| <b>Remark:</b>              | N/A.                                                                                                                |

Note: 1. N/A stands for no applicable.

2. The antenna gain is provided by the customer. For any reported data issues caused by the antenna gain, World Standardization Certification&Testing Group (Shenzhen) Co., Ltd assumes no responsibility.

3. The laboratory shall be responsible for all information in the report, except for the information provided by the client. The data provided by the client should be clearly identified. In addition, when the information provided by the client may affect the validity of the results, a disclaimer should be included in the report. When the laboratory is not responsible for sampling (such as when the sample is provided by the customer), the results should be declared in the report as applicable to the received sample.

### Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 0       | 2402MHz   | 20      | 2422MHz   | 40      | 2442MHz   | 60      | 2462MHz   |
| 1       | 2403MHz   | 21      | 2423MHz   | 41      | 2443MHz   | 61      | 2463MHz   |
| ...     | ...       | ...     | ...       | ...     | ...       | ...     | ...       |
| 10      | 2412MHz   | 30      | 2432MHz   | 50      | 2452MHz   | 70      | 2472MHz   |
| 11      | 2413MHz   | 31      | 2433MHz   | 51      | 2453MHz   | 71      | 2473MHz   |
| ...     | ...       | ...     | ...       | ...     | ...       | ...     | ...       |
| 18      | 2420MHz   | 38      | 2440MHz   | 58      | 2460MHz   | 78      | 2480MHz   |
| 19      | 2421MHz   | 39      | 2441MHz   | 59      | 2461MHz   | -       | -         |

Remark: Channel 0, 39 & 78 have been tested for GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation mode.

## 4. General Information

### 4.1. Test environment and mode

#### Operating Environment:

|                       |           |
|-----------------------|-----------|
| Temperature:          | 25.0 °C   |
| Humidity:             | 56 % RH   |
| Atmospheric Pressure: | 1010 mbar |

#### Test Mode:

|                   |                                                                                                      |
|-------------------|------------------------------------------------------------------------------------------------------|
| Engineering mode: | Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery |
|-------------------|------------------------------------------------------------------------------------------------------|

The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

### 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| /         | /         | /          | /      | /          |

#### Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyao Street, Bao'an District, Shenzhen City, Guangdong Province, China** of the World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 32. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:2017.

|        |                                    |
|--------|------------------------------------|
| USA    | ANAB - Certificate Number: AT-3951 |
| China  | CNAS (Registration Number: L3732)  |
| Canada | ISED(CAB identifier:CN0178)        |

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>

### 5.3. Measurement Uncertainty

| No. | Item                                                  | MU                        |
|-----|-------------------------------------------------------|---------------------------|
| 1   | Duty Cycle and Tx-Sequence and Tx-Gap                 | $\pm 1\%$                 |
| 2   | Dwell Time and Minimum Frequency Occupation           | $\pm 1.2\%$               |
| 3   | Medium Utilisation Factor                             | $\pm 1.3\%$               |
| 4   | Occupied Channel Bandwidth                            | $\pm 2.4\%$               |
| 5   | Transmitter Unwanted Emission in the out-of Band      | $\pm 1.3\%$               |
| 6   | Transmitter Unwanted Emissions in the Spurious Domain | $\pm 2.5\%$               |
| 7   | Receiver Spurious Emissions                           | $\pm 2.5\%$               |
| 8   | Conducted Emission Test                               | $\pm 3.2\text{dB}$        |
| 9   | RF power, conducted                                   | $\pm 0.16\text{dB}$       |
| 10  | Spurious emissions, conducted                         | $\pm 0.21\text{dB}$       |
| 11  | All emissions, radiated(<1GHz)                        | $\pm 4.7\text{dB}$        |
| 12  | All emissions, radiated(>1GHz)                        | $\pm 4.7\text{dB}$        |
| 13  | Temperature                                           | $\pm 0.5^{\circ}\text{C}$ |
| 14  | Humidity                                              | $\pm 2.0\%$               |

NOTE:1.The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

2. The  $U_{lab}$  is less than  $U_{cispr}$ , compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

3. For conducted emission test of laboratory have a measurement uncertainty greater than that specified in harmonized standard, this equipment can still be used provided that an adjustment is made follows : any additionan uncertainty in the test system over and above that specified in harmonized standard should be used to tighter the test requirements-making the test harder to pass. This procedure will ensure that a test system not comliant with harmonized standard does not increase the probability of passing a EUT that would otherwise have failed a test if a test system comliant with harmonized standard had been used.

## 5.4. MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT                    | MANUFACTURER           | MODEL        | SERIAL NUMBER | Calibration Date | Calibration Due. |
|--------------------------------------|------------------------|--------------|---------------|------------------|------------------|
| Test software                        | --                     | EZ-EMC       | CON-03A       | -                | -                |
| Test software                        | --                     | MTS8310      |               | -                |                  |
| EMI Test Receiver                    | R&S                    | ESCI         | 100005        | 11/05/2025       | 11/04/2026       |
| LISN                                 | AFJ                    | LS16         | 16010222119   | 11/05/2025       | 11/04/2026       |
| LISN(EUT)                            | Mestec                 | AN3016       | 04/10040      | 11/05/2025       | 11/04/2026       |
| Universal Radio Communication Tester | R&S                    | CMU 200      | 1100.0008.02  | 11/05/2025       | 11/04/2026       |
| Coaxial cable                        | Megalon                | LMR400       | N/A           | 11/05/2025       | 11/04/2026       |
| GPIO cable                           | Megalon                | GPIO         | N/A           | 11/05/2025       | 11/04/2026       |
| Spectrum Analyzer                    | R&S                    | FSU          | 100114        | 11/05/2025       | 11/04/2026       |
| Pre Amplifier                        | H.P.                   | HP8447E      | 2945A02715    | 11/05/2025       | 11/04/2026       |
| Pre-Amplifier                        | CDSI                   | PAP-1G18-38  | --            | 11/05/2025       | 11/04/2026       |
| Bi-log Antenna                       | SCHWARZBECK            | VULB9168     | 01488         | 07/29/2025       | 07/28/2026       |
| 9*6*6 Anechoic                       | --                     | --           | --            | 11/05/2025       | 11/04/2026       |
| Horn Antenna                         | COMPLIANCE ENGINEERING | CE18000      | --            | 11/05/2025       | 11/04/2026       |
| Horn Antenna                         | SCHWARZBECK            | BBHA9120D    | 9120D-631     | 11/05/2025       | 11/04/2026       |
| Cable                                | TIME MICROWAVE         | LMR-400      | N-TYPE04      | 11/05/2025       | 11/04/2026       |
| System-Controller                    | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Turn Table                           | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Antenna Tower                        | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| RF cable                             | Murata                 | MXHQ87WA3000 | -             | 11/05/2025       | 11/04/2026       |
| Loop Antenna                         | EMCO                   | 6502         | 00042960      | 11/05/2025       | 11/04/2026       |
| Horn Antenna                         | SCHWARZBECK            | BBHA 9170    | 1123          | 11/05/2025       | 11/04/2026       |
| Power meter                          | Anritsu                | ML2487A      | 6K00003613    | 11/05/2025       | 11/04/2026       |
| Power sensor                         | Anritsu                | MX248XD      | --            | 11/05/2025       | 11/04/2026       |
| Spectrum Analyzer                    | Keysight               | N9010B       | MY60241089    | 11/05/2025       | 11/04/2026       |

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | FCC Part15 C Section 15.203 /247(c) |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:<br/>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> |                                     |
| <b>E.U.T Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                     |
| <p>The Bluetooth antenna is a PCB Antenna. it meets the standards, and the best case gain of the antenna is 2.87dBi.<br/>Please refer to the attached "OPN-371 Internal Photo" for the antenna location</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                     |

## 6.2. Conducted Emission

### 6.2.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| Test Requirement: | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |              |           |
| Test Method:      | ANSI C63.10:2020                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |              |           |
| Frequency Range:  | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |           |
| Receiver setup:   | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |              |           |
| Limits:           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Limit (dBuV) |           |
|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Quasi-peak   | Average   |
|                   | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 66 to 56*    | 56 to 46* |
|                   | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 56           | 46        |
|                   | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 60           | 50        |
| Test Setup:       | <div><p>Reference Plane</p><p>40cm</p><p>10cm</p><p>E.U.T</p><p>Adapter</p><p>LISN</p><p>Filter</p><p>AC power</p><p>EMI Receiver</p><p>Test table/Insulation plane</p><p>Remark:<br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                |              |           |
| Test Mode:        | Refer to item 4.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |           |
| Test Procedure:   | <div><p>1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</p><p>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</p><p>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.</p></div> |              |           |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |              |           |

## 6.2.2. EUT OPERATING CONDITIONS


The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026

## Test data


Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.2085          | 6.63           | 20.68       | 27.31        | 63.26        | -35.95      | QP       |
| 2   | 0.2085          | -8.76          | 20.68       | 11.92        | 53.26        | -41.34      | AVG      |
| 3 * | 0.6180          | 11.69          | 20.53       | 32.22        | 56.00        | -23.78      | QP       |
| 4   | 0.6180          | -8.49          | 20.53       | 12.04        | 46.00        | -33.96      | AVG      |
| 5   | 1.9995          | 5.65           | 20.61       | 26.26        | 56.00        | -29.74      | QP       |
| 6   | 1.9995          | -10.75         | 20.61       | 9.86         | 46.00        | -36.14      | AVG      |
| 7   | 4.4160          | 6.88           | 20.58       | 27.46        | 56.00        | -28.54      | QP       |
| 8   | 4.4160          | -9.43          | 20.58       | 11.15        | 46.00        | -34.85      | AVG      |
| 9   | 10.6170         | 7.07           | 20.42       | 27.49        | 60.00        | -32.51      | QP       |
| 10  | 10.6170         | -8.12          | 20.42       | 12.30        | 50.00        | -37.70      | AVG      |
| 11  | 21.5115         | 7.43           | 20.36       | 27.79        | 60.00        | -32.21      | QP       |
| 12  | 21.5115         | -7.29          | 20.36       | 13.07        | 50.00        | -36.93      | AVG      |

Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026

## Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.2130          | 7.92           | 20.68       | 28.60        | 63.09        | -34.49      | QP       |
| 2   | 0.2130          | -7.71          | 20.68       | 12.97        | 53.09        | -40.12      | AVG      |
| 3 * | 0.6045          | 10.83          | 20.53       | 31.36        | 56.00        | -24.64      | QP       |
| 4   | 0.6045          | -10.99         | 20.53       | 9.54         | 46.00        | -36.46      | AVG      |
| 5   | 1.8735          | 4.54           | 20.62       | 25.16        | 56.00        | -30.84      | QP       |
| 6   | 1.8735          | -11.10         | 20.62       | 9.52         | 46.00        | -36.48      | AVG      |
| 7   | 4.4925          | 6.22           | 20.58       | 26.80        | 56.00        | -29.20      | QP       |
| 8   | 4.4925          | -8.75          | 20.58       | 11.83        | 46.00        | -34.17      | AVG      |
| 9   | 10.8105         | 7.00           | 20.40       | 27.40        | 60.00        | -32.60      | QP       |
| 10  | 10.8105         | -7.83          | 20.40       | 12.57        | 50.00        | -37.43      | AVG      |
| 11  | 27.3435         | 8.87           | 20.87       | 29.74        | 60.00        | -30.26      | QP       |
| 12  | 27.3435         | -8.20          | 20.87       | 12.67        | 50.00        | -37.33      | AVG      |

### Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN Factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) - Limits (dBuV)

Q.P. = Quasi-Peak AVG = average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

### 6.3. Conducted Output Power

#### 6.3.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Test Method:</b>      | ANSI C63.10:2020                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Limit:</b>            | Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.                    |
| <b>Test Setup:</b>       |  <p>Spectrum Analyzer      EUT</p>                                                                                                                                                                                                                                                                                                            |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Test Procedure:</b>   | <p>Use the following spectrum analyzer settings:</p> <p>Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</p> <p>RBW &gt; the 20 dB bandwidth of the emission being measured VBW ≥ RBW</p> <p>Sweep = auto</p> <p>Detector function = peak</p> <p>Trace = max hold</p> <p>Allow the trace to stabilize.</p> <p>Use the marker-to-peak function to set the marker to the peak of the emission.</p> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                            |

## 6.3.2. Test Data


| GFSK mode    |                                      |             |        |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest       | 8.48                                 | 20.97       | PASS   |
| Middle       | 8.98                                 | 20.97       | PASS   |
| Highest      | 11.43                                | 20.97       | PASS   |

| Pi/4DQPSK mode |                                      |             |        |
|----------------|--------------------------------------|-------------|--------|
| Test channel   | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest         | 10.78                                | 20.97       | PASS   |
| Middle         | 11.33                                | 20.97       | PASS   |
| Highest        | 11.5                                 | 20.97       | PASS   |



| 8DPSK mode   |                                      |             |        |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest       | 10.83                                | 20.97       | PASS   |
| Middle       | 11.41                                | 20.97       | PASS   |
| Highest      | 11.51                                | 20.97       | PASS   |



Test plots as follows:



Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026




Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026








Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026



## 6.4. 20dB Occupy Bandwidth

### 6.4.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Test Method:</b>      | ANSI C63.10:2020                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Limit:</b>            | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Test Setup:</b>       |  <p>Spectrum Analyzer      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows ANSI C63.10:2020 Measurement Guidelines.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.<br/>Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel; <math>1\% \leq RBW \leq 5\%</math> of the 20 dB bandwidth; <math>VBW \geq 3RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold.</li> <li>5. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Report No.: WSCT-ANAB-R&amp;E260200021A-BT Issued Date: 17 March 2026

#### 6.4.2. Test data

| Test channel | 20dB Occupy Bandwidth (MHz) |                |       |            |
|--------------|-----------------------------|----------------|-------|------------|
|              | GFSK                        | $\pi/4$ -DQPSK | 8DPSK | Conclusion |
| Lowest       | 0.853                       | 1.309          | 1.331 | PASS       |
| Middle       | 0.854                       | 1.305          | 1.292 | PASS       |
| Highest      | 0.953                       | 1.277          | 1.318 | PASS       |

Test plots as follows:

## Test Graphs


### -20dB Bandwidth NVNT 1-DH5 2402MHz Ant1





### -20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026



Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026



Report No.: WSCT-ANAB-R&E260200021A-BT Issued Date: 17 March 2026

