



Dwell 1-DH1 2480MHz One Burst




Dwell 1-DH1 2480MHz Accumulated




Dwell 1-DH3 2402MHz One Burst




Dwell 1-DH3 2402MHz Accumulated




Dwell 1-DH3 2441MHz One Burst




Dwell 1-DH3 2441MHz Accumulated




Dwell 1-DH3 2480MHz One Burst




Dwell 1-DH3 2480MHz Accumulated




Dwell 1-DH5 2402MHz One Burst




Dwell 1-DH5 2402MHz Accumulated




Dwell 1-DH5 2441MHz One Burst




Dwell 1-DH5 2441MHz Accumulated



Dwell 1-DH5 2480MHz One Burst



Dwell 1-DH5 2480MHz Accumulated



6.8. Pseudorandom Frequency Hopping Sequence

Test Requirement: FCC Part15 C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence


An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6.9. Conducted Band Edge Measurement



6.9.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2020
Limit:	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of ANSI C63.10:2020 Measurement Guidelines. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz ($\geq 1\%$ span=10MHz), VBW = 300 kHz ($\geq$RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used. 4. Enable hopping function of the EUT and then repeat step 2 and 3. 5. Measure and record the results in the test report.
Test Result:	PASS

6.9.2. Test Data


GFSK Modulation (the worst case)








Test Graphs

Band Edge(Hopping) 1-DH5 2402MHz Hopping Ref



Band Edge(Hopping) 1-DH5 2402MHz Hopping Emission







6.10. Conducted Spurious Emission Measurement


6.10.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2020
Limit:	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the guidelines in Spurious RF Conducted Emissions of ANSI C63.10:2020 Measurement Guidelines 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. 5. Measure and record the results in the test report. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


Test Data




Tx. Spurious 1-DH5 2441MHz Ref




Tx. Spurious 1-DH5 2441MHz Emission




Tx. Spurious 1-DH5 2480MHz Ref




Tx. Spurious 1-DH5 2480MHz Emission




Tx. Spurious 2-DH5 2402MHz Ref




Tx. Spurious 2-DH5 2402MHz Emission




Tx. Spurious 2-DH5 2441MHz Ref




Tx. Spurious 2-DH5 2441MHz Emission




Tx. Spurious 2-DH5 2480MHz Ref




Tx. Spurious 2-DH5 2480MHz Emission




Tx. Spurious 3-DH5 2402MHz Ref




Tx. Spurious 3-DH5 2402MHz Emission




Tx. Spurious 3-DH5 2441MHz Ref




Tx. Spurious 3-DH5 2441MHz Emission



Tx. Spurious 3-DH5 2480MHz Ref






Tx. Spurious 3-DH5 2480MHz Emission



6.11. Radiated Spurious Emission Measurement

6.11.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2020				
Frequency Range:	9 kHz to 25 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Frequency	Field Strength (microvolts/meter)		Measurement Distance (meters)	
	0.009-0.490	2400/F(KHz)		300	
	0.490-1.705	24000/F(KHz)		30	
	1.705-30	30		30	
	30-88	100		3	
	88-216	150		3	
	216-960	200		3	
	Above 960	500		3	
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	
	Above 1GHz	500	3	Average	
		5000	3	Peak	
Test setup:	For radiated emissions below 30MHz				
					
	30MHz to 1GHz				

	 Above 1GHz 
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10:2020 Measurement Guidelines. 2. For the radiated emission test below 1GHz: The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level. For the radiated emission test above 1GHz: Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$GHz ; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak (3) For average measurement: use duty cycle correction factor method per 15.35(c). Duty cycle = On time/100 milliseconds On time = $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$ Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
Test results:	PASS

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026


Revised: None

6.11.2. Test Data

Please refer to following diagram for individual

Below 1GHz


The worst mode is GFSK
Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		50.3700	42.90	-20.51	22.39	40.00	-17.61	QP
2		164.8300	40.81	-19.86	20.95	43.50	-22.55	QP
3		384.0500	45.32	-18.85	26.47	46.00	-19.53	QP
4		431.5800	47.99	-18.60	29.39	46.00	-16.61	QP
5		793.3900	46.80	-16.70	30.10	46.00	-15.90	QP
6	*	878.7500	48.89	-16.11	32.78	46.00	-13.22	QP

Report No.: WSCT-ANAB-R&E260500048A-BT Issued 04 June 2026
Vertical:

Revised: None



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	37.7599	46.53	-20.52	26.01	40.00	-13.99	QP
2		97.9000	48.32	-20.21	28.11	43.50	-15.39	QP
3		263.7700	40.14	-19.41	20.73	46.00	-25.27	QP
4		460.6800	43.20	-18.46	24.74	46.00	-21.26	QP
5		715.7900	45.81	-17.12	28.69	46.00	-17.31	QP
6		890.3900	47.69	-16.04	31.65	46.00	-14.35	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026

Revised: None

Above 1GHz


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

The worst mode is GFSK

Low channel: 2402MHz

Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1650.6250	39.07	24.93	14.14	74	-34.93	235.2	Horizontal	PK	Pass
1	1650.6250	30.74	24.93	5.81	54	-23.26	235.2	Horizontal	AV	Pass
2	2413.7500	51.29	27.31	23.98	74	-22.71	85.8	Horizontal	PK	Pass
2	2413.7500	36.88	27.31	9.57	54	-17.12	85.8	Horizontal	AV	Pass
3	4380.6250	52.27	30.39	21.88	74	-21.73	174.2	Horizontal	PK	Pass
3	4380.6250	42.74	30.39	12.35	54	-11.26	174.2	Horizontal	AV	Pass
4	7528.5000	38.15	7.63	30.52	74	-35.85	0.5	Horizontal	PK	Pass
4	7528.5000	29.38	7.63	21.75	54	-24.62	0.5	Horizontal	AV	Pass
5	10485.0000	42.56	13.88	28.68	74	-31.44	216.8	Horizontal	PK	Pass
5	10485.0000	35.73	13.88	21.85	54	-18.27	216.8	Horizontal	AV	Pass
6	15123.0000	48.77	19.74	29.03	74	-25.23	304.2	Horizontal	PK	Pass
6	15123.0000	42.06	19.74	22.32	54	-11.94	304.2	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026
Vertical:

Revised: None



Susputed Data List


NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1468.7500	39.48	25.03	14.45	74	-34.52	357.6	Vertical	PK	Pass
1	1468.7500	30.61	25.03	5.58	54	-23.39	357.6	Vertical	AV	Pass
2	2412.5000	48.21	27.3	20.91	74	-25.79	355.4	Vertical	PK	Pass
2	2412.5000	36.85	27.3	9.55	54	-17.15	355.4	Vertical	AV	Pass
3	3919.3750	50.66	29.51	21.15	74	-23.34	0	Vertical	PK	Pass
3	3919.3750	41.06	29.51	11.55	54	-12.94	0	Vertical	AV	Pass
4	7671.0000	37.34	7.96	29.38	74	-36.66	253.9	Vertical	PK	Pass
4	7671.0000	30.1	7.96	22.14	54	-23.9	253.9	Vertical	AV	Pass
5	10261.5000	42.3	13.17	29.13	74	-31.7	41.1	Vertical	PK	Pass
5	10261.5000	34.99	13.17	21.82	54	-19.01	41.1	Vertical	AV	Pass
6	12348.0000	45.19	16.47	28.72	74	-28.81	360	Vertical	PK	Pass
6	12348.0000	38.07	16.47	21.6	54	-15.93	360	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026

Revised: None

Middle channel: 2440MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1400.6250	39.61	25.1	14.51	74	-34.39	-0.1	Horizontal	PK	Pass
1	1400.6250	30.65	25.1	5.55	54	-23.35	-0.1	Horizontal	AV	Pass
2	2413.1250	47.8	27.3	20.5	74	-26.2	359.5	Horizontal	PK	Pass
2	2413.1250	36.93	27.3	9.63	54	-17.07	359.5	Horizontal	AV	Pass
3	3433.1250	47.46	28.46	19	74	-26.54	205.3	Horizontal	PK	Pass
3	3433.1250	38.04	28.46	9.58	54	-15.96	205.3	Horizontal	AV	Pass
4	7725.0000	38.46	7.96	30.5	74	-35.54	16.5	Horizontal	PK	Pass
4	7725.0000	30.85	7.96	22.89	54	-23.15	16.5	Horizontal	AV	Pass
5	10207.5000	42.7	13	29.7	74	-31.3	360.1	Horizontal	PK	Pass
5	10207.5000	35.23	13	22.23	54	-18.77	360.1	Horizontal	AV	Pass
6	13530.0000	46.83	17.77	29.06	74	-27.17	189.4	Horizontal	PK	Pass
6	13530.0000	39.06	17.77	21.29	54	-14.94	189.4	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026

Revised: None

Vertical:



Susputed Data List


NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1085.6250	38.24	24.34	13.9	74	-35.76	65.5	Vertical	PK	Pass
1	1085.6250	28.6	24.34	4.26	54	-25.4	65.5	Vertical	AV	Pass
2	2456.8750	49.53	27.45	22.08	74	-24.47	311.8	Vertical	PK	Pass
2	2456.8750	37.1	27.45	9.65	54	-16.9	311.8	Vertical	AV	Pass
3	3854.3750	50.82	29.35	21.47	74	-23.18	0	Vertical	PK	Pass
3	3854.3750	40.96	29.35	11.61	54	-13.04	0	Vertical	AV	Pass
4	7824.0000	37.63	8	29.63	74	-36.37	238.4	Vertical	PK	Pass
4	7824.0000	30.43	8	22.43	54	-23.57	238.4	Vertical	AV	Pass
5	9783.0000	41.96	11.85	30.11	74	-32.04	49.4	Vertical	PK	Pass
5	9783.0000	34.36	11.85	22.51	54	-19.64	49.4	Vertical	AV	Pass
6	13227.0000	45.15	16.82	28.33	74	-28.85	238.4	Vertical	PK	Pass
6	13227.0000	38.07	16.82	21.25	54	-15.93	238.4	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026

Revised: None

High channel: 2480MHz

Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1408.7500	22.27	25.09	-2.82	74	-51.73	171.8	Horizontal	PK	Pass
1	1408.7500	14.19	25.09	-10.9	54	-39.81	171.8	Horizontal	AV	Pass
2	2413.1250	39.2	27.3	11.9	74	-34.8	126.4	Horizontal	PK	Pass
2	2413.1250	27.86	27.3	0.56	54	-26.14	126.4	Horizontal	AV	Pass
3	3773.7500	42.55	29.16	13.39	74	-31.45	177.8	Horizontal	PK	Pass
3	3773.7500	33.44	29.16	4.28	54	-20.56	177.8	Horizontal	AV	Pass
4	7528.5000	38.32	7.63	30.69	74	-35.68	10.6	Horizontal	PK	Pass
4	7528.5000	29.91	7.63	22.28	54	-24.09	10.6	Horizontal	AV	Pass
5	11743.5000	46.87	16.11	30.76	74	-27.13	154.7	Horizontal	PK	Pass
5	11743.5000	41.88	16.11	25.77	54	-12.12	154.7	Horizontal	AV	Pass
6	15097.5000	49.88	19.6	30.28	74	-24.12	328	Horizontal	PK	Pass
6	15097.5000	41.58	19.6	21.98	54	-12.42	328	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A -BT Issued 04 June 2026
Vertical:

Revised: None



Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1163.1250	39.02	24.38	14.64	74	-34.98	89.5	Vertical	PK	Pass
1	1163.1250	29.39	24.38	5.01	54	-24.61	89.5	Vertical	AV	Pass
2	2414.3750	47.79	27.31	20.48	74	-26.21	0.1	Vertical	PK	Pass
2	2414.3750	36.38	27.31	9.07	54	-17.62	0.1	Vertical	AV	Pass
3	4708.1250	52.98	31.02	21.96	74	-21.02	144.5	Vertical	PK	Pass
3	4708.1250	44.25	31.02	13.23	54	-9.75	144.5	Vertical	AV	Pass
4	8148.0000	38.69	8.61	30.08	74	-35.31	231.2	Vertical	PK	Pass
4	8148.0000	30.76	8.61	22.15	54	-23.24	231.2	Vertical	AV	Pass
5	10375.5000	42.98	13.52	29.46	74	-31.02	357.5	Vertical	PK	Pass
5	10375.5000	35.17	13.52	21.65	54	-18.83	357.5	Vertical	AV	Pass
6	11745.0000	46.17	16.11	30.06	74	-27.83	288.6	Vertical	PK	Pass
6	11745.0000	42.5	16.11	26.39	54	-11.5	288.6	Vertical	AV	Pass

Note:

- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Data of measurement shown "---" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- Measurements were conducted in all three modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (GFSK) was submitted only.

6.11.3. Restricted Bands Requirements


Bluetooth (GFSK, Pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result GFSK model was report

as below

GFSK


Low channel

Horizontal:



Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2333.1250	19.38	-9.45	28.83	74	-54.62	0.6	Horizontal	PK	Pass
1	2333.1250	5.84	-9.45	15.29	54	-48.16	0.6	Horizontal	AV	Pass
2	2375.6000	19.34	-9.24	28.58	74	-54.66	7	Horizontal	PK	Pass
2	2375.6000	6.16	-9.24	15.4	54	-47.84	7	Horizontal	AV	Pass

Vertical:




Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2331.6625	19.45	-9.45	28.9	74	-54.55	3.5	Vertical	PK	Pass
1	2331.6625	5.89	-9.45	15.34	54	-48.11	3.5	Vertical	AV	Pass
2	2360.7750	20.47	-9.31	29.78	74	-53.53	358.8	Vertical	PK	Pass
2	2360.7750	5.8	-9.31	15.11	54	-48.2	358.8	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500048A-BT Issued 04 June 2026

Revised: None


High channel
Horizontal:



Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2474.8562	44.59	-8.67	53.26	74	-29.41	199	Horizontal	PK	Pass
1	2474.8562	7.84	-8.67	16.51	54	-46.16	199	Horizontal	AV	Pass
2	2484.8312	43.59	-8.6	52.19	74	-30.41	190.6	Horizontal	PK	Pass
2	2484.8312	7	-8.6	15.6	54	-47	190.6	Horizontal	AV	Pass

Vertical:



Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2476.6000	25.83	-8.66	34.49	74	-48.17	292.7	Vertical	PK	Pass
1	2476.6000	7.29	-8.66	15.95	54	-46.71	292.7	Vertical	AV	Pass
2	2490.2312	20.35	-8.57	28.92	74	-53.65	338	Vertical	PK	Pass
2	2490.2312	7.7	-8.57	16.27	54	-46.3	338	Vertical	AV	Pass

Note: Freq. = Emission frequency in MHz
Reading level (dBμV) = Receiver reading
Corr. Factor (dB) = Attenuation factor + Cable loss
Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)
Limit (dBμV) = Limit stated in standard
Margin (dB) = Level (dBμV) – Limits (dBμV)

*****END OF REPORT*****