


13 100kHz Bandwidth of Frequency Band Edge Requirement

13.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

13.2 Test Setup



13.3 Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

Reference Level:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum; Set to the maximum power setting and enable the EUT transmit continuously.
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto.
Detector function = peak, Trace = max hold.

Spurious Emissions Measurement:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto.
Detector function = peak, Trace = max hold.



13.4 Test Data

Test Item : Band edge
Test Voltage : DC 12V
Test Result : PASS


Test Mode : CH Low ~ CH High
Temperature : 24.5°C
Humidity : 55%RH

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-0.68	-40.2	≤-20.68	PASS
DH5	Ant1	High	2480	0.93	-39.57	≤-19.07	PASS
DH5	Ant1	Low	Hop_2402	-2.00	-41.76	≤-22	PASS
DH5	Ant1	High	Hop_2480	0.61	-41.38	≤-19.39	PASS
2DH5	Ant1	Low	2402	-0.62	-40.82	≤-20.62	PASS
2DH5	Ant1	High	2480	0.88	-40.62	≤-19.12	PASS
2DH5	Ant1	Low	Hop_2402	-3.01	-41.35	≤-23.01	PASS
2DH5	Ant1	High	Hop_2480	0.87	-40.51	≤-19.13	PASS
3DH5	Ant1	Low	2402	-0.61	-41.38	≤-20.61	PASS
3DH5	Ant1	High	2480	0.92	-40.75	≤-19.08	PASS
3DH5	Ant1	Low	Hop_2402	-2.25	-41.79	≤-22.25	PASS
3DH5	Ant1	High	Hop_2480	0.32	-41.4	≤-19.68	PASS




Test Graphs:


DH5-Ant1-2402-PASS




DH5-Ant1-2480-PASS




DH5-Ant1-Hop_2402-PASS




DH5-Ant1-Hop_2480-PASS




2DH5-Ant1-2402-PASS




2DH5-Ant1-2480-PASS




2DH5-Ant1-Hop_2402-PASS




2DH5-Ant1-Hop_2480-PASS




3DH5-Ant1-2402-PASS




3DH5-Ant1-2480-PASS



3DH5-Ant1-Hop_2402-PASS



3DH5-Ant1-Hop_2480-PASS





Conducted Emission Method

Test Result

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	0~Reference	-0.63	-0.63	---	PASS
DH5	Ant1	2402	30~1000	-0.63	-54.93	≤-20.63	PASS
DH5	Ant1	2402	1000~26500	-0.63	-41.81	≤-20.63	PASS
DH5	Ant1	2441	0~Reference	-0.87	-0.87	---	PASS
DH5	Ant1	2441	30~1000	-0.87	-54.24	≤-20.87	PASS
DH5	Ant1	2441	1000~26500	-0.87	-40.94	≤-20.87	PASS
DH5	Ant1	2480	0~Reference	0.91	0.91	---	PASS
DH5	Ant1	2480	30~1000	0.91	-55.25	≤-19.09	PASS
DH5	Ant1	2480	1000~26500	0.91	-40.2	≤-19.09	PASS
2DH5	Ant1	2402	0~Reference	-0.67	-0.67	---	PASS
2DH5	Ant1	2402	30~1000	-0.67	-54.81	≤-20.67	PASS
2DH5	Ant1	2402	1000~26500	-0.67	-41.44	≤-20.67	PASS
2DH5	Ant1	2441	0~Reference	-0.91	-0.91	---	PASS
2DH5	Ant1	2441	30~1000	-0.91	-54.37	≤-20.91	PASS
2DH5	Ant1	2441	1000~26500	-0.91	-40.82	≤-20.91	PASS
2DH5	Ant1	2480	0~Reference	0.88	0.88	---	PASS
2DH5	Ant1	2480	30~1000	0.88	-54.23	≤-19.12	PASS
2DH5	Ant1	2480	1000~26500	0.88	-42.87	≤-19.12	PASS
3DH5	Ant1	2402	0~Reference	-0.64	-0.64	---	PASS
3DH5	Ant1	2402	30~1000	-0.64	-54.7	≤-20.64	PASS
3DH5	Ant1	2402	1000~26500	-0.64	-42.54	≤-20.64	PASS
3DH5	Ant1	2441	0~Reference	-0.94	-0.94	---	PASS
3DH5	Ant1	2441	30~1000	-0.94	-54.72	≤-20.94	PASS
3DH5	Ant1	2441	1000~26500	-0.94	-42.3	≤-20.94	PASS
3DH5	Ant1	2480	0~Reference	0.97	0.97	---	PASS
3DH5	Ant1	2480	30~1000	0.97	-54.95	≤-19.03	PASS
3DH5	Ant1	2480	1000~26500	0.97	-42.33	≤-19.03	PASS




Test Graphs:

DH5-Ant1-2402-0~Reference-PASS



DH5-Ant1-2402-30~1000-PASS




DH5-Ant1-2402-1000~26500-PASS



DH5-Ant1-2441-0~Reference-PASS



DH5-Ant1-2441-30~1000-PASS




DH5-Ant1-2441-1000~26500-PASS



DH5-Ant1-2480-0~Reference-PASS



DH5-Ant1-2480-30~1000-PASS




DH5-Ant1-2480-1000~26500-PASS



2DH5-Ant1-2402-0~Reference-PASS



2DH5-Ant1-2402-30~1000-PASS




2DH5-Ant1-2402-1000~26500-PASS



2DH5-Ant1-2441-0~Reference-PASS



2DH5-Ant1-2441-30~1000-PASS




2DH5-Ant1-2441-1000~26500-PASS



2DH5-Ant1-2480-0~Reference-PASS



2DH5-Ant1-2480-30~1000-PASS




2DH5-Ant1-2480-1000~26500-PASS



3DH5-Ant1-2402-0~Reference-PASS



3DH5-Ant1-2402-30~1000-PASS




3DH5-Ant1-2402-1000~26500-PASS



3DH5-Ant1-2441-0~Reference-PASS



3DH5-Ant1-2441-30~1000-PASS




3DH5-Ant1-2441-1000~26500-PASS




3DH5-Ant1-2480-0~Reference-PASS



3DH5-Ant1-2480-30~1000-PASS



3DH5-Ant1-2480-1000~26500-PASS





14 Antenna Requirement

14.1 Test Standard and Requirement


Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

14.2 Antenna Connected Construction


The antenna is PCB Antenna which permanently attached, and the best case gain of the antenna is -0.58 dBi. It complies with the standard requirement.

15 APPENDIX I -- TEST SETUP PHOTOGRAPH


Conducted Emissions



Radiated Emissions
From 30M-1GHz



Above 1GHz






16 APPENDIX II -- EUT PHOTOGRAPH


















*****THE END REPORT*****