



FCC TEST REPORT

FCC ID: 2AXZU-BRIDGE2

On Behalf of

ERM Electronic Systems Ltd

TagLINK Bridge

Model No.: TagLINK Bridge

Prepared for : ERM Electronic Systems Ltd
Address : 16 Hasar Shapira St, Rishon Le'Zion, Israel

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2602073-C01-R06
Date of Receipt : March 5, 2026
Date of Test : March 5, 2026–May 8, 2026
Date of Report : May 8, 2026
Version Number : V0

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. Summary Of Standards And Results.....	6
1.1. Description of Standards and Results.....	6
2. General Information.....	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of Connection Between EUT and Simulators.....	8
2.5. Test Mode Description.....	9
2.6. Software test version and power setting information.....	9
2.7. Test Conditions.....	10
2.8. Test Facility.....	10
2.9. Measurement Uncertainty	10
2.10. Test Equipment List.....	11
3. Maximum Peak Output Power	12
3.1. Limit.....	12
3.2. Test Procedure	12
3.3. Test Setup	12
3.4. Test Result.....	13
4. Bandwidth.....	15
4.1. Limit.....	15
4.2. Test Procedure	15
4.3. Test Setup	16
4.4. Test Result.....	16
5. Carrier Frequency Separation	20
5.1. Limit.....	20
5.2. Test Procedure	20
5.3. Test Setup	20
5.4. Test Result.....	20
6. Number Of Hopping Channel	22
6.1. Limit.....	22
6.2. Test Procedure	22
6.3. Test Setup	22
6.4. Test Result.....	22
7. Dwell Time	24
7.1. Test limit	24
7.2. Test Procedure	24
7.3. Test Setup	24
7.4. Test Result.....	25
8. Out-of-band Emissions	26
8.1. Test Limits	26
8.2. Test Procedure	26
8.3. Test Setup	26

8.4. Test Results	26
9. Spurious Emission	33
9.1. Test Limits	33
9.2. Block Diagram of Test setup	34
9.3. Test Procedure	35
9.4. Test Results	36
10. Band Edge Test	41
10.1. Test Limit	41
10.2. Block Diagram of Test Setup	41
10.3. Test Procedure	41
10.4. Test Results	42
11. Power Line Conducted Emissions	46
11.1. Test Limits	46
11.2. Test Procedure	46
11.3. Test Setup	46
11.4. Test Results	47
12. Antenna Requirements	50
12.1. Limit	50
12.2. Result	50
13. Photos of test setup	51
14. Photos of EUT	51

TEST REPORT DECLARATION

Applicant : ERM Electronic Systems Ltd
Address : 16 Hasar Shapira St, Rishon Le'Zion, Israel
Manufacturer : ERM Electronic Systems Ltd
Address : 16 Hasar Shapira St, Rishon Le'Zion, Israel
EUT Description : TagLINK Bridge
(A) Model No. : TagLINK Bridge
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2020+Cor.1-2023

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Felix Pang
Test Engineer 

Approved by (name + signature).....: Simple Guan
Project Manager 

Date of issue.....: May 8, 2026

Revision History

Revision	Issue Date	Revisions	Revised By
V0	May 8, 2026	Initial released Issue	Felix Pang



1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(a)(1)& (b)(1), ANSI C63.10-2020+Cor.1-2023	P
Bandwidth	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020+Cor.1-2023	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020+Cor.1-2023	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii), ANSI C63.10-2020+Cor.1-2023	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii), ANSI C63.10-2020+Cor.1-2023	P
Radiated Spurious Emission	FCC Part 15: 15.247(d), ANSI C63.10-2020+Cor.1-2023	P
Out-of-band Emissions	FCC Part 15: 15.247(d), ANSI C63.10-2020+Cor.1-2023	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10-2020+Cor.1-2023	P
Power Line Conducted Emissions	FCC Part 15: 15.207(a), ANSI C63.10-2020+Cor.1-2023	P
Antenna requirement	FCC Part 15: 15.203	P

Note: 1. P is an abbreviation for Pass.
 2. F is an abbreviation for Fail.
 3. N/A is an abbreviation for Not Applicable.
 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.
 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.

2. General Information

2.1. Description of Device (EUT)

Product Name : TagLINK Bridge
Model No. : TagLINK Bridge
Diff : N/A
Power supply : DC 12V/24V power supply, DC 5V from Type-C.

Radio Technology : RFID
Operation frequency : 905~920MHz
Channel No. : 50 channels
Modulation : GFSK
Antenna Type : Internal antenna, Maximum Gain is 0.76dBi.

PMN : N/A
HVIN : N/A

Software version : N/A
Hardware version/FVIN : N/A

Note : Antenna information is provided by applicant.
Testing lab is not responsible for the accuracy of the information.

2.2. Accessories of Device (EUT)

Accessories 1 : N/A
 Manufacturer : N/A
 Model : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	Adapter	Baseus	CCXFK65CC	N/A
2	N/A	N/A	N/A	N/A

2.4. Block Diagram of Connection Between EUT and Simulators


Spurious Emission



Power Line Conducted Emission



RF



2.5. Test Mode Description

The test software used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK Carrier Tx Mode	CH1	905.0
	CH26	912.5
	CH50	920.0
GFSK hopping on Tx Mode	CH1	905.0
	CH26	912.5
	CH50	920.0
GFSK hopping off Tx Mode	CH1	905.0
	CH26	912.5
	CH50	920.0

Channel list:							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	905.0	CH15	909.2	CH29	913.4	CH43	917.6
CH2	905.3	CH16	909.5	CH30	913.7	CH44	917.9
CH3	905.6	CH17	909.8	CH31	914.0	CH45	918.2
CH4	905.9	CH18	910.1	CH32	914.3	CH46	918.5
CH5	906.2	CH19	910.4	CH33	914.6	CH47	918.8
CH6	906.5	CH20	910.7	CH34	914.9	CH48	919.4
CH7	906.8	CH21	911.0	CH35	915.2	CH49	919.7
CH8	907.1	CH22	911.3	CH36	915.5	CH50	920.0
CH9	907.4	CH23	911.6	CH37	915.8	--	--
CH10	907.7	CH24	911.9	CH38	916.1	--	--
CH11	908.0	CH25	912.2	CH39	916.4	--	--
CH12	908.3	CH26	912.5	CH40	916.7	--	--
CH13	908.6	CH27	912.8	CH41	917.0	--	--
CH14	908.9	CH28	913.1	CH42	917.3	--	--

2.6. Software test version and power setting information

Software testing version	TagBridgeTester.exe V1.25.5.1		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	Low :CH1	905.0	TX level is set as defaults value.
	Middle: CH26	912.5	TX level is set as defaults value.
	High: CH50	920.0	TX level is set as defaults value.

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Power Line Conducted Emissions Test	2.13dB
Radiation Emission test in 3m chamber(below 30MHz)	4.07dB
Radiation Emission test in 3m chamber(30MHz to 1GHz)	4.51dB
Radiation Emission test in 3m chamber(1GHz to 18GHz)	5.07dB
Radiation Emission test in 3m chamber(18GHz to 40GHz)	5.21dB
Radio Frequency	48.24KHz
Conducted RF Power	0.41dB
Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Duty Cycle	1%
Conducted-Spurious Emission	1.26dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.18	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV 216	102282	/	2025.12.18	1 Year
4.	L.I.S.N.#2	EMCO	3810-2	00094944	/	2025.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV40-N	101648	3.70	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LNPA_0118G-50	SK2022032901	/	2025.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_1840G-50	SK2019040302	/	2025.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-11 11533-Fz	/	2025.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P008	/	2025.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638	/	2025.12.18	1 Year
17.	Cable	SKET	Cable-RE-1	#02/#03	/	2025.12.18	1 Year
18.	Cable	SKET	Cable-RE-2	#01	/	2025.12.18	1 Year
19.	Cable	SKET	Cable-RE-3	#04	/	2025.12.18	1 Year
20.	Cable	SKET	Cable-CE-1	A-E-24	/	2025.12.18	1 Year
21.	6dB Attenuator	Schwarzbeck	DGA 9552N 6dB	CK4186	/	2025.12.18	1 Year
22.	Power meter	Agilent	E4419B	GB40202121	/	2025.12.18	1 Year
23.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer		Version			
RE	EZ_EMC	Farad		PSI-3A1			
CE	EZ_EMC	Farad		PSI-3A1			
RF	RTS	TACHOY		V1.0.0			

3. Maximum Peak Output Power

3.1. Limit

Please refer FCC part 15.247 & RSS-247.

For frequency hopping systems operating in the 902-928 MHz band: 1W(30dBm) for systems employing at least 50 hopping channels; 0.25W(24dBm) for systems employing less than 50 hopping channels and at least 25 hopping channels, as permitted under paragraph (b)(2) of this section.

3.2. Test Procedure

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW >= RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.


b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.

e) A plot of the test results and setup description shall be included in the test report.


3.3. Test Setup




3.4. Test Result


Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Limit(dBm)	Result
NVNT	ANT1	GFSK	905.0	27.61	30	Pass
NVNT	ANT1	GFSK	912.5	27.72	30	Pass
NVNT	ANT1	GFSK	920.0	27.47	30	Pass

Peak_Output_Power_NVNT_ANT1_GFSK_905_00



Peak_Output_Power_NVNT_ANT1_GFSK_912_50





4. Bandwidth

4.1. Limit


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument


display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3. Test Setup




4.4. Test Result


Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	Limit (kHz)	Results
NVNT	ANT1	GFSK	905.00	0.045	≤250	PASS
NVNT	ANT1	GFSK	912.50	0.046	≤250	PASS
NVNT	ANT1	GFSK	920.00	0.048	≤250	PASS



-20dB_Bandwidth_NVNT_ANT1_GFSK_912_50




-20dB_Bandwidth_NVNT_ANT1_GFSK_920_00





Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	GFSK	905.00	0.233
NVNT	ANT1	GFSK	912.50	0.233
NVNT	ANT1	GFSK	920.00	0.233

99% Occupied Bandwidth_NVNT_ANT1_GFSK_905_00



99% Occupied Bandwidth_NVNT_ANT1_GFSK_912_50





5. Carrier Frequency Separation

5.1. Limit

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies.


5.2. Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- Video (or average) bandwidth (VBW) $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.


Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

5.3. Test Setup



5.4. Test Result

Condition	Antenna	Modulation	Frequency(MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	GFSK	912.50	0.298	0.046	Pass



6. Number Of Hopping Channel

6.1. Limit

FCC Part15 C Section 15.247(a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.


6.2. Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.


It might prove necessary to break the span up into sub ranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

6.3. Test Setup



6.4. Test Result

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	GFSK	50	≥ 50	Pass



7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247(a)(1)(i) & RSS-247.

Frequency hopping systems operating in the 902-928 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec-onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test

for each variation in transmit time.


Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.


7.3. Test Setup




7.4. Test Result

Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	GFSK	5.350	21	112.35	0.40	Pass

Dwell_Time_(Hopping)_NVNT_ANT1_GFSK_912_50_One_Burst_Time



Dwell_Time_(Hopping)_NVNT_ANT1_GFSK_912_50_Accumulated



8. Out-of-band Emissions


8.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required.

8.2. Test Procedure

Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers. Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

8.3. Test Setup




8.4. Test Results

PASS.


The test results are listed in next pages.

Band Edge: Pass


Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Bandedge MAX.Value (dBm)	Limit(dBm)	Result
NVNT	ANT1	GFSK	905.00	27.578	-33.252	7.578	Pass
NVNT	ANT1	GFSK	Hopping_LCH	27.608	-37.415	7.608	Pass
NVNT	ANT1	GFSK	920.00	27.464	-39.994	7.464	Pass
NVNT	ANT1	GFSK	Hopping_HCH	27.459	-41.636	7.459	Pass

1_Reference_Level_NVNT_ANT1_GFSK_905_00**2_Bandedge_NVNT_ANT1_GFSK_905_00**


1 Reference_Level_Hopping_NVNT_ANT1_GFSK_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_GFSK_Hopping




1_Reference_Level_NVNT_ANT1_GFSK_920_00




2_Bandedge_NVNT_ANT1_GFSK_920_00



1 Reference_Level_Hopping_NVNT_ANT1_GFSK_Hopping





2 Band_Edge_(Hopping)_NVNT_ANT1_GFSK_Hopping




Conducted spurious emission: Pass


Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Spurious MAX.Value(dBm)	Limit(dBm)	Result
NVNT	ANT1	GFSK	905.00	27.620	-34.266	7.620	Pass
NVNT	ANT1	GFSK	920.00	27.464	-34.186	7.464	Pass

1 Reference_Level_NVNT_ANT1_User_905_00**2 Spurious Emissions_NVNT_ANT1_User_905_00**

1_Reference_Level_NVNT_ANT1_User_920_00



2_Spurious_Emissions_NVNT_ANT1_User_920_00



9. Spurious Emission

9.1. Test Limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

Note: The peak limit is 20 dB higher than the average limit


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

9.2. Block Diagram of Test setup


a. In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



b. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



c. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



9.3. Test Procedure

- (1) The test equipment is placed on a non-metallic tabletop. For false radiation emission tests below 1G, the distance between the equipment and the ground surface is 80 cm; for false radiation emission tests above 1G, the distance is 1.5 meters. The equipment is situated within a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10-2020+Cor.1-2023 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:

9KHz~150KHz	RBW 200Hz	VBW 1KHz
150KHz~30MHz	RBW 9KHz	VBW 30KHz
30MHz~1GHz	RBW 120KHz	VBW 300KHz
Above1GHz	RBW 1MHz	VBW 3MHz


9.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.

Detailed information please see the following page.


From 9KHz to 30MHz:	
Test Date : 2026.03.19	Temperature : 26°C
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Voltage : AC 120V/60Hz	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:	
Test Date : 2026.03.19	Temperature : 26°C
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Voltage : AC 120V/60Hz	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of GFSK mode, Channel 905MHz was listed in this report.

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.0995	12.51	14.27	26.78	40.00	-13.22	QP
2	50.3868	12.17	13.72	25.89	40.00	-14.11	QP
3	150.6038	11.98	15.21	27.19	43.50	-16.31	QP
4	319.2366	13.08	15.70	28.78	46.00	-17.22	QP
5	411.4632	13.42	17.97	31.39	46.00	-14.61	QP
6 *	739.9848	12.33	24.39	36.72	46.00	-9.28	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.2364	13.49	13.87	27.36	40.00	-12.64	QP
2	52.2308	12.05	13.64	25.69	40.00	-14.31	QP
3	149.6824	11.91	15.20	27.11	43.50	-16.39	QP
4	283.1092	12.48	14.60	27.08	46.00	-18.92	QP
5	445.8275	12.90	19.02	31.92	46.00	-14.08	QP
6 *	759.3710	14.52	24.64	39.16	46.00	-6.84	QP

Note: Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2026.03.19	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Voltage : AC 120V/60Hz	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Test Mode : GFSK TX Low CH01								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	1810	V	60.12	-13.25	46.87	74.00	-27.13	Peak
2	1810	V	47.79	-13.25	34.54	54.00	-19.46	Avg
3	2715	--	--	--	--	--	--	--
4	5430	--	--	--	--	--	--	--
5	1810	H	54.58	-13.25	41.33	74.00	-32.67	Peak
6	1810	H	45.06	-13.25	31.81	54.00	-22.19	Avg
7	2715	--	--	--	--	--	--	--
8	5430	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid CH25								
1	1825	V	57.11	-12.98	44.13	74.00	-29.87	Peak
2	1825	V	48.97	-12.98	35.99	54.00	-18.01	Avg
3	2737.5	--	--	--	--	--	--	--
4	5475	--	--	--	--	--	--	--
5	1825	H	58.20	-12.98	45.22	74.00	-28.78	Peak
6	1825	H	48.29	-12.98	35.31	54.00	-18.69	Avg
7	2737.5	--	--	--	--	--	--	--
8	5475	--	--	--	--	--	--	--
Test Mode : GFSK TX High CH50								
1	1840	V	59.90	-12.70	47.20	74.00	-26.80	Peak
2	1840	V	49.33	-12.70	36.63	54.00	-17.37	Avg
3	2760	--	--	--	--	--	--	--
4	5520	--	--	--	--	--	--	--
5	1840	H	56.27	-12.70	43.57	74.00	-30.43	Peak
6	1840	H	45.35	-12.70	32.65	54.00	-21.35	Avg
7	2760	--	--	--	--	--	--	--
8	5520	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

10. Band Edge Test


10.1. Test Limit

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241

10.2. Block Diagram of Test Setup



10.3. Test Procedure

ANSI C63.10-2020+Cor.1-2023 section 6.10.5.2

All restriction band and non- restriction band have been tested, only worse case is reported.

Details see the KDB558074 D01 Meas Guidance v05r02


1. Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
2. Check the spurious emissions out of band.
3. RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

10.4. Test Results

Test Date	: 2026.03.19	Temperature	: 26°C
Test Engineer	: Felix Pang	Humidity	: 54%
Test Results	: PASS		


Frequency Range	: 902MHz~928MHz
Test Mode	: GFSK TX Low CH01

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	9.23	28.09	37.32	46.00	-8.68	peak
2 *	904.9500	77.14	28.12	105.26	46.00	59.26	peak
3	928.0000	7.67	28.36	36.03	46.00	-9.97	peak

Note: Level = Reading + Factor Margin = Level – Limit

Polarization: Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	5.85	28.09	33.94	46.00	-12.06	peak
2 *	904.9500	65.03	28.12	93.15	46.00	47.15	peak
3	928.0000	7.14	28.36	35.50	46.00	-10.50	peak

Note: Level = Reading + Factor Margin = Level – Limit

Frequency Range : 902MHz~928MHz


Test Mode : GFSK TX High CH50

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	6.74	28.09	34.83	46.00	-11.17	peak
2 *	919.9500	75.63	28.28	103.91	46.00	57.91	peak
3	928.0000	7.14	28.36	35.50	46.00	-10.50	peak

Note: Level = Reading + Factor Margin = Level – Limit

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	7.64	28.09	35.73	46.00	-10.27	peak
2 *	919.9500	69.40	28.28	97.68	46.00	51.68	peak
3	928.0000	8.04	28.36	36.40	46.00	-9.60	peak

Note: Level = Reading + Factor Margin = Level - Limit

11. Power Line Conducted Emissions

11.1. Test Limits

Frequency (MHz)	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

11.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10-2020+Cor.1-2023 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.


11.3. Test Setup



11.4. Test Results

Test Date	: 2026.03.17	Temperature	: 24℃
Test Engineer	: Felix Pang	Humidity	: 56%
Test Mode	: GFSK mode		
Test voltage	: AC 120V/60Hz		
Test Results	: PASS		
Note:	1. The test results are listed in next pages.		
	2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out.		
	3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.		
	4. All modes have been tested, and only worst data of GFSK mode, Channel 905MHz was listed in this report.		


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1700	31.47	9.58	41.05	64.96	-23.91	QP
2	0.1700	21.73	9.58	31.31	54.96	-23.65	AVG
3	0.3740	30.31	9.40	39.71	58.41	-18.70	QP
4	0.3740	19.12	9.40	28.52	48.41	-19.89	AVG
5	0.7900	29.50	9.52	39.02	56.00	-16.98	QP
6	0.7900	18.33	9.52	27.85	46.00	-18.15	AVG
7 *	1.0940	30.24	9.81	40.05	56.00	-15.95	QP
8	1.0940	18.53	9.81	28.34	46.00	-17.66	AVG
9	14.0460	14.73	9.76	24.49	60.00	-35.51	QP
10	14.0460	4.55	9.76	14.31	50.00	-35.69	AVG
11	27.6740	20.87	9.55	30.42	60.00	-29.58	QP
12	27.6740	9.63	9.55	19.18	50.00	-30.82	AVG

Note: Level = Reading + Factor, Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1900	31.48	9.46	40.94	64.04	-23.10	QP
2	0.1900	20.65	9.46	30.11	54.04	-23.93	AVG
3	0.3140	30.34	9.40	39.74	59.86	-20.12	QP
4	0.3140	19.30	9.40	28.70	49.86	-21.16	AVG
5	0.7780	30.42	9.50	39.92	56.00	-16.08	QP
6 *	0.7780	21.03	9.50	30.53	46.00	-15.47	AVG
7	1.3380	30.20	9.83	40.03	56.00	-15.97	QP
8	1.3380	18.16	9.83	27.99	46.00	-18.01	AVG
9	13.3380	14.47	9.73	24.20	60.00	-35.80	QP
10	13.3380	3.61	9.73	13.34	50.00	-36.66	AVG
11	28.2100	19.59	9.54	29.13	60.00	-30.87	QP
12	28.2100	13.46	9.54	23.00	50.00	-27.00	AVG

Note: Level = Reading + Factor, Margin = Level - Limit

12. Antenna Requirements

12.1.Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the GFSK, but the use of a standard antenna jack or electrical connector is prohibited.

12.2.Result

The EUT antenna is internal antenna. It complies with the standard requirement.



13. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

14. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----

