

FCC TEST REPORT FOR

ERM ELECTRONIC SYSTEMS LTD

GPS 4G Tracker Scout BLE (CATM)

Test Model: GPS 4G Tracker Scout BLE (CATM)

Prepared for	:	ERM ELECTRONIC SYSTEMS LTD
Address	:	16 HASAR SHAPIRA, RISHON LE-ZION, ISRAEL
Prepared by	:	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	:	No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Tel	:	(+86) 020-39166689
Fax	:	(+86) 020-39166619
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	May 28, 2026
Number of tested samples	:	2
Sample No.	:	C260527009-1, C260527009-2
Serial number	:	Sample/serial production
Date of Test	:	May 28, 2026 ~ July 31, 2026
Date of Report	:	August 04, 2026

FCC PART 22/24/27 TEST REPORT**FCC Part 22H/Part 24E/Part 27**

Report Reference No.	LCSC05276005EB
Date of Issue	August 04, 2026
Testing Laboratory Name	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Applicant's name	ERM ELECTRONIC SYSTEMS LTD
Address	16 HASAR SHAPIRA, RISHON LE-ZION, ISRAEL
Test specification	
Standard	FCC CFR Title 47 Part 2, Part 22H, Part 24E, Part 27 TIA-603-E: 2016 KDB971168 D01 Power Meas License Digital Systems v03r01
TRF Originator	Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description	GPS 4G Tracker Scout BLE (CATM)
Trade Mark	STARLINK
Test Model	GPS 4G Tracker Scout BLE (CATM)
Modulation Type	QPSK,16QAM
Rating	Please Refer to Page 7
Result	Pass

Compiled by:

Lifeng Le/ Administrator

Supervised by:

Justin Zhu/ Technique Director

Approved by:

Gavin Liang/ Manager

TEST REPORT

Test Report No. :	LCSC05276005EB	August 04, 2026
		Date of issue

Test Model.....	: GPS 4G Tracker Scout BLE (CATM)
EUT.....	: GPS 4G Tracker Scout BLE (CATM)
Applicant.....	: ERM ELECTRONIC SYSTEMS LTD
Address.....	: 16 HASAR SHAPIRA, RISHON LE-ZION, ISRAEL
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: ERM ELECTRONIC SYSTEMS LTD
Address.....	: 16 HASAR SHAPIRA, RISHON LE-ZION, ISRAEL
Telephone.....	: /
Fax.....	: /
Factory.....	: ERM ELECTRONIC SYSTEMS LTD
Address.....	: 16 HASAR SHAPIRA, RISHON LE-ZION, ISRAEL
Telephone.....	: /
Fax.....	: /

Test Result:	Pass
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 04, 2026	Initial Issue	---

Contents

<u>1</u>	<u>TEST STANDARDS</u>	<u>6</u>
<u>2</u>	<u>SUMMARY</u>	<u>7</u>
2.1	Product Description	7
2.2	Equipment under Test	8
2.3	Short description of the Equipment under Test (EUT)	8
2.4	Support equipment List	8
2.5	External I/O Port	8
2.6	Normal Accessory setting	8
2.7	Test Sample	8
2.8	EUT configuration	9
2.9	Related Submittal(s) / Grant (s)	9
2.10	Modifications	9
2.11	General Test Conditions/Configurations	9
<u>3</u>	<u>TEST ENVIRONMENT</u>	<u>10</u>
3.1	Address of the test laboratory	10
3.2	Test Facility	10
3.3	Environmental conditions	10
3.4	Test Description	10
3.5	Equipments Used during the Test	13
3.6	Measurement uncertainty	14
<u>4</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>15</u>
4.1	Output Power	15
4.2	Peak-to-Average Ratio (PAR)	25
4.3	Occupied Bandwidth and Emission Bandwidth	26
4.4	Band Edge compliance	27
4.5	Spurious Emssion on Antenna Port	28
4.6	Radiated Spurious Emssion	30
4.7	Frequency Stability under Temperature & Voltage Variations	37
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>41</u>
<u>6</u>	<u>EXTERNAL PHOTOS OF THE EUT</u>	<u>41</u>
<u>7</u>	<u>INTERNAL PHOTOS OF THE EUT</u>	<u>41</u>

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22H](#): Cellular Radiotelephone Service

[FCC Part 24E](#): Broadband PCS

[FCC Part 27](#): MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[TIA-603-E March 2016](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[ANSI C63.4:2014](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

[FCC KDB971168 D01](#) Power Meas License Digital Systems v03r01

2 SUMMARY

2.1 Product Description

The **ERM ELECTRONIC SYSTEMS LTD**'s Model: GPS 4G Tracker Scout BLE (CATM) or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

EUT : GPS 4G Tracker Scout BLE (CATM)

Test Model : GPS 4G Tracker Scout BLE (CATM)

Ratings : Input: DC 12-24V
Battery: 3.7V $\approx$ 350mAh

Hardware Version : /

Software Version : /

Bluetooth :

Frequency Range : 2402MHz~2480MHz

Channel Number : 40 channels for Bluetooth V5.0 (DTS)

Channel Spacing : 2MHz for Bluetooth V5.0 (DTS)

Modulation Type : GFSK for Bluetooth V5.0 (DTS)

Bluetooth Version : V5.0

Antenna Description : Internal Antenna, -5.86dBi(Max.)

LTE :

Support Band : ☒ E-UTRA Band 2(U.S.-Band)
☒ E-UTRA Band 4(U.S.-Band)
☒ E-UTRA Band 5(U.S.-Band)
☒ E-UTRA Band 66(U.S.-Band)

LTE Release Version : R9

Type Of Modulation : QPSK/16QAM

Antenna Description : Internal Antenna
2.52dBi(max.) For E-UTRA Band 2
2.78dBi(max.) For E-UTRA Band 4
0.65dBi(max.) For E-UTRA Band 5
2.788dBi(max.) For E-UTRA Band 66

Power Class : Class 3

Extreme temp. : -30°C to +50°C

Tolerance

Extreme vol. Limits : 10.2VDC to 13.8VDC (nominal: 12VDC)
21.6VDC to 26.4VDC (nominal: 24VDC)

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

2.2 Equipment under Test

Power supply system utilised

Power supply voltage	:	○	120V/ 60 Hz	○	115V/60Hz
		○	12 V DC	○	24 V DC
		●	Other (specified in blank below) 12V/24V DC		

2.3 Short description of the Equipment under Test (EUT)

2.4.1 General Description

GPS 4G Tracker Scout BLE (CATM) is subscriber equipment in the BLE/LTE system. LTE frequency band is band 2/4/5/66. The GPS 4G Tracker Scout BLE (CATM) implements such functions as RF signal receiving/transmitting, LTE protocol processing, video MMS service and etc. Externally it provides SIM card interface.

2.4 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

2.5 External I/O Port

I/O Port Description	Quantity	Cable
--	--	--

2.6 Normal Accessory setting

Fully charged battery was used during the test.

2.7 Test Sample

The application provides 2 samples to meet requirement;

Sample Number	Description
Sample 1(C260527009-1)	Engineer sample – continuous transmit
Sample 2(C260527009-2)	Normal sample – Intermittent transmit

2.8 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
○	Multimeter	Manufacturer :	/
		Model No. :	/

2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AXZU-GTPMLC1E1 filing to comply with FCC Part 22, Part 24, Part 27 Rules

2.10 Modifications

No modifications were implemented to meet testing criteria.

2.11 General Test Conditions/Configurations

2.9.1 Test Environment

EnvironmentParameter	SelectedValuesDuringTests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	DC 10.2V
	VN	DC 12V
	VH	DC 13.8V

EnvironmentParameter	SelectedValuesDuringTests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	DC 21.6V
	VN	DC 24V
	VH	DC 26.4V

NOTE:VL=lower extreme testvoltage VN=nominal voltage

VH=upper extreme testvoltage TN=normal temperature

Pre-scan all modes and recorded the worst case results in this report Voltage : 12V

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen LCS Compliance Testing Laboratory Ltd

No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

Band 2 (1850-1910MHz pairedwith 1930-1990MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	PASS
Peak-Average Ratio	§2.1046, §24.232	FCC:Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	PASS
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to the frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤-13dBm/1MHz, from 9kHz to10 th harmonics but outside authorized Operating frequency ranges.	PASS
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	PASS
Frequency Stability	§2.1055, §24.235	FCC: within authorized frequency block.	PASS
NOTE 1:For the verdict, the“N/A”denotes“not applicable”,the“N/T”de notes “not tested”.			

Band 4 (1710-1755MHz pairedwith 2110-2155MHz)

Test Item	FCC RuleNo.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP $\leq$ 1W;	PASS
Peak-Average Ratio	§2.1046, §27.50(d)	Limit $\leq$ 13dB	Pass
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
BandEdges Compliance	§2.1051, §27.53(h)	$\leq$ -13dBm/1%*EBW, in1 MHz bands immediately outside and adjacent to the frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	$\leq$ -13dBm/1MHz, from 9kHz to10 th harmonics but outside authorized operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(h)	$\leq$ -13dBm/1MHz.	PASS

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" de notes "not tested"

Band 5 (824-849MHz pairedwith 869-894MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §22.913	FCC: ERP $\leq$ 7W.	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	$\leq$ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: $\leq$ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: $\leq$ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	$\leq \pm 2.5$ ppm.	Pass

NOTE 1:For the verdict, the"N/A"denotes"not applicable",the"N/T"de notes "not tested".

Band 66 (1710-1780MHz pairedwith 2110-2220MHz)

Test Item	FCC RuleNo.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP ≤ 1W;	PASS
Peak-Average Ratio	§2.1046, §27.50(d)	Limit≤13dB	Pass
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
Band Edges Compliance	§2.1051, §27.53(g)	≤ -13dBm/1%*EBW,in1 MHz bands immediately outside and adjacent to the frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	≤ -13dBm/1MHz, from 9kHz to10 th harmonics but outside authorized operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(g)	≤ -13dBm/1MHz.	PASS
NOTE 1: For the verdict, the “N/A” denotes “not applicable”, the “N/T” de notes “not tested”			

Note:Module EG800Q-NA UE Category is < 2, Therefore, the maximum Allocated resource blocks of 10MHz, 15MHz and 20MHz Channel bandwidth of module 16-QAM can only reach 27

3.5 Equipments Used during the Test

Item	Equipment	Manufacturer	Model No.	Equipment No.	Cal Date	Due Date
1	Power Meter	Keysight	E4417A	GLCS-E-279	2026-04-07	2027-04-06
2	Power Sensor	Keysight	E9304A	GLCS-E-280	2026-04-07	2027-04-06
3	Power Sensor	Keysight	E9304A	GLCS-E-281	2026-04-07	2027-04-06
4	LTE Test Software	Tonscend	JS1120-1	GLCS-E-368	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-1	GLCS-E-367	N/A	N/A
6	MXA Signal Analyzer	Keysight	N9020A	GLCS-E-361	2025-08-18	2026-08-17
7	DC Power Supply	Keysight	E3642A	GLCS-E-362	2025-08-18	2026-08-17
8	Signal Analyzer	Keysight	N5182A	GLCS-E-358	2025-08-18	2026-08-17
9	Signal Analyzer	Keysight	N5173B	GLCS-E-359	2025-08-18	2026-08-17
10	WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	GLCS-E-360	2025-08-18	2026-08-17
11	EMI Test Software	Farad	EZ-EMC(Ver.FA-03A2 RE+)	GLCS-E-012	N/A	N/A
12	Semi Anechoic Chamber#1	Maorui	966	GLCS-E-001	2024-04-21	2027-04-20
13	Positioning Controller	Max-Full	MF-7802	GLCS-E-015	N/A	N/A
14	Active Loop Antenna	TESEQ	HLA 6121	GLCS-E-155	2025-07-19 2026-07-17	2026-07-18 2027-07-16
15	By-log Antenna	SCHWARZBECK	VULB9163	GLCS-E-352	2025-08-16	2028-08-15
16	Low-frequency amplifier	Sonoma	310N	GLCS-E-036	2026-04-07	2027-04-06
17	Horn Antenna	SCHWARZBECK	BBHA 9120D	GLCS-E-060	2025-07-19 2026-07-17	2026-07-18 2027-07-16
18	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	GLCS-E-348	2025-08-18	2028-08-17
19	Broadband Preamplifier	Cesheng Technology	LNPA_30M06G-40(18GHz)	GLCS-E-286	2026-04-07	2027-04-06
20	Broadband Preamplifier	Cesheng Technology	LNPA 30M06G-40(40GHz)	GLCS-E-287	2026-04-10	2027-04-09
21	EMI Test Receiver	R&S	ESR 7	GLCS-E-192	2026-04-07	2027-04-06
22	RS SPECTRUM ANALYZER	R&S	FSP40	GLCS-E-213	2025-05-22	2026-05-21
23	6dB Attenuator	/	100W/6dB	GLCS-E-350	2025-08-13	2026-08-12
24	3dB Attenuator	/	2N-3dB	GLCS-E-351	2025-08-13	2026-08-12
25	Temperature & Humidity Chamber	GRE A TESTING	GR-HWS-225L	GLCS-E-369	2025-12-31	2026-12-30
26	EMI Test Receiver	ROHDE & SCHWARZ	ESR7	GLCS-E-158	2026-04-07	2027-04-06
27	Artificial Mains Network	ROHDE & SCHWARZ	ESH2-Z5	GLCS-E-011	2026-01-14	2027-01-13
28	EMI Test Software	Farad	EZ-EMC(Ver.FA-03A2 RE+)	GLCS-E-017	N/A	N/A
29	Antenna Mast	Maorui	BK-4AT-BS	GLCS-E-249	N/A	N/A
30	Pulse Limiter	SCHWARZBECK	VTSD 9561-F	GLCS-E-080	2026-04-07	2027-04-06

3.6 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028“Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics” and is documented in the Guangzhou LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Guangzhou LCS Compliance Testing Laboratory Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.10 dB	(1)
Radiated Emission	1~18GHz	3.80 dB	(1)
Radiated Emission	18-40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	1.63 dB	(1)
Conducted Power	9KHz~18GHz	0.61 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	1.22 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	1.22 dB	(1)
Occupied Bandwidth	9KHz~40GHz	-	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4 TEST CONDITIONS AND RESULTS


4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMW 500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1. Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a CMW 500 by an Att.
- EUT Communicate with CMW 500 then selects a channel for testing.
- Add a correction factor to the display CMW 500, and then test.

TEST RESULTS

Remark:

- We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
- For E-UTRA Band 2, please refer to Appendix B: Section B.1
- For E-UTRA Band 4, please refer to Appendix C: Section C.1
- For E-UTRA Band 5, please refer to Appendix D: Section D.1
- For E-UTRA Band 66, please refer to Appendix E: Section E.1

4.1.2. Radiated Output Power

LIMIT

This is the test for the maximum radiated power from the EUT.


Per §22.913(2) Extend coverage on a secondary basis into cellular unserved areas, as those areas are defined in §22.949, the ERP of base transmitters and cellular repeaters of such systems must not exceed 1000 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts. Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Per Part 27.50(d) (4) specifies, Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755MHz band are limited to 1W EIRP. Fixed stations operating in this band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in this band must employ a means for limiting power to the minimum necessary for successful communications.

Per Part 27.50(c) (10) specifies, Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

Per Part 27.50(h) (2) specifies Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

- The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
- The EUT shall be replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$
- This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.

TEST RESULTS

Radiated Measurement:

Remark:

- We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
- $\text{EIRP} = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
- $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ as EIRP by subtracting the gain of the dipole.
- Margin = Emission Level - Limit
- We tested the worst-case records for H and V directions, and only the worst-case records for V direction were recorded in the report.

CATM1 Band 2 Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.7	-19.61	5.04	9.39	36.52	21.26	33.01	-11.75	V
1880.0	-19.06	5.09	9.34	36.57	21.76	33.01	-11.25	V
1909.3	-19.29	5.15	9.27	36.64	21.47	33.01	-11.54	V

CATM1 Band 2 Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-19.76	5.04	9.39	36.52	21.11	33.01	-11.90	V
1880.0	-19.55	5.09	9.34	36.57	21.27	33.01	-11.74	V
1908.5	-20.07	5.15	9.27	36.64	20.69	33.01	-12.32	V

CATM1 Band 2 Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-20.95	5.04	9.39	36.52	19.92	33.01	-13.09	V
1880.0	-20.19	5.09	9.34	36.57	20.63	33.01	-12.38	V
1907.5	-20.08	5.15	9.27	36.64	20.68	33.01	-12.33	V

TRF-4-E-154 A/0

CATM1 Band 2_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-21.34	5.04	9.39	36.52	19.53	33.01	-13.48	V
1880.0	-20.88	5.09	9.34	36.57	19.94	33.01	-13.07	V
1905.0	-20.85	5.15	9.27	36.64	19.91	33.01	-13.10	V

CATM1 Band 2_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-21.76	5.04	9.39	36.52	19.11	33.01	-13.90	V
1880.0	-21.15	5.09	9.34	36.57	19.67	33.01	-13.34	V
1902.5	-21.68	5.15	9.27	36.64	19.08	33.01	-13.93	V

CATM1 Band 2_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-22.36	5.04	9.39	36.52	18.51	33.01	-14.50	V
1880.0	-22.41	5.09	9.34	36.57	18.41	33.01	-14.60	V
1900.0	-21.59	5.15	9.27	36.64	19.17	33.01	-13.84	V

CATM1 Band 2_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.7	-19.58	5.04	9.39	36.52	21.29	33.01	-11.72	V
1880.0	-20.17	5.09	9.34	36.57	20.65	33.01	-12.36	V
1909.3	-20.43	5.15	9.27	36.64	20.33	33.01	-12.68	V

CATM1 Band 2_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-20.19	5.04	9.39	36.52	20.68	33.01	-12.33	V
1880.0	-20.73	5.09	9.34	36.57	20.09	33.01	-12.92	V
1908.5	-20.67	5.15	9.27	36.64	20.09	33.01	-12.92	V

CATM1 Band 2_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-21.29	5.04	9.39	36.52	19.58	33.01	-13.43	V
1880.0	-20.71	5.09	9.34	36.57	20.11	33.01	-12.90	V
1907.5	-20.55	5.15	9.27	36.64	20.21	33.01	-12.80	V

CATM1 Band 2_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-21.21	5.04	9.39	36.52	19.66	33.01	-13.35	V
1880.0	-21.27	5.09	9.34	36.57	19.55	33.01	-13.46	V
1905.0	-21.76	5.15	9.27	36.64	19.00	33.01	-14.01	V

CATM1 Band 2_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-22.10	5.04	9.39	36.52	18.77	33.01	-14.24	V
1880.0	-22.00	5.09	9.34	36.57	18.82	33.01	-14.19	V
1902.5	-21.62	5.15	9.27	36.64	19.14	33.01	-13.87	V

CATM1 Band 2_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-22.88	5.04	9.39	36.52	17.99	33.01	-15.02	V
1880.0	-22.35	5.09	9.34	36.57	18.47	33.01	-14.54	V
1900.0	-22.18	5.15	9.27	36.64	18.58	33.01	-14.43	V

CATM1 Band 4_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-18.79	4.94	10.06	35.97	22.30	30.00	-7.70	V
1732.5	-19.04	4.94	9.90	36.02	21.94	30.00	-8.06	V
1754.3	-19.19	4.95	9.77	36.09	21.72	30.00	-8.28	V

CATM1 Band 4_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-19.30	4.94	10.06	35.97	21.79	30.00	-8.21	V
1732.5	-19.19	4.94	9.90	36.02	21.79	30.00	-8.21	V
1753.5	-19.47	4.95	9.77	36.09	21.44	30.00	-8.56	V

CATM1 Band 4_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-19.46	4.94	10.06	35.97	21.63	30.00	-8.37	V
1732.5	-19.28	4.94	9.90	36.02	21.70	30.00	-8.30	V
1752.5	-19.35	4.95	9.77	36.09	21.56	30.00	-8.44	V

TRF-4-E-154 A/0

Guangzhou LCS Compliance Testing Laboratory Ltd.
 Add: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
 Tel: +(86) 020-39166689 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
 Scan code to check authenticity

CATM1 Band 4_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-19.56	4.94	10.06	35.97	21.53	30.00	-8.47	V
1732.5	-19.36	4.94	9.90	36.02	21.62	30.00	-8.38	V
1750.0	-18.94	4.95	9.77	36.09	21.97	30.00	-8.03	V

CATM1 Band 4_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-18.61	4.94	10.06	35.97	22.48	30.00	-7.52	V
1732.5	-18.97	4.94	9.90	36.02	22.01	30.00	-7.99	V
1747.5	-18.73	4.95	9.77	36.09	22.18	30.00	-7.82	V

CATM1 Band 4_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-19.81	4.94	10.06	35.97	21.28	30.00	-8.72	V
1732.5	-19.08	4.94	9.90	36.02	21.90	30.00	-8.10	V
1745.0	-19.61	4.95	9.77	36.09	21.30	30.00	-8.70	V

CATM1 Band 4_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-19.31	4.94	10.06	35.97	21.78	30.00	-8.22	V
1732.5	-19.41	4.94	9.90	36.02	21.57	30.00	-8.43	V
1754.3	-19.67	4.95	9.77	36.09	21.24	30.00	-8.76	V

CATM1 Band 4_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-19.27	4.94	10.06	35.97	21.82	30.00	-8.18	V
1732.5	-18.79	4.94	9.90	36.02	22.19	30.00	-7.81	V
1753.5	-18.52	4.95	9.77	36.09	22.39	30.00	-7.61	V

CATM1 Band 4_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-19.05	4.94	10.06	35.97	22.04	30.00	-7.96	V
1732.5	-19.67	4.94	9.90	36.02	21.31	30.00	-8.69	V
1752.5	-19.40	4.95	9.77	36.09	21.51	30.00	-8.49	V

CATM1 Band 4_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-18.81	4.94	10.06	35.97	22.28	30.00	-7.72	V
1732.5	-19.18	4.94	9.90	36.02	21.80	30.00	-8.20	V
1750.0	-18.58	4.95	9.77	36.09	22.33	30.00	-7.67	V

CATM1 Band 4_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-19.23	4.94	10.06	35.97	21.86	30.00	-8.14	V
1732.5	-19.57	4.94	9.90	36.02	21.41	30.00	-8.59	V
1747.5	-19.46	4.95	9.77	36.09	21.45	30.00	-8.55	V

CATM1 Band 4_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-18.50	4.94	10.06	35.97	22.59	30.00	-7.41	V
1732.5	-18.69	4.94	9.90	36.02	22.29	30.00	-7.71	V
1745.0	-18.88	4.95	9.77	36.09	22.03	30.00	-7.97	V

CATM1 Band 5_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-16.47	4.46	9.46	3.16	34.80	20.17	38.45	-18.28	V
836.50	-16.17	4.50	9.46	3.16	34.86	20.49	38.45	-17.96	V
848.30	-15.79	4.56	9.37	3.16	34.89	20.75	38.45	-17.70	V

CATM1 Band 5_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-15.90	4.46	9.46	3.16	34.80	20.74	38.45	-17.71	V
836.50	-15.64	4.50	9.46	3.16	34.86	21.02	38.45	-17.43	V
847.50	-15.99	4.56	9.37	3.16	34.89	20.55	38.45	-17.90	V

CATM1 Band 5_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-15.92	4.46	9.46	3.16	34.80	20.72	38.45	-17.73	V
836.50	-16.38	4.50	9.46	3.16	34.86	20.28	38.45	-18.17	V
846.50	-15.77	4.56	9.37	3.16	34.89	20.77	38.45	-17.68	V

TRF-4-E-154 A/O

Guangzhou LCS Compliance Testing Laboratory Ltd.
 Add: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
 Tel: +(86) 020-39166689 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
 Scan code to check authenticity

CATM1 Band 5_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-16.12	4.46	9.46	3.16	34.80	20.52	38.45	-17.93	V
836.50	-16.49	4.50	9.46	3.16	34.86	20.17	38.45	-18.28	V
844.00	-15.95	4.56	9.37	3.16	34.89	20.59	38.45	-17.86	V

CATM1 Band 5_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-16.96	4.46	9.46	3.16	34.80	19.68	38.45	-18.77	V
836.50	-17.23	4.50	9.46	3.16	34.86	19.43	38.45	-19.02	V
848.30	-16.89	4.56	9.37	3.16	34.89	19.65	38.45	-18.80	V

CATM1 Band 5_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-17.27	4.46	9.46	3.16	34.80	19.37	38.45	-19.08	V
836.50	-17.22	4.50	9.46	3.16	34.86	19.44	38.45	-19.01	V
847.50	-17.14	4.56	9.37	3.16	34.89	19.40	38.45	-19.05	V

CATM1 Band 5_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-16.88	4.46	9.46	3.16	34.80	19.76	38.45	-18.69	V
836.50	-16.70	4.50	9.46	3.16	34.86	19.96	38.45	-18.49	V
846.50	-16.89	4.56	9.37	3.16	34.89	19.65	38.45	-18.80	V

CATM1 Band 5_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-17.29	4.46	9.46	3.16	34.80	19.35	38.45	-19.10	V
836.50	-16.93	4.50	9.46	3.16	34.86	19.73	38.45	-18.72	V
844.00	-16.84	4.56	9.37	3.16	34.89	19.70	38.45	-18.75	V

CATM1 Band 66_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-18.84	4.94	10.06	35.97	22.25	30.00	-7.75	V
1745.0	-19.43	4.94	9.90	36.02	21.55	30.00	-8.45	V
1779.3	-18.51	4.95	9.77	36.09	22.40	30.00	-7.60	V

CATM1 Band 66_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-19.58	4.94	10.06	35.97	21.51	30.00	-8.49	V
1745.0	-19.39	4.94	9.90	36.02	21.59	30.00	-8.41	V
1778.5	-19.09	4.95	9.77	36.09	21.82	30.00	-8.18	V

CATM1 Band 66_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-18.70	4.94	10.06	35.97	22.39	30.00	-7.61	V
1745.0	-18.98	4.94	9.90	36.02	22.00	30.00	-8.00	V
1777.5	-18.77	4.95	9.77	36.09	22.14	30.00	-7.86	V

CATM1 Band 66_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-19.13	4.94	10.06	35.97	21.96	30.00	-8.04	V
1745.0	-19.30	4.94	9.90	36.02	21.68	30.00	-8.32	V
1775.0	-19.78	4.95	9.77	36.09	21.13	30.00	-8.87	V

CATM1 Band 66_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-18.66	4.94	10.06	35.97	22.43	30.00	-7.57	V
1745.0	-19.44	4.94	9.90	36.02	21.54	30.00	-8.46	V
1772.5	-19.50	4.95	9.77	36.09	21.41	30.00	-8.59	V

CATM1 Band 66_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-19.26	4.94	10.06	35.97	21.83	30.00	-8.17	V
1745.0	-19.36	4.94	9.90	36.02	21.62	30.00	-8.38	V
1770.0	-19.29	4.95	9.77	36.09	21.62	30.00	-8.38	V

CATM1 Band 66_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-19.68	4.94	10.06	35.97	21.41	30.00	-8.59	V
1745.0	-19.04	4.94	9.90	36.02	21.94	30.00	-8.06	V
1779.3	-19.38	4.95	9.77	36.09	21.53	30.00	-8.47	V

CATM1 Band 66_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-19.48	4.94	10.06	35.97	21.61	30.00	-8.39	V
1745.0	-18.81	4.94	9.90	36.02	22.17	30.00	-7.83	V
1778.5	-18.72	4.95	9.77	36.09	22.19	30.00	-7.81	V

CATM1 Band 66_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-19.74	4.94	10.06	35.97	21.35	30.00	-8.65	V
1745.0	-19.83	4.94	9.90	36.02	21.15	30.00	-8.85	V
1777.5	-19.35	4.95	9.77	36.09	21.56	30.00	-8.44	V

CATM1 Band 66_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-18.72	4.94	10.06	35.97	22.37	30.00	-7.63	V
1745.0	-18.87	4.94	9.90	36.02	22.11	30.00	-7.89	V
1775.0	-19.20	4.95	9.77	36.09	21.71	30.00	-8.29	V

CATM1 Band 66_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-19.30	4.94	10.06	35.97	21.79	30.00	-8.21	V
1745.0	-19.65	4.94	9.90	36.02	21.33	30.00	-8.67	V
1772.5	-19.32	4.95	9.77	36.09	21.59	30.00	-8.41	V

CATM1 Band 66_Channel Bandwidth 20MHz_16QAM


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-19.14	4.94	10.06	35.97	21.95	30.00	-8.05	V
1745.0	-19.32	4.94	9.90	36.02	21.66	30.00	-8.34	V
1770.0	-19.13	4.95	9.77	36.09	21.78	30.00	-8.22	V

4.2 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,
 - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Remark:


1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.2
3. For E-UTRA Band 4, please refer to Appendix C: Section C.2
4. For E-UTRA Band 5, please refer to Appendix D: Section D.2
5. For E-UTRA Band 66, please refer to Appendix E: Section E.2

4.3 Occupied Bandwidth and Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded. Set RBW was set to about 1% of emission BW, VBW $\geq$ 3 times RBW. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.3
3. For E-UTRA Band 4, please refer to Appendix C: Section C.3
4. For E-UTRA Band 5, please refer to Appendix D: Section D.3
5. For E-UTRA Band 66, please refer to Appendix E: Section E.3

4.4 Band Edge compliance

LIMIT


For CATM1 Band 2: Per FCC §24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 4: Per §27.53(h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For CATM1 Band 5: Per FCC §22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 66: Per §27.53(h): For operations in the 1710–1780 MHz and 2110–2200 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.4
3. For E-UTRA Band 4, please refer to Appendix C: Section C.4
4. For E-UTRA Band 5, please refer to Appendix D: Section D.4
5. For E-UTRA Band 66, please refer to Appendix E: Section E.4

4.5 Spurious Emission on Antenna Port

LIMIT


For CATM1 Band 2: Per FCC §24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 4: Per §27.53(h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For CATM1 Band 5: Per FCC §22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 66: Per §27.53(h): For operations in the 1710–1780 MHz and 2110–2200 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to TIA-603-E

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW 500 by a Directional Couple.
- EUT Communicate with CMW 500, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.
- Please refer to following tables for test antenna conducted emissions.

Working Frequency	Sub range (GHz)	RBW	VBW	Sweep time (s)
CATM1 Band 2	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~20	1 MHz	3 MHz	Auto
CATM1 Band 4	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~20	1 MHz	3 MHz	Auto
CATM1 Band 5	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~10	1 MHz	3 MHz	Auto
CATM1 Band 66	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~20	1 MHz	3 MHz	Auto

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.5
3. For E-UTRA Band 4, please refer to Appendix C: Section C.5
4. For E-UTRA Band 5, please refer to Appendix D: Section D.5
5. For E-UTRA Band 66, please refer to Appendix E: Section E.5

4.6 Radiated Spurious Emission

LIMIT


For CATM1 Band 2: Per FCC §24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 4: Per §27.53(h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For CATM1 Band 5: Per FCC §22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For CATM1 Band 66: Per §27.53(h): For operations in the 1710–1780 MHz and 2110–2200 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (Pr).
4. The EUT shall be replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
The measurement results are obtained as described below:
 $\text{Power(EIRP)} = \text{PMea} + \text{PAg} - \text{Pcl} + \text{Ga}$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
CATM1 Band 2	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
CATM1 Band 4	18~20	1 MHz	3 MHz	2
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
CATM1 Band 5	14~18	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
CATM1 Band 66	8~9	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3

Frequency	Channel	Frequency Range	Verdict
CATM1 Band 2	Low	9KHz -20GHz	PASS
	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS
CATM1 Band 4	Low	9KHz -18GHz	PASS
	Middle	9KHz -18GHz	PASS
	High	9KHz -18GHz	PASS
CATM1 Band 5	Low	9KHz -9GHz	PASS
	Middle	9KHz -9GHz	PASS
	High	9KHz -9GHz	PASS
CATM1 Band 66	Low	9KHz -18GHz	PASS
	Middle	9KHz -18GHz	PASS
	High	9KHz -18GHz	PASS

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.

3. We were not recorded other points as values lower than limits.

4. $\text{Power(EIRP)} = P_{\text{Mea}} + P_{\text{Ag}} - P_{\text{cl}} + G_a$

5. $\text{Margin} = \text{EIRP} - \text{Limit}$

Note: All adapters and all the modes have been tested and recorded worst mode in the report.

CATM1 Band 2_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-40.42	6.27	3.00	10.89	-35.80	-13.00	-22.80	H
5572.5	-43.05	7.12	3.00	12.37	-37.80	-13.00	-24.80	H
3715.0	-29.73	6.27	3.00	10.89	-25.11	-13.00	-12.11	V
5572.5	-36.01	7.12	3.00	12.37	-30.76	-13.00	-17.76	V

CATM1 Band 2_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-40.58	6.33	3.00	11.04	-35.87	-13.00	-22.87	H
5580.0	-45.20	7.20	3.00	12.42	-39.98	-13.00	-26.98	H
3720.0	-30.00	6.33	3.00	11.04	-25.29	-13.00	-12.29	V
5580.0	-36.97	7.20	3.00	12.42	-31.75	-13.00	-18.75	V

CATM1 Band 2_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-37.90	6.37	3.00	10.63	-33.64	-13.00	-20.64	H
5700.0	-45.96	7.25	3.00	12.47	-40.74	-13.00	-27.74	H
3800.0	-31.14	6.37	3.00	10.63	-26.88	-13.00	-13.88	V
5700.0	-33.80	7.25	3.00	12.47	-28.58	-13.00	-15.58	V

CATM1 Band 2_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-40.84	6.27	3.00	10.89	-36.22	-13.00	-23.22	H
5572.5	-47.63	7.12	3.00	12.37	-42.38	-13.00	-29.38	H
3715.0	-31.11	6.27	3.00	10.89	-26.49	-13.00	-13.49	V
5572.5	-40.13	7.12	3.00	12.37	-34.88	-13.00	-21.88	V

CATM1 Band 2_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-41.93	6.33	3.00	11.04	-37.22	-13.00	-24.22	H
5580.0	-48.93	7.20	3.00	12.42	-43.71	-13.00	-30.71	H
3720.0	-34.76	6.33	3.00	11.04	-30.05	-13.00	-17.05	V
5580.0	-38.13	7.20	3.00	12.42	-32.91	-13.00	-19.91	V

CATM1 Band 2_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-41.03	6.37	3.00	10.63	-36.77	-13.00	-23.77	H
5700.0	-49.83	7.25	3.00	12.47	-44.61	-13.00	-31.61	H
3800.0	-33.84	6.37	3.00	10.63	-29.58	-13.00	-16.58	V
5700.0	-40.40	7.25	3.00	12.47	-35.18	-13.00	-22.18	V

CATM1 Band 4_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440	-43.45	5.63	3.00	10.82	-38.26	-13.00	-25.26	H
5160	-48.66	6.95	3.00	11.87	-43.74	-13.00	-30.74	H
3440	-36.20	5.63	3.00	10.82	-31.01	-13.00	-18.01	V
5160	-39.91	6.95	3.00	11.87	-34.99	-13.00	-21.99	V

CATM1 Band 4_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465	-42.63	5.64	3.00	10.85	-37.42	-13.00	-24.42	H
5197.5	-47.77	6.95	3.00	11.87	-42.85	-13.00	-29.85	H
3465	-36.90	5.64	3.00	10.85	-31.69	-13.00	-18.69	V
5197.5	-39.56	6.95	3.00	11.87	-34.64	-13.00	-21.64	V

CATM1 Band 4_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490	-43.07	5.66	3.00	10.91	-37.82	-13.00	-24.82	H
5235	-48.80	6.96	3.00	11.92	-43.84	-13.00	-30.84	H
3490	-35.30	5.66	3.00	10.91	-30.05	-13.00	-17.05	V
5235	-38.98	6.96	3.00	11.92	-34.02	-13.00	-21.02	V

CATM1 Band 4_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440	-43.46	5.63	3.00	10.82	-38.27	-13.00	-25.27	H
5160	-51.47	6.95	3.00	11.87	-46.55	-13.00	-33.55	H
3440	-39.96	5.63	3.00	10.82	-34.77	-13.00	-21.77	V
5160	-42.91	6.95	3.00	11.87	-37.99	-13.00	-24.99	V

CATM1 Band 4_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-46.41	5.64	3.00	10.85	-41.20	-13.00	-28.20	H
5197.5	-51.94	6.95	3.00	11.87	-47.02	-13.00	-34.02	H
3465.0	-37.76	5.64	3.00	10.85	-32.55	-13.00	-19.55	V
5197.5	-44.88	6.95	3.00	11.87	-39.96	-13.00	-26.96	V

CATM1 Band 4_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-45.99	5.66	3.00	10.91	-40.74	-13.00	-27.74	H
5235.0	-49.89	6.96	3.00	11.92	-44.93	-13.00	-31.93	H
3490.0	-37.80	5.66	3.00	10.91	-32.55	-13.00	-19.55	V
5235.0	-43.67	6.96	3.00	11.92	-38.71	-13.00	-25.71	V

CATM1 Band 5_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-39.25	4.87	3.00	9.57	-34.55	-13.00	-21.55	H
2487.00	-46.83	5.30	3.00	7.99	-44.14	-13.00	-31.14	H
1658.00	-35.62	4.87	3.00	9.57	-30.92	-13.00	-17.92	V
2487.00	-36.26	5.30	3.00	7.99	-33.57	-13.00	-20.57	V

CATM1 Band 5_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-38.54	4.91	3.00	9.59	-33.86	-13.00	-20.86	H
2509.50	-47.07	5.33	3.00	7.81	-44.59	-13.00	-31.59	H
1673.00	-35.69	4.91	3.00	9.59	-31.01	-13.00	-18.01	V
2509.50	-38.54	5.33	3.00	7.81	-36.06	-13.00	-23.06	V

CATM1 Band 5_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-39.54	4.92	3.00	10.07	-34.39	-13.00	-21.39	H
2532.00	-47.17	5.33	3.00	7.66	-44.84	-13.00	-31.84	H
1688.00	-34.63	4.92	3.00	10.07	-29.48	-13.00	-16.48	V
2532.00	-38.45	5.33	3.00	7.66	-36.12	-13.00	-23.12	V

TRF-4-E-154 A/0

Guangzhou LCS Compliance Testing Laboratory Ltd.
 Add: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
 Tel: +(86) 020-39166689 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
 Scan code to check authenticity

CATM1 Band 5_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-43.16	4.87	3.00	9.57	-38.46	-13.00	-25.46	H
2487.00	-49.84	5.30	3.00	7.99	-47.15	-13.00	-34.15	H
1658.00	-38.52	4.87	3.00	9.57	-33.82	-13.00	-20.82	V
2487.00	-41.50	5.30	3.00	7.99	-38.81	-13.00	-25.81	V

CATM1 Band 5_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-41.76	4.91	3.00	9.59	-37.08	-13.00	-24.08	H
2509.50	-47.78	5.33	3.00	7.81	-45.30	-13.00	-32.30	H
1673.00	-38.11	5.92	3.00	9.59	-34.44	-13.00	-21.44	V
2509.50	-41.80	6.34	3.00	7.81	-40.33	-13.00	-27.33	V

CATM1 Band 5_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-41.55	4.92	3.00	10.07	-36.40	-13.00	-23.40	H
2532.00	-46.70	5.33	3.00	7.66	-44.37	-13.00	-31.37	H
1688.00	-36.06	4.92	3.00	10.07	-30.91	-13.00	-17.91	V
2532.00	-41.07	5.33	3.00	7.66	-38.74	-13.00	-25.74	V

CATM1 Band 66_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-43.76	6.94	3.00	12.47	-38.23	-13.00	-25.23	H
5160.0	-45.08	7.80	3.00	14.34	-38.54	-13.00	-25.54	H
3440.0	-36.65	6.94	3.00	12.47	-31.12	-13.00	-18.12	V
5160.0	-41.53	7.80	3.00	14.34	-34.99	-13.00	-21.99	V

CATM1 Band 66_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-43.07	7.01	3.00	13.14	-36.94	-13.00	-23.94	H
5235.0	-45.73	7.87	3.00	14.04	-39.56	-13.00	-26.56	H
3490.0	-36.27	7.01	3.00	13.14	-30.14	-13.00	-17.14	V
5235.0	-41.08	7.87	3.00	14.04	-34.91	-13.00	-21.91	V

CATM1 Band 66_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540.0	-41.66	7.14	3.00	12.00	-36.80	-13.00	-23.80	H
5310.0	-48.44	7.95	3.00	13.68	-42.71	-13.00	-29.71	H
3540.0	-33.85	7.14	3.00	12.00	-28.99	-13.00	-15.99	V
5310.0	-39.60	7.95	3.00	13.68	-33.87	-13.00	-20.87	V

TRF-4-E-154 A/0

Guangzhou LCS Compliance Testing Laboratory Ltd.
 Add: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
 Tel: +(86) 020-39166689 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
 Scan code to check authenticity

CATM1 Band 66_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-45.73	6.94	3.00	12.47	-40.20	-13.00	-27.20	H
5160.0	-48.36	7.80	3.00	14.34	-41.82	-13.00	-28.82	H
3440.0	-39.92	6.94	3.00	12.47	-34.39	-13.00	-21.39	V
5160.0	-44.18	7.80	3.00	14.34	-37.64	-13.00	-24.64	V

CATM1 Band 66_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-46.17	7.01	3.00	13.14	-40.04	-13.00	-27.04	H
5235.0	-51.55	7.87	3.00	14.04	-45.38	-13.00	-32.38	H
3490.0	-36.91	7.01	3.00	13.14	-30.78	-13.00	-17.78	V
5235.0	-43.87	7.87	3.00	14.04	-37.70	-13.00	-24.70	V

CATM1 Band 66_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3540.0	-43.67	7.14	3.00	12.00	-38.81	-13.00	-25.81	H
5310.0	-48.74	7.95	3.00	13.68	-43.01	-13.00	-30.01	H
3540.0	-36.45	7.14	3.00	12.00	-31.59	-13.00	-18.59	V
5310.0	-43.97	7.95	3.00	13.68	-38.24	-13.00	-25.24	V


Notes: All channel bandwidth were tested,the report recorded the worst data.

4.7 Frequency Stability under Temperature & Voltage Variations

LIMIT

According to FCC §2.1055, §22.355, §24.235, §27.54 and §90.213 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to TIA-603-E

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMW 500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on middle channel for LTE band 2, LTE band 4, LTE band 5, LTE Band 66; measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TRF-4-E-154 A/0

TEST RESULTS*Remark:*

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66; recorded worst case for each Channel Bandwidth of CATM1 Band 2, CATM1 Band 4, CATM1 Band 5, CATM1 Band 66.

LTE Band 2, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

CATM1 Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	-11	-0.006	±2.50	PASS
VN	20	-12	-0.006	±2.50	PASS
VH	20	13	0.007	±2.50	PASS
VN	-30	0	0.000	±2.50	PASS
VN	-20	-6	-0.003	±2.50	PASS
VN	-10	20	0.011	±2.50	PASS
VN	0	14	0.007	±2.50	PASS
VN	10	19	0.010	±2.50	PASS
VN	20	-15	-0.008	±2.50	PASS
VN	30	-19	-0.010	±2.50	PASS
VN	40	-18	-0.010	±2.50	PASS
VN	50	10	0.005	±2.50	PASS

LTE Band 2, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

CATM1 Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	8	0.004	±2.50	PASS
VN	20	12	0.006	±2.50	PASS
VH	20	-4	-0.002	±2.50	PASS
VN	-30	0	0.000	±2.50	PASS
VN	-20	11	0.006	±2.50	PASS
VN	-10	-16	-0.009	±2.50	PASS
VN	0	-5	-0.003	±2.50	PASS
VN	10	-7	-0.004	±2.50	PASS
VN	20	-12	-0.006	±2.50	PASS
VN	30	10	0.005	±2.50	PASS
VN	40	-4	-0.002	±2.50	PASS
VN	50	14	0.007	±2.50	PASS

LTE Band 4, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

CATM1 Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	-20	-0.011	±2.50	PASS
VN	20	-7	-0.004	±2.50	PASS
VH	20	22	0.013	±2.50	PASS
VN	-30	-42	-0.024	±2.50	PASS
VN	-20	-45	-0.026	±2.50	PASS
VN	-10	-16	-0.009	±2.50	PASS
VN	0	22	0.013	±2.50	PASS
VN	10	5	0.003	±2.50	PASS
VN	20	47	0.027	±2.50	PASS
VN	30	39	0.022	±2.50	PASS
VN	40	-48	-0.027	±2.50	PASS
VN	50	20	0.011	±2.50	PASS

LTE Band 4, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

CATM1 Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	19	0.011	±2.50	PASS
VN	20	-36	-0.021	±2.50	PASS
VH	20	-27	-0.015	±2.50	PASS
VN	-30	11	0.006	±2.50	PASS
VN	-20	24	0.014	±2.50	PASS
VN	-10	47	0.027	±2.50	PASS
VN	0	3	0.002	±2.50	PASS
VN	10	22	0.013	±2.50	PASS
VN	20	44	0.025	±2.50	PASS
VN	30	-14	-0.008	±2.50	PASS
VN	40	32	0.018	±2.50	PASS
VN	50	-27	-0.015	±2.50	PASS

LTE Band 5, QPSK, 1.4MHz bandwidth(worst case of all bandwidths)

CATM1 Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	-34	-0.041	±2.50	PASS
VN	20	9	0.011	±2.50	PASS
VH	20	14	0.017	±2.50	PASS
VN	-30	7	0.008	±2.50	PASS
VN	-20	-27	-0.033	±2.50	PASS
VN	-10	-10	-0.012	±2.50	PASS
VN	0	-4	-0.005	±2.50	PASS
VN	10	-46	-0.056	±2.50	PASS
VN	20	-5	-0.006	±2.50	PASS
VN	30	37	0.045	±2.50	PASS
VN	40	0	0.000	±2.50	PASS
VN	50	-11	-0.013	±2.50	PASS

LTE Band 5, 16QAM, 1.4MHz bandwidth(worst case of all bandwidths)

CATM1 Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	-21	-0.025	±2.50	PASS
VN	20	-17	-0.021	±2.50	PASS
VH	20	33	0.040	±2.50	PASS
VN	-30	34	0.041	±2.50	PASS
VN	-20	-12	-0.015	±2.50	PASS
VN	-10	50	0.061	±2.50	PASS
VN	0	-18	-0.022	±2.50	PASS
VN	10	34	0.041	±2.50	PASS
VN	20	-48	-0.058	±2.50	PASS
VN	30	-14	-0.017	±2.50	PASS
VN	40	-27	-0.033	±2.50	PASS
VN	50	24	0.029	±2.50	PASS

LTE Band 66, 1.4MHz bandwidth, QPSK (worst case of all bandwidths)

CATM1 Band 66					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	12	0.007	2.50	PASS
VN	20	13	0.007	2.50	PASS
VH	20	68	0.039	2.50	PASS
VN	-30	11	0.006	2.50	PASS
VN	-20	17	0.010	2.50	PASS
VN	-10	8	0.005	2.50	PASS
VN	0	52	0.030	2.50	PASS
VN	10	12	0.007	2.50	PASS
VN	20	4	0.002	2.50	PASS
VN	30	67	0.038	2.50	PASS
VN	40	4	0.002	2.50	PASS
VN	50	81	0.046	2.50	PASS

LTE Band 66, 1.4MHz bandwidth, 16QAM (worst case of all bandwidths)

CATM1 Band 66					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	20	9	0.005	2.50	PASS
VN	20	26	0.015	2.50	PASS
VH	20	42	0.024	2.50	PASS
VN	-30	67	0.038	2.50	PASS
VN	-20	24	0.014	2.50	PASS
VN	-10	47	0.027	2.50	PASS
VN	0	20	0.011	2.50	PASS
VN	10	18	0.010	2.50	PASS
VN	20	40	0.023	2.50	PASS
VN	30	89	0.051	2.50	PASS
VN	40	73	0.042	2.50	PASS
VN	50	82	0.047	2.50	PASS

5 Test Setup Photos of the EUT

Pleaserefer to separated files for Test Setup Photos of the EUT.

6 External Photos of the EUT

Pleaserefer to separated files for External Photos of the EUT.

7 Internal Photos of the EUT

Pleaserefer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----