

FCC TEST REPORT

FCC ID: 2AY3H-AK820PRO

Report No. : SSP23120221-2E

Prepared For : Shenzhen Ajazz Tongchuang Electronic Technology Co., Ltd.

Product Name : Mechanical keyboard

Model Name : AJAZZ AK820PRO

FCC Rule : FCC Part 15.249

Date of Issue : 2024-03-19

Prepared By : Shenzhen CCUT Quality Technology Co., Ltd.



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.: +86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated
without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Shenzhen Ajazz Tongchuang Electronic Technology Co., Ltd. 2104-1, Block A, CIMC Low Orbit Satellite Internet of Things Industrial Park, Dongkeng Community, Fenghuang Street, Guangming District, Shenzhen, Address of Applicant.....: Guangdong, China	
Manufacturer:	Shenzhen Ajazz Tongchuang Electronic Technology Co., Ltd. 2104-1, Block A, CIMC Low Orbit Satellite Internet of Things Industrial Park, Dongkeng Community, Fenghuang Street, Guangming District, Shenzhen, Address of Manufacturer.....: Guangdong, China	
Product Name:	Mechanical keyboard	
Brand Name:	AJAZZ	
Main Model:	AJAZZ AK820PRO	
Series Models:	AK820 MAX, AK75PRO, AK820	
Test Standard:	FCC Part 15 Subpart C ANSI C63.10-2013	
Date of Test	2024-01-05 to 2024-01-18	
Test Result:	PASS	
Tested Engineer	<u>Colin Chen</u> (Colin Chen)	
Project Manager:	<u>Lieber Ouyang</u> (Lieber Ouyang)	
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)	
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.		

CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	8
2. Summary of Test Results	9
3. Antenna Requirement.....	10
3.1 Standard and Limit.....	10
3.2 Test Result	10
4. Conducted Emissions	11
4.1 Standard and Limit.....	11
4.2 Test Procedure.....	11
4.3 Test Data and Results	12
5. Radiated Emissions	15
5.1 Standard and Limit.....	15
5.2 Test Procedure.....	15
5.3 Test Data and Results	17
6. Out of Band Emissions.....	22
6.1 Standard and Limit.....	22
6.2 Test Procedure.....	22
6.3 Test Data and Results	22
7. Occupied Bandwidth	27
7.1 Standard and Limit.....	27
7.2 Test Procedure.....	27
7.3 Test Data and Results	27

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-03-19	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Mechanical keyboard
Trade Name:	AJAZZ
Main Model:	AJAZZ AK820PRO
Series Models:	AK820 MAX, AK75PRO, AK820
Rated Voltage:	DC 3.7V by Battery, USB 5V Charging
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	2.4G RF
Operating Frequency:	2402 ~ 2480 MHz
Max. Field Strength:	86.29dBuV/m
Quantity of Channel:	16
Channel Separation:	2MHz
Modulation:	GFSK
Antenna Gain:	2.41dBi
Type of Antenna:	PCB Antenna
Type of Device:	☒ Portable Device ☐ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Lowest Channel	2402MHz	
TM2	Middle Channel	2440MHz	
TM3	Highest Channel	2480MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2023-10-21	2024-10-20
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2023-07-31	2024-07-30
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2023-07-31	2024-07-30
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2023-07-31	2024-07-30
Amplifier	SCHWARZBECK	BBV 9743B	00251	2023-07-31	2024-07-30
Amplifier	HUABO	YXL0518-2.5-45	--	2023-07-31	2024-07-30
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2023-07-31	2024-07-30
Loop Antenna	DAZE	ZN30900C	21104	2023-08-07	2024-08-06
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2023-08-07	2024-08-06
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2023-08-07	2024-08-06
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2023-08-07	2024-08-06
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2023-07-31	2024-07-30

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.249(a)&(d)	Radiated Emissions	Passed
FCC Part 15.249(d)	Out of Band Emissions	Passed
FCC Part 15.215(c)	Occupied Bandwidth	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an PCB antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.


4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions

Tested Mode:	TM1
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2445	31.50	9.67	41.17	61.94	-20.77	QP	P	
2	0.2445	15.44	9.67	25.11	51.94	-26.83	AVG	P	
3	0.4605	27.08	9.95	37.03	56.68	-19.65	QP	P	
4	0.4605	14.26	9.95	24.21	46.68	-22.47	AVG	P	
5 *	0.7125	32.81	9.62	42.43	56.00	-13.57	QP	P	
6	0.7125	15.96	9.62	25.58	46.00	-20.42	AVG	P	
7	1.4280	26.70	10.03	36.73	56.00	-19.27	QP	P	
8	1.4280	12.63	10.03	22.66	46.00	-23.34	AVG	P	
9	3.7770	23.93	10.14	34.07	56.00	-21.93	QP	P	
10	3.7770	10.79	10.14	20.93	46.00	-25.07	AVG	P	
11	5.6490	23.89	10.23	34.12	60.00	-25.88	QP	P	
12	5.6490	11.97	10.23	22.20	50.00	-27.80	AVG	P	


Test Plots and Data of Conducted Emissions

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1905	31.67	8.98	40.65	64.01	-23.36	QP	P	
2	0.1905	15.68	8.98	24.66	54.01	-29.35	AVG	P	
3	0.2850	31.66	9.71	41.37	60.67	-19.30	QP	P	
4	0.2850	14.38	9.71	24.09	50.67	-26.58	AVG	P	
5 *	0.7170	35.85	9.86	45.71	56.00	-10.29	QP	P	
6	0.7170	18.69	9.86	28.55	46.00	-17.45	AVG	P	
7	1.3740	29.97	10.03	40.00	56.00	-16.00	QP	P	
8	1.3740	14.84	10.03	24.87	46.00	-21.13	AVG	P	
9	2.3415	28.49	10.07	38.56	56.00	-17.44	QP	P	
10	2.3415	13.60	10.07	23.67	46.00	-22.33	AVG	P	
11	5.5995	30.23	10.24	40.47	60.00	-19.53	QP	P	
12	5.5995	16.06	10.24	26.30	50.00	-23.70	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


5.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.249 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	52.5753	26.76	-9.05	17.71	40.00	-22.29	QP	100	11	P	
2	127.2176	29.24	-10.16	19.08	43.50	-24.42	QP	100	11	P	
3	234.9909	33.24	-10.30	22.94	46.00	-23.06	QP	100	312	P	
4	279.0436	34.83	-8.88	25.95	46.00	-20.05	QP	100	282	P	
5	401.8385	30.53	-5.84	24.69	46.00	-21.31	QP	100	242	P	
6 *	785.0935	27.95	1.99	29.94	46.00	-16.06	QP	100	11	P	

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	125.0066	29.21	-10.31	18.90	43.50	-24.60	QP	100	0	P	
2	176.2686	27.59	-10.32	17.27	43.50	-26.23	QP	100	7	P	
3	229.2931	28.95	-10.68	18.27	46.00	-27.73	QP	100	307	P	
4	279.0436	28.54	-8.88	19.66	46.00	-26.34	QP	100	135	P	
5	580.7026	28.73	-1.73	27.00	46.00	-19.00	QP	100	226	P	
6 *	787.8513	31.33	2.07	33.40	46.00	-12.60	QP	100	348	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (2402MHz)							
2402	107.19	-20.90	86.29	114	-27.71	H	PK
2402	90.25	-20.90	69.35	94	-24.65	H	AV
4804	76.46	-14.72	61.74	74	-12.26	H	PK
4804	61.88	-14.72	47.16	54	-6.84	H	AV
7208	63.64	-8.41	55.23	74	-18.77	H	PK
7208	49.52	-8.41	41.11	54	-12.89	H	AV
2402	98.28	-20.90	77.38	114	-36.62	V	PK
2402	81.75	-20.90	60.85	94	-33.15	V	AV
4804	74.87	-14.72	60.15	74	-13.85	V	PK
4804	58.45	-14.72	43.73	54	-10.27	V	AV
7208	64.18	-8.41	55.77	74	-18.23	V	PK
7208	47.16	-8.41	38.75	54	-15.25	V	AV
Middle Channel (2440MHz)							
2440	102.14	-20.61	81.53	114	-32.47	H	PK
2440	89.86	-20.61	69.25	94	-24.75	H	AV
4880	77.76	-14.64	63.12	74	-10.88	H	PK
4880	59.55	-14.64	44.91	54	-9.09	H	AV
7320	62.15	-8.28	53.87	74	-20.13	H	PK
7320	45.71	-8.28	37.43	54	-16.57	H	AV
2440	97.34	-20.61	76.73	114	-37.27	V	PK
2440	85.56	-20.61	64.95	94	-29.05	V	AV
4880	76	-14.64	61.36	74	-12.64	V	PK
4880	57.54	-14.64	42.9	54	-11.1	V	AV
7320	63.02	-8.28	54.74	74	-19.26	V	PK
7320	48.8	-8.28	40.52	54	-13.48	V	AV

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Highest Channel (2480MHz)							
2480	105.96	-20.53	85.43	114	-28.57	H	PK
2480	87.86	-20.53	67.33	94	-26.67	H	AV
4960	78.28	-14.53	63.75	74	-10.25	H	PK
4960	59.24	-14.53	44.71	54	-9.29	H	AV
7440	63.06	-8.13	54.93	74	-19.07	H	PK
7440	49.75	-8.13	41.62	54	-12.38	H	AV
2480	95.59	-20.53	75.06	114	-38.94	V	PK
2480	78.51	-20.53	57.98	94	-36.02	V	AV
4960	78.03	-14.53	63.5	74	-10.5	V	PK
4960	59.67	-14.53	45.14	54	-8.86	V	AV
7440	62.99	-8.13	54.86	74	-19.14	V	PK
7440	50.12	-8.13	41.99	54	-12.01	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.


6. Out of Band Emissions

6.1 Standard and Limit

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results


Based on all tested data, the EUT complied with the FCC Part 15.249 standard limit, and with the worst case as below:

Remark: Level = Reading + Factor; Margin = Level - Limit

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Test Plots and Data of Out of Band Emissions


Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Test Band-edge:	Lowest band-edge
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	62.80	-21.34	41.46	74.00	-32.54	peak	150	91	P	
2	2310.000	43.45	-21.34	22.11	54.00	-31.89	AVG	150	91	P	
3	2390.000	63.02	-20.96	42.06	74.00	-31.94	peak	150	91	P	
4	2390.000	44.08	-20.96	23.12	54.00	-30.88	AVG	150	91	P	
5	2402.000	107.19	-20.90	86.29	114.00	-27.71	peak	150	58	P	
6 *	2402.000	90.25	-20.90	69.35	94.00	-24.65	AVG	150	58	P	

Test Plots and Data of Out of Band Emissions


Tested Mode:	TM1
Test Antenna Polarization:	Vertical
Test Band-edge:	Lowest band-edge
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	56.93	-21.34	35.59	74.00	-38.41	peak	150	208	P	
2	2310.000	43.44	-21.34	22.10	54.00	-31.90	AVG	150	208	P	
3	2390.000	56.47	-20.96	35.51	74.00	-38.49	peak	150	251	P	
4 *	2390.000	44.05	-20.96	23.09	54.00	-30.91	AVG	150	251	P	
5	2402.000	98.28	-20.90	77.38	114.00	-36.62	peak	150	196	P	
6	2402.000	81.75	-20.90	60.85	94.00	-33.15	AVG	150	196	P	

Test Plots and Data of Out of Band Emissions


Tested Mode:	TM3
Test Antenna Polarization:	Horizontal
Test Band-edge:	Highest band-edge
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2480.000	105.96	-20.53	85.43	114.00	-28.57	peak	150	74	P	
2	2480.000	87.86	-20.53	67.33	94.00	-26.67	AVG	150	74	P	
3 *	2483.500	87.15	-20.51	66.64	74.00	-7.36	peak	150	74	P	
4	2483.500	46.28	-20.51	25.77	54.00	-28.23	AVG	150	74	P	
5	2500.000	62.95	-20.43	42.52	74.00	-31.48	peak	150	74	P	
6	2500.000	44.06	-20.43	23.63	54.00	-30.37	AVG	150	74	P	

Test Plots and Data of Out of Band Emissions

Tested Mode:	TM3
Test Antenna Polarization:	Vertical
Test Band-edge:	Highest band-edge
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2480.000	95.59	-20.53	75.06	114.00	-38.94	peak	150	342	P	
2	2480.000	78.51	-20.53	57.98	94.00	-36.02	AVG	150	342	P	
3 *	2483.500	76.57	-20.51	56.06	74.00	-17.94	peak	150	342	P	
4	2483.500	44.53	-20.51	24.02	54.00	-29.98	AVG	150	342	P	
5	2498.000	44.23	-20.44	23.79	54.00	-30.21	AVG	150	182	P	
6	2500.000	56.67	-20.43	36.24	74.00	-37.76	peak	150	182	P	

7. Occupied Bandwidth

7.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

7.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 2MHz, centered on a transmitting channel

RBW $\geq 1\%$ 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.




Test Setup Block Diagram

7.3 Test Data and Results


Test Channel	Test Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Lowest Channel	2402MHz	1.098	1.2692
Middle Channel	2440MHz	1.106	1.7128
Highest Channel	2480MHz	1.658	1.7845

Test Plots of Occupied Bandwidth


2402MHz



2440MHz



2480MHz



***** END OF REPORT *****