

Test Report

Report No.: MTi220214011-08E2

Date of issue: May 22, 2022

Applicant: YFW Technology Co., Ltd.

Product: 3 in 1 wireless charger

Model(s): YFW-W008, YFW-F167, YFW-W009, YFW-F168,
YFW-F169, YFW-F170, YFW-F171, YFW-F172,
YFW-F173, YFW-F174

FCC ID: 2AY3K-YFWW008

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions


1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Description of support units	6
2	Test facilities and accreditations	7
2.1	Test laboratory	7
3	List of test equipment	7
4	Test result.....	8
4.2	Test setup	9
4.3	Test Procedures.....	9
4.4	Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01.....	10
4.5	Test results	11
	Photographs of the Test Setup.....	12
	Photographs of the EUT	12


Test Result Certification	
Applicant:	YFW Technology Co., Ltd.
Address:	Floor 5, Building 2, Guangxi Industrial Zone, Longhua Industrial West Road, Shenzhen, China
Manufacturer:	Shenzhen Yongfengwang Technology Co., Ltd.
Address:	3rd floor, building B, Shengjia Industrial Park, 154 Huating Road, Dalang street, Longhua District, Shenzhen
Product description	
Product name:	3 in 1 wireless charger
Trademark:	N/A
Model name:	YFW-W008
Serial Model:	YFW-F167, YFW-W009, YFW-F168, YFW-F169, YFW-F170, YFW-F171, YFW-F172, YFW-F173, YFW-F174
Standards:	FCC CFR 47 PART 1, § 1.1310
Test method:	KDB 680106 v03r01
Date of Test	
Date of test:	2022-02-22 ~ 2022-05-11
Test result:	Pass

Test Engineer :



(Gary Lu)

Reviewed By :



(Leon Chen)

Approved By :



(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	3 in 1 wireless charger
Model name:	YFW-W008
Series Model:	YFW-F167, YFW-W009, YFW-F168, YFW-F169, YFW-F170, YFW-F171, YFW-F172, YFW-F173, YFW-F174
Model difference:	All the models are the same circuit and module, except the model's name
Electrical rating:	Input: DC 9V 3A/12V 1.5A Output: DC 9V 1.2A/5V 0.6A/5V 1A
Accessories:	USB-A to USB-C cable (1m)
Hardware version:	BRN-SC9608-YFW
Software version:	V21
EUT serial number:	MTi220214011-08E1S1001
RF specification:	
Operation frequency:	Transmitter1: 115 kHz – 205 kHz Transmitter2: 326.5kHz
Modulation type:	ASK
Antenna type:	Coil Antenna

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode 1	Wireless Output(5W+3W)
Mode 2	Wireless Output(7.5W+3W)
Mode 3	Wireless Output(10W+3W)
Mode 4	Wireless Output(15W+3W)
Mode 5	Stand-by mode
The test data only show worst test mode: Mode 4	

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Mobile phone	OPPO Find X3	/	OPPO
Adapter	XY-PQ018E1	/	Dongguan Xu Yuan Electronic Technology Co., Ltd
Watch	/	/	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Test facilities and accreditations

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

3 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E115	Electric and Magnetic Field Probe – Analyzer	Narda	EHP-200A	101166	2021/06/02	2022/06/01

4 Test result

4.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

4.2 Test setup



4.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with the center of the probe at a distance of 15 cm surrounding the device and 20 cm above the top surface of the primary/client pair.
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 v03r01.

4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01

Requirement	Device
1. Power transfer frequency is less than 1 MHz.	Yes. The operating frequencies are: Transmitter 1: 115 kHz – 205 kHz Transmitter 2: 326.5 kHz
2. Output power from each primary coil is less than or equal to 15 watts	Yes. The maximum output power are: Transmitter 1: 15 W Transmitter 2: 3W
3. The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes. The EUT has two source primary coils, the coil pairs may be powered on at the same time
4. Client device is placed directly in contact with the transmitter.	Yes. The client devices are placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. Mobile exposure conditions only.
6. The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes. See the test result in item 4.5.

4.5 Test results

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

Antenna	Probe Position	E –field (V/m)			H–field (A/m)		
		Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
1	Z axis	1.423	614	0.23%	0.0495	1.63	4.10%
	Left	0.468			0.0474		
	Right	1.0572			0.0567		
	Front	1.2888			0.0465		
	Rear	0.7242			0.0482		
	Bottom	0.7405			0.0669		

Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Antenna	Probe Position	E –field (V/m)			H–field (A/m)		
		Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
1	Z axis	1.4109	614	0.23%	0.0461	1.63	3.71%
	Left	0.4852			0.0446		
	Right	1.0414			0.0449		
	Front	1.3039			0.0456		
	Rear	0.7164			0.0418		
	bottom	0.7279			0.0605		

Test condition 3: Mode 4 operating mode with client device (99 % battery status of client device)

Antenna	Probe Position	E –field (V/m)			H–field (A/m)		
		Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
1	Z axis	1.4214	614	0.23%	0.0482	1.63	3.56%
	Left	0.4501			0.0462		
	Right	1.0552			0.0446		
	Front	1.2791			0.0449		
	Rear	0.7219			0.0409		
	bottom	0.7367			0.0581		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

----End of Report----