FCC TEST REPORT

FCC ID: 2AY59-GSPS4

On Behalf of

CLD Distribution S.A.

Wireless Game Controller

Model No.: GSPS4-BK, GSPS4-WH, GSPS4-BL, GSPS4-RD

Prepared for	:	CLD Distribution S.A.
Address	:	Rue du Grand Champ 14, 5380 Fernelmont, Belgium

Prepared By	:	Shenzhen Alpha Product Testing Co., Ltd.
Address	:	Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number	:	A2101045-C01-R01
Date of Receipt	:	January 28, 2021
Date of Test	:	January 28, 2021 – March 02, 2021
Date of Report	:	March 02, 2021
Version Number	:	V0

TABLE OF CONTENTS

Description Page

1. Summary Of Standards And Results 6
1.1. Description of Standards and Results 6
2. General Information 7
2.1. Description of Device (EUT) 7
2.2. Accessories of Device (EUT) 8
2.3. Tested Supporting System Details 8
2.4. Block Diagram of connection between EUT and simulators 8
2.5. Test Mode Description 8
2.6. Test Conditions 9
2.7. Test Facility 9
2.8. Measurement Uncertainty 9
2.9. Test Equipment List 10
3. Maximum Peak Output Power 11
3.1. Limit 11
3.2. Test Procedure 11
3.3. Test Setup 11
3.4. Test Result 11
4. Bandwidth 12
4.1. Limit 12
4.2. Test Procedure 12
4.3. Test Result 12
5. Carrier Frequency Separation 17
5.1. Limit 17
5.2. Test Procedure 17
5.3. Test Result 17
6. Number Of Hopping Channel 19
6.1. Limit 19
6.2. Test Procedure 19
6.3. Test Result 19
7. Dwell Time 20
7.1. Test limit 20
7.2. Test Procedure 20
7.3. Test Result 20
8. Radiated emissions 23
8.1. Limit 23
8.2. Block Diagram of Test setup 24
8.3. Test Procedure 25
8.4. Test Result 25
9. Band Edge Compliance 29

9.1. Block Diagram of Test Setup 29
9.2. Limit 29
9.3. Test Procedure 29
9.4. Test Result 29
10. Power Line Conducted Emissions 40
10.1. Block Diagram of Test Setup 40
10.2. Limit 40
10.3. Test Procedure 40
10.4. Test Result 40
11. Antenna Requirements 42
11.1. Limit 42
11.2. Result 42
12. Test Setup Photo 43
12.1. Photos of Radiated Emission Test (In Semi Anechoic Chamber 30MHz~1GHz) 43
12.2. Photos of Radiated Emission Test (In Semi Anechoic Chamber above 1GHz) 43
12.3. Photos of Conducted disturbance at mains terminals test 44
13. Photographs Of The EUT 45

TEST REPORT DECLARATION

Applicant	:	CLD Distribution S.A.
Address	:	Rue du Grand Champ 14, 5380 Fernelmont, Belgium
Manufacturer	:	Shenzhen CHT Technology Co., Ltd.
Address	:	Building L, Shengguang Industrial Park, No. 152 Shajing DongHuan Road, XinQiao Street, Bao'An District, Shenzhen, China
EUT Description	:	Wireless Game Controller
		(A) Model No. : GSPS4-BK, GSPS4-WH, GSPS4-BL, GSPS4-RD
		(B) Trademark : DRAGON WAR

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....…..:	Reak Yang Project Engineer	.....
Approved by (name + signature)…....:	Simple Guan Project Manager	.....
Date of issue…… ……..:	March 02, 2021	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	March 02, 2021	Initial released Issue	Reak Yang

1. Summary Of Standards And Results

1.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. General Information

2.1.Description of Device (EUT)

Description	:	Wireless Game Controller
Trademark	:	DRAGON WAR
Model Number	:	GSPS4-BK, GSPS4-WH, GSPS4-BL, GSPS4-RD
DIFF.	:	All models are the same, except the appearance color, the data in this report is based on model: GSPS4-BK.
Test Voltage	:	DC 3.7V From Battery, DC 5V From USB Port
BT		
Radio Technology	:	Bluetooth (BR+EDR)
Operation frequency	:	2402-2480MHz
Channel No.	:	79 Channels
Modulation type	:	GFSK, π/4 DQPSK
Antenna Type	:	Internal antenna, Maximum Gain is 1dBi.
Software version	:	V1.0
Hardware version	:	V1.0

2.2.Accessories of Device (EUT)

Accessories1	:	N/A
Manufacturer	:	N/A
Model	:	N/A
Ratings	:	N/A

2.3.Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	DELL	Latitude 3490	--	SDOC

2.4.Block Diagram of connection between EUT and simulators



2.5.Test Mode Description

Tested mode, channel, and data rate information		
Mode	**Channel**	**Frequency (MHz)**
GFSK	Low :CH0	2402
	Middle: CH39	2441
	High: CH78	2480
π/4 DQPSK	Low :CH0	2402
	Middle: CH39	2441
	High: CH78	2480

2.6.Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7.Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961
Designation Number: CN1236
July 15, 2019 Certificated by IC
Registration Number: CN0085

2.8.Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.16dB(Polarize: H)
	4.13dB(Polarize: V)
Uncertainty for radio frequency	5.4×10-8
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9.Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2020.09.02	1Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2020.09.02	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2020.09.02	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-102082-Wa	2020.09.02	1Year
Receiver	R&S	ESCI	101165	2020.09.02	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2020.04.12	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2019.09.07	2Year
Cable	Resenberger	N/A	No.1	2020.09.02	1Year
Cable	Resenberger	N/A	No.2	2020.09.02	1Year
Cable	Resenberger	N/A	No.3	2020.09.02	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2020.09.02	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2020.09.02	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2020.09.02	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2020.09.02	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2020.09.02	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2019.09.07	2 Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2020.09.02	1 Year
Power Meter	Agilent	E9300A	MY41496625	2020.09.02	1 Year
Power Sensor	DARE	RPR3006W	15100041SNO91	2020.09.02	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-880	100631	2020.09.02	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2020.09.02	1 Year

3. Maximum Peak Output Power

3.1.Limit

Please refer section15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2.Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the average power detection.

3.3.Test Setup



3.4.Test Result

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	1.907	30	Pass
NVNT	1-DH1	2441	3.991	30	Pass
NVNT	1-DH1	2480	4.891	30	Pass
NVNT	2-DH1	2402	2.027	21	Pass
NVNT	2-DH1	2441	4.304	21	Pass
NVNT	2-DH1	2480	5.06	21	Pass

4. Bandwidth

4.1.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.Test Result

Condition	Mode	Frequency (MHz)	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	0.7947	0.782	/	Pass
NVNT	1-DH1	2441	0.7999	0.7768	/	Pass
NVNT	1-DH1	2480	0.7953	0.8348	/	Pass
NVNT	2-DH1	2402	1.1585	1.201	/	Pass
NVNT	2-DH1	2441	1.1661	1.2054	/	Pass
NVNT	2-DH1	2480	1.1453	1.202	/	Pass

OBW NVNT 1-DH1 2402MHz Ant1



-20 dB BW NVNT 1-DH1 2402MHz Ant1



OBW NVNT 1-DH1 2440MHz Ant1



-20 dB BW NVNT 1-DH1 2440MHz Ant1



Date: 5.FEB.2021 03:21:46

OBW NVNT 1-DH1 2480MHz Ant1



Date: 5.FEB.2021 03:22:18

-20 dB BW NVNT 1-DH1 2480MHz Ant1



Date: 5.FEB.2021 03:22:22

OBW NVNT 2-DH1 2402MHz Ant1



Date: 5.FEB.2021 03:42:01

-20 dB BW NVNT 2-DH1 2402MHz Ant1



Date: 5.FEB.2021 03:42:04

OBW NVNT 2-DH1 2440MHz Ant1



Date: 5.FEB.2021 03:44:03

-20 dB BW NVNT 2-DH1 2440MHz Ant1



Date: 5.FEB.2021 03:44:06

OBW NVNT 2-DH1 2480MHz Ant1



Date: 5.FEB.2021 03:45:15

-20 dB BW NVNT 2-DH1 2480MHz Ant1



Date: 5.FEB.2021 03:45:18

5. Carrier Frequency Separation

5.1.Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 20kHz RBW and 62kHz VBW.

5.3.Test Result

Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	2439.998	2441.008	1.01	0.557	Pass
NVNT	2-DH1	2439.998	2441	1.002	0.804	Pass

CFS NVNT 1-DH1 2441MHz



CFS NVNT 2-DH1 2441MHz



6. Number Of Hopping Channel

6.1.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3.Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz



Hopping No. NVNT 2-DH1 2441MHz



7. Dwell Time

7.1.Test limit

Please refer section15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2.Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3.Test Result

PASS.

Condition	Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.422	135.04	31600	400	Pass
NVNT	1-DH3	2441	1.678	268.48	31600	400	Pass
NVNT	1-DH5	2441	2.926	312.11	31600	400	Pass
NVNT	2-DH1	2441	0.379	121.28	31600	400	Pass
NVNT	2-DH3	2441	1.631	260.96	31600	400	Pass
NVNT	2-DH5	2441	2.872	306.35	31600	400	Pass

Note: 1 A period time = 0.4 (s) * 79 = 31.6(s)

2 DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time

DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time

DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time

Dwell NVNT 1-DH1 2441MHz



Dwell NVNT 1-DH3 2441MHz



Dwell NVNT 1-DH5 2441MHz



Dwell NVNT 2-DH1 2441MHz



Date: 5.FEB.2021 03:49:45

Dwell NVNT 2-DH3 2441MHz



Date: 5.FEB.2021 03:55:45

Dwell NVNT 2-DH5 2441MHz



Date: 5.FEB.2021 03:56:35

8. Radiated emissions

8.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2.Block Diagram of Test setup

8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3.Test Procedure

(1) EUT was placed on a non-metallic table, 0.8 m high above ground for below 1GHz testing and 1.5m high for above1GHz testing inside a semi-anechoic chamber.
(2) Setup EUT and simulator as shown in section 1.4 and 6.1
(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
(a) Change work frequency or channel of device if practicable.
(b) Change modulation type of device if practicable.
(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.
(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4.Test Result

We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS			
EUT Description	Wireless Game Controller	**Model No.**	GSPS4-BK
Temperature	24℃	**Humidity**	56%
Pol	Vertical	**Test date**	2021/03/02
Test Voltage	DC 5V From USB Port	**Test mode**	GFSK (2480MHz)



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Factor dB/m	Detector
1*	126.151 MHz	43.5	25.1	-18.4	15.1	PK
2*	137.791 MHz	43.5	23.9	-19.6	15.7	PK
3*	166.528 MHz	43.5	25.2	-18.3	16.4	PK
4*	258.071 MHz	46.0	29.3	-16.7	15.1	PK
5*	322.697 MHz	46.0	27.2	-18.8	15.3	PK
6*	407.936 MHz	46.0	30.7	-15.3	17.3	PK

Pol	Horizontal



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Factor dB/m	Detector
1	126.168 MHz	43.5	31.6	-11.9	15.1	QP
2*	113.784 MHz	43.5	27.9	-15.6	14.0	PK
3*	137.791 MHz	43.5	36.3	-7.2	15.7	PK
4*	165.194 MHz	43.5	27.7	-15.8	16.4	PK
5*	191.990 MHz	43.5	33.7	-9.8	13.6	PK
6*	258.071 MHz	46.0	38.1	-7.9	15.1	PK

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of GFSK (2480MHz) was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.55	V	33.95	10.18	34.26	54.42	74	-19.58	PK
4804	35.74	V	33.95	10.18	34.26	45.61	54	-8.39	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.68	H	33.95	10.18	34.26	52.55	74	-21.45	PK
4804	35.57	H	33.95	10.18	34.26	45.44	54	-8.56	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	45.82	V	33.93	10.2	34.29	55.66	74	-18.34	PK
4882	35.53	V	33.93	10.2	34.29	45.37	54	-8.63	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	44.89	H	33.93	10.2	34.29	54.73	74	-19.27	PK
4882	33.32	H	33.93	10.2	34.29	43.16	54	-10.84	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	44.16	V	33.98	10.22	34.25	54.11	74	-19.89	PK
4960	35.58	V	33.98	10.22	34.25	45.53	54	-8.47	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	46.99	H	33.98	10.22	34.25	56.94	74	-17.06	PK
4960	35.91	H	33.98	10.22	34.25	45.86	54	-8.14	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Test Mode: π/4 DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.25	V	33.95	10.18	34.26	54.12	74	-19.88	PK
4804	35.07	V	33.95	10.18	34.26	44.94	54	-9.06	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.13	H	33.95	10.18	34.26	52.00	74	-22.00	PK
4804	35.05	H	33.95	10.18	34.26	44.92	54	-9.08	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX Mid									
4882	45.71	V	33.93	10.2	34.25	55.59	74	-18.41	PK
4882	35.58	V	33.93	10.2	34.25	45.46	54	-8.54	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	45.20	H	33.93	10.2	34.29	55.04	74	-18.96	PK
4882	33.74	H	33.93	10.2	34.29	43.58	54	-10.42	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX High									
4960	43.54	V	33.98	10.22	34.25	53.49	74	-20.51	PK
4960	35.10	V	33.98	10.22	34.25	45.05	54	-8.95	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	47.07	H	33.98	10.22	34.25	57.02	74	-16.98	PK
4960	35.95	H	33.98	10.22	34.25	45.90	54	-8.10	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

9. Band Edge Compliance

9.1.Block Diagram of Test Setup



9.2.Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3.Test Procedure

All restriction band and non- restriction band have been tested, only worse case is reported.

9.4.Test Result

PASS. (See below detailed test data)

Radiated Method:

Hopping off

Polarization: Vertical & Horizontal Test Mode: GFSK-Low



Hopping on

Polarization: Vertical & Horizontal



Hopping off

Polarization: Vertical & Horizontal Test Mode: GFSK-High



Hopping on

Polarization: Vertical & Horizontal



Hopping off

Polarization: Vertical & Horizontal Test Mode: π/4 DQPSK -Low



Hopping on

Polarization: Vertical & Horizontal



Hopping off

Polarization: Vertical & Horizontal Test Mode: π/4 DQPSK -High



Hopping on

Polarization: Vertical & Horizontal



Conducted Method

Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission



10. Power Line Conducted Emissions

10.1.Block Diagram of Test Setup



:50Ω Terminator

10.2.Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

10.3.Test Procedure

(1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
(2) Setup the EUT and simulator as shown in 10.1
(3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on conducted Emission test.
(4) The bandwidth of test receiver is set at 10KHz.
(5) The frequency range from 150 KHz to 30MHz is checked.

10.4.Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

EUT Description	Wireless Game Controller	**Model No.**	GSPS4-BK
Temperature	24℃	**Humidity**	56%
Pol	Line	**Test date**	2021/02/02
Test Voltage	AC 120V/ 60Hz	**Test mode**	GFSK (2480MHz)



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Factor dB	Detector
1*	246.000 kHz	61.9	46.8	-15.1	9.7	PK
2*	590.000 kHz	56.0	45.8	-10.2	9.8	PK
3*	790.000 kHz	56.0	45.7	-10.3	9.8	PK
4*	938.000 kHz	56.0	46.3	-9.7	9.8	PK
5*	1.082 MHz	56.0	45.8	-10.2	9.9	PK
6*	1.922 MHz	56.0	44.3	-11.7	9.9	PK
7*	234.000 kHz	52.3	35.7	-16.6	9.7	AV
8*	438.000 kHz	47.1	35.5	-11.6	9.8	AV
9*	582.000 kHz	46.0	36.2	-9.8	9.8	AV
10*	746.000 kHz	46.0	34.3	-11.7	9.8	AV
11*	962.000 kHz	46.0	33.2	-12.8	9.8	AV
12*	2.070 MHz	46.0	32.2	-13.8	9.9	AV

Pol	Neutral



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Factor dB	Detector
1*	242.000 kHz	62.0	48.9	-13.2	9.7	PK
2*	442.000 kHz	57.0	45.8	-11.2	9.7	PK
3*	590.000 kHz	56.0	46.2	-9.8	9.7	PK
4*	946.000 kHz	56.0	45.7	-10.3	9.7	PK
5*	1.242 MHz	56.0	45.5	-10.5	9.8	PK
6*	1.406 MHz	56.0	46.0	-10.0	9.8	PK
7*	226.000 kHz	52.6	37.3	-15.3	9.7	AV
8*	414.000 kHz	47.6	36.4	-11.1	9.7	AV
9*	578.000 kHz	46.0	34.1	-11.9	9.7	AV
10*	746.000 kHz	46.0	34.4	-11.6	9.7	AV
11*	914.000 kHz	46.0	32.7	-13.3	9.7	AV
12*	1.406 MHz	46.0	33.7	-12.3	9.8	AV

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of GFSK (2480MHz) was listed in this report.

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The EUT antenna is internal antenna. It complies with the standard requirement.

12. Test Setup Photo

12.1.Photos of Radiated Emission Test (In Semi Anechoic Chamber 30MHz~1GHz)



12.2.Photos of Radiated Emission Test (In Full Anechoic Chamber above 1GHz)



12.3.Photos of Conducted disturbance at mains terminals test

13. Photographs Of The EUT

DRAGON




SP4232_TOUCH_GH-V1.1









--------- END OF REPORT-------