

TEST REPORT

Report No.: 25050465HKG-002

Sauber Technology Co., Ltd.

Application For Original Grant of 47 CFR Part 15 Certification

Air Purifier

FCC ID: 2AY6C-FLATV181

This report contains the data of Bluetooth portion only

Prepared and Checked by:

Approved by:

Signed on File

Leung Chun Ning, Peter
Engineer

 Digitally signed by
Herbert Wong
Location: Intertek
Testing Services
Hong Kong
Limited

Wong Cheuk Ho, Herbert
Assistant Manager
Date: July 21, 2026

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

TEST REPORT

GENERAL INFORMATION

Grantee:	Sauber Technology Co., Ltd.
Grantee Address:	1F, 338-1, Neihu Road, Sec. 2, Neihu District, Taipei 114023, Taiwan.
FCC Specification Standard:	FCC Part 15, October 1, 2024 Edition
FCC ID:	2AY6C-FLATV181
FCC Model(s):	FLAT-ULTRA, FLAT-BT
Type of EUT:	Transceiver
Description of EUT:	Air Purifier
Brand Name:	Sauberair
Sample Receipt Date:	September 04, 2025
Date of Test:	September 04, 2025 to June 22, 2026
Report Date:	July 21, 2026
Environmental Conditions:	Temperature: +10 to 40°C Relative Humidity: 10 to 90%
Conclusion:	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 Certification. This report contains the data of Bluetooth portion only

TEST REPORT

SUMMARY OF TEST RESULT

Test Items	FCC Part 15 Section	Results
Transmitter Power Line Conducted Emissions	15.207	Complied
Radiated Emission	15.249, 15.209	Complied
Radiated Emission on the Bandedge		Complied
Radiated Emission in Restricted Bands	15.205	Complied

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2024 Edition

- Note:
1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.
 2. Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

TEST REPORT

TABLE OF CONTENTS

1.0	GENERAL DESCRIPTION.....	5
1.1	Product Description	5
1.2	Related Submittal(s) Grants.....	5
1.3	Test Methodology	5
1.4	Test Facility	5
2.0	SYSTEM TEST CONFIGURATION.....	6
2.1	Justification	6
2.2	EUT Exercising Software	7
2.3	Details of EUT and Description of Accessories	7
2.4	Measurement Uncertainty	7
3.0	EMISSION RESULTS.....	8
3.1	Field Strength Calculation.....	8
3.2	Radiated Emission Configuration Photograph.....	9
3.3	Radiated Emission Data	9
3.4	Conducted Emission Configuration Photograph	9
3.5	Conducted Emission Data	9
4.0	EQUIPMENT PHOTOGRAPHS.....	18
5.0	PRODUCT LABELLING	18
6.0	TECHNICAL SPECIFICATIONS	18
7.0	INSTRUCTION MANUAL	18
8.0	MISCELLANEOUS INFORMATION	19
8.1	Radiated Emission on the Bandedge	19
8.2	Discussion of Pulse Desensitization	22
8.3	Calculation of Average Factor.....	22
8.4	Emissions Test Procedures.....	23
8.5	Occupied Bandwidth.....	27
9.0	CONFIDENTIALITY REQUEST.....	28
10.0	EQUIPMENT LIST	28

TEST REPORT

1.0 GENERAL DESCRIPTION

1.1 Product Description

The Equipment Under Test (EUT) is an air purifier which contains Wi-Fi and Bluetooth features.

For Bluetooth Mode, it operates at frequency range of 2402.000 MHz to 2480.000 MHz with 79 channels, the channels are separated with 1MHz spacing.

The EUT is powered by 100-240VAC 50/60Hz 1.8A adaptor.

The antenna(s) used in the EUT is integral, and the test sample is a prototype.
Peak Antenna Gain: 1.927dBi

The difference in model number represent the following as declared by client:

Models	Description
FLAT-ULTRA	Fully popularize
FLAT-BT	Removed UV function

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: Descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver (Bluetooth Portion).

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024. All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC and IC No. 2042H, CABID is “HKAP01”.

TEST REPORT

2.0 SYSTEM TEST CONFIGURATION

2.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit / receive continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The EUT was powered by 120VAC during test.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable at 0.8m height from the ground plane for emission testing at or below 1GHz and 1.5m for emission measurements above 1GHz.

For maximizing emissions below 30MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For any intentional radiator powered by AC power line, measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Radiated emission measurement for transmitter were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Emission that are directly caused by digital circuits in the transmit path and transmitter portion were measured, and the limit are according to FCC Part 15 Section 15.209 / RSS-247 2.5. Digital circuitries used to control additional functions other than the operation of the transmitter are subject to FCC Part 15 Section 15.109 / RSS-247 Section 5.5 Limits.

TEST REPORT

2.1 Justification (Cont'd)

Detector function for radiated emissions was in peak mode. Average readings, when required, were taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 4.8.3.

Determination of pulse desensitization was made according to Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF. The effective period (Teff) was referred to Exhibit 4.8.3. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC power line-conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst-case data is included in this report.

For simultaneous transmission, both Wi-Fi and Bluetooth portions are also switched on when taking radiated emission for determining worst-case spurious emission.

2.2 EUT Exercising Software

The EUT exercise program (ISRT Ver.2.1.32.5881) used during radiated testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Details of EUT and Description of Accessories

Details of EUT:

An AC/DC Adaptor (provided with the unit) was used to power the device.
Their descriptions are listed below.

- (1) An AC adaptor (Model: CW72E1205000BB; Input: 100-240VAC 50/60Hz 1.8A; Output: 12.0VDC 5.0A 60.0W) (Provided by Applicant)

2.4 Measurement Uncertainty

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044.

TEST REPORT

3.0 EMISSION RESULTS

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

FS	=	Field Strength in dB μ V/m
RA	=	Receiver Amplitude (including preamplifier) in dB μ V
AF	=	Antenna Factor in dB
CF	=	Cable Attenuation Factor in dB
AG	=	Amplifier Gain in dB
AV	=	Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain.

An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

FS	=	Field Strength in dB μ V/m
RR	=	RA - AG - AV in dB μ V
LF	=	CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29.0 dB and average factor of 5.0 dB are subtracted, giving a field strength of 27.0 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA	=	52.0 dB μ V/m	
AF	=	7.4 dB	RR = 18.0 dB μ V
CF	=	1.6 dB	LF = 9.0 dB
AG	=	29.0 dB	
AV	=	5.0 dB	
FS	=	RR + LF	
FS	=	18.0 + 9.0 = 27.0 dB μ V/m	

Level in μ V/m = Common Antilogarithm [(27.0 dB μ V/m)/20] = 22.4 μ V/m

TEST REPORT

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 9760.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: Setup Photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 1.8 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.159 MHz

For electronic filing, the worst-case line-conducted configuration photographs are saved with filename: Setup Photos.pdf.

3.5 Conducted Emission Data


The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Pass by 7.08 dB

TEST REPORT

CONDUCTED EMISSION

Model: FLAT-BT
Date of Test: June 22, 2026
Worst-Case Operating Mode: Wi-Fi and Bluetooth Operating



Note: Measurement Uncertainty is ± 4.2 dB at a level of confidence of 95%.

TEST REPORT

CONDUCTED EMISSION

Model: FLAT-BT
Date of Test: June 22, 2026
Worst-Case Operating Mode: Wi-Fi and Bluetooth Operating

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV		DELTA LIMIT dB
1 Quasi Peak	154.5 kHz	49.02	L1	-16.72
2 CISPR Average	204 kHz	38.77	N	-14.67
2 CISPR Average	271.5 kHz	40.91	N	-10.15
1 Quasi Peak	276 kHz	49.06	N	-11.87
1 Quasi Peak	298.5 kHz	40.25	N	-20.03
2 CISPR Average	343.5 kHz	32.14	N	-16.97
1 Quasi Peak	411 kHz	41.63	N	-15.99
1 Quasi Peak	591 kHz	37.36	N	-18.63
1 Quasi Peak	816 kHz	38.78	N	-17.22
2 CISPR Average	816 kHz	34.54	N	-11.45
1 Quasi Peak	1.365 MHz	35.34	N	-20.66
2 CISPR Average	1.365 MHz	30.49	N	-15.50
2 CISPR Average	1.905 MHz	29.93	N	-16.07
2 CISPR Average	2.454 MHz	29.52	N	-16.47
2 CISPR Average	2.9985 MHz	29.28	N	-16.71
2 CISPR Average	4.632 MHz	27.54	N	-18.45
2 CISPR Average	14.163 MHz	27.28	L1	-22.71
1 Quasi Peak	14.2935 MHz	31.71	L1	-28.28
2 CISPR Average	17.4345 MHz	21.49	L1	-28.50
2 CISPR Average	27.7845 MHz	30.06	N	-19.93


EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV		DELTA LIMIT dB
1 Quasi Peak	28.329 MHz	37.18	N	-22.81

Note: Measurement Uncertainty is ± 4.2 dB at a level of confidence of 95%.

TEST REPORT

CONDUCTED EMISSION

Model: FLAT-ULTRA
Date of Test: June 22, 2026
Worst-Case Operating Mode: Wi-Fi and Bluetooth Operating



EDIT PEAK LIST (Final Measurement Results)

Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
	TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1	Quasi Peak	159 kHz	58.42 L1	-7.08
2	CISPR Average	159 kHz	39.34 N	-16.17
1	Quasi Peak	231 kHz	47.16 L1	-15.25
2	CISPR Average	285 kHz	38.64 L1	-12.02
2	CISPR Average	312 kHz	36.14 L1	-13.76
1	Quasi Peak	321 kHz	45.89 L1	-13.78
1	Quasi Peak	487.5 kHz	40.10 L1	-16.10
2	CISPR Average	546 kHz	25.75 L1	-20.24
1	Quasi Peak	609 kHz	35.41 L1	-20.58
1	Quasi Peak	856.5 kHz	36.73 L1	-19.26
2	CISPR Average	856.5 kHz	33.80 L1	-12.19
1	Quasi Peak	1.428 MHz	34.02 L1	-21.97
2	CISPR Average	1.4325 MHz	30.83 L1	-15.16
1	Quasi Peak	1.9995 MHz	34.27 L1	-21.72
2	CISPR Average	2.004 MHz	31.41 N	-14.58
2	CISPR Average	2.5755 MHz	30.98 N	-15.01
1	Quasi Peak	2.58 MHz	31.57 L1	-24.42
1	Quasi Peak	3.147 MHz	34.66 L1	-21.33
2	CISPR Average	3.7185 MHz	28.46 L1	-17.53
2	CISPR Average	4.8615 MHz	26.15 L1	-19.84

Note: Measurement Uncertainty is ± 4.2 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSIONS

Model: FLAT-ULTRA
Date of Test: September 4, 2025
Worst-Case Operating Mode: Transmitting

Table 1

Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2402.000	89.9	33	29.4	86.3	94.0	-7.7
H	4804.000	38.8	33	34.9	40.7	54.0	-13.3
V	7206.000	38.6	33	37.9	43.5	54.0	-10.5
V	9608.000	42.0	33	40.4	49.4	54.0	-4.6
H	12010.000	38.9	33	40.5	46.4	54.0	-7.6
H	14412.000	39.4	33	40.0	46.4	54.0	-7.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2402.000	100.7	33	29.4	97.1	114.0	-16.9
H	4804.000	52.1	33	34.9	54.0	74.0	-20.0
V	7206.000	53.6	33	37.9	58.5	74.0	-15.5
V	9608.000	50.1	33	40.4	57.5	74.0	-16.5
H	12010.000	52.2	33	40.5	59.7	74.0	-14.3
H	14412.000	53.0	33	40.0	60.0	74.0	-14.0

- Notes: 1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+ Errata to C63.10a-2024.
3. All measurements were made at 3 meters.
4. Negative value in the margin column shows emission below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSIONS

Model: FLAT-ULTRA
Date of Test: September 4, 2025
Worst-Case Operating Mode: Transmitting

Table 2

Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	88.3	33	29.4	84.7	94.0	-9.3
H	4880.000	34.5	33	34.9	36.4	54.0	-17.6
V	7320.000	36.4	33	37.9	41.3	54.0	-12.7
V	9760.000	44.8	33	40.4	52.2	54.0	-1.8
H	12200.000	38.7	33	40.5	46.2	54.0	-7.8
V	14640.000	38.8	33	38.4	44.2	54.0	-9.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2440.000	99.1	33	29.4	95.5	114.0	-18.5
H	4880.000	50.4	33	34.9	52.3	74.0	-21.7
V	7320.000	50.3	33	37.9	55.2	74.0	-18.8
V	9760.000	51.5	33	40.4	58.9	74.0	-15.1
H	12200.000	52.2	33	40.5	59.7	74.0	-14.3
V	14640.000	52.3	33	38.4	57.7	74.0	-16.3

- Notes: 1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+ Errata to C63.10a-2024.
3. All measurements were made at 3 meters.
4. Negative value in the margin column shows emission below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 .
7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSIONS

Model: FLAT-ULTRA
Date of Test: September 4, 2025
Worst-Case Operating Mode: Transmitting

Table 3

Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2480.000	90.1	33	29.4	86.5	94.0	-7.5
H	4960.000	38.2	33	34.9	40.1	54.0	-13.9
H	7440.000	36.7	33	37.9	41.6	54.0	-12.4
V	9920.000	33.5	33	40.4	40.9	54.0	-13.1
V	12400.000	39.4	33	40.5	46.9	54.0	-7.1
H	14880.000	38.6	33	38.4	44.0	54.0	-10.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2480.000	100.8	33	29.4	97.2	114.0	-16.8
H	4960.000	53.4	33	34.9	55.3	74.0	-18.7
H	7440.000	51.3	33	37.9	56.2	74.0	-17.8
V	9920.000	47.2	33	40.4	54.6	74.0	-19.4
V	12400.000	52.8	33	40.5	60.3	74.0	-13.7
H	14880.000	51.7	33	38.4	57.1	74.0	-16.9

- Notes: 1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+ Errata to C63.10a-2024.
3. All measurements were made at 3 meters.
4. Negative value in the margin column shows emission below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSIONS

Model: FLAT-ULTRA
Date of Test: June 22, 2026
Worst-Case Operating Mode: Wi-Fi and Bluetooth Operating

Table 4

Pursuant to FCC Part 15 Section 15.209 Requirement

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
H	153.796	36.3	16	15.0	35.3	43.5	-8.2
H	214.785	38.7	16	17.0	39.7	43.5	-3.8
H	882.266	19.7	16	32.0	35.7	46.0	-10.3
V	913.064	15.0	16	33.0	32.0	46.0	-14.0
H	933.555	20.0	16	33.0	37.0	46.0	-9.0
V	954.046	22.5	16	33.0	39.5	46.0	-6.5

- Notes:
1. Quasi-Peak Detector Data unless otherwise stated.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 6. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSIONS

Model: FLAT-BT
Date of Test: June 22, 2026
Worst-Case Operating Mode: Wi-Fi and Bluetooth Operating

Table 5

Pursuant to FCC Part 15 Section 15.209 Requirement

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	153.796	36.0	16	15.0	35.0	43.5	-8.5
H	174.409	34.8	16	19.0	37.8	43.5	-5.7
H	882.266	19.7	16	32.0	35.7	46.0	-10.3
V	913.064	15.1	16	33.0	32.1	46.0	-13.9
H	933.555	20.7	16	33.0	37.7	46.0	-8.3
H	954.046	22.1	16	33.0	39.1	46.0	-6.9

- Notes:
1. Quasi-Peak Detector Data unless otherwise stated.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205.
 6. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: External Photos.pdf and Internal Photos.pdf.

5.0 PRODUCT LABELLING

For electronics filing, the FCC ID label artwork and the label location are saved with filename: Label.pdf.

6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: Block.pdf and Circuit.pdf respectively.

7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: Manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

TEST REPORT


8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024 for frequency being measured.



Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of Part 15.249(d).



Block diagram of Test setup

TEST REPORT

PEAK MEASUREMENT (Bluetooth)



TEST REPORT

PEAK MEASUREMENT (Bluetooth)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$= 97.1 \text{ dB}\mu\text{V/m} - 45.9 \text{ dB}$$

$$= 51.2 \text{ dB}\mu\text{V/m}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$= 86.3 \text{ dB}\mu\text{V/m} - 45.9 \text{ dB}$$

$$= 40.4 \text{ dB}\mu\text{V/m}$$

Upper Bandedge

Peak Resultant Field Strength = Fundamental Emissions (Peak Value) – delta from the plot

$$= 97.2 \text{ dB}\mu\text{V/m} - 56.2 \text{ dB}$$

$$= 41.0 \text{ dB}\mu\text{V/m}$$

Average Resultant Field Strength = Fundamental Emissions (Average Value) – delta from the plot

$$= 86.5 \text{ dB}\mu\text{V/m} - 56.2 \text{ dB}$$

$$= 30.3 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) and 54 dB μ V/m (Average Limit).

TEST REPORT

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately $625\mu s$ for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 3MHz, so the pulse desensitivity factor is 0dB.

8.3 Calculation of Average Factor

Not Applicable

TEST REPORT

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024.


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


TEST REPORT

8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.




Test setup of radiated emissions 9kHz to 30MHz



Test setup of radiated emissions up to 1GHz

TEST REPORT



Test setup of radiated emissions above 1GHz


TEST REPORT

8.4.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.


All connecting cables of EUT and peripherals were moved to find the maximum emission.

8.4.3 Conducted Emission Test Setup



TEST REPORT

8.5 Occupied Bandwidth




Spectrum Analyzer

Block diagram of Test setup

Occupied Bandwidth Results: (Bluetooth)

Bluetooth (MHz)	Occupied Bandwidth (kHz)
Low Channel: 2402	636
Middle Channel: 2440	640
High Channel: 2480	632

The worst case is shown as below:



TEST REPORT

9.0 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: Request.pdf.

10.0 EQUIPMENT LIST

1) Radiated Emissions Test

Equipment	EMI Test Receiver (9kHz to 26.5GHz)	Biconical Antenna (30MHz to 300MHz)	Log Periodic Antenna
Registration No.	EW-3156	EW-3242	EW-3243
Manufacturer	ROHDESCHWARZ	EMCO	EMCO
Model No.	ESR26	3110C	3148B
Calibration Date	May 02, 2025	July 30, 2024	July 30, 2024
Calibration Due Date	August 02, 2026	July 30, 2026	July 30, 2026

Equipment	Double Ridged Guide Antenna (1GHz - 18GHz)	Active Loop Antenna (H-field) (9kHz to 30MHz)	Solid State Low Noise Preamplifier Assembly (1 - 18)GHz
Registration No.	EW-1133	EW-2313	EW-3229
Manufacturer	EMCO	ELECTROMETRI	BONN ELEKTRO
Model No.	3115	EM-6876	BLMA 0118-5G
Calibration Date	January 23, 2025	December 19, 2025	October 14, 2024
Calibration Due Date	July 23, 2026	December 19, 2027	January 14, 2026

Equipment	2.4GHz Notch Filter	14m Double Shield RF Cable (9kHz - 6GHz)	RF Cable 14m (1GHz to 26.5GHz)
Registration No.	EW-3435	EW-2376	EW-2781
Manufacturer	MICROWAVE	RADIALL	GREATBILLION
Model No.	N0324413	n m/br56/bnc m 14m	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	October 09, 2024	November 06, 2024	February 18, 2025
Calibration Due Date	January 09, 2026	November 06, 2025	August 18, 2026

Equipment	12 metre RF Cable (1-40)GHz	Pyramidal Horn Antenna
Registration No.	EW-2774	EW-1679
Manufacturer	GREATBILLION	SCHWARZBECK
Model No.	SMA m-m ra 12m 40G outdoor	BBHA9170
Calibration Date	February 18, 2025	August 20, 2025
Calibration Due Date	February 18, 2026	February 20, 2027

TEST REPORT

2) OBW Measurement

Equipment	EMI Test Receiver (9kHz to 3GHz)
Registration No.	EW-3095
Manufacturer	ROHDESCHWARZ
Model No.	ESCI
Calibration Date	June 19, 2025
Calibration Due Date	June 19, 2026

3) Conducted Emissions Test

Equipment	RF Cable 240cm (RG142) (9kHz to 30MHz)	Artificial Mains Network	EMI Test Receiver (9kHz to 3GHz)
Registration No.	EW-2454	EW-3360	EW-3095
Manufacturer	RADIAL	ROHDESCHWARZ	ROHDESCHWARZ
Model No.	Bnc m st / 142 / bnc mra 240cm	ENV-216	ESCI
Calibration Date	June 12, 2025	June 23, 2025	June 19, 2025
Calibration Due Date	September 12, 2026	September 23, 2026	September 19, 2026

4) Control Software for Radiated Emission

Software Information	
Software Name	EMC32
Manufacturer	ROHDESCHWARZ
Software version	10.50.40

END OF TEST REPORT