



## FCC TEST REPORT FOR

Artsun Enterprise Company Limited

Bluetooth FM Transmitter with Gooseneck

Test Model: VM-208N

Prepared for : Artsun Enterprise Company Limited  
Address : 19H Maxgrand plaza, No.3 Tai Yau Street, San Po Kong, Kowloon, HongKong

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : October 25, 2023  
Number of tested samples : 2  
Sample No. : A10253042-1, A10253042-2  
Serial number : Prototype  
Date of Test : October 25, 2023 ~ November 07, 2023  
Date of Report : November 07, 2023



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: + (86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**FCC TEST REPORT****FCC CFR 47 PART 15.239****Report Reference No.** ..... : **LCSA10253042EB**

Date of Issue..... : November 07, 2023

**Testing Laboratory Name**..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,  
Shajing Street, Baoan District, Shenzhen, 518000, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □**Applicant's Name**..... : **Artsun Enterprise Company Limited**Address..... : 19H Maxgrand plaza, No.3 Tai Yau Street, San Po Kong, Kowloon,  
HongKong**Test Specification**

Standard..... : FCC CFR 47 PART 15.239 / ANSI C63.10: 2013

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description**..... : **Bluetooth FM Transmitter with Gooseneck**

Trade Mark..... : AUTO DRIVE

Test Model..... : VM-208N

Ratings..... : Input: DC 12V-24V

**Result** ..... : **Positive****Compiled by:**

Li Huan/Administrator

**Supervised by:**

Cary Luo/ Technique principal

**Approved by:**

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,  
518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**FCC -- TEST REPORT**

|                          |                       |                                           |
|--------------------------|-----------------------|-------------------------------------------|
| <b>Test Report No. :</b> | <b>LCSA10253042EB</b> | <u>November 07, 2023</u><br>Date of issue |
|--------------------------|-----------------------|-------------------------------------------|

|                          |                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Test Model.....          | : VM-208N                                                                                                                 |
| EUT.....                 | : Bluetooth FM Transmitter with Gooseneck                                                                                 |
| <b>Applicant.....</b>    | <b>: Artsun Enterprise Company Limited</b>                                                                                |
| Address.....             | : 19H Maxgrand plaza, No.3 Tai Yau Street, San Po Kong, Kowloon, HongKong                                                 |
| Telephone.....           | : /                                                                                                                       |
| Fax.....                 | : /                                                                                                                       |
| <b>Manufacturer.....</b> | <b>: Artsun Enterprise Company Limited</b>                                                                                |
| Address.....             | : 19H Maxgrand plaza, No.3 Tai Yau Street, San Po Kong, Kowloon, HongKong                                                 |
| Telephone.....           | : /                                                                                                                       |
| Fax.....                 | : /                                                                                                                       |
| <b>Factory.....</b>      | <b>: TELSTAR VIETNAM COMPANY LIMITED/Telstar</b>                                                                          |
| Address.....             | : CN-07-01 factory, lot CN-07, Van Trung Industrial Park, Van Trung Ward, Viet Yen District, Bac Giang Province, Viet Nam |
| Telephone.....           | : /                                                                                                                       |
| Fax.....                 | : /                                                                                                                       |

|                    |                 |
|--------------------|-----------------|
| <b>Test Result</b> | <b>Positive</b> |
|--------------------|-----------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



### Revision History

| Report Version | Issue Date        | Revision Content | Revised By |
|----------------|-------------------|------------------|------------|
| 000            | November 07, 2023 | Initial Issue    | ---        |
|                |                   |                  |            |
|                |                   |                  |            |





## TABLE OF CONTENTS

| Description                                       | Page      |
|---------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                | <b>6</b>  |
| 1.1 Description of Device (EUT).....              | 6         |
| 1.2 Support equipment List.....                   | 7         |
| 1.3 External I/O Cable.....                       | 7         |
| 1.4 Description of Test Facility.....             | 7         |
| 1.5 Statement of The Measurement Uncertainty..... | 7         |
| 1.6 Measurement Uncertainty.....                  | 7         |
| 1.7 Description Of Test Modes.....                | 8         |
| <b>2. TEST METHODOLOGY.....</b>                   | <b>9</b>  |
| 2.1 EUT Configuration.....                        | 9         |
| 2.2 EUT Exercise.....                             | 9         |
| 2.3 General Test Procedures.....                  | 9         |
| <b>3. SYSTEM TEST CONFIGURATION.....</b>          | <b>10</b> |
| 3.1 Justification.....                            | 10        |
| 3.2 EUT Exercise Software.....                    | 10        |
| 3.3 Special Accessories.....                      | 10        |
| 3.4 Block Diagram/Schematics.....                 | 10        |
| 3.5 Equipment Modifications.....                  | 10        |
| 3.6 Test Setup.....                               | 10        |
| <b>4. 20 DB BANDWIDTH.....</b>                    | <b>11</b> |
| 4.1 Limit.....                                    | 12        |
| 4.2 Block Diagram of Test Setup.....              | 12        |
| 4.3 Test Procedure.....                           | 12        |
| 4.4 Test Results.....                             | 12        |
| <b>5. RADIATED MEASUREMENT.....</b>               | <b>14</b> |
| 5.1 Block Diagram of Test Setup.....              | 14        |
| 5.2 Radiated Emission Limit 30~1000MHz.....       | 15        |
| 5.3 Instruments Setting.....                      | 15        |
| <b>6. POWER LINE CONDUCTED EMISSIONS.....</b>     | <b>32</b> |
| 6.1 Standard Applicable.....                      | 32        |
| 6.2 Block Diagram of Test Setup.....              | 32        |
| <b>7. ANTENNA REQUIREMENT.....</b>                | <b>33</b> |
| <b>8. LIST OF TEST EQUIPMENT.....</b>             | <b>34</b> |
| <b>9. TEST SETUP PHOTOGRAPHS OF EUT.....</b>      | <b>35</b> |
| <b>10. EXTERIOR PHOTOGRAPHS OF THE EUT.....</b>   | <b>35</b> |
| <b>11. INTERIOR PHOTOGRAPHS OF THE EUT.....</b>   | <b>35</b> |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 1. GENERAL INFORMATION

### 1.1 Description of Device (EUT)

EUT : Bluetooth FM Transmitter with Gooseneck

Test Model : VM-208N

Power Supply : Input: DC 12V-24V

Hardware Version : REV:04

Software Version : V2.6.3

Bluetooth :

Frequency Range : 2402MHz ~ 2480MHz

Channel Number : 79 channels for Bluetooth V5.3(DSS)

Channel Spacing : 1MHz for Bluetooth V5.3 (DSS)

Modulation Type : GFSK,  $\pi/4$ -DQPSK for Bluetooth V5.3(DSS)

Bluetooth Version : V5.3

Antenna Description : PCB Antenna, -0.68dBi (max.)

FM transmitter :

Frequency Range : 88.1 MHz~107.9 MHz

Channel Number : 199

Channel Spacing : 100 KHz

Channel frequency : 88.1MHz~107.9MHz (Channel Number: 199,  
Channel Frequency=88.1+0.1\*(K-1), K=1, 2, 3, 4, ..., 199)

Modulation Type : FM

Antenna Description : Internal Antenna, 0dBi(Max.)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 1.2 Support equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| --           | --          | --    | --            | --          |

## 1.3 External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| USB Port             | 1        | N/A   |
| AUX IN Port          | 1        | N/A   |
| TF Card Port         | 1        | N/A   |

## 1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6 Measurement Uncertainty

| Test Item                  | Frequency Range | Uncertainty | Note |
|----------------------------|-----------------|-------------|------|
| Radiation Uncertainty      | 9KHz~30MHz      | 3.10dB      | (1)  |
|                            | 30MHz~200MHz    | 2.96dB      | (1)  |
|                            | 200MHz~1000MHz  | 3.10dB      | (1)  |
|                            | 1GHz~26.5GHz    | 3.80dB      | (1)  |
|                            | 26.5GHz~40GHz   | 3.90dB      | (1)  |
| Conduction Uncertainty     | 150kHz~30MHz    | 1.63dB      | (1)  |
| Power disturbance          | 30MHz~300MHz    | 1.60dB      | (1)  |
| Occupied Channel Bandwidth | 1GHz-40GHz      | ±5%         | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 1.7 Description of Test Modes

The Bluetooth FM Transmitter with Gooseneck is powered by DC 12V. In the audio port and MIC port give a 2.5 kHz tone at a level 16 dB higher than that required to produce a frequency deviation of 75 KHz and make it works in TX mode (88.1 MHz, 98.0 MHz and 107.9 MHz).

DC12V and DC24V data has been tested, and the report only records the worst value

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR PART 15C 15.207, 15.209 and 15.239.

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.239 under the FCC Rules Part 15 Subpart C.

### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions(N/A)

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table 0.8 meter above ground for below 1GHz and 1.5m for above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification

The system was configured for testing in a continuous transmit condition.

#### 3.2 EUT Exercise Software

N/A.

#### 3.3 Special Accessories

N/A.

#### 3.4 Block Diagram/Schematics

Please refer to the related document.

#### 3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6 Test Setup

Please refer to the test setup photo.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



#### 4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC CFR 47 PART 15.239 |                                         |           |
|------------------------------------------|-----------------------------------------|-----------|
| FCC Rules                                | Description of Test                     | Result    |
| 15.239 (a)                               | Occupied Bandwidth                      | Compliant |
| 15.239 (b)                               | Field Strength of Fundamental frequency | Compliant |
| 15.205 (a)<br>15.209 (a)                 | Radiated Spurious Emissions             | Compliant |
| 15.207 (a)                               | AC Conducted Emissions                  | /         |
| 15.203                                   | Antenna Requirements                    | Compliant |






## 5. 99% BANDWIDTH

### 5.1 Limit

According to §15.239 (a) Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108MHz.

### 5.2 Block Diagram of Test Setup



### 5.3 Test Procedure

- 1) The transmitter shall be operated at its maximum carrier power measured under normal test conditions
- 2) The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- 4) Detector function = peak.
- 5) Trace = max hold.




### 5.4 Test Results

| Frequency (MHz) | 20dB Bandwidth (KHz) | 99% Bandwidth (KHz) | Limit (KHz) | Conclusion |
|-----------------|----------------------|---------------------|-------------|------------|
| 88.1            | 30.58                | 22.782              | 200.00      | PASS       |
| 98.1            | 30.55                | 22.778              | 200.00      | PASS       |
| 107.9           | 30.61                | 22.787              | 200.00      | PASS       |

**Remark:**

1. Test results including cable loss;
2. Please refer to the following page.




**99% and 20dB Bandwidth****Low Channel / 88.1 MHz****Middle Channel / 98.1 MHz****High Channel / 107.9 MHz**




## 6. RADIATED MEASUREMENT


### 6.1 Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 6.2 Radiated Fundamental Frequency Limit

According to §15.239 (b): The field strength of any emissions within the permitted 200 kHz band shall not exceed 250 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                       | 300                           |
| 0.490~1.705       | 24000/F(KHz)                      | 30                            |
| 1.705~30.0        | 30                                | 30                            |
| 30~88             | 100                               | 3                             |
| 88~216            | 150                               | 3                             |
| 216~960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Remark: (1) Emission level dBμV = 20 log Emission level μV/m;

(2) The smaller limit shall apply at the cross point between two frequency bands;

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 5.3 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                            |
|-------------------------------------------|----------------------------------------------------|
| Attenuation                               | Auto                                               |
| Start Frequency                           | 30 MHz                                             |
| Stop Frequency                            | 1000 MHz                                           |
| RB / VB (Emission in restricted band)     | 120KHz / 1MHz for Peak, 120 KHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 120KHz / 1MHz for Peak, 120 KHz / 10Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |





## 5.4 Test Procedures

### 1) Sequence of testing 9 kHz to 30 MHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

#### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

##### Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.

##### Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

#### 5.5 Results for Radiated Emissions


##### PASS.

Only record the worst test result in this report.

The test data please refer to following page:

|               |           |          |       |
|---------------|-----------|----------|-------|
| Temperature   | 24.1℃     | Humidity | 52.0% |
| Test Engineer | Taylor Hu |          |       |



**Below 1GHz****TX-88.1MHz****Horizontal**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 30.4237         | 38.08          | -18.40        | 19.68          | 40.00          | -20.32      | peak     |
| 2   | 88.0327         | 57.63          | -19.08        | 38.55          | 40.00          | -1.45       | peak     |
| 3   | 135.0318        | 46.21          | -20.73        | 25.48          | 43.50          | -18.02      | peak     |
| 4   | 287.9904        | 42.57          | -15.50        | 27.07          | 46.00          | -18.93      | peak     |
| 5   | 672.8442        | 41.40          | -11.06        | 30.34          | 46.00          | -15.66      | peak     |
| 6   | 906.4823        | 35.94          | -8.20         | 27.74          | 46.00          | -18.26      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8953         | 34.25          | -17.69        | 16.56          | 40.00          | -23.44      | AVG      |
| 2   | 88.0329         | 40.34          | -19.08        | 21.26          | 40.00          | -18.74      | AVG      |
| 3   | 143.8295        | 35.24          | -20.49        | 14.75          | 43.50          | -28.75      | AVG      |
| 4   | 274.1938        | 28.56          | -15.37        | 13.19          | 46.00          | -32.81      | AVG      |
| 5   | 403.2500        | 24.98          | -14.30        | 10.68          | 46.00          | -35.32      | AVG      |
| 6   | 824.5968        | 17.47          | -9.07         | 8.40           | 46.00          | -37.60      | AVG      |



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Vertical



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 35.2511         | 37.31          | -17.79        | 19.52          | 40.00          | -20.48      | peak     |
| 2   | 88.0327         | 47.42          | -19.08        | 28.34          | 40.00          | -11.66      | peak     |
| 3   | 287.9904        | 39.77          | -15.50        | 24.27          | 46.00          | -21.73      | peak     |
| 4   | 383.9318        | 36.88          | -14.63        | 22.25          | 46.00          | -23.75      | peak     |
| 5   | 480.5276        | 34.95          | -14.18        | 20.77          | 46.00          | -25.23      | peak     |
| 6   | 848.0561        | 28.86          | -8.98         | 19.88          | 46.00          | -26.12      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8953         | 34.23          | -17.69        | 16.54          | 40.00          | -23.46      | AVG      |
| 2   | 88.0329         | 33.64          | -19.08        | 14.56          | 40.00          | -25.44      | AVG      |
| 3   | 216.0239        | 20.41          | -16.98        | 3.43           | 46.00          | -42.57      | AVG      |
| 4   | 404.6665        | 20.76          | -14.42        | 6.34           | 46.00          | -39.66      | AVG      |
| 5   | 556.7743        | 17.98          | -11.55        | 6.43           | 46.00          | -39.57      | AVG      |
| 6   | 804.6027        | 17.73          | -9.78         | 7.95           | 46.00          | -38.05      | AVG      |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## TX-98MHz

## Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 30.5306         | 38.62          | -18.39        | 20.23          | 40.00          | -19.77      | peak     |
| 2   | 98.1418         | 49.93          | -18.31        | 31.62          | 68.00          | -36.38      | peak     |
| 3   | 135.0318        | 49.22          | -20.73        | 28.49          | 43.50          | -15.01      | peak     |
| 4   | 287.9904        | 52.13          | -15.50        | 36.63          | 46.00          | -9.37       | peak     |
| 5   | 383.9318        | 48.62          | -14.63        | 33.99          | 46.00          | -12.01      | peak     |
| 6   | 480.5276        | 41.42          | -14.18        | 27.24          | 46.00          | -18.76      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 35.2511         | 31.04          | -17.79        | 13.25          | 40.00          | -26.75      | AVG      |
| 2   | 98.1418         | 40.67          | -18.31        | 22.36          | 48.00          | -25.64      | AVG      |
| 3   | 135.0318        | 38.14          | -20.73        | 17.41          | 43.50          | -26.09      | AVG      |
| 4   | 278.0668        | 27.19          | -15.40        | 11.79          | 46.00          | -34.21      | AVG      |
| 5   | 400.4318        | 24.24          | -14.39        | 9.85           | 46.00          | -36.15      | AVG      |
| 6   | 935.5463        | 17.57          | -7.90         | 9.67           | 46.00          | -36.33      | AVG      |



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Vertical



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 35.2511         | 37.36          | -17.79        | 19.57          | 40.00          | -20.43      | peak     |
| 2   | 60.9175         | 31.26          | -18.92        | 12.34          | 40.00          | -27.66      | peak     |
| 3   | 98.1418         | 41.69          | -18.31        | 23.38          | 68.00          | -44.62      | peak     |
| 4   | 287.9904        | 36.45          | -15.50        | 20.95          | 46.00          | -25.05      | peak     |
| 5   | 383.9318        | 41.11          | -14.63        | 26.48          | 46.00          | -19.52      | peak     |
| 6   | 893.8566        | 35.39          | -8.40         | 26.99          | 46.00          | -19.01      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8953         | 34.03          | -17.69        | 16.34          | 40.00          | -23.66      | AVG      |
| 2   | 98.1418         | 32.05          | -18.31        | 13.74          | 48.00          | -34.26      | AVG      |
| 3   | 135.0318        | 26.64          | -20.73        | 5.91           | 43.50          | -37.59      | AVG      |
| 4   | 281.0074        | 18.74          | -15.42        | 3.32           | 46.00          | -42.68      | AVG      |
| 5   | 640.6110        | 18.25          | -11.05        | 7.20           | 46.00          | -38.80      | AVG      |
| 6   | 993.0114        | 17.46          | -7.38         | 10.08          | 54.00          | -43.92      | AVG      |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## TX-107.9MHz

## Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 30.5305         | 37.91          | -18.39        | 19.52          | 40.00          | -20.48      | peak     |
| 2   | 67.4381         | 38.02          | -19.32        | 18.70          | 40.00          | -21.30      | peak     |
| 3   | 107.8876        | 53.66          | -18.87        | 34.79          | 68.00          | -33.21      | peak     |
| 4   | 287.9904        | 50.88          | -15.50        | 35.38          | 46.00          | -10.62      | peak     |
| 5   | 383.9318        | 47.47          | -14.63        | 32.84          | 46.00          | -13.16      | peak     |
| 6   | 830.4000        | 28.93          | -9.05         | 19.88          | 46.00          | -26.12      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8952         | 34.17          | -17.70        | 16.47          | 40.00          | -23.53      | AVG      |
| 2   | 67.4381         | 30.23          | -19.32        | 10.91          | 40.00          | -29.09      | AVG      |
| 3   | 107.8876        | 44.32          | -18.87        | 25.45          | 48.00          | -22.55      | AVG      |
| 4   | 216.0238        | 33.28          | -16.98        | 16.30          | 46.00          | -29.70      | AVG      |
| 5   | 603.5390        | 18.10          | -10.52        | 7.58           | 46.00          | -38.42      | AVG      |
| 6   | 942.1304        | 17.90          | -7.88         | 10.02          | 46.00          | -35.98      | AVG      |



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Vertical



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8952         | 38.08          | -17.70        | 20.38          | 40.00          | -19.62      | peak     |
| 2   | 107.8876        | 50.71          | -18.87        | 31.84          | 68.00          | -36.16      | peak     |
| 3   | 135.0318        | 38.85          | -20.73        | 18.12          | 43.50          | -25.38      | peak     |
| 4   | 287.9904        | 40.44          | -15.50        | 24.94          | 46.00          | -21.06      | peak     |
| 5   | 383.9318        | 38.95          | -14.63        | 24.32          | 46.00          | -21.68      | peak     |
| 6   | 779.6067        | 29.30          | -10.10        | 19.20          | 46.00          | -26.80      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 36.8952         | 34.21          | -17.70        | 16.51          | 40.00          | -23.49      | AVG      |
| 2   | 59.4405         | 26.94          | -18.75        | 8.19           | 40.00          | -31.81      | AVG      |
| 3   | 107.8876        | 34.18          | -18.87        | 15.31          | 48.00          | -32.69      | AVG      |
| 4   | 216.0238        | 22.23          | -16.98        | 5.25           | 46.00          | -40.75      | AVG      |
| 5   | 477.1693        | 19.47          | -14.36        | 5.11           | 46.00          | -40.89      | AVG      |
| 6   | 755.3872        | 17.73          | -10.14        | 7.59           | 46.00          | -38.41      | AVG      |

Note: The result below 30MHz and above 1GHz is too low so there is no record. The test setup show in the test setup photograph is the worst case.





## 6. POWER LINE CONDUCTED EMISSIONS


### 6.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBμV) |          |
|-----------------------|---------------|----------|
|                       | Quasi-peak    | Average  |
| 0.15 to 0.50          | 66 to 56      | 56 to 46 |
| 0.50 to 5             | 56            | 46       |
| 5 to 30               | 60            | 50       |

\* Decreasing linearly with the logarithm of the frequency

### 6.2 Block Diagram of Test Setup



### 6.3 Test Results

**Not applicable.**





## 7. ANTENNA REQUIREMENT

### 7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### 7.2 Antenna Connected Construction

#### 7.2.1. Standard Applicable

According to § 15.203 & RSS-Gen Issue 4, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 7.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an PCB Antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

#### 7.2.3. Results: Compliance.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 8. LIST OF TEST EQUIPMENT

| Item | Equipment                      | Manufacturer      | Model No.   | Serial No.      | Cal Date                 | Due Date                 |
|------|--------------------------------|-------------------|-------------|-----------------|--------------------------|--------------------------|
| 1    | MXA Signal Analyzer            | Agilent           | N9020A      | MY49100060      | 2022-10-29<br>2023-10-28 | 2023-10-28<br>2024-10-27 |
| 2    | DC Power Supply                | Agilent           | E3642A      | N/A             | 2022-10-29<br>2023-10-28 | 2023-10-28<br>2024-10-27 |
| 3    | Temperature & Humidity Chamber | GUANGZHOU GOGNWEN | GDS-100     | 70932           | 2023-10-05               | 2024-10-04               |
| 4    | EMI Test Software              | AUDIX             | E3          | /               | N/A                      | N/A                      |
| 5    | 3m Semi Anechoic Chamber       | SIDT FRANKONIA    | SAC-3M      | 03CH03-HY       | 2023-06-09               | 2024-06-08               |
| 6    | Positioning Controller         | Max-Full          | MF7802BS    | MF780208586     | N/A                      | N/A                      |
| 7    | Active Loop Antenna            | SCHWARZBECK       | FMZB 1519B  | 00005           | 2021-08-29               | 2024-08-28               |
| 8    | By-log Antenna                 | SCHWARZBECK       | VULB9163    | 9163-470        | 2021-09-12               | 2024-09-11               |
| 9    | Horn Antenna                   | SCHWARZBECK       | BBHA 9120D  | 9120D-1925      | 2021-09-05               | 2024-09-04               |
| 10   | EMI Test Receiver              | R&S               | ESR 7       | 101181          | 2023-06-09               | 2024-06-08               |
| 11   | RS SPECTRUM ANALYZER           | R&S               | FSP40       | 100503          | 2022-10-29<br>2023-10-28 | 2023-10-28<br>2024-10-27 |
| 12   | Broadband Preamplifier         | /                 | BP-01M18G   | P190501         | 2023-06-09               | 2024-06-08               |
| 13   | EMI Test Receiver              | R&S               | ESPI        | 101940          | 2023-08-15               | 2024-08-14               |
| 14   | Artificial Mains               | R&S               | ENV216      | 101288          | 2023-06-09               | 2024-06-08               |
| 15   | 10dB Attenuator                | SCHWARZBECK       | MTS-IMP-136 | 261115-001-0032 | 2023-06-09               | 2024-06-08               |
| 16   | EMI Test Software              | Farad             | EZ          | /               | N/A                      | N/A                      |





## 9. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

## 10. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

## 11. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity