

MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

2.1091 Radio frequency radiation exposure evaluation: mobile devices.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2AYANIMMOG5
EUT	Immobilizer Programmer
Frequency band (Operating)	☐ BT: 2.402GHz ~ 2.480GHz ☐ WLAN: 2.412GHz ~ 2.462GHz ☐ RLAN: 5.180GHz ~ 5.240GHz ☐ RLAN: 5.260GHz ~ 5.320GHz ☐ RLAN: 5.500GHz ~ 5.700GHz ☐ RLAN: 5.745GHz ~ 5.825GHz ☒ Others: 125kHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	0dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-3.0	614	1.63	*(100)	30
3.0-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1	30
f = frequency in MHz. * = Plane-wave equivalent power density.				

According with 680106 D01 Wireless Power Transfer v04 clause 3.2.

Accordingly, for § 2.1091-Mobile devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at 300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m.

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G= gain of antenna in linear scale

π =3.1416

R= distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operating Mode	Freq. (MHz)	Maximum Field Strength: (dBuV/m at 3 meter)	Declared maximum EIRP	Declared maximum EIRP	Limit	
			V/m	A/m	V/m	A/m
RFID	0.125	73.37	0.004661	0.000012	614	1.63

Result: No Standalone SAR test is required.