MEASUREMENT REPORT

FCC PART 15.247 WLAN 802.11b/g/n

FCC ID:	2AYD4UWA-100
APPLICANT:	NPOINT INFOTECH Co., LTD
Application Type:	Certification
Product:	Intelligent Wi-Fi / Bluetooth Sensor Detector
Model No.:	UWA-110; UWA-XXX, GWB-XXX ; SWB-XXX (X:0~9 and A~Z)
Brand Name:	N-POINT
FCC Classification:	(DTS) Digital Transmission System
FCC Rule Part(s):	Part 15.247
Test Procedure(s):	ANSI C63.10-2013
Received Date:	November 19, 2020
Test Date:	November 24~December 1, 2020

Tested By : Peter Syu
(Peter Syu)

Reviewed By : Paddy Chen
(Paddy Chen)

Approved By : Chenz Ker
(Chenz Ker)

Testing Laboratory
3261

The test results only relate to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2011TWF101-U3	1.0	Original Report	2021-02-04	

CONTENTS

Description Page

§2.1033 General Information 5

1. INTRODUCTION 6

1.1. Scope 6
1.2. MRT Test Location 6

2. PRODUCT INFORMATION 7

2.1. Equipment Description 7
2.2. Working Frequencies for this Report 8
2.3. Test Mode 10
2.4. Test Software 10
2.5. Test Configuration 11
2.6. EMI Suppression Device(s)/Modifications 11
2.7. Labeling Requirements 11

3. DESCRIPTION of TEST 12

3.1. Evaluation Procedure 12
3.2. AC Line Conducted Emissions 12
3.3. Radiated Emissions 13

4. ANTENNA REQUIREMENTS 14

5. TEST EQUIPMENT CALIBRATION DATE 15

6. MEASUREMENT UNCERTAINTY 16

7. TEST RESULT 17

7.1. Summary 17
7.2. 6dB Bandwidth Measurement 18
7.2.1. Test Limit 18
7.2.2. Test Procedure used 18
7.2.3. Test Setting 18
7.2.4. Test Setup 18
7.2.5. Test Result 19
7.3. Output Power Measurement 22
7.3.1. Test Limit 22
7.3.2. Test Procedure Used 22
7.3.3. Test Setting 22
7.3.4. Test Setup 22
7.3.5. Test Result of Output Power 23
7.4. Power Spectral Density Measurement 24
7.4.1. Test Limit 24
7.4.2. Test Procedure Used 24
7.4.3. Test Setting 24
7.4.4. Test Setup 24
7.4.5. Test Result 25
7.5. Out-of-Band Spurious Emissions Emissions Measurement 28

7.5.1. Test Limit 28
7.5.2. Test Procedure Used 28
7.5.3. Test Settitng 28
7.5.4. Test Setup 28
7.5.5. Test Result 29
7.6. Radiated Spurious Emission Measurement 38
7.6.1. Test Limit 38
7.6.2. Test Procedure Used 38
7.6.3. Test Setting 38
7.6.4. Test Setup 40
7.6.5. Test Result 42
7.7. Radiated Restricted Band Edge Measurement 68
7.7.1. Test Limit 68
7.7.2. Test Procedure Used 68
7.7.3. Test Setting 68
7.7.4. Test Setup 70
7.7.5. Test Result 71
7.8. AC Conducted Emissions Measurement 103
7.8.1. Test Limit 103
7.8.2. Test Setup 103
7.8.3. Test Result 104

8. CONCLUSION 108

§2.1033 General Information

Applicant	NPOINT INFOTECH Co., LTD
Applicant Address	6F.-8, NO.716, ZHONGZHENG RD., ZHONGHE DIST., NEW TAIPEI CITY 23552, TAIWAN (R.O.C.)
Manufacturer	Intelligent Technology Inc.
Manufacturer Address	Yuanhesan Street, Yeyuan, Tongshagong, Dongcheng District, Dongwan City, China
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.247
Test Device Serial No.	N/A ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.

1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Intelligent Wi-Fi / Bluetooth Sensor Detector
Model No.	UWA-110; UWA-XXX, GWB-XXX ; SWB-XXX (X:0~9 and A~Z)
Brand Name	N-POINT
Supports Radios Spec.	2.4G: 802.11b/g/n-20/n-40 Bluetooth: V5.0 LE
Wi-Fi Specification	802.11b/g/n (1TX / 1RX)
Frequency Range	**2.4GHz:** For 802.11b/g/n-HT20: 2412 ~ 2462 MHz For 802.11n-HT40: 2422 ~ 2452 MHz
2.4GHz Maximum Output Power	802.11b: 19.71dBm 802.11g: 25.60dBm 802.11n-HT20: 24.16dBm 802.11n-HT40: 23.78dBm
Type of Modulation	802.11b: DSSS, DBPSK, DQPSK, CCK 802.11g/n-20M: OFDM, BPSK, QPSK, 16QAM, 64QAM

Note:

1. Model difference as below table (Declared by the manufacturer).

Model	Description	Note
UWA-110 & UWA-XXX	only for marketing different	X:0~9 and A~Z, only for marketing different
GWB-XXX	Turn off microphone function by software	X:0~9 and A~Z, only for marketing different
SWB-XXX	Connect with different sensor by software	X:0~9 and A~Z, only for marketing different

2. The difference does not affect the RF test result, so we selected UWA-110 for all RF testing.

2.2. Working Frequencies for this Report

802.11b/g/n-20M

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

Duty Cycle

Test Mode	Duty Cycle
802.11b	100%
802.11g	100%
802.11 n-HT20	100%
802.11 n-HT40	100%

802.11b

Date: 24.NOV.2020 21:05:52

802.11g

Date: 24.NOV.2020 21:19:00

802.11 n20



Date: 24.NOV.2020 21:08:42

802.11 n40



Date: 24.NOV.2020 21:11:04

2.3. Test Mode

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n-20M
	Mode 4: Transmit by 802.11n-40M

Note:

1. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.

2.4. Test Software

The test utility software used during testing was “Putty”.

2.5. Test Configuration

This device was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.7. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v05r02 were used in the measurement of the device.

Deviation from measurement procedure…….....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated emissions test results are shown in Section 7.6 & 7.7 .

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the **Intelligent Wi-Fi / Bluetooth Sensor Detector,** is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	N/A	AP800-02-P5	PIFA	0.69dBi

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2021/3/26
Cable	Rosnol	N1C50-RG400-B1C50-500CM	MRTTWE00013	1 year	2021/6/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2021/10/5
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25
Acitve Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2021/4/27
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2021/4/24
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2021/4/24
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2021/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2021/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2021/6/16
Cable	Rosnol	K1K50-UP0264-K1K50-4M	MRTTWE00012	1 year	2021/6/21

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2021/3/26

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Conducted Emission- Power Line
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 0.15MHz~30MHz: ± 2.53dB
Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz~30MHz: ± 3.92dB 30MHz~1GHz: ± 4.25dB 1GHz~18GHz: ± 4.40dB 18GHz~40GHz: ± 4.45dB
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±78.4Hz
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ± 0.84dB
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):± 2.65 dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±0.82°C/ ±3%
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±0.3%

7. TEST RESULT

7.1. Summary

Product Name: **Intelligent Wi-Fi / Bluetooth Sensor Detector**

FCC Classification: **(DTS) Digital Transmission System**

Data Rate(s) Tested: **1Mbps ~ 11Mbps (b); 6Mbps ~ 54Mbps (g); 6.5/7.2Mbps ~ 65/72.2Mbps (n-20M); 13.5/15Mbps ~ 135/150Mbps (n-40M)**

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	≥ 500kHz	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 30.00dBm		Pass	Section 7.3
15.247(e)	Power Spectral Density	≤ 8.00dBm/3kHz		Pass	Section 7.4
15.247(d)	Out-of-Band Emissions	Conducted ≥ 20dBc		Pass	Section 7.5
15.205 15.209	Spurious Emission	< FCC 15.209 limits	Radiated	Pass	Section 7.6
15.205 15.209	Band Edge Measurement	≦ 74dBuV/m(Peak) ≦ 54dBuV/m(Average)		Pass	Section 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

Notes:

1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified when applicable. The test results shown in the following sections represent the worst case emissions.
3) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
4) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

7.2.2. Test Procedure used

ANSI C63.10- Section 11.8.2 Option 2

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW ≥ 3 × RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

7.2.4. Test Setup



7.2.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
802.11b	01	2412	10.080	14.753	≥ 0.5	Pass
802.11b	06	2437	10.080	14.643	≥ 0.5	Pass
802.11b	11	2462	10.080	14.739	≥ 0.5	Pass
802.11g	01	2412	16.560	16.431	≥ 0.5	Pass
802.11g	06	2437	16.560	16.434	≥ 0.5	Pass
802.11g	11	2462	16.550	16.437	≥ 0.5	Pass
802.11n-20M	01	2412	17.710	17.629	≥ 0.5	Pass
802.11n-20M	06	2437	17.710	17.636	≥ 0.5	Pass
802.11n-20M	11	2462	17.690	17.627	≥ 0.5	Pass
802.11n-40M	03	2422	36.400	35.864	≥ 0.5	Pass
802.11n-40M	06	2437	36.410	35.862	≥ 0.5	Pass
802.11n-40M	09	2452	36.400	35.863	≥ 0.5	Pass

802.11 b CH01 (2412MHz)



802.11 b CH06 (2437MHz)



802.11 b CH11 (2462MHz)



802.11 g CH01 (2412MHz)



802.11 g CH06 (2437MHz)



802.11 g CH11 (2462MHz)



802.11 n-20M CH01 (2412MHz)



802.11 n-20M CH06 (2437MHz)



802.11 n-20M CH11 (2462MHz)



802.11 n-40M CH03 (2422MHz)



802.11 n-40M CH06 (2437MHz)



802.11 n-40M CH09 (2452MHz)



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2. Test Procedure Used

KDB 558074 D01v05r02 - Section 8.3

7.3.3. Test Setting

Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

2.4GHz 802.11b RF Output Power (dBm)							
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit
		1	2	5.5	11	1	
01	2412	17.10	--	--	--	19.59	1Watt= 30 dBm
06	2437	17.02	16.88	16.80	16.78	19.59	1Watt= 30 dBm
11	2462	17.14	--	--	--	19.71	1Watt= 30 dBm

2.4GHz 802.11g RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		6	9	12	18	24	36	48	54	6	
01	2412	16.07	--	--	--	--	--	--	--	25.33	1Watt= 30 dBm
06	2437	16.46	16.32	16.24	16.16	16.12	16.03	15.91	15.80	25.60	1Watt= 30 dBm
11	2462	16.05	--	--	--	--	--	--	--	25.22	1Watt= 30 dBm

2.4GHz 802.11n-20M RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS0	
01	2412	15.24	--	--	--	--	--	--	--	23.78	1Watt= 30 dBm
06	2437	15.12	15.01	14.98	14.95	14.93	14.88	14.85	14.81	23.53	1Watt= 30 dBm
11	2462	15.13	--	--	--	--	--	--	--	24.16	1Watt= 30 dBm

2.4GHz 802.11n-40M RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS0	
03	2422	14.98	--	--	--	--	--	--	--	23.78	1Watt= 30 dBm
06	2437	15.13	15.05	15.01	14.95	14.91	14.90	14.89	14.88	23.50	1Watt= 30 dBm
09	2452	15.15	--	--	--	--	--	--	--	23.43	1Watt= 30 dBm

Note: Output power =Reading value on power meter + duty cycle factor + cable loss。

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2. Test Procedure Used

KDB 558074 D01v05r02 - Section 8.4 Method PKPSD

7.4.3. Test Setting

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

a) Set analyzer center frequency to DTS channel center frequency.

b) Set the span to 1.5 times the DTS bandwidth.

c) Set the RBW to: 3 kHz.

d) Set the VBW ≥ 3* RBW.

e) Detector = peak.

f) Sweep time = auto couple.

g) Trace mode = max hold.

h) Allow trace to fully stabilize.

i) Use the peak marker function to determine the maximum amplitude level within the RBW.

7.4.4. Test Setup



7.4.5. Test Result

Test Mode	Channel No.	Freq. (MHz)	PSD (dBm)	Limit (dBm)	Result
11b	1	2412	-12.749	≤ 8	Pass
11b	6	2437	-12.905	≤ 8	Pass
11b	11	2462	-12.639	≤ 8	Pass
11g	1	2412	-12.503	≤ 8	Pass
11g	6	2437	-12.372	≤ 8	Pass
11g	11	2462	-12.262	≤ 8	Pass
11n-20M	1	2412	-13.661	≤ 8	Pass
11n-20M	6	2437	-13.648	≤ 8	Pass
11n-20M	11	2462	-12.903	≤ 8	Pass
11n-40M	3	2422	-13.635	≤ 8	Pass
11n-40M	6	2437	-12.782	≤ 8	Pass
11n-40M	9	2452	-13.099	≤ 8	Pass

802.11 b CH01 (2412MHz)



802.11 b CH06 (2437MHz)

802.11 b CH11 (2462MHz)



802.11 g CH01 (2412MHz)



802.11 g CH06 (2437MHz)



802.11 g CH11 (2462MHz)



802.11 n-20M CH01 (2412MHz)



802.11 n-20M CH06 (2437MHz)



802.11 n-20M CH11 (2462MHz)



802.11 n-40M CH03 (2422MHz)



802.11 n-40M CH06 (2437MHz)



802.11 n-40M CH09 (2452MHz)



7.5. Out-of-Band Spurious Emissions Emissions Measurement

7.5.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.5.2. Test Procedure Used

ANSI C63.10- Section 11.1 & 11.2

7.5.3. Test Settitng

(a) Set instrument center frequency to DTS channel center frequency

(b) Set the span to ≥ 1.5 times the DTS bandwidth

(c) Set the RBW = 100 kHz

(d) Set the VBW ≥ 3 x RBW

(e) Detector = peak

(f) Sweep time = auto couple

(g) Trace mode = max hold

(h) Allow trace to fully stabilize

7.5.4. Test Setup



7.5.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
802.11b	01	2412	20dBc	Pass
802.11b	06	2437	20dBc	Pass
802.11b	11	2462	20dBc	Pass
802.11g	01	2412	20dBc	Pass
802.11g	06	2437	20dBc	Pass
802.11g	11	2462	20dBc	Pass
802.11n-20M	01	2412	20dBc	Pass
802.11n-20M	06	2437	20dBc	Pass
802.11n-20M	11	2462	20dBc	Pass
802.11n-40M	03	2422	20dBc	Pass
802.11n-40M	06	2437	20dBc	Pass
802.11n-40M	09	2452	20dBc	Pass

802.11b CH01 (2412MHz)



802.11b CH01 (2412MHz)



802.11b CH01 (2412MHz)



802.11b CH01 (2412MHz)



802.11b CH06 (2437MHz)



802.11b CH06 (2437MHz)



802.11b CH06 (2437MHz)



802.11b CH06 (2437MHz)



802.11b CH011 (2462MHz)



802.11b CH011 (2462MHz)



802.11b CH011 (2462MHz)



802.11b CH011 (2462MHz)



802.11g CH01 (2412MHz)



802.11g CH01 (2412MHz)



802.11g CH01 (2412MHz)



802.11g CH01 (2412MHz)



802.11g CH06 (2437MHz)



802.11g CH06 (2437MHz)



802.11g CH06 (2437MHz)



802.11g CH06 (2437MHz)



802.11g CH011 (2462MHz)



802.11g CH011 (2462MHz)



802.11g CH011 (2462MHz)



802.11g CH011 (2462MHz)