



SAR Test Report

For

Applicant Name: Imin Technology Pte Ltd
Address: 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943
EUT Name: Wireless Cashier Terminal, Wireless Data Terminal, Mobile Cashier Terminal, POS Device
Model Number: I24T02

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF240808R01001
FCC 47 CFR§2.1093 IEC/IEEE 62209-1528: 2020
Test Standards: IEEE C95.1-2019 KDB447498 D01 KDB865664 D01
KDB865664 D02 KDB941225 D01 KDB941225 D05
KDB248227 D01 KDB941225 D06 KDB648474 D04
KDB690783 D01
FCC ID: 2AYD5-I24T02
Test Conclusion: Pass
Test Date: 2024-08-08 to 2024-08-17
Date of Issue: 2024-08-19

Tested By: Amenda Zhong
Amenda Zhong / Tester

Prepared By: Zoey Zhang
Zoey Zhang / Project Engineer

Date: 2024-08-19

Approved By: Ryan.CJ
Ryan.CJ / EMC Manager
Date: 2024-08-19



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2024-08-19	Original
Note:		Once the revision has been made, then previous versions reports are invalid.

Table of Contents

1. Introduction	4
1.1 Identification of Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
1.3 Laboratory Condition	4
1.4 Announcement	4
2. Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Equipment under Test Ancillary Equipment	5
2.6 Technical Information	5
3. Summary of Test Results	7
3.1 Test Standards	7
3.2 Device Category and SAR Limit	7
3.3 Test Result Summary	8
3.4 Test Uncertainty	9
4. Measurement System	11
4.1 Specific Absorption Rate (SAR) Definition	11
4.2 MVG SAR System	11
5. System Verification	16
5.1 Purpose of System Check	16
5.2 System Check Setup	16
6. TEST POSITION CONFIGURATIONS	17
6.1 Head Exposure Conditions	17
6.2 Body-worn Position Conditions	22
6.3 Hotspot Mode Exposure Position Conditions	23
6.4 Product Specific 10g Exposure Consideration	23
7. Measurement Procedure	24
7.1 Measurement Process Diagram	24
7.2 SAR Scan General Requirement	25
7.3 Measurement Procedure	26
7.4 Area & Zoom Scan Procedure	26
8. Conducted RF Output Power	27
8.1 GSM	27
8.2 WCDMA	28
8.3 LTE	29
8.4 Wi-Fi	46
8.5 Bluetooth	48
8.6 NFC	48
9. Test Exclusion Consideration	48
9.1 SAR Test Exclusion Consideration Table	49
10. Test Result	50
Body 1g SAR Data	50
11. SAR Measurement Variability	52
12. Simultaneous Transmission	53
12.1 Simultaneous Transmission Mode Considerations	53
12.2 Sum SAR of Simultaneous Transmission	53
13. Test Equipment List	54
ANNEX A Simulating Liquid Verification Result	55
ANNEX B System Check Result	55
ANNEX C SAR Dipole Calibrations	56
ANNEX C Test Data	80
ANNEX D SAR Test Setup Photos	124
ANNEX E EUT External and Internal Photos	125
ANNEX F Calibration Information	125

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
FCC Registration Number	518915
Designation Number	CN1330

1.3 Laboratory Condition

Ambient Temperature:	21°C to 25°C
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	Imin Technology Pte Ltd
Address:	11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

2.2 Manufacturer Information

Company Name:	Imin Technology Pte Ltd
Address:	11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

2.3 Factory Information

Company Name:	Jiangxi Neostra Electronic Co. Ltd
Address:	279 Shenzhen Road, Jinggangshan economic and Technological Development Zone, Ji'an, Jiangxi
Company Name:	Neosta Technology Sdn. Bhd.
Address:	No.78, Jln I-Park SAC 5, Taman Perindustrian i-ParkSAC, 81400 Senai, Johor, Malaysia

2.4 General Description of Equipment under Test (EUT)

EUT Name	Wireless Cashier Terminal, Wireless Data Terminal, Mobile Cashier Terminal, POS Device
Under Test Model Name	I24T02

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	8000mAh
	Nominal Voltage	3.8V

2.6 Technical Information

Network and Wireless connectivity	2G Network GPRS/EGPRS 850/1900 3G Network WCDMA/HSDPA/HSUPA Band 2/5 4G Network FDD LTE Band 2/4/5/7/12/14/17/25/26/66 TDD LTE Band 41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) BT (EDR+BLE) NFC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, WCDMA, LTE, WLAN, Bluetooth, NFC		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE Band 12	TX: 698 ~ 716 MHz	RX: 728 ~ 746 MHz
	LTE Band 14	TX: 788 ~ 798 MHz	
	LTE Band 17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
	LTE Band 25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE Band 26 part 90	TX: 814.7 ~ 823.3 MHz	RX: 859.7 ~ 868.3 MHz
	LTE Band 26 part 22	TX: 824.7 ~ 848.3 MHz	RX: 869.7 ~ 893.3 MHz
	LTE Band 66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	LTE Band 41	2496 ~ 2690 MHz	
	802.11b/g/n(HT20)	2412 ~ 2462 MHz	
	802.11a /802.11n(HT20/40) /802.11ac(VHT20/40/80)	5150 ~ 5250 MHz 5250 ~ 5350 MHz 5470 ~ 5725 MHz 5725 ~ 5850 MHz	
	Bluetooth	2402 ~ 2480 MHz	
	NFC	13.56 MHz	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna BT: PIFA Antenna NFC: PIFA Antenna		
Hotspot Function	Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Type		
	☐ Production unit	☒ Identical prototype	

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEC/IEEE 62209-1528: 2020	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB447498 D01	General RF Exposure Guidance v06
5	KDB865664 D01	SAR measurement 100MHz to 6GHz v01r04
6	KDB865664 D02	RF Exposure Reporting v01r02
7	KDB941225 D01	3G SAR Procedures v03r01
8	KDB941225 D05	SAR for LTE Devices v02r05
9	KDB248227 D01	802.11 Wi-Fi SAR v02r02
10	KDB941225 D06	Hotspot Mode v02r01
11	KDB648474 D04	Handset SAR v01r03
12	KDB690783 D01	SAR Listings on Grant v01r03

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as follows:

<Highest Reported standalone SAR>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)	
Hotspot(Body) 1-g SAR (0 mm Gap)	GSM 850	0.912	PCB	0.962	
	GSM 1900	0.278			
	WCDMA Band 2	0.511			
	WCDMA Band 5	0.660			
	LTE Band 2	0.962			
	LTE Band 4	0.516			
	LTE Band 5	0.507			
	LTE Band 7	0.798			
	LTE Band 12	0.360			
	LTE Band 14	0.585			
	LTE Band 17	0.337			
	LTE Band 25	0.186			
	LTE Band 26 part 90	0.714			
	LTE Band 26 part 22	0.716			
	LTE Band 41	0.911			
	LTE Band 66	0.327			
	WLAN 2.4 GHz	0.533			DTS
	Bluetooth	0.598			DSS
	WLAN 5.2 GHz	0.442	NII		
	WLAN 5.4 GHz	0.442			
	WLAN 5.6 GHz	0.223			
	WLAN 5.8 GHz	0.494			

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEC/IEEE 62209-1528: 2020.

<Highest Reported Simultaneous SAR>

Exposure Position	Simultaneous Configuration	Highest Reported Simultaneous Transmission SAR (W/kg)	Limit (W/kg)	Verdict
Hotspot(Body) 1-g SAR (0 mm Gap)	LTE Band 2 + 5G WIFI	1.562	1.6	Pass

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

Measurement uncertainty evaluation for SAR test (300MHz to 6GHz)

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+- %)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	√3	√0.5	√0.5	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	√3	√0.5	√0.5	2.41	2.41	∞
Boundary effect	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	4.7	R	√3	1	1	2.71	2.71	∞
System detection limits	1.0	R	√3	1	1	0.58	0.58	∞
Modulation response	3.0	R	√3	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	√3	1	1	0.00	0.00	∞
Integration Time	1.4	R	√3	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	√3	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	√3	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	√3	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	√3	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	√3	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3.0	N	1	1	1	3.00	3.00	7
Output power Variation - SAR drift measurement	5.0	R	√3	1	1	2.89	2.89	∞
SAR scaling	2.0	R	√3	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	√3	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4.0	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	√3	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	√3	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		k				20.95	20.69	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.4.2 Measurement uncertainty evaluation for system check

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10 g)	1g Ui (+- %)	10 g Ui (+- %)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR drift measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Dist.	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		k				20.32	20.06	

4. Measurement System

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 MVG SAR System

4.2.1 SAR system diagram



4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for $f \geq 4\text{GHz}$.
- Probe linearity: $< 0.25\text{dB}$.
- Axial Isotropy: $< 0.25\text{dB}$.
- Spherical Isotropy: $< 0.50\text{dB}$.
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than 20° .




4.2.4 Phantoms

SAM Phantom			
		The thickness of the phantom amounts to 2 mm±0.2 mm. The materials for the phantom do not affect the radiation of the device under test (DUT) : $\epsilon_r' < 5$ The head is filled with tissue simulating liquid. The hand do not have to be modeled.	
SAM Phantom			
TWIN SAM phantom			
Mechanical		Electrical	
Overall thickness	2±0.2 mm(except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		


ELLIPTICAL Phantom	
The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.	
	The shape of the phantom is an ellipse with length $600 \text{ mm} \pm 5 \text{ mm}$ and width $400 \text{ mm} \pm 5 \text{ mm}$. The phantom shell is made of low-loss and low-permittivity material, having loss tangent $\tan \delta \leq 0.05$ and relative permittivity: $\epsilon_r' \leq 5$ for $f \leq 3 \text{ GHz}$ $3 \leq \epsilon_r' \leq 5$ for $f > 3 \text{ GHz}$ The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of $\pm 0.2 \text{ mm}$.
ELLI Phantom	
Technical & mechanical characteristics	
Shell thickness	$2 \text{ mm} \pm 0.2 \text{ mm}$
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder

					
System Material	Permittivity	Loss tangent	System Material	Permittivity	Loss tangent
Delrin	3.7	0.005	PMMA	2.9	0.028
The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°..					

4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.


Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS

According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEC IEEE 62209-1528:2020 using the SAM phantom illustrated as below.

6.1.1 Definition of the cheek position

The cheek position is established using steps a) to j) as follows.

- (a) Configure the DUT for voice operation, if necessary. For example, for a DUT with a flip.a)swivel, or slide cover piece, open the cover if this is consistent with voice operation. If the DUT can also be used with the cover closed, both configurations shall be tested.
- (b) Define two imaginary lines on the DUT, the vertical centreline and the horizontal line, relative to the DUT in vertical orientation as shown in Figure 15.
- (c) The vertical centreline passes through two points on the front side of the DUT: the midpoint of the width w of the DUT at the level of the acoustic output (Point A in Figure 15), and the midpoint of the width w_t at the bottom of the DUT (Point B). The horizontal line is perpendicular to the vertical centerline, and passes through the centre of the acoustic output (Figure 15). The two lines intersect at Point A. Note that for many DUTs, Point A coincides with the centre of the acoustic output. However, the acoustic output could be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the DUT, especially for clamshell DUTs, DUTs with flip cover pieces, and other irregularly shaped DUTs.
- (d) Position the DUT close to the surface of the phantom such that Point A is on the (virtual) extension of the line passing through points RE (right-ear ear reference point) and LE left-ear ear reference point) on the phantom (see Figure 16a) and Figure 16b)). The plane determined by the vertical centreline and the horizontal line of the DUT shall be parallel to the sagittal plane of the phantom.
- (e) Translate the DUT towards the phantom along the line passing through RE and LE until the DUT touches the ear (see Figure 16c)).
- (f) Rotate the DUT around the (virtual) LE-RE Line until the DUT vertical centreline is in the)reference plane(see Figure 16d)).
- (g) Rotate the DUT around its vertical centreline until the plane established by the DUT vertical centreline and horizontal line is parallel to the N-F line (see Annex G), and then translate the DUT towards the phantom along the LE-RE line until DUT Point A touches the ear at the ERP (ear reference point) (see Figure 16e))
- (h) While keeping Point A on the line passing through RE and LE and maintaining the DUT in contact with the pinna, rotate the DUT about the N-F line until any point on the DUT is in contact with a phantom point below the pinna (cheek) (see Figure 16f)). The physical angles of rotation shall be documented.
- (i) While keeping DUT Point A in contact with the ERP rotate the DUT around a line perpendicular to the plane established by the DUT vertical centreline and horizontal line and passing through DUT Point A, until the DUT vertical centreline is in the reference plane(see Figure 16g)).

- (j) Verify that the cheek position is correct as follows:
- 1) the N-F line is in the plane established by the DUT vertical centreline and horizontal line;
 - 2) DUT Point A touches the pinna at the ERP
 - 3) the DUT vertical centreline is in the reference plane.





Figure 15 - Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right)




NOTE The reference points for the right-ear ear reference point (RE), left-ear ear reference point (LE), and mouth (M), which establish the reference plane for DUT positioning, are indicated. This device position shall be maintained for the sagittal phantom test set-up shown in Figure G.4.

a) Phone position 1 – cheek position




b) One possible DUT position against the head after applying 7.2.4.2.2 c)




NOTE The black arrows show the direction of translation of the DUT for 7.2.4.2.2 d).

c) DUT position after applying 7.2.4.2.2 d)




NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 e).

d) DUT position after applying 7.2.4.2.2 e)



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 f).


e) DUT position after applying 7.2.4.2.2 f)



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 g)

f) DUT position after applying 7.2.4.2.2 g)

© IEC/IEEE 2020



NOTE The curved black arrows show the direction of rotation of the DUT for 7.2.4.2.2 h).


g) DUT position after applying 7.2.4.2.2 h)

Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up

6.1.2 Definition of the tilt position

The tilt position is established using steps a) through d) as follows.

- Repeat steps a) through j) of 7.2.4.2.2 to place the DUT in the cheek position)(see Figure 16).
- While maintaining the orientation of the DUT, move the DUT away from the pinna along the line passing through RE and LE far enough to allow a rotation of the DUT away from the cheek by 15°.
- Rotate the DUT around the horizontal line by 15°(see Figure 17).
- While maintaining the orientation of the DUT. move the DUT towards the phantom on a line passing through RE and LE until any part of the DUT touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g. an extended antenna in contact with the back of the head phantom, the angle of the DUT shall be reduced. in this case, the tilt position is obtained if any part of the DUT is in contact with the pinna and a second point on the DUT is in contact with the phantom, e.g. the antenna in contact with the back of the head.



Key

- M Mouth reference point
- LE Left-ear ear reference point
- RE Right-ear ear reference point

This device position shall be maintained for the phantom test set-up.


Figure 17 – Tilt position of the DUT on the left side of SAM

6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



IEC

7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEC/IEEE 62209-1528: 2020.

Table 3 – Area scan parameters

Parameter	DUT transmit frequency being tested	
	$f \leq 3 \text{ GHz}$	$3 \text{ GHz} < f \leq 10 \text{ GHz}$
Maximum distance between the measured points (geometric centre of the sensors) and the inner phantom surface (z_{M1} in Figure 20 in mm)	5 ± 1	$\delta \ln(2)/2 \pm 0,5^a$
Maximum spacing between adjacent measured points in mm (see O.8.3.1) ^b	20, or half of the corresponding zoom scan length, whichever is smaller	$60/f$, or half of the corresponding zoom scan length, whichever is smaller
Maximum angle between the probe axis and the phantom surface normal (α in Figure 20) ^c	5° (flat phantom only) 30° (other phantoms)	5° (flat phantom only) 20° (other phantoms)
Tolerance in the probe angle	1°	1°
^a δ is the penetration depth for a plane-wave incident normally on a planar half-space.		
^b See Clause O.8 on how Δx and Δy may be selected for individual area scan requirements.		
^c The probe angle relative to the phantom surface normal is restricted due to the degradation in the measurement accuracy in fields with steep spatial gradients. The measurement accuracy decreases with increasing probe angle and increasing frequency. This is the reason for the tighter probe angle restriction at frequencies above 3 GHz.		

Table 4 – Zoom scan parameters

Parameter	DUT transmit frequency being tested	
	$f \leq 3 \text{ GHz}$	$3 \text{ GHz} < f \leq 10 \text{ GHz}$
Maximum distance between the closest measured points and the phantom surface (z_{M1} in Figure 20 and Table 3, in mm)	5	$\delta \ln(2)/2^a$
Maximum angle between the probe axis and the phantom surface normal (α in Figure 20)	5° (flat phantom only) 30° (other phantoms)	5° (flat phantom only) 20° (other phantoms)
Maximum spacing between measured points in the x- and y-directions (Δx and Δy , in mm)	8	$24/f^b$
For uniform grids: Maximum spacing between measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	5	$10/(f - 1)$
For graded grids: Maximum spacing between the two closest measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	4	$12/f$
For graded grids: Maximum incremental increase in the spacing between measured points in the direction normal to the phantom shell ($R_z = \Delta z_2/\Delta z_1$ in Figure 20)	1,5	1,5
Minimum edge length of the zoom scan volume in the x- and y-directions (L_z in O.8.3.2, in mm)	30	22
Minimum edge length of the zoom scan volume in the direction normal to the phantom shell (L_h in O.8.3.2 in mm)	30	22
Tolerance in the probe angle	1°	1°
^a δ is the penetration depth for a plane-wave incident normally on a planar half-space.		
^b This is the maximum spacing allowed, which might not work for all circumstances.		

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8. Conducted RF Output Power

8.1 GSM

Mode: GSM850		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH128	CH190	CH251		CH128	CH190	CH251
			824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GPRS (GMSK)	1Tx slot	32.50	32.17	32.31	32.34	-9.03	23.14	23.28	23.31
	2Tx slots	31.50	31.13	31.3	31.27	-6.02	25.11	25.28	25.25
	3Tx slots	31.50	31.15	31.11	31.18	-4.26	26.89	26.85	26.92
	4Tx slots	31.50	31.25	31.14	31.14	-3.01	28.24	28.13	28.13
EGPRS (8PSK)	1Tx slot	31.50	31.17	31.23	31.30	-9.03	22.14	22.20	22.27
	2Tx slots	31.50	31.13	31.19	31.11	-6.02	25.11	25.17	25.09
	3Tx slots	31.50	31.28	31.17	31.12	-4.26	27.02	26.91	26.86
	4Tx slots	31.50	31.19	31.14	31.21	-3.01	28.18	28.13	28.20
Mode: GSM1900		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH512	CH661	CH810		CH512	CH661	CH810
			1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GPRS (GMSK)	1Tx slot	30.50	30.20	30.27	30.31	-9.03	21.17	21.24	21.28
	2Tx slots	29.50	29.45	29.48	29.48	-6.02	23.43	23.46	23.46
	3Tx slots	30.00	29.46	29.47	29.52	-4.26	25.20	25.21	25.26
	4Tx slots	30.00	29.60	29.51	29.49	-3.01	26.59	26.50	26.48
EGPRS (8PSK)	1Tx slot	30.00	29.52	29.51	29.52	-9.03	20.49	20.48	20.49
	2Tx slots	30.00	29.44	29.6	29.45	-6.02	23.42	23.58	23.43
	3Tx slots	30.00	29.5	29.55	29.44	-4.26	25.24	25.29	25.18
	4Tx slots	30.00	29.58	29.58	29.56	-3.01	26.57	26.57	26.55
Note: 1) Division Factors To average the power, the division factor is as follows: 1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB									

8.2 WCDMA

Mode		Maximum Tune-up(dBm)	WCDMA Band II		
			Conducted Power (dBm)		
			CH9262	CH9400	CH9538
			1852.4	1880.0	1907.6
RMC 12.2K		22.50	22.32	22.29	22.34
HSDPA	Subtest-1	22.50	22.28	22.26	22.25
	Subtest-2	22.50	22.28	22.38	22.35
	Subtest-3	22.50	22.36	22.38	22.33
	Subtest-4	22.50	22.21	22.28	22.32
HSUPA	Subtest-1	22.50	22.35	22.33	22.24
	Subtest-2	22.50	22.32	22.20	22.24
	Subtest-3	22.50	22.20	22.33	22.26
	Subtest-4	22.50	22.20	22.32	22.40
	Subtest-5	22.50	22.31	22.32	22.31
Mode		Maximum Tune-up(dBm)	WCDMA Band V		
			Conducted Power (dBm)		
			CH4132	CH4183	CH4233
			826.4	836.6	846.6
RMC 12.2K		22.50	22.43	22.45	22.39
HSDPA	Subtest-1	23.00	22.49	22.5	22.36
	Subtest-2	22.50	22.37	22.39	22.36
	Subtest-3	22.50	22.43	22.31	22.45
	Subtest-4	22.50	22.32	22.48	22.33
HSUPA	Subtest-1	22.50	22.41	22.44	22.36
	Subtest-2	22.50	22.42	22.32	22.40
	Subtest-3	22.50	22.40	22.44	22.49
	Subtest-4	22.50	22.35	22.30	22.36
	Subtest-5	22.50	22.38	22.35	22.47
Per KDB 941225 D01, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/2$ dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.					

8.3 LTE

Band 2

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		18607	18900	19193
					1850.7MHz	1880.0MHz	1909.3MHz
1.4MHz	QPSK	1	0	23.00	22.68	22.72	22.61
			2	23.00	22.68	22.72	22.61
			5	23.00	22.64	22.67	22.58
		3	0	23.00	22.80	22.78	22.73
			2	23.00	22.79	22.78	22.72
			3	23.00	22.76	22.77	22.71
		6	0	22.00	21.80	21.76	21.71
	16QAM	1	0	22.00	21.56	21.49	21.30
			2	22.00	21.63	21.56	21.32
			5	22.00	21.57	21.53	21.30
		3	0	22.00	21.59	21.61	21.45
			2	22.00	21.61	21.60	21.46
			3	22.00	21.59	21.58	21.43
		6	0	21.00	20.82	20.61	20.69
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18615	18900	19185
					1851.5MHz	1880.0MHz	1908.5MHz
3MHz	QPSK	1	0	23.00	22.59	22.56	22.53
			7	23.00	22.66	22.68	22.62
			14	23.00	22.55	22.62	22.50
		8	0	22.00	21.81	21.70	21.71
			4	22.00	21.79	21.70	21.69
			7	22.00	21.81	21.74	21.68
		15	0	22.00	21.80	21.75	21.71
	16QAM	1	0	22.00	21.58	21.48	21.26
			7	22.00	21.65	21.47	21.36
			14	22.00	21.60	21.41	21.18
		8	0	21.00	20.81	20.68	20.70
			4	21.00	20.84	20.73	20.65
			7	21.00	20.79	20.75	20.67
		15	0	21.00	20.78	20.71	20.64
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18625	18900	19175
					1852.5MHz	1880.0MHz	1907.5MHz
5MHz	QPSK	1	0	23.00	22.86	22.83	22.84
			13	23.50	23.00	22.92	22.89
			24	23.00	22.95	22.79	22.76
		12	0	22.00	21.88	21.83	21.78
			6	22.00	21.82	21.79	21.77
			13	22.00	21.87	21.83	21.74
		25	0	22.00	21.92	21.84	21.83
	16QAM	1	0	22.00	21.78	21.92	21.72
			13	22.50	21.93	22.00	21.80
			24	22.00	21.87	21.88	21.70
		12	0	21.00	20.83	20.84	20.79
			6	21.00	20.85	20.86	20.80
			13	21.00	20.87	20.89	20.75
		25	0	21.00	20.93	20.85	20.84

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		18650	18900	19150		
					1855.0MHz	1880.0MHz	1905.0MHz		
10MHz	QPSK	1	0	23.00	22.91	22.94	22.89		
			25	23.00	22.97	22.97	22.92		
			49	23.00	22.99	22.94	22.83		
		25	0	22.00	21.87	21.82	21.80		
			13	22.00	21.84	21.80	21.84		
			25	22.00	21.95	21.90	21.88		
		50	0	22.00	21.94	21.85	21.83		
			16QAM	1	0	22.00	21.91	21.78	21.66
					25	22.00	21.97	21.75	21.64
	49	22.50			22.06	21.74	21.61		
	25	0		21.00	20.91	20.88	20.83		
		13		21.00	20.89	20.88	20.86		
		25		21.00	20.98	20.93	20.93		
	50	0	21.00	20.99	20.93	20.90			
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18675	18900	19125	
1857.5MHz						1880.0MHz	1902.5MHz		
15MHz	QPSK	1	0	23.00	22.84	22.81	22.84		
			38	23.50	23.02	22.88	22.90		
			74	23.00	22.98	22.78	22.79		
		36	0	22.00	21.86	21.93	21.59		
			18	22.50	22.08	21.98	21.69		
			39	22.50	22.02	21.95	21.55		
		75	0	22.00	21.98	21.88	21.87		
			16QAM	1	0	22.00	21.83	21.95	21.59
					38	22.50	22.04	21.99	21.65
	74	22.00			21.99	21.93	21.51		
	36	0		22.00	21.86	21.94	21.59		
		18		22.50	22.00	22.00	21.63		
		39		22.50	22.00	21.96	21.49		
	75	0	21.00	20.95	20.90	20.91			
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18700	18900	19100	
1860.0MHz						1880.0MHz	1900.0MHz		
20MHz	QPSK	1	0	23.00	22.79	22.83	22.73		
			50	23.50	23.08	22.91	22.93		
			99	23.00	23.00	22.83	22.69		
		50	0	22.00	21.91	21.86	21.91		
			25	22.00	21.93	21.85	21.90		
			50	22.50	22.06	21.91	21.97		
		100	0	22.00	21.99	21.86	21.91		
			16QAM	1	0	22.00	21.67	21.91	21.52
					50	22.50	21.99	22.09	21.71
	99	22.00			21.81	21.98	21.55		
	50	0		21.00	20.94	20.87	20.97		
		25		21.00	20.93	20.90	20.99		
		50		21.50	21.03	20.97	20.97		
	100	0	21.50	21.02	20.90	20.92			

Band 4

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		19957	20175	20393
					1710.7MHz	1732.5MHz	1754.3MHz
1.4MHz	QPSK	1	0	23.00	22.83	22.39	22.64
			2	23.00	22.79	22.41	22.61
			5	23.00	22.81	22.40	22.59
		3	0	23.00	22.93	22.48	22.77
			2	23.00	22.90	22.46	22.80
			3	23.00	22.89	22.44	22.74
		6	0	22.50	22.03	21.59	21.80
	16QAM	1	0	22.00	21.74	21.24	21.61
			2	22.00	21.75	21.31	21.59
			5	22.00	21.68	21.25	21.52
		3	0	22.00	21.69	21.27	21.54
			2	22.00	21.70	21.27	21.58
			3	22.00	21.71	21.25	21.53
		6	0	21.50	21.04	20.55	20.84
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19965	20175	20385
					1711.5MHz	1732.5MHz	1753.5MHz
3MHz	QPSK	1	0	23.00	22.78	22.30	22.67
			7	23.00	22.85	22.44	22.67
			14	23.00	22.71	22.35	22.58
		8	0	22.00	21.94	21.46	21.84
			4	22.00	21.90	21.44	21.81
			7	22.00	21.96	21.49	21.87
		15	0	22.00	21.95	21.48	21.87
	16QAM	1	0	22.00	21.72	21.10	21.66
			7	22.00	21.85	21.18	21.73
			14	22.00	21.70	21.15	21.57
		8	0	21.00	20.93	20.39	20.82
			4	21.00	20.92	20.43	20.82
			7	21.00	20.94	20.44	20.79
		15	0	21.00	20.92	20.37	20.86
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19976	20175	20375
					1712.5MHz	1732.5MHz	1752.5MHz
5MHz	QPSK	1	0	23.50	23.07	22.44	23.03
			13	23.50	23.17	22.65	23.12
			24	23.00	22.98	22.64	22.94
		12	0	22.00	21.95	21.48	21.93
			6	22.00	21.94	21.48	21.92
			13	22.00	21.97	21.57	21.90
		25	0	22.00	21.98	21.55	21.94
	16QAM	1	0	22.00	21.91	21.49	21.90
			13	22.50	22.00	21.69	21.94
			24	22.00	21.87	21.68	21.81
		12	0	21.00	20.85	20.48	20.91
			6	21.00	20.88	20.40	20.84
			13	21.00	20.94	20.55	20.81
		25	0	21.50	21.01	20.50	20.91

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)			
Bandwidth	Modulation	RB allocation	RB offset		20000	20175	20350	
					1715.0MHz	1732.5MHz	1750.0MHz	
10MHz	QPSK	1	0	23.50	23.10	22.57	23.03	
			25	23.50	23.01	22.67	23.06	
			49	23.00	22.79	22.82	22.89	
		25	0	22.00	21.84	21.38	21.93	
			13	22.00	21.89	21.35	21.97	
			25	22.00	21.81	21.66	21.95	
		50	0	22.50	21.84	21.52	22.04	
		16QAM	1	0	22.50	22.05	21.32	22.09
				25	22.50	21.98	21.47	22.06
	49			22.00	21.76	21.69	21.93	
	25		0	21.00	20.83	20.38	20.98	
			13	21.00	20.83	20.41	20.99	
			25	21.00	20.77	20.70	20.98	
	50		0	21.50	20.82	20.54	21.02	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20025	20175	20325
						1717.5MHz	1732.5MHz	1747.5MHz
15MHz	QPSK	1	0	23.50	23.03	22.40	22.95	
			38	23.50	22.92	22.60	23.17	
			74	23.00	22.61	22.79	22.90	
		36	0	22.50	22.01	21.45	21.94	
			18	22.50	21.95	21.72	22.13	
			39	22.00	21.62	21.93	21.97	
		75	0	22.50	21.80	21.56	22.01	
		16QAM	1	0	22.50	22.01	21.47	21.90
				38	22.50	21.85	21.70	22.18
	74			22.00	21.56	21.92	21.93	
	36		0	22.00	21.98	21.48	21.88	
			18	22.50	21.91	21.73	22.18	
			39	22.00	21.58	21.94	21.92	
	75		0	21.00	20.73	20.57	20.96	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20050	20175	20300
						1720.0MHz	1732.5MHz	1745.0MHz
20MHz	QPSK	1	0	23.00	22.91	22.46	22.57	
			50	23.50	22.83	22.67	23.13	
			99	23.00	22.51	22.95	22.92	
		50	0	22.00	21.74	21.34	21.89	
			25	22.00	21.73	21.31	21.88	
			50	22.50	21.63	21.78	22.12	
		100	0	22.00	21.64	21.54	21.96	
		16QAM	1	0	22.00	21.80	21.55	21.48
				50	22.50	21.66	21.76	22.06
	99			22.50	21.34	22.08	21.81	
	50		0	21.00	20.75	20.32	20.87	
			25	21.00	20.68	20.33	20.82	
			50	21.50	20.59	20.75	21.08	
	100		0	21.00	20.66	20.53	20.96	

Band 5

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	24.50	24.13	24.22	24.20
			2	24.50	24.12	24.17	24.17
			5	24.50	24.11	24.18	24.21
		3	0	24.50	24.18	24.19	24.28
			2	24.50	24.17	24.19	24.21
			3	24.50	24.16	24.26	24.27
		6	0	23.50	23.27	23.27	23.31
	16QAM	1	0	23.50	23.01	22.92	23.05
			2	23.50	23.00	22.99	23.12
			5	23.50	22.98	22.98	23.01
		3	0	23.50	22.97	22.98	23.03
			2	23.50	22.92	22.98	23.01
			3	23.50	22.91	22.95	23.01
		6	0	22.50	22.29	22.18	22.36
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20415	20525	20635
					825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	24.50	24.04	24.03	24.13
			7	24.50	24.10	24.18	24.16
			14	24.50	24.03	24.14	24.09
		8	0	23.50	23.14	23.15	23.26
			4	23.50	23.13	23.16	23.24
			7	23.50	23.16	23.15	23.27
		15	0	23.50	23.13	23.13	23.22
	16QAM	1	0	23.50	22.90	22.91	23.02
			7	23.50	23.06	22.91	23.15
			14	23.50	22.99	22.81	23.01
		8	0	22.50	22.21	22.18	22.28
			4	22.50	22.18	22.19	22.29
			7	22.50	22.17	22.16	22.26
		15	0	22.50	22.13	22.10	22.23

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20425	20525	20625
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	24.50	24.26	24.27	24.40
			13	25.00	24.43	24.38	24.50
			24	24.50	24.33	24.29	24.36
		12	0	23.50	23.22	23.20	23.24
			6	23.50	23.23	23.24	23.27
			13	23.50	23.21	23.22	23.28
		25	0	23.50	23.24	23.21	23.23
	16QAM	1	0	23.50	23.15	23.23	23.26
			13	23.50	23.28	23.41	23.34
			24	23.50	23.15	23.29	23.26
		12	0	22.50	22.23	22.24	22.23
			6	22.50	22.23	22.20	22.26
			13	22.50	22.23	22.21	22.25
		25	0	22.50	22.24	22.23	22.30

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20450	20525	20600
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	24.50	24.32	24.32	24.40
			25	24.50	24.37	24.41	24.45
			49	24.50	24.34	24.44	24.45
		25	0	23.50	23.24	23.12	23.34
			13	23.50	23.24	23.13	23.37
			25	23.50	23.32	23.13	23.36
		50	0	23.50	23.33	23.17	23.39
			0	23.50	23.25	23.12	23.29
			25	23.50	23.31	23.19	23.43
	16QAM	1	49	23.50	23.29	23.21	23.39
		25	0	22.50	22.22	22.12	22.35
			13	22.50	22.24	22.14	22.37
			25	22.50	22.35	22.19	22.39
		50	0	22.50	22.30	22.18	22.44
			0	22.50	22.30	22.18	22.44

Band 7

LTE-FDD Band 7					Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20775	21100	21425
					2502.5MHz	2535.0MHz	2567.5MHz
5MHz	QPSK	1	0	22.50	22.41	22.28	22.28
			12	23.00	22.57	22.39	22.44
			24	22.50	22.44	22.28	22.30
		12	0	21.50	21.39	21.37	21.29
			6	21.50	21.35	21.41	21.31
			13	21.50	21.38	21.34	21.26
		25	0	21.50	21.41	21.39	21.26
	16QAM	1	0	21.50	21.32	21.38	21.20
			12	21.50	21.44	21.45	21.31
			24	21.50	21.39	21.37	21.12
		12	0	20.50	20.39	20.41	20.31
			6	20.50	20.38	20.40	20.32
			13	20.50	20.40	20.40	20.32
		25	0	20.50	20.46	20.42	20.35
			0	20.50	20.46	20.42	20.35
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20800	21100	21400
					2505.0MHz	2535.0MHz	2565.0MHz
10MHz	QPSK	1	0	22.50	22.36	22.42	22.41
			24	22.50	22.48	22.40	22.42
			49	23.00	22.45	22.50	22.25
		25	0	21.50	21.37	21.40	21.38
			12	21.50	21.37	21.37	21.37
			25	21.50	21.45	21.36	21.34
		50	0	21.50	21.48	21.43	21.39
	16QAM	1	0	21.50	21.40	21.29	21.18
			24	22.00	21.50	21.30	21.16
			49	21.50	21.46	21.30	21.10
		25	0	20.50	20.41	20.48	20.40
			12	20.50	20.39	20.43	20.42
			25	20.50	20.48	20.43	20.41
		50	0	20.50	20.46	20.42	20.43
			0	20.50	20.46	20.42	20.43

LTE-FDD Band 7				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20825	21100	21375
					2507.5MHz	2535.0MHz	2562.5MHz
15MHz	QPSK	1	0	22.50	22.21	22.32	22.35
			38	22.50	22.40	22.39	22.43
			74	22.50	22.36	22.38	22.20
		38	0	22.00	21.35	21.35	21.51
			18	22.00	21.54	21.41	21.54
			37	22.00	21.55	21.42	21.36
		75	0	21.50	21.37	21.30	21.36
	16QAM	1	0	22.00	21.37	21.32	21.52
			38	22.00	21.57	21.44	21.57
			74	22.00	21.59	21.44	21.40
		38	0	22.00	21.41	21.37	21.54
			18	22.00	21.62	21.42	21.56
			37	22.00	21.59	21.41	21.41
		75	0	20.50	20.40	20.28	20.42
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20850	21100	21350
					2510.0MHz	2535.0MHz	2560.0MHz
20MHz	QPSK	1	0	22.50	22.21	22.27	22.30
			49	23.00	22.55	22.46	22.48
			99	22.50	22.46	22.42	22.22
		50	0	21.50	21.25	21.30	21.34
			25	21.50	21.26	21.36	21.37
			50	22.00	21.50	21.29	21.43
		100	0	21.50	21.41	21.33	21.44
	16QAM	1	0	21.50	21.12	21.35	21.15
			49	22.00	21.43	21.55	21.33
			99	22.00	21.37	21.53	21.00
		50	0	20.50	20.28	20.39	20.46
			25	20.50	20.29	20.36	20.43
			50	21.00	20.53	20.34	20.49
		100	0	20.50	20.45	20.33	20.43

Band 12

LTE-FDD Band 12				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23017	23095	23173
					699.7MHz	707.5MHz	715.3MHz
1.4MHz	QPSK	1	0	24.50	24.11	24.22	23.82
			2	24.50	24.17	24.23	23.93
			5	24.50	24.16	24.15	23.83
		3	0	24.50	24.20	24.22	24.25
			2	24.50	24.23	24.22	24.25
			3	24.50	24.17	24.21	24.24
		6	0	23.50	23.33	23.20	23.07
	16QAM	1	0	23.50	23.04	22.94	23.04
			2	23.50	23.08	23.01	23.19
			5	23.50	23.02	22.93	23.07
		3	0	23.50	22.99	23.07	23.08
			2	23.50	23.01	23.02	23.13
			3	23.50	22.96	23.01	23.12
		6	0	22.50	22.31	22.27	22.28

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 35 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23025	23095	23165
					700.5MHz	707.5MHz	714.5MHz
3MHz	QPSK	1	0	24.50	24.00	24.07	23.96
			7	24.50	24.12	24.19	23.88
			14	24.50	24.00	24.05	23.86
		8	0	23.50	23.25	23.16	23.08
			4	23.50	23.26	23.16	23.08
			7	23.50	23.16	23.24	23.15
		15	0	23.50	23.17	23.18	23.15
	16QAM	1	0	23.50	22.94	23.07	22.75
			7	23.50	23.02	23.04	22.85
			14	23.50	23.01	22.85	22.78
		8	0	22.50	22.23	22.18	22.17
			4	22.50	22.19	22.15	22.17
			7	22.50	22.12	22.16	22.31
		15	0	22.50	22.13	22.07	22.22
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23035	23095	23155
					701.5MHz	707.5MHz	713.5MHz
5MHz	QPSK	1	0	24.50	24.29	24.29	24.26
			13	24.50	24.42	24.40	24.29
			24	24.50	24.29	24.23	24.11
		12	0	23.50	23.40	23.16	23.48
			6	24.00	23.45	23.15	23.53
			13	23.50	23.25	23.38	23.28
		25	0	24.00	23.41	23.30	23.53
	16QAM	1	0	24.00	23.14	23.50	23.10
			13	23.50	23.27	23.46	23.29
			24	23.50	23.33	23.24	23.28
		12	0	23.00	22.38	22.14	22.52
			6	23.00	22.39	22.14	22.50
			13	22.50	22.25	22.39	22.44
		25	0	23.00	22.43	22.28	22.55
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23060	23095	23130
					704.0MHz	707.5MHz	711.0MHz
10MHz	QPSK	1	0	24.50	24.26	24.25	24.45
			25	24.50	24.39	24.37	24.32
			49	24.50	24.37	24.40	24.27
		25	0	24.00	23.54	22.98	23.00
			13	24.00	23.55	23.02	23.00
			25	24.00	23.82	23.16	23.04
		50	0	24.00	23.68	23.03	23.08
	16QAM	1	0	23.50	23.26	23.28	23.16
			25	24.00	23.54	23.30	23.01
			49	23.50	23.33	23.15	23.20
		25	0	23.00	22.53	22.06	22.04
			13	23.00	22.55	22.02	22.02
			25	23.00	22.77	22.12	22.05
		50	0	23.00	22.70	22.07	22.08

Band 14

LTE-FDD Band 14				Maximum Tune-up(dBm)	Conducted Power(dBm)			
Bandwidth	Modulation	RB allocation	RB offset		23305	23330	23355	
					790.5MHz	793.0MHz	795.5MHz	
5MHz	QPSK	1	0	24.50	24.19	24.20	24.28	
			12	24.50	24.38	24.46	24.39	
			24	24.50	24.26	24.25	24.34	
		12	0	23.50	23.37	23.25	23.20	
			6	23.50	23.37	23.29	23.23	
			13	23.50	23.33	23.37	23.22	
		25	0	23.50	23.37	23.33	23.24	
		16QAM	1	0	23.50	23.29	23.22	23.19
				12	24.00	23.51	23.36	23.36
	24			23.50	23.41	23.23	23.26	
	12		0	22.50	22.36	22.26	22.19	
			6	22.50	22.39	22.25	22.20	
	13	22.50	22.30	22.32	22.20			
	25	0	22.50	22.36	22.36	22.24		
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23330			
					793.0MHz			
10MHz	QPSK	1	0	24.50	24.31			
			25	24.50	24.40			
			49	24.50	24.29			
		25	0	23.50	23.27			
			13	23.50	23.29			
			25	23.50	23.32			
		50	0	23.50	23.36			
		16QAM	1	0	23.50	23.34		
				25	23.50	23.43		
	49			23.50	23.41			
	25		0	22.50	22.27			
			13	22.50	22.29			
			25	22.50	22.33			
	50		0	22.50	22.33			

Band 17

LTE-FDD Band 17				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23755	23790	23825
					706.5MHz	710MHz	713.5MHz
5MHz	QPSK	1	0	24.50	24.34	24.39	24.22
			13	25.00	24.58	24.42	24.27
			24	24.50	24.30	24.25	24.10
		12	0	24.00	23.24	23.07	23.50
			6	24.00	23.22	23.08	23.52
			13	24.00	23.61	23.01	23.32
		25	0	23.50	23.47	23.07	23.46
	16QAM	1	0	23.50	23.36	23.23	23.18
			13	23.50	23.40	23.32	23.48
			24	23.50	23.21	23.22	23.42
		12	0	23.00	22.18	22.02	22.54
			6	22.50	22.12	22.05	22.49
			13	23.00	22.48	21.90	22.52
		25	0	23.00	22.47	22.08	22.50

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23780	23790	23800
					709MHz	710MHz	711MHz
10MHz	QPSK	1	0	24.50	24.30	24.38	24.36
			25	24.50	24.31	24.36	24.33
			49	24.50	24.26	24.21	24.26
		25	0	23.50	22.87	22.90	23.03
			13	23.50	22.89	22.92	23.06
			25	23.50	22.74	22.85	23.10
		50	0	23.50	22.83	22.89	23.07
			0	23.50	23.42	23.43	23.13
			25	23.50	23.28	23.13	23.11
	16QAM	1	49	23.50	23.30	23.26	23.17
			0	22.50	21.84	21.89	22.03
			13	22.50	21.85	21.88	22.01
		25	25	22.50	21.75	21.83	22.08
			0	22.50	21.78	21.85	22.10
			0	22.50	21.78	21.85	22.10
		50	0	22.50	21.78	21.85	22.10

Band 25

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26047	26365	26683
					1850.7MHz	1882.5MHz	1914.3MHz
1.4MHz	QPSK	1	0	23.00	22.77	22.71	22.54
			2	23.00	22.77	22.70	22.48
			5	23.00	22.75	22.72	22.49
		3	0	23.00	22.89	22.87	22.74
			2	23.00	22.93	22.85	22.70
			3	23.00	22.84	22.86	22.66
		6	0	22.00	21.86	21.86	21.73
	16QAM	1	0	22.00	21.57	21.50	21.49
			2	22.00	21.59	21.51	21.47
			5	22.00	21.58	21.45	21.40
		3	0	22.00	21.71	21.60	21.48
			2	22.00	21.75	21.66	21.48
			3	22.00	21.68	21.59	21.48
		6	0	21.00	20.73	20.81	20.78
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26055	26365	26675
					1851.5MHz	1882.5MHz	1913.5MHz
3MHz	QPSK	1	0	23.00	22.63	22.63	22.43
			7	23.00	22.71	22.68	22.54
			14	23.00	22.57	22.63	22.46
		8	0	22.00	21.80	21.78	21.63
			4	22.00	21.81	21.76	21.66
			7	22.00	21.84	21.81	21.67
		15	0	22.00	21.86	21.84	21.63
	16QAM	1	0	22.00	21.59	21.47	21.14
			7	22.00	21.71	21.53	21.28
			14	22.00	21.62	21.44	21.20
		8	0	21.00	20.81	20.75	20.63
			4	21.00	20.85	20.77	20.64
			7	21.00	20.84	20.77	20.63
		15	0	21.00	20.87	20.75	20.61

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26065	26365	26665
					1852.5MHz	1882.5MHz	1912.5MHz
5MHz	QPSK	1	0	23.00	22.89	22.91	22.76
			13	23.50	22.99	23.01	22.84
			24	23.00	22.94	22.90	22.66
		12	0	22.00	21.94	21.83	21.79
			6	22.00	21.93	21.84	21.77
			13	22.00	21.96	21.92	21.72
		25	0	22.00	21.98	21.86	21.76
			0	22.50	22.02	21.84	21.75
			13	22.50	22.11	21.91	21.96
	16QAM	1	24	22.00	21.99	21.85	21.77
			0	21.00	20.99	20.86	20.88
			6	21.50	21.04	20.80	20.85
		12	13	21.00	20.94	20.86	20.75
			25	21.00	20.97	20.99	20.75
			0	21.00	20.97	20.99	20.75
			0	21.00	20.97	20.99	20.75

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26090	26365	26640
					1855.0MHz	1882.5MHz	1910.0MHz
10MHz	QPSK	1	0	23.00	22.90	22.98	22.85
			25	23.00	22.98	22.93	22.80
			49	23.00	22.97	22.97	22.77
		25	0	22.00	21.97	21.82	21.75
			13	22.00	21.94	21.79	21.70
			25	22.50	22.00	21.91	21.57
		50	0	22.00	21.99	21.93	21.66
			0	22.00	21.97	21.80	21.58
			25	22.00	21.98	21.77	21.54
	16QAM	1	49	22.50	22.05	21.78	21.55
			0	21.00	20.94	20.85	20.75
			13	21.00	20.98	20.88	20.77
		25	25	21.50	21.01	20.95	20.68
			0	21.00	20.98	20.97	20.73
			0	21.00	20.98	20.97	20.73
		0	21.00	20.98	20.97	20.73	
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26115	26365	26615
					1857.5MHz	1882.5MHz	1907.5MHz
15MHz	QPSK	1	0	23.00	22.88	22.78	22.89
			38	23.50	23.11	22.85	22.90
			74	23.00	22.97	22.80	22.76
		36	0	22.00	21.90	21.99	21.66
			18	22.50	22.09	22.05	21.70
			39	22.50	22.03	22.03	21.55
		75	0	22.50	22.00	21.89	21.79
			0	22.00	21.90	21.98	21.66
			38	22.50	22.12	22.06	21.70
	16QAM	1	74	22.50	22.03	22.02	21.47
			0	22.00	21.94	21.95	21.67
			18	22.50	22.09	22.03	21.70
		36	39	22.50	22.07	21.96	21.50
			0	21.00	20.95	20.87	20.79
			0	21.00	20.95	20.87	20.79
		0	21.00	20.95	20.87	20.79	

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26140	26365	26590
					1860.0MHz	1882.5MHz	1905.0MHz
20MHz	QPSK	1	0	23.00	22.82	22.87	22.71
			50	23.50	23.14	22.94	22.91
			99	23.00	22.99	22.84	22.60
		50	0	22.00	21.95	21.83	21.89
			25	22.00	21.97	21.89	21.90
			50	22.50	22.04	21.99	21.76
		100	0	22.50	22.00	21.86	21.81
	16QAM	1	0	22.00	21.73	21.94	21.55
			50	22.50	22.01	22.11	21.72
			99	22.50	21.89	22.01	21.46
		50	0	21.00	20.97	20.88	20.91
			25	21.50	21.04	20.87	20.95
			50	21.50	21.05	21.01	20.80
		100	0	21.50	21.01	20.87	20.87

Band 26 Part90

LTE-FDD Band 26 Part90				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26697	26740	26783
					814.7MHz	819.0MHz	823.3MHz
1.4MHz	QPSK	1	0	24.50	24.31	24.39	24.16
			2	24.50	24.27	24.34	24.14
			5	24.50	24.25	24.33	24.11
		3	0	24.50	24.32	24.33	24.19
			2	24.50	24.40	24.36	24.22
			3	24.50	24.32	24.34	24.14
		6	0	23.50	23.46	23.42	23.31
	16QAM	1	0	23.50	23.21	23.15	23.01
			2	23.50	23.24	23.17	23.03
			5	23.50	23.19	23.11	22.94
		3	0	23.50	23.16	23.13	22.97
			2	23.50	23.14	23.16	22.96
			3	23.50	23.12	23.11	22.92
		6	0	23.00	22.50	22.32	22.34
					26705	26740	26775
					815.5MHz	819.0MHz	822.5MHz
3MHz	QPSK	1	0	24.50	24.25	24.18	24.06
			7	24.50	24.31	24.23	24.14
			14	24.50	24.20	24.15	24.03
		8	0	23.50	23.32	23.30	23.19
			4	23.50	23.30	23.27	23.19
			7	23.50	23.36	23.33	23.23
		15	0	23.50	23.33	23.27	23.20
	16QAM	1	0	23.50	23.06	22.91	22.99
			7	23.50	23.16	23.01	23.07
			14	23.50	23.01	22.83	23.01
		8	0	22.50	22.34	22.32	22.22
			4	22.50	22.36	22.30	22.25
			7	22.50	22.39	22.36	22.15
		15	0	22.50	22.25	22.25	22.20

LTE-FDD Band 26 Part90				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26715	26740	26765
					816.5MHz	819.0MHz	821.5MHz
5MHz	QPSK	1	0	24.50	24.41	24.41	24.45
			13	25.00	24.50	24.56	24.49
			24	24.50	24.41	24.37	24.32
		12	0	23.50	23.40	23.25	23.25
			6	23.50	23.35	23.27	23.23
			13	24.00	23.52	23.40	23.20
	25	0	23.50	23.49	23.36	23.24	
	16QAM	1	0	23.50	23.45	23.27	23.27
			13	24.00	23.55	23.36	23.35
			24	23.50	23.45	23.20	23.18
		12	0	22.50	22.40	22.25	22.22
			6	22.50	22.41	22.28	22.24
			13	23.00	22.53	22.38	22.19
		25	0	22.50	22.44	22.41	22.30
Bandwidth		Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26740	
	819.0MHz						
10MHz	QPSK	1	0	24.50	24.49		
			25	25.00	24.51		
			49	24.50	24.41		
		25	0	23.50	23.23		
			13	23.50	23.18		
			25	23.50	23.33		
	50	0	23.50	23.28			
	16QAM	1	0	23.50	23.30		
			25	23.50	23.33		
			49	23.50	23.17		
		25	0	22.50	22.25		
			13	22.50	22.19		
			25	22.50	22.39		
		50	0	22.50	22.30		

Band 26 Part22

LTE-FDD Band 26 Part22				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26797	26915	27033
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	23.50	23.16	23.16	23.20
			2	23.50	23.16	23.22	23.19
			5	23.50	23.09	23.18	23.19
		3	0	23.50	23.20	23.23	23.21
			2	23.50	23.18	23.22	23.27
			3	23.50	23.16	23.25	23.22
	6	0	22.50	22.29	22.31	22.34	
	16QAM	1	0	22.50	22.01	21.91	22.06
			2	22.50	22.03	21.95	22.08
			5	22.50	21.98	21.90	22.00
		3	0	22.00	21.98	21.94	21.99
			2	22.00	21.96	21.96	21.98
			3	22.50	21.93	21.94	22.00
		6	0	21.50	21.32	21.33	21.38

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26805	26915	27025
					825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	23.50	23.03	23.05	23.13
			7	23.50	23.15	23.17	23.22
			14	23.50	23.00	23.11	23.12
		8	0	22.50	22.16	22.20	22.31
			4	22.50	22.19	22.16	22.27
			7	22.50	22.21	22.22	22.30
		15	0	22.50	22.13	22.20	22.26
	16QAM	1	0	22.50	21.91	21.82	22.00
			7	22.50	22.08	21.91	22.14
			14	22.50	21.99	21.86	22.08
		8	0	21.50	21.18	21.17	21.35
			4	21.50	21.23	21.18	21.31
			7	21.50	21.24	21.18	21.25
		15	0	21.50	21.12	21.12	21.25

LTE-FDD Band 26 Part22				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26815	26915	27015
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	23.50	23.28	23.21	23.41
			13	24.00	23.42	23.39	23.51
			24	23.50	23.33	23.31	23.38
		12	0	22.50	22.31	22.24	22.24
			6	22.50	22.30	22.20	22.26
			13	22.50	22.21	22.20	22.25
		25	0	22.50	22.26	22.23	22.25
	16QAM	1	0	22.50	22.16	22.21	22.29
			13	22.50	22.31	22.41	22.38
			24	22.50	22.16	22.35	22.26
		12	0	21.50	21.23	21.25	21.23
			6	21.50	21.25	21.24	21.27
			13	21.50	21.23	21.28	21.27
		25	0	21.50	21.24	21.21	21.33
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26840	26915	26990
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	23.50	23.30	23.28	23.40
			25	23.50	23.35	23.35	23.48
			49	23.50	23.33	23.38	23.42
		25	0	22.50	22.24	22.09	22.35
			13	22.50	22.25	22.09	22.39
			25	22.50	22.28	22.15	22.34
		50	0	22.50	22.26	22.09	22.40
	16QAM	1	0	22.50	22.28	22.07	22.35
			25	22.50	22.30	22.16	22.42
			49	22.50	22.26	22.20	22.35
		25	0	21.50	21.26	21.11	21.38
			13	21.50	21.24	21.14	21.39
			25	21.50	21.34	21.19	21.32
		50	0	21.50	21.27	21.11	21.40

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26865	26915	26965
					831.5MHz	836.5MHz	841.5MHz
15MHz	QPSK	1	0	23.50	23.25	23.18	23.28
			38	23.50	23.40	23.33	23.48
			74	23.50	23.35	23.32	23.36
		36	0	22.50	22.22	22.28	22.19
			18	22.50	22.34	22.40	22.43
			39	22.50	22.33	22.44	22.35
		75	0	22.50	22.29	22.15	22.44
	16QAM	1	0	22.50	22.22	22.28	22.20
			38	22.50	22.31	22.46	22.44
			74	22.50	22.30	22.44	22.35
		36	0	22.50	22.20	22.28	22.23
			18	22.50	22.34	22.38	22.47
			39	22.50	22.35	22.41	22.31
		75	0	21.50	21.24	21.18	21.41

Band 41

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		39675	40620	41565
					2498.5MHz	2593.0MHz	2687.5MHz
5MHz	QPSK	1	0	24.00	23.57	23.45	23.56
			13	24.00	23.72	23.56	23.67
			24	24.00	23.60	23.44	23.56
		12	0	22.50	22.49	22.44	22.47
			6	23.00	22.51	22.47	22.48
			13	23.00	22.50	22.47	22.51
		25	0	23.00	22.54	22.46	22.49
	16QAM	1	0	22.50	22.48	22.48	22.34
			13	23.00	22.59	22.59	22.49
			24	22.50	22.46	22.45	22.43
		12	0	21.50	21.48	21.49	21.45
			6	21.50	21.47	21.49	21.47
			13	22.00	21.50	21.48	21.45
		25	0	22.00	21.57	21.44	21.51
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39700	40620	41540
					2501.0MHz	2593.0MHz	2685.0MHz
10MHz	QPSK	1	0	24.00	23.61	23.53	23.56
			25	24.00	23.69	23.59	23.62
			49	24.00	23.62	23.51	23.60
		25	0	23.00	22.54	22.49	22.48
			13	23.00	22.52	22.49	22.49
			25	23.00	22.53	22.54	22.51
		50	0	23.00	22.58	22.55	22.55
	16QAM	1	0	22.50	22.46	22.28	22.46
			25	23.00	22.47	22.29	22.51
			49	23.00	22.38	22.25	22.50
		25	0	22.00	21.58	21.54	21.47
			13	22.00	21.57	21.51	21.44
			25	22.00	21.59	21.53	21.50
		50	0	22.00	21.55	21.53	21.53

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		39725	40620	41515
					2503.5MHz	2593.0MHz	2682.5MHz
15MHz	QPSK	1	0	24.00	23.45	23.50	23.52
			38	24.00	23.57	23.59	23.63
			74	24.00	23.36	23.42	23.56
		36	0	23.00	22.58	22.21	22.44
			18	23.00	22.65	22.33	22.51
			39	22.50	22.48	22.18	22.47
		75	0	23.00	22.50	22.55	22.68
	16QAM	1	0	23.00	22.58	22.25	22.42
			38	23.00	22.65	22.33	22.52
			74	22.50	22.48	22.21	22.47
		36	0	23.00	22.56	22.24	22.42
			18	23.00	22.65	22.35	22.53
			39	22.50	22.47	22.16	22.49
		75	0	22.00	21.53	21.53	21.54
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39750	40620	41490
					2506.0MHz	2593.0MHz	2680.0MHz
20MHz	QPSK	1	0	23.00	22.43	22.31	22.52
			50	24.00	23.62	23.61	23.77
			99	24.00	23.35	23.40	23.60
		50	0	23.00	22.42	22.43	22.50
			25	22.50	22.43	22.42	22.47
			50	23.00	22.43	22.51	22.55
		100	0	23.00	22.39	22.45	22.54
	16QAM	1	0	22.00	21.55	21.18	21.35
			50	23.00	22.72	22.41	22.43
			99	22.50	22.44	22.22	22.34
		50	0	21.50	21.49	21.48	21.46
			25	21.50	21.45	21.47	21.49
			50	22.00	21.46	21.56	21.51
		100	0	21.50	21.43	21.49	21.45

Band 66

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		131979	132322	132665
					1710.7MHz	1745.0MHz	1779.3MHz
1.4MHz	QPSK	1	0	23.50	23.22	23.32	23.28
			2	23.50	23.22	23.24	23.27
			5	23.50	23.22	23.25	23.27
		3	0	23.50	23.29	23.31	23.37
			2	23.50	23.34	23.33	23.38
			3	23.50	23.28	23.41	23.38
		6	0	22.50	22.42	22.43	22.40
	16QAM	1	0	22.50	22.11	22.09	22.09
			2	22.50	22.14	22.10	22.16
			5	22.50	22.15	22.10	22.11
		3	0	22.50	22.08	22.21	22.17
			2	22.50	22.10	22.18	22.16
			3	22.50	22.08	22.20	22.13
		6	0	21.50	21.38	21.24	21.44

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 44 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131987	132322	132657
					1711.5MHz	1745.0MHz	1778.5MHz
3MHz	QPSK	1	0	23.50	23.17	23.14	23.23
			7	23.50	23.30	23.31	23.35
			14	23.50	23.24	23.16	23.27
		8	0	22.50	22.37	22.31	22.43
			4	22.50	22.35	22.37	22.41
			7	22.50	22.38	22.43	22.44
		15	0	22.50	22.36	22.43	22.44
			0	22.50	22.11	22.20	22.25
			7	22.50	22.26	22.21	22.37
	16QAM	1	14	22.50	22.20	22.22	22.19
			0	21.50	21.35	21.39	21.42
			4	21.50	21.34	21.38	21.40
		8	7	21.50	21.38	21.37	21.45
			0	21.50	21.35	21.43	21.48
			0	21.50	21.35	21.43	21.48
		15	0	21.50	21.35	21.43	21.48
			0	21.50	21.35	21.43	21.48
			0	21.50	21.35	21.43	21.48
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131997	132322	132647
					1712.5MHz	1745.0MHz	1777.5MHz
5MHz	QPSK	1	0	24.00	23.42	23.51	23.61
			13	24.00	23.69	23.70	23.62
			24	24.00	23.54	23.50	23.51
		12	0	23.00	22.37	22.48	22.51
			6	23.00	22.37	22.50	22.55
			13	23.00	22.51	22.50	22.50
		25	0	22.50	22.48	22.46	22.48
			0	22.50	22.32	22.39	22.44
			13	23.00	22.47	22.56	22.57
	16QAM	1	24	22.50	22.42	22.44	22.44
			0	21.50	21.28	21.42	21.44
			6	21.50	21.34	21.43	21.46
		12	13	21.50	21.41	21.47	21.41
			0	22.00	21.46	21.48	21.51
			0	22.00	21.46	21.48	21.51
		25	0	22.00	21.46	21.48	21.51
			0	22.00	21.46	21.48	21.51
			0	22.00	21.46	21.48	21.51
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132022	132322	132622
					1715.0MHz	1745.0MHz	1775.0MHz
10MHz	QPSK	1	0	24.00	23.45	23.55	23.60
			25	24.00	23.54	23.54	23.64
			49	24.00	23.64	23.57	23.60
		25	0	23.00	22.30	22.42	22.57
			13	23.00	22.33	22.43	22.59
			25	23.00	22.50	22.49	22.53
		50	0	23.00	22.45	22.46	22.60
			0	23.00	22.39	22.54	22.56
			25	23.00	22.52	22.54	22.67
	16QAM	1	49	23.00	22.60	22.62	22.61
			0	22.00	21.23	21.42	21.62
			13	22.00	21.28	21.43	21.60
		25	25	22.00	21.45	21.43	21.53
			0	22.00	21.42	21.45	21.58
			0	22.00	21.42	21.45	21.58
		50	0	22.00	21.42	21.45	21.58
			0	22.00	21.42	21.45	21.58
			0	22.00	21.42	21.45	21.58

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		132047	132322	132597		
					1717.5MHz	1745.0MHz	1772.5MHz		
15MHz	QPSK	1	0	24.00	23.43	23.52	23.58		
			38	24.00	23.67	23.60	23.72		
			74	24.00	23.67	23.61	23.51		
		36	0	23.00	22.37	22.46	22.60		
			18	23.00	22.66	22.62	22.70		
			39	23.00	22.64	22.60	22.59		
		75	0	23.00	22.56	22.57	22.65		
			16QAM	1	0	23.00	22.40	22.50	22.57
					38	23.00	22.62	22.59	22.71
	74	23.00			22.61	22.61	22.56		
	36	0		23.00	22.40	22.51	22.58		
		18		23.00	22.63	22.63	22.67		
		39		23.00	22.63	22.55	22.59		
	75	0		22.00	21.49	21.46	21.57		
	Bandwidth	Modulation		RB allocation	RB offset	Maximum Tune-up(dBm)	132072	132322	132572
1720.0MHz							1745.0MHz	1770.0MHz	
20MHz	QPSK	1	0	24.00	23.31	23.45	23.55		
			50	24.00	23.72	23.63	23.75		
			99	24.00	23.65	23.58	23.54		
		50	0	23.00	22.35	22.46	22.60		
			25	23.00	22.37	22.46	22.55		
			50	23.00	22.65	22.54	22.57		
		100	0	23.00	22.57	22.49	22.53		
			16QAM	1	0	22.50	22.15	22.33	22.43
					50	23.00	22.55	22.51	22.60
	99	22.50			22.46	22.49	22.37		
	50	0		22.00	21.30	21.42	21.55		
		25		22.00	21.32	21.43	21.53		
		50		22.00	21.64	21.55	21.57		
	100	0		22.00	21.48	21.54	21.53		

8.4 Wi-Fi

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	16.31	16.50	No
		6	2437	16.75	17.00	Yes
		11	2462	16.70	17.00	No
	802.11g	1	2412	16.22	16.50	No
		6	2437	15.56	16.00	No
		11	2462	15.60	16.00	No
	802.11n(HT20)	1	2412	13.18	13.50	No
		6	2437	15.47	15.50	No
		11	2462	14.51	15.00	No

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	11.46	11.50	No
		40	5200	12.01	12.50	No
		48	5240	12.14	12.50	Yes
	802.11n(HT20)	36	5180	11.44	11.50	No
		40	5200	11.86	12.00	No
		48	5240	12.03	12.50	No
	802.11ac(VHT20)	36	5180	11.47	11.50	No
		40	5200	11.99	12.00	No
		48	5240	12.04	12.50	No
	802.11n(HT40)	38	5190	11.39	11.50	No
		46	5230	11.83	12.00	No
	802.11ac(VHT40)	38	5190	10.49	10.50	No
		46	5230	10.87	11.00	No
	802.11ac(VHT80)	42	5210	10.35	10.50	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2a (5.250~5.350)	802.11a	52	5260	11.53	12.00	No
		56	5280	11.16	11.50	No
		64	5320	9.48	9.50	No
	802.11n(HT20)	52	5260	11.64	12.00	No
		56	5280	11.04	11.50	No
		64	5320	9.39	9.50	No
	802.11ac(VHT20)	52	5260	11.73	12.00	Yes
		56	5280	10.56	11.00	No
		64	5320	9.15	9.50	No
	802.11n(HT40)	54	5270	10.70	11.00	No
		62	5310	9.17	9.50	No
	802.11ac(VHT40)	54	5270	11.15	11.50	No
		62	5310	9.19	9.50	No
	802.11ac(VHT80)	58	5290	10.13	10.50	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2c (5.470~5.725)	802.11a	100	5500	10.97	11.00	No
		120	5600	12.11	12.50	No
		140	5700	10.91	11.00	No
	802.11n(HT20)	100	5500	10.91	11.00	No
		120	5600	12.16	12.50	No
		140	5700	10.82	11.00	No
	802.11ac(VHT20)	100	5500	11.55	12.00	No
		120	5600	12.33	12.50	Yes
		140	5700	11.25	11.50	No
	802.11n(HT40)	102	5510	11.11	11.50	No
		118	5590	11.68	12.00	No
		134	5670	11.02	11.50	No
	802.11ac(VHT40)	102	5510	11.45	11.50	No
		118	5590	11.88	12.00	No
		134	5670	11.02	11.50	No
	802.11ac(VHT80)	106	5530	11.32	11.50	No
		122	5610	10.80	11.00	No

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	10.04	10.50	No
		157	5785	11.73	12.00	No
		165	5825	12.13	12.50	Yes
	802.11n(HT20)	149	5745	10.15	10.50	No
		157	5785	11.73	12.00	No
		165	5825	12.06	12.50	No
	802.11ac(VHT20)	149	5745	10.07	10.50	No
		157	5785	11.60	12.00	No
		165	5825	12.04	12.50	No
	802.11n(HT40)	151	5755	9.66	10.00	No
		159	5795	11.60	12.00	No
	802.11ac(VHT40)	151	5755	10.22	10.50	No
		159	5795	11.60	12.00	No
	802.11ac(VHT80)	155	5775	10.79	11.00	No

8.5 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
	GFSK	13.50	11.25	11.22	13.06
	$\pi/4$ QPSK	12.50	10.58	10.36	12.01
BLE	8DPSK	12.00	10.78	10.69	12.00
	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	19	39
			2402MHz	2440MHz	2480MHz
	1Mbps	-2.50	-2.96	-3.45	-3.99

8.6 NFC

Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)
	13.56MHz
12.00	11.57

Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Exclusion thresholds for 1-g SAR(mW)	RF exposure evaluation required
78	2.480	13.50	22.39	0	10	Yes
/	0.01356	12.00	15.85	0	39	No

Note

- Per KDB 447498 D01 General RF Exposure Guidance v06, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances* ≤ 40 cm are determined by:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

*When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR. .

- The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


Page 48 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

9. Test Exclusion Consideration

Antenna information:



WWAN Antenna	GSM/WCDMA/LTE TX/RX
WLAN Antenna	BT/WLAN TX/RX
NFC Antenna	NFC TX/RX
Note: 1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. 2. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg.	

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	<25	<25	<25	150	40	180
WIFI/BT	<25	<25	<25	150	180	40
Positions for SAR tests						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	No	Yes	Yes	No	Yes	No
WIFI/BT	No	Yes	Yes	No	No	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

$$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Mode	Channel	Frequency (GHz)	Max tune-up power (dBm)	Max. Power (mW)	Exposure Position	Body-worn
NFC	/	0.01356	12.00	15.85	Test Dist.(mm)	0
					Estimated SAR(W/kg)	0.049

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 49 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

10. Test Result

Body 1g SAR Data

Band	Mode	Test Position with 0 mm	CH.	Freq. (MHz)	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)	Meas. No.
GSM 850	GPRS 4slots	Back	128	824.2	31.25	31.50	-4.950	0.861	1.059	0.912	1#
		Back	190	836.6	31.14	31.50	2.110	0.776	1.086	0.843	/
		Back	251	848.8	31.14	31.50	-0.340	0.761	1.086	0.826	/
		Back(repeated)	128	824.2	31.25	31.50	3.970	0.839	1.059	0.889	/
		Left	128	824.2	31.25	31.50	0.260	0.592	1.059	0.627	/
		Top	128	824.2	31.25	31.50	1.270	0.325	1.059	0.344	/
GSM 1900	GPRS 4slots	Back	512	1850.2	29.60	30.00	2.370	0.254	1.096	0.278	2#
		Left	512	1850.2	29.60	30.00	4.950	0.125	1.096	0.137	/
		Top	512	1850.2	29.60	30.00	-0.660	0.078	1.096	0.085	/
WCDMA Band II	RMC	Back	9538	1907.6	22.34	22.50	-3.370	0.492	1.038	0.511	3#
		Left	9538	1907.6	22.34	22.50	0.420	0.285	1.038	0.296	/
		Top	9538	1907.6	22.34	22.50	-2.480	0.103	1.038	0.107	/
WCDMA Band V	RMC	Back	4183	836.6	22.45	22.50	-4.080	0.652	1.012	0.660	4#
		Left	4183	836.6	22.45	22.50	1.790	0.423	1.012	0.428	/
		Top	4183	836.6	22.45	22.50	3.150	0.112	1.012	0.113	/
2.4 (2.4~2.4835)	802.11b	Back	6	2437	16.75	17.00	2.730	0.503	1.059	0.533	17#
		Left	6	2437	16.75	17.00	1.360	0.374	1.059	0.396	/
U-NII-1 (5.150~5.250)	802.11a	Back	48	5240	12.14	12.50	-4.840	0.407	1.086	0.442	18#
		Left	48	5240	12.14	12.50	2.350	0.213	1.086	0.231	/
U-NII-2a (5.250~5.350)	802.11ac (VHT20)	Back	52	5260	11.73	12.00	-1.130	0.564	1.064	0.600	19#
		Left	52	5260	11.73	12.00	0.890	0.402	1.064	0.428	/
U-NII-2c (5.470~5.725)	802.11ac (VHT20)	Back	120	5600	12.33	12.50	2.320	0.214	1.040	0.223	20#
		Left	120	5600	12.33	12.50	-1.620	0.101	1.040	0.105	/
U-NII-3 (5.725~5.850)	802.11a	Back	165	5825	12.13	12.50	-3.150	0.454	1.089	0.494	21#
		Left	165	5825	12.13	12.50	4.490	0.296	1.089	0.322	/
Bluetooth	Bluetooth	Back	78	2480	13.06	13.50	3.460	0.540	1.107	0.598	22#
		Left	78	2480	13.06	13.50	2.550	0.268	1.107	0.297	/

Band	Mode	Test Position with 0 mm	CH.	Freq. (MHz)	RB allocation	RB offset	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)	Meas. No.
LTE Band 2	QPSK (20MHz)	Back	18700	1860.0	1	50	23.08	23.50	-1.410	0.873	1.102	0.962	5#
					50	50	22.06	22.50	1.230	0.576	1.107	0.638	/
		Back	18900	1880.0	1	50	22.91	23.00	0.110	0.659	1.021	0.673	/
					1	50	22.93	23.00	4.560	0.687	1.016	0.698	/
		Back(repeated)	18700	1860.0	1	50	23.08	23.50	-3.970	0.831	1.102	0.916	/
					1	50	23.08	23.50	-1.240	0.601	1.102	0.662	/
		Left	18700	1860.0	1	50	22.06	22.50	1.930	0.425	1.107	0.470	/
					50	50	22.06	22.50	1.930	0.425	1.107	0.470	/
		Top	18700	1860.0	1	50	23.08	23.50	-2.490	0.214	1.102	0.236	/
					50	50	22.06	22.50	4.810	0.112	1.107	0.124	/
LTE Band 4	QPSK (20MHz)	Back	20300	1745.0	1	50	23.13	23.50	-4.070	0.474	1.089	0.516	6#
					50	50	22.12	22.50	2.150	0.231	1.091	0.252	/
		Left	20300	1745.0	1	50	23.13	23.50	0.420	0.322	1.089	0.351	/
					50	50	22.12	22.50	-1.520	0.176	1.091	0.192	/
		Top	20300	1745.0	1	50	23.13	23.50	2.640	0.102	1.089	0.111	/
					50	50	22.12	22.50	-0.790	0.089	1.091	0.097	/

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 50 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

LTE Band 5	QPSK (10MHz)	Back	20600	844.0	1	25	24.45	24.50	-4.360	0.501	1.012	0.507	7#
					25	13	23.37	23.50	2.740	0.403	1.030	0.415	/
		Left	20600	844.0	1	25	24.45	24.50	-3.230	0.368	1.012	0.372	/
					25	13	23.37	23.50	0.970	0.287	1.030	0.296	/
		Top	20600	844.0	1	25	24.45	24.50	1.520	0.120	1.012	0.121	/
					25	13	23.37	23.50	-2.460	0.098	1.030	0.101	/
LTE Band 7	QPSK (20MHz)	Back	20850	2510.0	1	49	22.55	23.00	-0.680	0.720	1.109	0.798	8#
					50	50	21.50	22.00	3.120	0.554	1.122	0.622	/
		Left	20850	2510.0	1	49	22.55	23.00	-4.990	0.531	1.109	0.589	/
					50	50	21.50	22.00	2.780	0.369	1.122	0.414	/
		Top	20850	2510.0	1	49	22.55	23.00	-1.560	0.205	1.109	0.227	/
					50	50	21.50	22.00	4.910	0.117	1.122	0.131	/
LTE Band 12	QPSK (10MHz)	Back	23130	711.0	1	0	24.45	24.50	-3.290	0.356	1.012	0.360	9#
					25	25	23.04	23.50	1.340	0.216	1.112	0.240	/
		Left	23130	711.0	1	0	24.45	24.50	0.770	0.188	1.012	0.190	/
					25	25	23.04	23.50	4.870	0.098	1.112	0.109	/
		Top	23130	711.0	1	0	24.45	24.50	1.480	0.087	1.012	0.088	/
					25	25	23.04	23.50	-2.160	0.053	1.112	0.059	/
LTE Band 14	QPSK (10MHz)	Back	23330	793.0	1	25	24.40	24.50	1.710	0.572	1.023	0.585	10#
					25	25	23.32	23.50	2.910	0.411	1.042	0.428	/
		Left	23330	793.0	1	25	24.40	24.50	-3.440	0.362	1.023	0.370	/
					25	25	23.32	23.50	-0.290	0.257	1.042	0.268	/
		Top	23330	793.0	1	25	24.40	24.50	3.410	0.105	1.023	0.107	/
					25	25	23.32	23.50	-4.090	0.081	1.042	0.084	/
LTE Band 17	QPSK (10MHz)	Back	23790	710.0	1	0	24.38	24.50	-2.240	0.328	1.028	0.337	11#
					25	13	22.92	23.00	0.840	0.205	1.019	0.209	/
		Left	23790	710.0	1	0	24.38	24.50	2.720	0.214	1.028	0.220	/
					25	13	22.92	23.00	-4.610	0.121	1.019	0.123	/
		Top	23790	710.0	1	0	24.38	24.50	2.050	0.090	1.028	0.093	/
					25	13	22.92	23.00	-1.970	0.064	1.019	0.065	/
LTE Band 25	QPSK (20MHz)	Back	26140	1860.0	1	50	23.14	23.50	2.250	0.171	1.086	0.186	12#
					50	50	22.04	22.50	-1.560	0.113	1.112	0.126	/
		Left	26140	1860.0	1	50	23.14	23.50	0.640	0.105	1.086	0.114	/
					50	50	22.04	22.50	-3.690	0.082	1.112	0.091	/
		Top	26140	1860.0	1	50	23.14	23.50	2.110	0.062	1.086	0.067	/
					50	50	22.04	22.50	-3.200	0.041	1.112	0.046	/
LTE Band 26 Part 90	QPSK (10MHz)	Back	26740	819.0	1	25	24.51	25.00	-2.110	0.638	1.119	0.714	13#
					25	25	23.33	23.50	-0.330	0.479	1.040	0.498	/
		Left	26740	819.0	1	25	24.51	25.00	4.600	0.406	1.119	0.454	/
					25	25	23.33	23.50	1.250	0.274	1.040	0.285	/
		Top	26740	819.0	1	25	24.51	25.00	-1.050	0.126	1.119	0.141	/
					25	25	23.33	23.50	4.820	0.083	1.040	0.086	/
LTE Band 26 Part 22	QPSK (15MHz)	Back	26965	841.5	1	38	23.48	23.50	-2.650	0.712	1.005	0.716	14#
					36	18	22.43	22.50	2.480	0.589	1.016	0.598	/
		Left	26965	841.5	1	38	23.48	23.50	-3.150	0.547	1.005	0.550	/
					36	18	22.43	22.50	0.960	0.347	1.016	0.353	/
		Top	26965	841.5	1	38	23.48	23.50	-2.300	0.196	1.005	0.197	/
					36	18	22.43	22.50	1.890	0.100	1.016	0.102	/
LTE Band 41	QPSK (20MHz)	Back	39750	2506.0	1	50	23.62	24.00	2.640	0.816	1.091	0.890	/
		Back	40620	2593.0	1	50	23.61	24.00	-4.820	0.805	1.094	0.881	/
		Back	41490	2680.0	1	50	23.77	24.00	-1.630	0.864	1.054	0.911	15#
					50	50	22.55	23.00	0.790	0.645	1.109	0.715	/

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 51 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

LTE Band 66	QPSK (20MHz)	Back(repeated)	41490	2680.0	1	50	23.77	24.00	-1.530	0.828	1.054	0.873	/
		Left	41490	2680.0	1	50	23.77	24.00	4.150	0.592	1.054	0.624	/
					50	50	22.55	23.00	-0.550	0.425	1.109	0.471	/
		Top	41490	2680.0	1	50	23.77	24.00	-2.970	0.211	1.054	0.222	/
					50	50	22.55	23.00	0.540	0.123	1.109	0.136	/
		Back	132572	1770.0	1	50	23.75	24.00	4.870	0.309	1.059	0.327	16#
					50	0	22.60	23.00	-1.690	0.236	1.096	0.259	/
		Left	132572	1770.0	1	50	23.75	24.00	2.100	0.212	1.059	0.225	/
					50	0	22.60	23.00	-3.020	0.179	1.096	0.196	/
		Top	132572	1770.0	1	50	23.75	24.00	-4.130	0.097	1.059	0.103	/
					50	0	22.60	23.00	0.990	0.071	1.096	0.078	/

Note:

- Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR ≤ 0.8 W/kg, other channels SAR testing is not necessary.
- Per KDB 447498 D01 v06, body use is evaluated with the device positioned at 0mm from a flat phantom respectively filled with body tissue-equivalent medium.
- Per KDB 616217 D04 where SAR test considerations for tablets are based on a composite test separation distance of 0 mm from the back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices.
- Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor = $10^{[(\text{tune-up limit power (dBm)} - \text{Ave. power power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg) = Measured SAR (W/kg) * Scaling Factor.

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

- When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
- When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
- If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.873 > 0.80$ W/kg, repeated measurement is as below.

Mode	Position	Ch.	Freq. (MHz)	1g Meas SAR (W/kg)	the ratio of largest to smallest SAR for the original and first repeated measurements
GSM 850	Back	128	824.2	0.912	1.026
	Back-repeat	128	824.2	0.889	
LTE Band 2	Back	18700	1860.0	0.962	1.050
	Back-repeat	18700	1860.0	0.916	
LTE Band 41	Back	41490	2680.0	0.911	1.044
	Back-repeat	41490	2680.0	0.873	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 52 of 125

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G/5G Wi-Fi and BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

NO.	Configuration	Body-worn
1	WWAN+WIFI(2.4g)	Yes
2	WWAN+WIFI(5g)	Yes
3	WWAN+BT	Yes
4	WWAN+NFC	Yes

12.2 Sum SAR of Simultaneous Transmission

Hotspot(body-worn)

Band	Test Position	RB allocation	Scaled					Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	Σ SAR (W/kg) WWAN + NFC	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth	NFC						
LTE Band 2 QPSK (20MHz)	Back	1RB	0.962	0.533	0.600	0.598	0.049	1.495	1.562	1.560	1.011	N/A	N/A
	Left		0.662	0.396	0.428	0.297	/	1.058	1.090	0.959	0.662	N/A	N/A
	Top		0.236	/	/	/	/	0.236	0.236	0.236	0.236	N/A	N/A
	Back	50%RB	0.638	0.533	0.600	0.598	0.049	1.171	1.238	1.236	0.687	N/A	N/A
	Left		0.470	0.396	0.428	0.297	/	0.866	0.898	0.767	0.470	N/A	N/A
	Top		0.124	/	/	/	/	0.124	0.124	0.124	0.124	N/A	N/A

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	04/22 EPG0365	2024/02/06	2025/02/05
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2023/11/16	2024/11/15
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2023/11/16	2024/11/15
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2023/11/16	2024/11/15
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2024/03/20	2025/03/19
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2024/03/20	2025/03/19
10dB Attenuator	MIDWEST MICROWAVE	263-10dB	/	2024/03/20	2025/03/19
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	2024/03/20	2025/03/19
750MHz Validation Dipole	MVG	SID750	07/22 DIP 0G750-655	2023/02/06	2025/02/05
835MHz Validation Dipole	MVG	SID835	07/22 DIP 0G835-656	2023/02/06	2025/02/05
1800MHz Validation Dipole	MVG	SID1800	07/22 DIP 1G800-657	2023/02/06	2025/02/05
1900MHz Validation Dipole	MVG	SID1900	07/22 DIP 1G900-658	2023/02/06	2025/02/05
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2023/02/06	2025/02/05
2600MHz Validation Dipole	MVG	SID2600	07/22 DIP 2G600-663	2023/02/06	2025/02/05
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2023/02/06	2025/02/05
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	2024/02/02	2025/02/01
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2023/11/16	2024/11/15
Thermometer	Riters	DT-232	21A11	2024/03/20	2025/03/19
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	/	/
SAM Phantom	MVG	SAM	07/22 SAM149	/	/
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	/	/
Mechanical Calibration Kit	PNA	/	/	2023/11/16	2024/11/15
Open SAR test software	MVG	/	V5.3.5	/	/
Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria: 1. There is no physical damage on the dipole; 2. System validation with specific dipole is within 10% of calibrated value; 3. Return-loss in within 20% of calibrated measurement. 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.					

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
750	41.90	41.80	0.89	0.86	-0.24%	-3.37%	±5%	20.0	8/8/2024
835	41.50	41.41	0.90	0.87	-0.22%	-3.33%	±5%	20.0	9/8/2024
1800	40.00	39.91	1.40	1.37	-0.23%	-2.14%	±5%	20.0	12/8/2024
1900	40.00	39.88	1.40	1.41	-0.30%	0.71%	±5%	20.0	13/8/2024
2450	39.20	39.08	1.80	1.81	-0.31%	0.56%	±5%	20.0	14/8/2024
2600	39.00	38.88	1.96	1.97	-0.31%	0.51%	±5%	20.0	15/8/2024
5200	36.00	35.88	4.66	4.70	-0.33%	0.86%	±5%	20.0	16/8/2024
5400	35.80	35.68	4.86	4.90	-0.34%	0.82%	±5%	20.0	16/8/2024
5600	35.50	35.38	5.07	5.11	-0.34%	0.79%	±5%	20.0	17/8/2024
5800	35.30	35.18	5.27	5.31	-0.34%	0.76%	±5%	20.0	17/8/2024

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %(for 10 g).


Frequency (MHz)	Input Power (mW)	10g SAR (W/Kg)	1g SAR (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Deviation	1g SAR Deviation
750	16	0.092	0.138	5.75	8.63	5.55	8.49	3.60%	1.59%
835	16	0.106	0.163	6.63	10.19	6.22	9.56	6.51%	6.56%
1800	16	0.312	0.588	19.50	36.75	20.10	38.40	-2.99%	-4.30%
1900	16	0.322	0.630	20.13	39.38	20.50	39.70	-1.83%	-0.82%
2450	16	0.352	0.793	22.00	49.56	23.86	54.4	-7.80%	-8.89%
2600	16	0.421	0.866	26.31	54.13	24.60	55.30	6.96%	-2.12%
5200	13	0.288	1.019	22.15	78.38	21.29	73.88	4.05%	6.09%
5400	13	0.299	1.051	23.00	80.85	23.23	81.47	-0.99%	-0.77%
5600	13	0.304	1.084	23.38	83.38	22.64	78.71	3.29%	5.94%
5800	13	0.277	0.981	21.31	75.46	21.5	74.21	-0.89%	1.69%


ANNEX C SAR Dipole Calibrations


Justification for Extended SAR Dipole Calibrations


Referring to KDB 865664D01V01r04, if dipoles are verified in return loss ($\leq -20\text{dB}$, within 20% of prior calibration) and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended. While calibration intervals not exceed 3 years.

Frequency (MHz)	Return loss(dB)		Impedance(Ω)				error range (%)		Results	Date of Measure ment
	measurement	target	measurement		target		Return loss(±20%)	Impedance(±5 Ω)	(P/F)	
			real part	imaginary part	real part	imaginary part				
CW750	-20.92	-25.44	55.89	1.5	55.2	-1.2	-17.77%	3.4	P	2/5/2024
CW835	-29.88	-26.27	52.8	-1.7	52.5	-4.2	13.74%	2.8	P	2/5/2024
CW1800	-24.55	-26.54	52.4	-0.2	52.8	+3.8	-7.50%	4.4	P	2/5/2024
CW1900	-25.67	-23.01	51.9	-5.3	51.0	-7.0	11.56%	2.6	P	2/5/2024
CW2450	-24.37	-21.23	48.3	5.7	49.4	+8.6	14.79%	4.0	P	2/5/2024
CW2600	-20.56	-23.05	57.3	5.7	54.3	+5.5	-10.80%	3.2	P	2/5/2024
CW5200	-21.14	-20.29	58.4	-4.5	58.76	-4.43	4.19%	0.43	P	2/5/2024
CW5400	-27.63	-29.09	57.5	1.2	53.46	+0.61	-5.02%	4.63	P	2/5/2024
CW5600	-33.45	-31.06	51.7	0.7	52.76	-0.45	7.69%	2.21	P	2/5/2024
CW5800	-28.88	-28.48	50.8	0.1	50.12	-3.76	1.40%	4.34	P	2/5/2024









System Performance Check Data (750 MHz)

System check at 750 MHz

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	750.000
Relative permittivity (real part)	41.800
Relative permittivity (imaginary part)	21.460
Conductivity (S/m)	0.860

C. SAR Surface and Volume




Maximum location: X=0.00, Y=9.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.092
SAR 1g (W/Kg)	0.138
Variation (%)	-2.190
Horizontal validation criteria: minimum distance (mm)	9.285
Vertical validation criteria: SAR ratio M2/M1 (%)	64.79%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.287	0.142	0.092	0.073	0.042



F. 3D Image



System Performance Check Data (835 MHz)

System check at 835 MHz

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	835.000
Relative permittivity (real part)	43.250
Relative permittivity (imaginary part)	19.490
Conductivity (S/m)	0.870

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-3.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.106
SAR 1g (W/Kg)	0.163
Variation (%)	-3.390
Horizontal validation criteria: minimum distance (mm)	8.000
Vertical validation criteria: SAR ratio M2/M1 (%)	66.47%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.059	0.173	0.115	0.061	0.072



F. 3D Image



System Performance Check Data (1800 MHz)

System check at 1800 MHz

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1800.000
Relative permittivity (real part)	41.530
Relative permittivity (imaginary part)	14.090
Conductivity (S/m)	1.370

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.312
SAR 1g (W/Kg)	0.588
Variation (%)	-0.250
Horizontal validation criteria: minimum distance (mm)	8.000
Vertical validation criteria: SAR ratio M2/M1 (%)	55.80%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.003	0.638	0.356	0.204	0.127



F. 3D Image



System Performance Check Data (1900 MHz)

System check at 1900 MHz

Date of measurement: 13/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1900.000
Relative permittivity (real part)	39.880
Relative permittivity (imaginary part)	13.380
Conductivity (S/m)	1.410

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.18 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.322
SAR 1g (W/Kg)	0.630
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	9.000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.96%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.201	0.759	0.402	0.239	0.156



F. 3D Image



System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2450.000
Relative permittivity (real part)	39.080
Relative permittivity (imaginary part)	13.340
Conductivity (S/m)	1.810

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.47 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.352
SAR 1g (W/Kg)	0.793
Variation (%)	-2.570
Horizontal validation criteria: minimum distance (mm)	9.000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.89%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.466	0.900	0.477	0.261	0.158



F. 3D Image



System Performance Check Data (2600 MHz)

System check at 2600 MHz

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2600.000
Relative permittivity (real part)	38.880
Relative permittivity (imaginary part)	12.690
Conductivity (S/m)	1.970

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 1.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.421
SAR 1g (W/Kg)	0.866
Variation (%)	2.980
Horizontal validation criteria: minimum distance (mm)	8.298
Vertical validation criteria: SAR ratio M2/M1 (%)	54.81%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.020	0.655	0.359	0.187	0.091



F. 3D Image



System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 16/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.288
SAR 1g (W/Kg)	1.019
Variation (%)	-3.400
Horizontal validation criteria: minimum distance (mm)	6.598
Vertical validation criteria: SAR ratio M2/M1 (%)	54.05%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.268	1.889	1.021	0.523	0.266	0.142	0.085	0.060	0.052



F. 3D Image



System Performance Check Data (5400 MHz)

System check at 5400 MHz

Date of measurement: 16/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.12
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5400.000
Relative permittivity (real part)	35.680
Relative permittivity (imaginary part)	16.320
Conductivity (S/m)	4.900

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.78 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.299
SAR 1g (W/Kg)	1.051
Variation (%)	-4.610
Horizontal validation criteria: minimum distance (mm)	6.274
Vertical validation criteria: SAR ratio M2/M1 (%)	54.97%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.660	2.141	1.177	0.614	0.317	0.169	0.098	0.065	0.050



F. 3D Image



System Performance Check Data (5600 MHz)

System check at 5600 MHz

Date of measurement: 17/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.18
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5600.000
Relative permittivity (real part)	35.380
Relative permittivity (imaginary part)	16.420
Conductivity (S/m)	5.110

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.90 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.304
SAR 1g (W/Kg)	1.084
Variation (%)	-0.190
Horizontal validation criteria: minimum distance (mm)	7.214
Vertical validation criteria: SAR ratio M2/M1 (%)	51.31%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.748	2.093	1.074	0.514	0.243	0.122	0.072	0.056	0.056



F. 3D Image



System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 17/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5800.000
Relative permittivity (real part)	35.180
Relative permittivity (imaginary part)	16.480
Conductivity (S/m)	5.310

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 4.17 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.277
SAR 1g (W/Kg)	0.981
Variation (%)	0.490
Horizontal validation criteria: minimum distance (mm)	7.145
Vertical validation criteria: SAR ratio M2/M1 (%)	44.92%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.948	2.037	0.915	0.361	0.135	0.055	0.033	0.037	0.059



F. 3D Image



ANNEX C Test Data

1-Body with back position in dist. 0mm on Channel 128 in GPRS850+4slots

SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Channels	Lower (128)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	824.200
Relative permittivity (real part)	41.460
Relative permittivity (imaginary part)	19.740
Conductivity (S/m)	0.869

C. SAR Surface and Volume



Maximum location: X=-9.00, Y=24.00 ; SAR Peak: 1.48 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.511
SAR 1g (W/Kg)	0.861
Variation (%)	-4.950
Horizontal validation criteria: minimum distance (mm)	8.495
Vertical validation criteria: SAR ratio M2/M1 (%)	58.73%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 80 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.483	0.974	0.572	0.349	0.232



F. 3D Image



2-Body with back position in dist. 0mm on Channel 512 in GPRS1900+4slots

SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Channels	Lower (512)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	1850.200
Relative permittivity (real part)	39.895
Relative permittivity (imaginary part)	13.734
Conductivity (S/m)	1.390

C. SAR Surface and Volume



Maximum location: X=-15.00, Y=23.00 ; SAR Peak: 0.43 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.125
SAR 1g (W/Kg)	0.254
Variation (%)	2.370
Horizontal validation criteria: minimum distance (mm)	8.826
Vertical validation criteria: SAR ratio M2/M1 (%)	53.08%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 82 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.422	0.260	0.138	0.076	0.046
------------	-------	-------	-------	-------	-------



F. 3D Image



3-Body with back position in dist. 0mm on Channel 9538 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 13/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Channels	Higher (9538)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1907.600
Relative permittivity (real part)	39.869
Relative permittivity (imaginary part)	13.379
Conductivity (S/m)	1.416

C. SAR Surface and Volume



Maximum location: X=-10.00, Y=16.00 ; SAR Peak: 0.83 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.246
SAR 1g (W/Kg)	0.492
Variation (%)	-3.370
Horizontal validation criteria: minimum distance (mm)	8.467
Vertical validation criteria: SAR ratio M2/M1 (%)	51.54%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 84 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.814	0.487	0.251	0.136	0.085
------------	-------	-------	-------	-------	-------



F. 3D Image



4-Body with back position in dist. 0mm on Channel 4183 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Channels	Middle (4183)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	836.600
Relative permittivity (real part)	41.408
Relative permittivity (imaginary part)	19.481
Conductivity (S/m)	0.871

C. SAR Surface and Volume



Maximum location: X=-9.00, Y=15.00 ; SAR Peak: 1.08 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.311
SAR 1g (W/Kg)	0.652
Variation (%)	-4.080
Horizontal validation criteria: minimum distance (mm)	8.495
Vertical validation criteria: SAR ratio M2/M1 (%)	49.69%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 86 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

SAR (W/Kg)	1.078	0.640	0.318	0.158	0.083
------------	-------	-------	-------	-------	-------



F. 3D Image



5-Body with back position in dist. 0mm on Channel 18700 in LTE band 2

SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Channels	Lower (18700)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1860.090
Relative permittivity (real part)	39.892
Relative permittivity (imaginary part)	13.663
Conductivity (S/m)	1.394

C. SAR Surface and Volume



Maximum location: X=-3.00, Y=26.00 ; SAR Peak: 1.99 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.485
SAR 1g (W/Kg)	0.873
Variation (%)	-1.410
Horizontal validation criteria: minimum distance (mm)	8.373
Vertical validation criteria: SAR ratio M2/M1 (%)	46.78%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 88 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.991	1.135	0.531	0.247	0.127



F. 3D Image



6-Body with back position in dist. 0mm on Channel 20300 in LTE band 4

SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Channels	Higher (20300)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1745.090
Relative permittivity (real part)	39.995
Relative permittivity (imaginary part)	14.397
Conductivity (S/m)	1.342

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.226
SAR 1g (W/Kg)	0.474
Variation (%)	-4.070
Horizontal validation criteria: minimum distance (mm)	8.498
Vertical validation criteria: SAR ratio M2/M1 (%)	43.51%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 90 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.878	0.478	0.208	0.091	0.047



F. 3D Image



7-Body with back position in dist. 0mm on Channel 20600 in LTE band 5

SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels	Higher (20600)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	844.090
Relative permittivity (real part)	41.396
Relative permittivity (imaginary part)	19.439
Conductivity (S/m)	0.875

C. SAR Surface and Volume



Maximum location: X=-8.00, Y=25.00 ; SAR Peak: 0.68 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.302
SAR 1g (W/Kg)	0.501
Variation (%)	-4.360
Horizontal validation criteria: minimum distance (mm)	8.813
Vertical validation criteria: SAR ratio M2/M1 (%)	66.25%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 92 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.660	0.480	0.318	0.210	0.139



F. 3D Image



8-Body with back position in dist. 0mm on Channel 20850 in LTE band 7

SAR Measurement at LTE band 7 (Body, Validation Plane)

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Channels	Lower (20850)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	2509.910
Relative permittivity (real part)	39.000
Relative permittivity (imaginary part)	13.080
Conductivity (S/m)	1.874

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.353
SAR 1g (W/Kg)	0.720
Variation (%)	-0.680
Horizontal validation criteria: minimum distance (mm)	8.468
Vertical validation criteria: SAR ratio M2/M1 (%)	46.77%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 94 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.664	0.928	0.434	0.224	0.154



F. 3D Image



9-Body with back position in dist. 0mm on Channel 23130 in LTE band 12

SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Channels	Higher (23130)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	706.590
Relative permittivity (real part)	41.999
Relative permittivity (imaginary part)	22.466
Conductivity (S/m)	0.855

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.198
SAR 1g (W/Kg)	0.356
Variation (%)	-3.290
Horizontal validation criteria: minimum distance (mm)	8.556
Vertical validation criteria: SAR ratio M2/M1 (%)	48.50%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 96 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.581	0.334	0.162	0.084	0.054



F. 3D Image



10-Body with back position in dist. 0mm on Channel 23330 in LTE band 14

SAR Measurement at LTE band 14 (Body, Validation Plane)

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 14
Channels	Middle (23330)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	793.090
Relative permittivity (real part)	41.602
Relative permittivity (imaginary part)	20.461
Conductivity (S/m)	0.865

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.342
SAR 1g (W/Kg)	0.572
Variation (%)	1.710
Horizontal validation criteria: minimum distance (mm)	8.623
Vertical validation criteria: SAR ratio M2/M1 (%)	61.25%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 98 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.805	0.542	0.332	0.214	0.152



F. 3D Image



11-Body with back position in dist. 0mm on Channel 23790 in LTE band 17

SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 8/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Channels	Middle (23790)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	705.590
Relative permittivity (real part)	42.004
Relative permittivity (imaginary part)	22.489
Conductivity (S/m)	0.855

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.210
SAR 1g (W/Kg)	0.328
Variation (%)	-2.240
Horizontal validation criteria: minimum distance (mm)	8.746
Vertical validation criteria: SAR ratio M2/M1 (%)	66.88%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 100 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.436	0.314	0.210	0.145	0.106



F. 3D Image



12-Body with back position in dist. 0mm on Channel 26140 in LTE band 25

SAR Measurement at LTE band 25 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 25
Channels	Lower (26140)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1860.090
Relative permittivity (real part)	39.892
Relative permittivity (imaginary part)	13.663
Conductivity (S/m)	1.394

C. SAR Surface and Volume



Maximum location: X=-10.00, Y=47.00 ; SAR Peak: 0.29 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.097
SAR 1g (W/Kg)	0.171
Variation (%)	2.250
Horizontal validation criteria: minimum distance (mm)	8.441
Vertical validation criteria: SAR ratio M2/M1 (%)	51.83%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 102 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.278	0.164	0.085	0.051	0.040



F. 3D Image



13-Body with back position in dist. 0mm on Channel 26740 in LTE band 26 Part 90

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels	Lower (26740)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Frequency (MHz)	819.090
Relative permittivity (real part)	41.483
Relative permittivity (imaginary part)	19.859
Conductivity (S/m)	0.868

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.390
SAR 1g (W/Kg)	0.638
Variation (%)	-2.110
Horizontal validation criteria: minimum distance (mm)	8.419
Vertical validation criteria: SAR ratio M2/M1 (%)	69.67%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 104 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.793	0.610	0.425	0.282	0.174



F. 3D Image



14-Body with back position in dist. 0mm on Channel 26965 in LTE band 26 Part 22

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 9/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels	Higher (26965)
Signal	LTE FDD
Cell Bandwidth	15 Mhz
Modulation	SC-OFDM - QPSK
RB offset	38
RB size	1

B. Permittivity

Frequency (MHz)	841.680
Relative permittivity (real part)	41.400
Relative permittivity (imaginary part)	19.453
Conductivity (S/m)	0.873

C. SAR Surface and Volume



Maximum location: X=-16.00, Y=25.00 ; SAR Peak: 1.01 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.416
SAR 1g (W/Kg)	0.712
Variation (%)	-2.650
Horizontal validation criteria: minimum distance (mm)	8.447
Vertical validation criteria: SAR ratio M2/M1 (%)	61.22%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 106 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.013	0.686	0.420	0.266	0.180



F. 3D Image



15-Body with back position in dist. 0mm on Channel 41490 in LTE band 41

SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 15/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels	Higher (41490)
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Frequency (MHz)	2680.090
Relative permittivity (real part)	38.788
Relative permittivity (imaginary part)	12.800
Conductivity (S/m)	2.054

C. SAR Surface and Volume



Maximum location: X=-16.00, Y=5.00 ; SAR Peak: 1.63 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.397
SAR 1g (W/Kg)	0.864
Variation (%)	-1.630

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 108 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China


Horizontal validation criteria: minimum distance (mm)	8.926
Vertical validation criteria: SAR ratio M2/M1 (%)	48.10%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.598	0.923	0.444	0.219	0.124



F. 3D Image



16-Body with back position in dist. 0mm on Channel 132572 in LTE band 66

SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 12/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	Higher (132572)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1770.090
Relative permittivity (real part)	39.956
Relative permittivity (imaginary part)	14.257
Conductivity (S/m)	1.355

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.150
SAR 1g (W/Kg)	0.309
Variation (%)	4.870
Horizontal validation criteria: minimum distance (mm)	8.518
Vertical validation criteria: SAR ratio M2/M1 (%)	36.81%

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 110 of 125


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.633	0.307	0.113	0.050	0.039



F. 3D Image



17-Body with back position in dist. 0mm on Channel 6 in IEEE 802.11b ISM

SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	Middle (6)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	2437.000
Relative permittivity (real part)	39.099
Relative permittivity (imaginary part)	13.341
Conductivity (S/m)	1.801

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.231
SAR 1g (W/Kg)	0.503
Variation (%)	2.730
Horizontal validation criteria: minimum distance (mm)	8.523
Vertical validation criteria: SAR ratio M2/M1 (%)	47.90%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.925	0.524	0.251	0.132	0.090



F. 3D Image



18-Body with back position in dist. 0mm on Channel 48 in IEEE 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 16/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPGO365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Higher (48)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5240.000
Relative permittivity (real part)	35.840
Relative permittivity (imaginary part)	16.264
Conductivity (S/m)	4.740

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-24.00 ; SAR Peak: 0.98 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.200
SAR 1g (W/Kg)	0.407
Variation (%)	-4.840
Horizontal validation criteria: minimum distance (mm)	8.237
Vertical validation criteria: SAR ratio M2/M1 (%)	59.72%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	1.001	0.566	0.338	0.170	0.194	0.075	0.142	0.077	0.096



F. 3D Image



19-Body with back position in dist. 0mm on Channel 52 in IEEE 802.11ac U-NII

SAR Measurement at IEEE 802.11ac U-NII (Body, Validation Plane)

Date of measurement: 16/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPGO365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11ac U-NII
Channels	Lower (52)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5260.000
Relative permittivity (real part)	35.820
Relative permittivity (imaginary part)	16.271
Conductivity (S/m)	4.760

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.248
SAR 1g (W/Kg)	0.564
Variation (%)	-1.130
Horizontal validation criteria: minimum distance (mm)	5.623
Vertical validation criteria: SAR ratio M2/M1 (%)	54.07%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	1.433	0.823	0.445	0.234	0.132	0.086	0.069	0.070	0.082



F. 3D Image



20-Body with back position in dist. 0mm on Channel 120 in IEEE 802.11ac U-NII

SAR Measurement at IEEE 802.11ac U-NII (Body, Validation Plane)

Date of measurement: 17/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.18
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11ac U-NII
Channels	Middle (120)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5600.000
Relative permittivity (real part)	35.380
Relative permittivity (imaginary part)	16.420
Conductivity (S/m)	5.110

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-17.00 ; SAR Peak: 0.81 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.123
SAR 1g (W/Kg)	0.214
Variation (%)	2.320
Horizontal validation criteria: minimum distance (mm)	5.112
Vertical validation criteria: SAR ratio M2/M1 (%)	30.91%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.765	0.330	0.102	0.018	0.034	0.011	0.062	0.021	0.070



F. 3D Image



21-Body with back position in dist. 0mm on Channel 165 in IEEE 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 17/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2mm, Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Higher (165)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5825.000
Relative permittivity (real part)	35.155
Relative permittivity (imaginary part)	16.488
Conductivity (S/m)	5.335

C. SAR Surface and Volume




Maximum location: X=-8.00, Y=-2.00 ; SAR Peak: 1.54 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.165
SAR 1g (W/Kg)	0.454
Variation (%)	-3.150
Horizontal validation criteria: minimum distance (mm)	4.986
Vertical validation criteria: SAR ratio M2/M1 (%)	32.69%

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	1.475	0.618	0.202	0.042	0.041	0.018	0.078	0.001	0.016



F. 3D Image



22-Body with back position in dist. 0mm on Channel 78 in Bluetooth

SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 14/8/2024


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Bluetooth
Channels	Higher (78)
Signal	Bluetooth

B. Permittivity

Frequency (MHz)	2480.000
Relative permittivity (real part)	39.040
Relative permittivity (imaginary part)	13.210
Conductivity (S/m)	1.842

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-27.00 ; SAR Peak: 1.34 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.297
SAR 1g (W/Kg)	0.540
Variation (%)	3.460
Horizontal validation criteria: minimum distance (mm)	8.467
Vertical validation criteria: SAR ratio M2/M1 (%)	44.43%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.330	0.727	0.323	0.152	0.090




F. 3D Image



ANNEX D SAR Test Setup Photos

Reference Photo: simulation liquid depth 15cm



Test positions



Back (dist. 0mm)



Left (dist. 0mm)



Top (dist. 0mm)

ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--