



Shenzhen Global Test Service Co.,Ltd.

Room No. 101, Building 1, and Room No. 101, Building 3, No. 88 Jinkang Road, Jinsha Community, Kengzi Sub-district, Pingshan District, Shenzhen City, Guangdong, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.....: GTS20260316016-1-13

FCC ID.....: 2AYD5-I26K01

Compiled by

(position+printed name+signature)...: File administrators Peter Xiao

Peter Xiao

Supervised by

(position+printed name+signature)...: Test Engineer Evan Ouyang

Evan Ouyang

Approved by

(position+printed name+signature)...: Manager Jason Hu



Jason Hu

Date of issue.....: Jul.29, 2026

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: Room No. 101, Building 1, and Room No. 101, Building 3, No. 88 Jinkang Road, Jinsha Community, Kengzi Sub-district, Pingshan District, Shenzhen City, Guangdong, China

Applicant's name.....: Imin Technology Pte Ltd

Address: 11 Bishan Street 21 #03-05 Singapore 573943

Test specification

Standard: **FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description **Touch All-in-One Computer, Kitchen Display Terminal, POS Device**

Trade Mark: **imin**

Manufacturer: Imin Technology Pte Ltd

Model/Type reference.....: I26K01

Listed Models: I26K02

Operation Frequency.....: From 2412MHz to 2462MHz

Hardware Version: N/A

Software Version: N/A

Rating: PoE++(IEEE 802.3bt), DC 42-57V, 60W Max OR
DC 24V/2.5A by Adapter

Result.....: **PASS**

TEST REPORT

Test Report No. :	GTS20260316016-1-13	Jul.29, 2026
		Date of issue

Equipment under Test : Touch All-in-One Computer, Kitchen Display Terminal, POS Device

Model /Type : I26K01

Listed model : I26K02

Applicant : **Imin Technology Pte Ltd**

Address : 11 Bishan Street 21 #03-05 Singapore 573943

Manufacturer : **Imin Technology Pte Ltd**

Address : 11 Bishan Street 21 #03-05 Singapore 573943

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	7
2.4. Short description of the Equipment under Test (EUT)	7
2.5. EUT operation mode	7
2.6. Block Diagram of Test Setup	7
2.7. Related Submittal(s) / Grant (s)	8
2.8. EUT Exercise Software	8
2.9. Special Accessories	8
2.10. External I/O Cable	8
2.11. Modifications	8
3. TEST ENVIRONMENT	9
3.1. Address of the test laboratory	9
3.2. Test Facility	9
3.3. Environmental conditions	9
3.4. Statement of the measurement uncertainty	9
3.5. Test Description	10
3.6. Equipments Used during the Test.....	11
4. TEST CONDITIONS AND RESULTS	12
4.1. AC Power Conducted Emission	12
4.2. Radiated Emission	13
4.3. On Time and Duty Cycle	32
4.4. Maximum Peak Output Power	33
4.5. Power Spectral Density	34
4.6. 99% and 6dB Bandwidth	35
4.7. Conducted Spurious Emissions and Band Edge Compliance of RF Emission.....	36
4.8. Antenna Requirement	38
5. TEST SETUP PHOTOS OF THE EUT.....	39
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	39

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 DTS Meas Guidance v05r02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Jul.10, 2026
	:	
Testing commenced on	:	Jul.10, 2026
	:	
Testing concluded on	:	Jul.28, 2026

2.2. Product Description

Product Name:	Touch All-in-One Computer, Kitchen Display Terminal, POS Device
Trade Mark:	
Model/Type reference:	I26K01
List Model:	I26K02
Model Declaration	PCB board, structure and internal of these model(s) are the same, It was merely a matter of model naming, differences in product size and antenna design. Tests were conducted to address the various differences.
Power supply:	PoE++(IEEE 802.3bt), DC 42-57V, 60W Max OR DC 24V/2.5A by Adapter
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20260316016-1-S001-1#>S20260316016-1-S001-2#& GTS20260316016-1-S001-3#>S20260316016-1-S001-4#
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	79 channels for Bluetooth (DSS) 40 channels for Bluetooth (DTS)
Channel Spacing	1MHz for Bluetooth (DSS) 2MHz for Bluetooth (DTS)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth (DSS) GFSK for Bluetooth (DTS)
2.4GWLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz IEEE 802.11ax HE20:2412-2462MHz IEEE 802.11ax HE40:2422-2452MHz
WLAN Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE40: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n/ax (HT20) 7 Channel for IEEE 802.11n/ax (HT40)
Channel separation:	5MHz
WIFI(5.2G/5.3G/5.7G/5.8G Band)	
WLAN Operation frequency	5180-5250MHz/ 5250MHz to 5320MHz/ 5500MHz to 5700MHz/ 5745MHz

	to 5825MHz
WLAN Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT20: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM,256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT40: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ax HE40: OFDMA (1024QAM,256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT80: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ax HE80: OFDMA (1024QAM,256QAM,64QAM, 16QAM, QPSK,BPSK)
Channel number:	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530-5610MHz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna Description	I26K01:Internal Antenna, 2.28dBi(Max.) for 2.4G Band and 3.55dBi(Max.) for 5G Band I26K02:Internal Antenna, 2.56dBi(Max.) for 2.4G Band and 0.55dBi(Max.) for 5G Band Note: Antenna port measurement pre-scan all models and recorded worst case at model: I26K01;
Remark: Both the I26K01 model and the I26K02 model have two versions. The only difference between the two versions lies in whether there is PoE power supply; Version A: Support PoE power supply, and DC adapter is not provided; Version B: Does not support PoE power supply, and DC adapter is provided.	

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☒ 24 V DC
		☒ Other (specified in blank below)	

DC 24.0V or DC 55.0V

Pre-test at both voltage DC 24V and DC 55.0V, but we only recorded the worst case in this report.(DC 24V to Adapter)

2.4. Short description of the Equipment under Test (EUT)

This is a Touch All-in-One Computer, Kitchen Display Terminal, POS Device .
For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX for testing meet KDS758074 test requirement.

IEEE 802.11b/g/n/ax(HT20): Eleven channels are provided to the EUT.

IEEE 802.11n/ax(HT40): seven channels are provided to the EUT.

Antenna	Chain 1		Chain 2		Simultaneously
Bandwidth Mode	20MHz	40MHz	20MHz	40MHz	/
IEEE 802.11b	☒	☐	☐	☐	☐
IEEE 802.11g	☒	☐	☐	☐	☐
IEEE 802.11n	☒	☒	☐	☐	☐
IEEE 802.11ax	☒	☒	☐	☐	☐


Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

The EUT has been tested under operating condition.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case(AC 120V/60Hz).

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position. Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11g mode (MCH).
AX mode tested all RU, only worst case mode (Full RU) recorded in report.

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AYD5-I26K01** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (QDART-Connectivity1.0-00094) provided by application.

2.9. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN HONOR ELECTRONIC CO.,LTD.	Adapter	ADS-65HI-19A-124060F	--	SDOC
Jiangsu Chenyang Electron Co.,Ltd.	Adapter	CYSE65-240250	--	SDOC
LIANGUO	PoE Injector	LG-BTG-N601(2.5G)	--	SDOC
LENOVO	PC	DESKYOP-EUIVCNR	--	SDOC

Note: The PoE Injector and PC is only used for auxiliary testing.

2.10. External I/O Cable

I/O Port Description	Quantity	Cable
DC IN Port	1	Non-Shielded, 1.0m
USB Port	1	N/A
Type-C Port	1	N/A
RJ45 Port	1	Non-Shielded, 1.0m

2.11. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

Room No. 101, Building 1, and Room No. 101, Building 3, No. 88 Jinkang Road, Jinsha Community, Kengzi Sub-district, Pingshan District, Shenzhen City, Guangdong, China.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

Applied Standard: FCC Part 15 Subpart C				
FCC Rules	Description of Test	Test Sample	Result	Remark
/	On Time and Duty Cycle	GTS20260316016-1-S001-1#	Compliant	Appendix C
§15.247(b)	Maximum Conducted Output Power	GTS20260316016-1-S001-1# GTS20260316016-1-S001-2#	Compliant	Appendix C
§15.247(e)	Power Spectral Density	GTS20260316016-1-S001-1#	Compliant	Appendix C
§15.247(a)(2)	6dB Bandwidth	GTS20260316016-1-S001-1#	Compliant	Appendix C
§2.1047	99% Occupied Bandwidth	GTS20260316016-1-S001-1#	Compliant	Appendix C
§15.209, §15.247(d)	Conducted Spurious Emissions and Band Edges Test	GTS20260316016-1-S001-1#	Compliant	Appendix C
§15.209, §15.247(d)	Radiated Spurious Emissions	GTS20260316016-1-S001-1# GTS20260316016-1-S001-2# GTS20260316016-1-S001-3# GTS20260316016-1-S001-4#	Compliant	Note 1
§15.205	Emissions at Restricted Band	GTS20260316016-1-S001-1#	Compliant	Appendix C
§15.207(a)	AC Conducted Emissions	GTS20260316016-1-S001-1# GTS20260316016-1-S001-2# GTS20260316016-1-S001-3# GTS20260316016-1-S001-4#	Compliant	Note 1
§15.203 §15.247(c)	Antenna Requirements	GTS20260316016-1-S001-1#	Compliant	Note 1
§15.247(i)§2.1091	RF Exposure	/	Compliant	Note 2

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10 th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/09
	11ax(20MHz)/OFDMA	8.6Mbps	1/6/11
	11ax(40MHz)/OFDMA	17.2Mbps	3/6/09
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/9
	11ax(20MHz)/OFDMA	8.6Mbps	1/11
	11ax(40MHz)/OFDMA	17.2Mbps	3/9

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Artificial Mains	CYBERTEK	EM5040A	E1850400205	2026/06/11	2027/06/10
LISN	R&S	ESH2-Z5	893606/008	2026/06/11	2027/06/10
EMI Test Receiver	R&S	ESPI 3	/	2026/07/04	2027/07/03
Test Receiver	R&S	ESCI 7	101102	2026/07/04	2027/07/03
Spectrum Analyzer	Agilent	N9020A	MY48010425	2026/06/12	2027/06/11
Spectrum Analyzer	R&S	FSV40-N	101800	2026/06/12	2027/06/11
Vector Signal generator	Agilent	N5181A	MY49060502	2026/06/11	2027/06/10
Signal generator	Agilent	N5182A	MY50141550	2026/06/11	2027/06/10
Climate Chamber	ESPEC	EL-10KA	A20120523	2026/06/12	2027/06/11
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2026/07/04	2027/07/03
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	/	2026/06/13	2027/06/12
By-log Antenna	SCHWARZBECK	VULB9163	00976	2026/07/04	2027/07/03
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2026/07/04	2027/07/03
Amplifier	SKET	LAPA_30M01G-32	SK20240104001	2025/12/23	2026/12/22
Amplifier	EMCI	EMC012645SE	980340	2025/12/23	2026/12/22
Amplifier	Schwarzbeck	BBV9179	9719-025	2025/12/01	2026/11/30
Temperature/Humidity Meter	HUATU	HTC-1	/	2026/06/12	2027/06/11
High-Pass Filter	Stest	1	/	2026/07/04	2027/07/03
High-Pass Filter	Stest	2	/	2026/07/04	2027/07/03
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2026/06/12	2027/06/11
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2026/06/12	2027/06/11
Data acquisition card	Agilent	U2531A	TW53323507	2026/06/12	2027/06/11
Power Sensor	Keysight	E9301A	MY41495308	2026/06/11	2027/06/10
Control Unit	Tonscend	JS0806-2	/	2026/07/07	2027/07/06
Control Unit	Tonscend	JS0806-2	/	2026/07/07	2027/07/06
integrated measuring instrument	R&S	CMW500	107519	2026/06/12	2027/06/11
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 4 The EUT received DC 24V power, the adapter received AC120V/60Hz or AC 240V/50Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.
- 9 The LISN is more than 40cm away from the vertical reference plane.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

DISTURBANCE Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

TEST RESULTS

Remark: We measured Conducted Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40/802.11ax HE20/802.11ax HE40 mode from 150 KHz to 30MHz in AC120V and the worst case was recorded.

Temperature	25°C	Humidity	60%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11g (MCH)

Model: I26K01_Version A

Adapter: ADS-65HI-19A-124060F

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph

Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
	[MHz]	Reading	Reading	[dB]	Result	Result	Limit	Limit	Margin	Margin		
		[dBμV]	[dBμV]		[dBμV]	[dBμV]	[dBμV]	[dBμV]	[dB]	[dB]		
1	0.1545	31.66	10.60	10.33	41.99	20.93	65.75	55.75	23.76	34.82	L1	PASS
2	0.375	22.33	11.05	10.15	32.48	21.20	58.39	48.39	25.91	27.19	L1	PASS
3	0.555	13.00	-2.59	10.21	23.21	7.62	56.00	46.00	32.79	38.38	L1	PASS
4	1.806	12.43	1.34	10.26	22.69	11.60	56.00	46.00	33.31	34.40	L1	PASS
5	3.327	15.78	1.86	10.35	26.13	12.21	56.00	46.00	29.87	33.79	L1	PASS
6	26.304	25.67	22.99	11.64	37.31	34.63	60.00	50.00	22.69	15.37	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph

Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
	[MHz]	Reading	Reading	[dB]	Result	Result	Limit	Limit	Margin	Margin		
		[dBμV]	[dBμV]		[dBμV]	[dBμV]	[dBμV]	[dBμV]	[dB]	[dB]		
1	0.15	33.24	16.90	10.35	43.59	27.25	66.00	56.00	22.41	28.75	N	PASS
2	0.3525	27.65	19.69	10.13	37.78	29.82	58.90	48.90	21.12	19.08	N	PASS
3	0.69	19.81	9.72	10.22	30.03	19.94	56.00	46.00	25.97	26.06	N	PASS
4	1.5495	23.21	14.14	10.24	33.45	24.38	56.00	46.00	22.55	21.62	N	PASS
5	3.021	23.01	12.01	10.34	33.35	22.35	56.00	46.00	22.65	23.65	N	PASS
6	26.304	31.53	28.25	11.61	43.14	39.86	60.00	50.00	16.86	10.14	N	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: CYSE65-240250

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.1545	32.19	12.18	10.33	42.52	22.51	65.75	55.75	23.23	33.24	L1	PASS
2	0.375	22.86	12.98	10.15	33.01	23.13	58.39	48.39	25.38	25.26	L1	PASS
3	0.6945	12.10	-1.54	10.22	22.32	8.68	56.00	46.00	33.68	37.32	L1	PASS
4	1.8485	11.93	1.22	10.26	22.19	11.48	56.00	46.00	33.81	34.52	L1	PASS
5	3.633	15.03	3.89	10.36	25.39	14.25	56.00	46.00	30.61	31.75	L1	PASS
6	26.304	25.89	22.19	11.64	37.33	33.83	60.00	50.00	22.67	16.17	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.1545	33.02	14.99	10.33	43.35	25.32	65.75	55.75	22.40	30.43	N	PASS
2	0.3525	27.66	19.60	10.13	37.79	29.73	58.90	48.90	21.11	19.17	N	PASS
3	0.672	20.67	11.68	10.21	30.88	21.89	56.00	46.00	25.12	24.11	N	PASS
4	1.779	21.19	12.69	10.25	31.44	22.94	56.00	46.00	24.56	23.06	N	PASS
5	3.777	24.20	11.63	10.36	34.56	21.99	56.00	46.00	21.44	24.01	N	PASS
6	27.8025	30.80	25.64	11.75	42.55	37.39	60.00	50.00	17.45	12.61	N	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Model: I26K01_Version B

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.1545	39.90	18.83	10.33	50.23	29.16	65.75	55.75	15.52	26.59	L1	PASS
2	0.3525	25.47	12.86	10.13	35.60	22.99	58.90	48.90	23.30	25.91	L1	PASS
3	2.049	29.47	13.47	10.27	39.74	23.74	56.00	46.00	16.26	22.26	L1	PASS
4	2.562	27.13	9.20	10.31	37.44	19.51	56.00	46.00	18.56	26.49	L1	PASS
5	9.2175	17.74	4.88	10.55	28.29	15.43	60.00	50.00	31.71	34.57	L1	PASS
6	26.9655	28.28	17.34	11.70	39.98	29.04	60.00	50.00	20.02	20.96	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.159	38.84	14.47	10.31	49.15	24.78	65.52	55.52	16.37	30.74	N	PASS
2	0.348	26.85	15.63	10.13	36.98	25.76	59.01	49.01	22.03	23.25	N	PASS
3	1.23	21.43	1.77	10.22	31.65	11.99	56.00	46.00	24.35	34.01	N	PASS
4	1.7025	23.04	2.22	10.25	33.29	12.47	56.00	46.00	22.71	33.53	N	PASS
5	9.267	24.50	9.98	10.56	35.06	20.54	60.00	50.00	24.94	29.46	N	PASS
6	26.4615	31.78	26.14	11.62	43.40	37.76	60.00	50.00	16.60	12.24	N	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Model: I26K02_Version A
 Adapter: ADS-65HI-19A-124060F


Power supply:

AC 120V/60Hz

Polarization

L

Test Graph



Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.15	39.08	17.55	10.35	49.41	27.90	66.00	56.00	16.59	28.10	L1	PASS
2	0.177	34.82	12.72	10.22	45.04	22.94	64.63	54.63	19.59	31.69	L1	PASS
3	0.375	23.92	10.98	10.15	34.07	21.13	58.39	48.39	24.32	27.26	L1	PASS
4	2.058	29.46	13.09	10.27	39.73	23.36	56.00	46.00	16.27	22.64	L1	PASS
5	2.571	27.89	11.58	10.31	38.20	21.89	56.00	46.00	17.80	24.11	L1	PASS
6	27.9845	27.50	22.87	11.79	39.29	34.66	60.00	50.00	20.71	15.34	L1	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


Power supply:

AC 120V/60Hz

Polarization

N

Test Graph



Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.1545	36.71	16.53	10.33	47.04	26.86	65.75	55.75	18.71	28.89	N	PASS
2	0.3525	23.64	13.56	10.13	33.77	23.69	58.90	48.90	25.13	25.21	N	PASS
3	0.582	16.34	3.57	10.20	26.54	13.77	56.00	46.00	29.46	32.23	N	PASS
4	2.058	23.14	9.76	10.27	33.41	20.03	56.00	46.00	22.59	25.97	N	PASS
5	2.481	23.03	9.59	10.30	33.33	19.89	56.00	46.00	22.67	26.11	N	PASS
6	9.2265	24.03	10.31	10.55	34.58	20.86	60.00	50.00	25.42	29.14	N	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: CYSE65-240250

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.3795	20.60	9.76	10.15	30.75	19.91	58.29	48.29	27.54	28.38	L1	PASS
2	1.131	14.77	1.25	10.21	24.98	11.46	56.00	46.00	31.02	34.54	L1	PASS
3	2.058	28.32	14.21	10.27	38.59	24.48	56.00	46.00	17.41	21.52	L1	PASS
4	2.58	26.24	8.32	10.31	36.55	18.63	56.00	46.00	19.45	27.37	L1	PASS
5	9.9375	17.74	4.31	10.58	28.32	14.89	60.00	50.00	31.68	35.11	L1	PASS
6	27.294	24.85	9.89	11.73	36.58	21.62	60.00	50.00	23.42	28.38	L1	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph

Final Data List

NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.15	36.20	15.94	10.35	46.55	26.29	56.00	46.00	19.45	29.71	N	PASS
2	0.3795	22.13	15.65	10.15	32.28	25.80	58.29	48.29	26.01	22.49	N	PASS
3	2.0715	23.14	7.71	10.28	33.42	17.99	56.00	46.00	22.58	28.01	N	PASS
4	3.3315	22.02	9.45	10.35	32.37	19.80	56.00	46.00	23.63	26.20	N	PASS
5	9.231	23.73	9.41	10.55	34.28	19.96	60.00	50.00	25.72	30.04	N	PASS
6	26.4435	28.93	23.29	11.62	40.55	34.91	60.00	50.00	19.45	15.09	N	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Model: I26K02_Version B

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph

Final Data List												
NO.	Frequency [MHz]	QP Reading [dBμV]	AVG. Reading [dBμV]	Factor [dB]	QP Result [dBμV]	AVG. Result [dBμV]	QP Limit [dBμV]	AVG. Limit [dBμV]	QP Margin [dB]	AVG. Margin [dB]	Line	Remark
1	0.1545	35.35	16.65	10.33	45.68	26.98	65.75	55.75	20.07	28.77	L1	PASS
2	0.3795	21.98	10.41	10.15	32.13	20.56	58.29	48.29	26.16	27.73	L1	PASS
3	1.1265	14.95	0.59	10.21	25.16	10.80	56.00	46.00	30.84	35.20	L1	PASS
4	2.0535	30.22	14.32	10.27	40.49	24.59	56.00	46.00	15.51	21.41	L1	PASS
5	2.5665	28.73	9.97	10.31	39.04	20.28	56.00	46.00	16.96	25.72	L1	PASS
6	26.9025	27.57	15.42	11.69	39.26	27.11	60.00	50.00	20.74	22.89	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).
2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


Test Graph

NOTE: All the modes have been tested and recorded worst mode in the report.


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 30MHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 30MHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at 802.11b/802.11g/802.11n/ax HT20/HT40 mode from 30 MHz to 25GHz in AC120V and the worst case was recorded.

Temperature	22.6℃	Humidity	51%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11g (MCH)

For 9 KHz~30MHz

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


For 30MHz-1GHz

Model: I26K01_Version A

Adapter: ADS-65HI-19A-124060F

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	148.34	39.79	-14.22	25.57	43.50	17.93	100	180	PK	Horizontal	PASS
2	222.545	50.54	-9.47	41.07	46.00	4.93	100	320	PK	Horizontal	PASS
3	250.19	45.85	-8.70	37.15	46.00	8.85	100	360	PK	Horizontal	PASS
4	297.235	45.11	-7.55	37.56	46.00	8.44	100	280	PK	Horizontal	PASS
5	519.85	44.91	-2.29	42.62	46.00	3.38	100	140	PK	Horizontal	PASS
6	594.54	40.58	-0.59	39.99	46.00	6.01	100	270	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	44.55	39.29	-11.41	27.88	40.00	12.12	100	130	PK	Vertical	PASS
2	222.545	39.46	-9.47	29.99	46.00	16.01	100	320	PK	Vertical	PASS
3	445.645	45.48	-3.91	41.57	46.00	4.43	100	40	PK	Vertical	PASS
4	519.85	45.12	-2.29	42.83	46.00	3.17	100	250	PK	Vertical	PASS
5	594.54	43.82	-0.59	43.23	46.00	2.77	100	250	PK	Vertical	PASS
6	966.05	39.55	2.48	42.03	54.00	11.97	100	360	PK	Vertical	PASS


Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: CYSE65-240250

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	148.34	39.01	-14.22	24.79	43.50	18.71	100	90	PK	Horizontal	PASS
2	222.545	49.96	-9.47	40.49	46.00	5.51	100	10	PK	Horizontal	PASS
3	250.19	45.57	-8.70	36.87	46.00	9.13	100	90	PK	Horizontal	PASS
4	297.235	42.34	-7.55	34.79	46.00	11.21	100	330	PK	Horizontal	PASS
5	519.85	45.30	-2.29	43.01	46.00	2.99	100	120	PK	Horizontal	PASS
6	594.54	43.64	-0.59	43.05	46.00	2.95	100	100	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	44.065	39.15	-11.45	27.70	40.00	12.30	100	270	PK	Vertical	PASS
2	223.03	38.72	-9.46	29.26	46.00	16.74	100	230	PK	Vertical	PASS
3	445.645	45.38	-3.91	41.47	46.00	4.53	100	280	PK	Vertical	PASS
4	519.85	45.18	-2.29	42.89	46.00	3.11	100	260	PK	Vertical	PASS
5	594.54	43.03	-0.59	42.44	46.00	3.56	100	300	PK	Vertical	PASS
6	966.05	39.50	2.48	41.98	54.00	12.02	100	300	PK	Vertical	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .


2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Model: I26K01_Version B

Adapter: ADS-65HI-19A-124060F

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	222.545	50.06	-9.47	40.59	46.00	5.41	100	10	PK	Horizontal	PASS
2	250.19	45.87	-8.70	37.17	46.00	8.83	100	160	PK	Horizontal	PASS
3	297.235	41.55	-7.55	34.00	46.00	12.00	100	100	PK	Horizontal	PASS
4	445.645	36.76	-3.91	32.85	46.00	13.15	100	120	PK	Horizontal	PASS
5	519.85	45.08	-2.29	42.79	46.00	3.21	100	140	PK	Horizontal	PASS
6	594.54	44.44	-0.59	43.85	46.00	2.15	100	260	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	36.79	39.97	-12.23	27.74	40.00	12.26	100	250	PK	Vertical	PASS
2	44.065	38.65	-11.45	27.20	40.00	12.80	100	290	PK	Vertical	PASS
3	445.645	45.57	-3.91	41.66	46.00	4.34	100	80	PK	Vertical	PASS
4	519.85	45.58	-2.29	43.29	46.00	2.71	100	300	PK	Vertical	PASS
5	817.155	36.79	1.72	38.51	46.00	7.49	100	240	PK	Vertical	PASS
6	966.05	39.51	2.48	41.99	54.00	12.01	100	200	PK	Vertical	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .


2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Model: I26K02_Version A

Adapter: ADS-65HI-19A-124060F

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	223.03	49.76	-9.46	40.30	46.00	5.70	100	90	PK	Horizontal	PASS
2	250.19	45.80	-8.70	37.10	46.00	8.90	100	120	PK	Horizontal	PASS
3	297.235	44.75	-7.55	37.20	46.00	8.80	100	40	PK	Horizontal	PASS
4	519.85	44.91	-2.29	42.62	46.00	3.38	100	300	PK	Horizontal	PASS
5	594.54	43.74	-0.59	43.15	46.00	2.85	100	20	PK	Horizontal	PASS
6	668.745	32.96	0.37	33.33	46.00	12.67	100	340	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	36.79	40.87	-12.23	28.64	40.00	11.36	100	340	PK	Vertical	PASS
2	445.645	45.46	-3.91	41.55	46.00	4.45	100	40	PK	Vertical	PASS
3	519.85	45.56	-2.29	43.27	46.00	2.73	100	90	PK	Vertical	PASS
4	594.54	43.16	-0.59	42.57	46.00	3.43	100	70	PK	Vertical	PASS
5	817.155	36.60	1.72	38.32	46.00	7.68	100	360	PK	Vertical	PASS
6	966.05	39.65	2.48	42.13	54.00	11.87	100	310	PK	Vertical	PASS


Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: CYSE65-240250

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	148.34	39.86	-14.22	25.64	43.50	17.86	100	180	PK	Horizontal	PASS
2	222.545	50.10	-9.47	40.63	46.00	5.37	100	300	PK	Horizontal	PASS
3	250.19	45.72	-8.70	37.02	46.00	8.98	100	240	PK	Horizontal	PASS
4	297.235	41.86	-7.55	34.11	46.00	11.89	100	70	PK	Horizontal	PASS
5	519.85	44.85	-2.29	42.56	46.00	3.44	100	150	PK	Horizontal	PASS
6	594.54	43.91	-0.59	43.32	46.00	2.68	100	120	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	36.79	40.42	-12.23	28.19	40.00	11.81	100	30	PK	Vertical	PASS
2	445.645	45.72	-3.91	41.81	46.00	4.19	100	60	PK	Vertical	PASS
3	519.85	45.31	-2.29	43.02	46.00	2.98	100	290	PK	Vertical	PASS
4	594.54	43.87	-0.59	43.28	46.00	2.72	100	10	PK	Vertical	PASS
5	817.155	36.75	1.72	38.47	46.00	7.53	100	200	PK	Vertical	PASS
6	966.05	39.69	2.48	42.17	54.00	11.83	100	250	PK	Vertical	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .


2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Model: I26K02_Version B

Adapter: ADS-65HI-19A-124060F

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	223.03	50.25	-9.46	40.79	46.00	5.21	100	40	PK	Horizontal	PASS
2	249.705	45.75	-8.72	37.03	46.00	8.97	100	190	PK	Horizontal	PASS
3	519.85	45.11	-2.29	42.82	46.00	3.18	100	130	PK	Horizontal	PASS
4	594.54	43.87	-0.59	43.28	46.00	2.72	100	50	PK	Horizontal	PASS
5	668.745	33.79	0.37	34.16	46.00	11.84	100	310	PK	Horizontal	PASS
6	966.05	35.49	2.48	37.97	54.00	16.03	100	340	PK	Horizontal	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBuV/m]	Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	43.58	38.36	-11.49	26.87	40.00	13.13	100	180	PK	Vertical	PASS
2	374.835	39.07	-5.71	33.36	46.00	12.64	100	120	PK	Vertical	PASS
3	445.645	45.62	-3.91	41.71	46.00	4.29	100	70	PK	Vertical	PASS
4	519.85	45.46	-2.29	43.17	46.00	2.83	100	210	PK	Vertical	PASS
5	817.155	36.75	1.72	38.47	46.00	7.53	100	260	PK	Vertical	PASS
6	966.05	39.62	2.48	42.10	54.00	11.90	100	240	PK	Vertical	PASS

Note:1. Result (dBuV/m) = Reading(dBuV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

NOTE: All the modes have been tested and recorded worst mode in the report.

For 1GHz to 25GHz**Model: I26K01_Version A**

IEEE 802.11ax HE20 (Worst Case)

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	51.14	32.44	30.25	7.95	61.28	74.00	-12.72	Peak	Horizontal
4824.00	36.30	32.44	30.25	7.95	46.44	54.00	-7.56	Average	Horizontal
4824.00	52.90	32.44	30.25	7.95	63.04	74.00	-10.96	Peak	Vertical
4824.00	35.80	32.44	30.25	7.95	45.94	54.00	-8.06	Average	Vertical

Channel 06 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	50.25	32.52	30.31	8.12	60.58	74.00	-13.42	Peak	Horizontal
4874.00	36.08	32.52	30.31	8.12	46.41	54.00	-7.59	Average	Horizontal
4874.00	51.78	32.52	30.31	8.12	62.11	74.00	-11.89	Peak	Vertical
4874.00	36.21	32.52	30.31	8.12	46.54	54.00	-7.46	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	51.46	32.68	30.27	7.88	61.75	74.00	-12.25	Peak	Horizontal
4924.00	35.46	32.68	30.27	7.88	45.75	54.00	-8.25	Average	Horizontal
4924.00	49.02	32.68	30.27	7.88	59.31	74.00	-14.69	Peak	Vertical
4924.00	30.62	32.68	30.27	7.88	40.91	54.00	-13.09	Average	Vertical

Model: I26K01_Version B

IEEE 802.11ax HE20 (Worst Case)

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	50.03	32.44	30.25	7.95	60.17	74.00	-13.83	Peak	Horizontal
4824.00	35.51	32.44	30.25	7.95	45.65	54.00	-8.35	Average	Horizontal
4824.00	54.42	32.44	30.25	7.95	64.56	74.00	-9.44	Peak	Vertical
4824.00	35.33	32.44	30.25	7.95	45.47	54.00	-8.53	Average	Vertical

Channel 06 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	50.33	32.52	30.31	8.12	60.66	74.00	-13.34	Peak	Horizontal
4874.00	36.67	32.52	30.31	8.12	47.00	54.00	-7.00	Average	Horizontal
4874.00	51.36	32.52	30.31	8.12	61.69	74.00	-12.31	Peak	Vertical
4874.00	36.53	32.52	30.31	8.12	46.86	54.00	-7.14	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	50.34	32.68	30.27	7.88	60.63	74.00	-13.37	Peak	Horizontal
4924.00	35.95	32.68	30.27	7.88	46.24	54.00	-7.76	Average	Horizontal
4924.00	48.84	32.68	30.27	7.88	59.13	74.00	-14.87	Peak	Vertical
4924.00	32.38	32.68	30.27	7.88	42.67	54.00	-11.33	Average	Vertical

Model: I26K02_Version A

IEEE 802.11ax HE20 (Worst Case)

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	49.99	32.44	30.25	7.95	60.13	74.00	-13.87	Peak	Horizontal
4824.00	35.88	32.44	30.25	7.95	46.02	54.00	-7.98	Average	Horizontal
4824.00	53.22	32.44	30.25	7.95	63.36	74.00	-10.64	Peak	Vertical
4824.00	34.40	32.44	30.25	7.95	44.54	54.00	-9.46	Average	Vertical

Channel 06 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	50.93	32.52	30.31	8.12	61.26	74.00	-12.74	Peak	Horizontal
4874.00	36.84	32.52	30.31	8.12	47.17	54.00	-6.83	Average	Horizontal
4874.00	50.90	32.52	30.31	8.12	61.23	74.00	-12.77	Peak	Vertical
4874.00	35.20	32.52	30.31	8.12	45.53	54.00	-8.47	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	50.12	32.68	30.27	7.88	60.41	74.00	-13.59	Peak	Horizontal
4924.00	36.86	32.68	30.27	7.88	47.15	54.00	-6.85	Average	Horizontal
4924.00	49.48	32.68	30.27	7.88	59.77	74.00	-14.23	Peak	Vertical
4924.00	32.29	32.68	30.27	7.88	42.58	54.00	-11.42	Average	Vertical

Model: I26K02_Version B

IEEE 802.11ax HE20 (Worst Case)

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	51.23	32.44	30.25	7.95	61.37	74.00	-12.63	Peak	Horizontal
4824.00	36.71	32.44	30.25	7.95	46.85	54.00	-7.15	Average	Horizontal
4824.00	53.81	32.44	30.25	7.95	63.95	74.00	-10.05	Peak	Vertical
4824.00	35.08	32.44	30.25	7.95	45.22	54.00	-8.78	Average	Vertical

Channel 06 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	49.04	32.52	30.31	8.12	59.37	74.00	-14.63	Peak	Horizontal
4874.00	37.95	32.52	30.31	8.12	48.28	54.00	-5.72	Average	Horizontal
4874.00	51.66	32.52	30.31	8.12	61.99	74.00	-12.01	Peak	Vertical
4874.00	35.38	32.52	30.31	8.12	45.71	54.00	-8.29	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	50.09	32.68	30.27	7.88	60.38	74.00	-13.62	Peak	Horizontal
4924.00	36.88	32.68	30.27	7.88	47.17	54.00	-6.83	Average	Horizontal
4924.00	48.81	32.68	30.27	7.88	59.10	74.00	-14.90	Peak	Vertical
4924.00	31.64	32.68	30.27	7.88	41.93	54.00	-12.07	Average	Vertical

Notes:

- 1). Measuring frequencies from 9 KHz~10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Measured= Reading- Pre. Fac.+ Ant. Fac.+ Cab. Loss
- 5). Margin = Measured- Limit

NOTE: All the modes have been tested and recorded worst mode in the report.

4.3. On Time and Duty Cycle


LIMIT

None; for reporting purpose only.

TEST PROCEDURE

1. Set the center frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=8MHz, Sweep time= auto couple;
3. Detector = peak;
4. Trace mode = Single hold.

TEST CONFIGURATION




TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.7.

4.4. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 15.247 Measurement Guidance v05r02 Section 8.3.1 Maximum peak conducted output power, 8.3.1.3 The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.


TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.3.

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \text{ RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.4.

4.6. 99% and 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

6dB Bandwidth:

The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 430 kHz&820 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99% Bandwidth:

According to section 6.9.3 of ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, for the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Set RBW = 1%~5% OBW; VBW ≥ 3 *RBW (for occupied bandwidth measurement).
3. Measured the 6dB bandwidth and 99% occupied bandwidth by related function of the spectrum analyzer.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

For reporting purpose only.

6dB Bandwidth

Please refer to Appendix C.1.

99% Bandwidth

Please refer to Appendix C.2.

4.7. Conducted Spurious Emissions and Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

TEST RESULTS

4.6.1 For Conducted at Restricted Band Measurement

For reporting purpose only.

Please refer to Appendix C.8.

4.6.2 For Conducted Bandedge Measurement

For reporting purpose only.

Please refer to Appendix C.5.

4.6.3 For Conducted Spurious Emissions Measurement

For reporting purpose only.

Please refer to Appendix C.6.

4.8. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna is Internal Antenna and Internal Antenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 2.28dBi&2.56dBi.

Reference to the **GTS20260316016-1-11**.

5. TEST SETUP PHOTOS OF THE EUT

Reference to the Test Report: GTS20260316016-1-11.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the Test Report: GTS20260316016-1-11.

.....**End of Report**.....