

AR500 PLUS

Rechargeable Lithium-ion Battery
IFpP/12/144/242[1P4S]M/-10+40/95



Charge Mode: CC
Rated Voltage: 12.8V
Rated Capacity: 37Ah
Rated Energy: 473Wh
Dimension: 303×198×160mm
Ingress Protection: IP20
FCC ID: 2AYEFAR500PLUS

CAUTION/MISE EN GARDE:

·Risk of Electric Shock. Do not remove cover. No user serviceable parts inside. Refer servicing to qualified service personnel
·Risque de décharge électrique. Ne pas enlever le couvercle. Aucune des pièces à l'intérieur ne peut être réparée par l'utilisateur. L'entretien courant doit être effectué par un personnel d'entretien qualifié.

USB-A1 Output: 5V-3A/9V-2A/12V-2A, 24W Max
USB-A2 Output: 5V-3A/9V-2A/12V-2A/20V-1.2A, 24W Max
USB-C Output: 5V-3A/9V-3A/12V-3A/15V-3A/20V-3A, 60W Max
DC5521 Output(×2): Single Port 13.6V-5A Max, Double Ports 13.6V-5A Max
Car Charger Output: 12V-10A Max
Wireless Charge Output: 5V-12V-1.25A, 15W Max
AC Output(×2): 120V-4.2A Max, 60Hz, 500W Max
Standard Charge Input: 11-28V-5A Max
Fast Charge Input: 14.6V-15A Max
USB-C Input: 5V-3A/9V-3A/12V-3A/15V-3A/20V-5A, 100W Max

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.



Pylon Technologies Co., Ltd.

www.pylontech.com.cn

5/F, No.71-72, Lane 887, Zu Chongzhi Road, China (Shanghai) Pilot Free Trade Zone

未转曲

AR500 PLUS

Rechargeable Lithium-ion Battery
IFpP/12/144/242[1P4S]M/-10+40/95



Charge Mode: CC
Rated Voltage: 12.8V
Rated Capacity: 37Ah
Rated Energy: 473Wh
Dimension: 303×198×160mm
Ingress Protection: IP20
FCC ID: 2AYEFAR500PLUS

CAUTION/MISE EN GARDE:

·Risk of Electric Shock. Do not remove cover. No user serviceable parts inside. Refer servicing to qualified service personnel
·Risque de décharge électrique. Ne pas enlever le couvercle. Aucune des pièces à l'intérieur ne peut être réparée par l'utilisateur. L'entretien courant doit être effectué par un personnel d'entretien qualifié.

USB-A1 Output: 5V-3A/9V-2A/12V-2A, 24W Max
USB-A2 Output: 5V-3A/9V-2A/12V-2A/20V-1.2A, 24W Max
USB-C Output: 5V-3A/9V-3A/12V-3A/15V-3A/20V-3A, 60W Max
DC5521 Output(×2): Single Port 13.6V-5A Max, Double Ports 13.6V-5A Max
Car Charger Output: 12V-10A Max
Wireless Charge Output: 5V-12V-1.25A, 15W Max
AC Output(×2): 120V-4.2A Max, 60Hz, 500W Max
Standard Charge Input: 11-28V-5A Max
Fast Charge Input: 14.6V-15A Max
USB-C Input: 5V-3A/9V-3A/12V-3A/15V-3A/20V-5A, 100W Max

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.



Pylon Technologies Co., Ltd.

www.pylontech.com.cn

5/F, No.71-72, Lane 887, Zu Chongzhi Road, China (Shanghai) Pilot Free Trade Zone

转曲

材料：100#压纹PET，尺寸：140*60