


FCC RF Exposure Report

FCC ID : 2AYG4-KUD001
Equipment : RecovR
Model No. : HW1915
Brand Name : OpenTV
Applicant : OpenTV Inc.
Address : 5090 North 40th St., Suite 450 Phoenix, AZ
85018
Standard : 47 CFR FCC Part 2.1093
Received Date : Aug. 18, 2025
Tested Date : Aug. 21 ~ Sep. 04, 2025


We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:



Along Chen / Assistant Manager



Gary Chang / Manager

Table of Contents

1	RF EXPOSURE TEST EXEMPTIONS.....	4
1.1	1-mW TEST EXEMPTION	4
1.2	SAR-BASED EXEMPTION	4
1.3	MPE-BASED EXEMPTION	5
1.4	REFERENCE GUIDANCE	5
1.5	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
1.7	EXEMPTION CALCULATION	6
2	TEST LABORATORY INFORMATION	7

Release Record

Report No.	Version	Description	Issued Date
FA581801	Rev. 01	Initial issue	Nov. 03, 2025

1 RF Exposure Test Exemptions

1.1 1-mW TEST EXEMPTION

Available maximum time-averaged power is no more than 1 mW.

1.2 SAR-BASED EXEMPTION

This exemption is applicable to the frequency range between 300 and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

The maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$

$$P_{th} \text{ (mW)} = ERP_{20cm}(d/20)^x \quad d \leq 20cm$$

$$P_{th} \text{ (mW)} = ERP_{20cm} \quad 20 \text{ cm} < d \leq 40cm$$

Where $x = -\log_{10}\left(\frac{60}{ERP_{20cm}\sqrt{f}}\right)$

$$P_{th} \text{ (mW)} = ERP_{20cm} \text{ (mW)} = 2040f \quad 0.3GHz \leq f < 1.5 \text{ GHz}$$

$$P_{th} \text{ (mW)} = ERP_{20cm} \text{ (mW)} = 3060 \quad 1.5GHz \leq f < 6 \text{ GHz}$$

Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

When 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds

1.3 MPE-BASED EXEMPTION

For a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Radio Source Frequency			Minimum Distance			Threshold ERP
F_L		F_H	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	-	1.34	159 m	-	35.6 m	$1920 R^2$
1.34	-	30	35.6 m	-	1.6 m	$3450 R^2/f^2$
30	-	300	1.6 m	-	159 mm	$3.83 R^2$
300	-	1500	159 mm	-	31.8 mm	$0.0128 R^2f$
1500	-	100000	31.8 mm	-	0.5 mm	$19.2 R^2$

Note: R is the antenna-person separation distance.

1.4 REFERENCE GUIDANCE

447498 D04 Interim General RF Exposure Guidance v01

1.5 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.6 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Parameters	Uncertainty
Conducted power	± 0.808 dB

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1.7 EXEMPTION CALCULATION

Frequency Range ()	Maximum Conducted Power (dBm)	Maximum Tune Up Limit		Antenna Gain (dBi)	EIRP (dBm)	ERP (dBm)		SAR-Based Exemption Thresholds @50mm (mW)	
		(dBm)	(mW)			(dBm)	(mW)	1-g	10-g
BT (2402~2480)	7.53	8	6.31	2.80	10.8	8.65	7.33	220.34	550.86

SAR evaluation of BT is not required since conducted power and ERP is less than SAR-Based exemption Thresholds (10-g) @50mm

Simultaneous Transmission Evaluation

The device contains a certified WWAN module, FCC ID: 2ANPO00NRF9151

Band	Frequency Range (MHz)	Maximum Tune Up Limit		Antenna Gain (dBi)	EIRP (dBm)	ERP		SAR-Based Exemption Thresholds @50mm (mW)	
		(dBm)	(mW)			(dBm)	(mW)	1-g	10-g
2	1850 – 1910	24	251.19	4.1	28.1	25.95	393.55	238.36	595.90
5	824 – 849	24	251.19	1.5	25.5	23.35	216.27	239.57	598.93
4	1710 – 1755	24	251.19	3.5	27.5	25.35	342.77	244.07	610.18
12	699 – 716	24	251.19	-2.1	21.9	19.75	94.41	235.79	589.48
13	777 – 787	24	251.19	-0.1	23.9	21.75	149.62	238.21	595.53
25	1850 – 1915	24	251.19	4.2	28.2	26.05	402.72	238.36	595.90
26	814 – 849	24	251.19	1.5	25.5	23.35	216.27	239.29	598.23
66	1710 – 1780	24	251.19	3.8	27.8	25.65	367.28	244.07	610.18

Note: Value of Maximum Tune up limit are from test report no.: 77535RAN.002

Mode	Max Ratio of Each Mode
BT	0.01
WWAN (Band25)	0.68
Sum	0.69
Limit	1
Pass / Fail	Pass

Simultaneous transmission SAR evaluation is not required since ratio of SAR-Based exemption is < 1

2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <https://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==