

TEST REPORT

Product Name : NeuralRock
Model/Type reference : RMTS-XT-NR-001
Report Number : HTC20250825001
Date of Issue : August 25, 2025
Test Standards : GB/T 9410-2008
: ANSI/IEEE Std149-1979

Compiled by:

Eason

Reviewed by:

Acron

Approved by:

Jason

Date:

August 25, 2025



Prepared by:
Shenzhen XinHua Technology co.,Ltd
E-mail: jason.chen@htc-cert.com

Version

Version No.	Date	Description
00	August 25, 2025	Original

Contents

1. General Information	3rd
1.1 General information of testing institutions	3rd
1.2 Applicant and Manufacturer	3rd
1.3 Testing principle	3rd
1.4 Test equipment	4th
1.5 Test environment	4th
1.6 Statement	4th
2. Sample Information	5th
2.1 Description of EUT(S)	5th
2.2 EUT appearance	5th
Antenna Dimensions	6th
2.3 EUT setup photo of free space OTA testing	7th
3. Test Results	8th
3.1 Test uncertainty	8th
3.2 Test data	9th
3.2.1 VSWR parameters	9th
3.2.2 VSWR data	9th
3.2.3 Typical free space efficiency and gain	9th
3.2.4 Radiation pattern	10th

1. General Information


1.1 General information of testing institutions

Name	Shenzhen XinHua Technology co.,Ltd
Address	C709, Building D, Juji Industrial Park, Yabian Xueziwei, Shajing Street, Bao'an District, Shenzhen City

1.2 Applicant and Manufacturer

Applicant/Client Name	Peytec Inc.
Applicant Address	120 East Beaver Creek Rd #200, Richmond Hill, ON L4B 4V1

1.3 Testing principle



1.4 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
OTA Test System	RayZone-5000	A0011	GTS	2025.5.10	2027.5.9
Network Analyzer	E5071C	C0017	KEYSIGHT	2025.5.10	2026.5.9

1.5 Test environment

Temperature	24.8°C
Humidity	83%RH
Pressure	100.06kPa

1.6 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen XinHua Technology co.,Ltd have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

2.Sample Information


2.1 Description of EUT(S)

Test Item	VSWR;Antenna gain; Efficiency; Radiation pattern
Frequency Range	902-928MHz
Received Date	August 21, 2025
Test Date	August 23, 2025

2.2 EUT appearance



View Of Product-01




View Of Product-02



Antenna Dimensions

2.3 EUT setup photo of free space OTA testing



3. Test Results


3.1 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of $K=2$ and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
VSWR	± 0.3
Antenna gain	$\pm 0.72\text{dB}$
Radiation efficiency	$\pm 0.72\text{dB}$

3.2 Test data

3.2.1 VSWR parameters



3.2.2 VSWR data


Frequency/MHz	902	928
VSWR	6.1	5.28

3.2.3 Typical free space efficiency and gain


Frequency ID	Frequency (MHz)	Gain (dBi)	Efficiency (%)
1	902.0	-19.09	0.41
2	904.0	-19.52	0.41
3	906.0	-19.51	0.41
4	908.0	-18.28	0.42
5	910.0	-19.28	0.43
6	912.0	-19.55	0.42
7	914.0	-19.37	0.43
8	916.0	-18.49	0.45
9	918.0	-19.03	0.44
10	920.0	-19.25	0.46
11	922.0	-18.24	0.46
12	924.0	-19.42	0.45
13	926.0	-18.70	0.45
14	928.0	-19.28	0.46

3.2.4 Radiation pattern


(1) 902.0MHz Total(E1-XZ), Max= -19.88dBi:




(2) 914.0MHz Total(E1-XZ), Max= -20.26dBi:




(3) 928.0MHz Total(E1-XZ), Max= -19.54dBi






(5) Typical Free Space 3D Radiation Pattern at 914MHz(unit:dBi)



(6) Typical Free Space 3D Radiation Pattern at 928MHz(unit:dBi)



End