



TEST REPORT

No. I22N02494-EMC -UMTS

for

Honor Device Co., Ltd.

Smart Phone

Model Name: CRT-LX3

With

Hardware Version: HL3CRTM

Software Version:6.1.0.90(C900E21R1P2)

FCC ID: 2AYGCCRT-LX3

Issued Date: 2022-12-09

Designation Number: CN1210

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen,
Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@saict.ac.cn. www.saict.ac.cn



No. I22N02494-EMC-UMTS

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I22N02494-EMC-UMTS	Rev.0	1st edition	2022-12-09

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. SUMMARY OF TEST REPORT	4
1.1. TEST ITEMS.....	4
1.2. TEST STANDARDS	4
1.3. TEST RESULT	4
1.4. TESTING LOCATION	4
1.5. PROJECT DATA	4
1.6. SIGNATURE.....	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION.....	5
2.2. MANUFACTURER INFORMATION.....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT.....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
3.4. GENERAL DESCRIPTION	8
4. REFERENCE DOCUMENTS.....	9
5. LABORATORY ENVIRONMENT.....	10
6. SUMMARY OF TEST RESULTS.....	11
7. STATEMENT	12
8. TEST EQUIPMENTS UTILIZED.....	13
ANNEX A: MEASUREMENT RESULTS	14
A.1 OUTPUT POWER.....	14
A.2 FIELD STRENGTH OF SPURIOUS RADIATION.....	19

1. SUMMARY OF TEST REPORT

1.1. Test Items

Description	Smart Phone
Model Name	CRT-LX3
Applicant's name	Honor Device Co., Ltd.
Manufacturer's Name	Honor Device Co., Ltd.

1.2. Test Standards

FCC Part 2/22/24/27	10-1-20
	Edition
ANSI C63.26	2015
KDB971168 D01	v03r01

1.3. Test Result

PASS/FAIL

Total test 2 items, pass 2 items. Please refer to "6 Summary of Test Results" for detail.

1.4. Testing Location


Address: EMC Laboratory, Building G, Shenzhen International Innovation Center, No.1006
Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000

1.5. Project Data

Testing Start Date: 2022-12-01

Testing End Date: 2022-12-09

1.6. Signature




Liu Xiangzhou

(Prepared this test report)



Liang Yong

(Reviewed this test report)



Cao Junfei

(Approved this test report)



2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: Honor Device Co., Ltd.
Address: Suite 3401, Unit A, Building 6, Shum Yip Sky Park, No. 8089, Hongli
West Road, Xiangmihu Street, Futian District, Shenzhen, P.R.China
Contact Li Ming
Email liming136@hihonor.com
Tel. 0755-61886688
Fax: /

2.2. Manufacturer Information

Company Name: Honor Device Co., Ltd.
Address: Suite 3401, Unit A, Building 6, Shum Yip Sky Park, No. 8089, Hongli
West Road, Xiangmihu Street, Futian District, Shenzhen, P.R.China
Contact Li Ming
Email liming136@hihonor.com
Tel. 0755-61886688
Fax:

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT

(AE)

3.1. About EUT

Description	Smart Phone
Model Name	CRT-LX3
FCC ID	2AYGCCRT-LX3
Frequency Bands	WCDMA Bands 2/4/5
Antenna	Integrated
Condition of EUT as received	No obvious damage in appearance

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Receive Date
UT05aa	866902060024676	HL3CRTM	6.1.0.90(C900E21R1P2)	2022-12-01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Adapter
AE3	Data Cable
AE4	Headset
AE5	Earphone, USB Type-C to 3.5mm Adapter Assembly

AE1-1

Model	HB416594EGW
Manufacturer	Honor Device Co., Ltd.(SCUD)
Capacity	4400mAh
Nominal Voltage	3.89 V

AE1-2

Model	HB416594EGW
Manufacturer	Honor Device Co., Ltd.(Desay)
Capacity	4400mAh
Nominal Voltage	3.89 V

AE2-1

Model	HN-100225E00
Manufacturer	Honor Device Co., Ltd. (Huntkey/Salcomp)

AE2-2



Model	HN-100225U00
Manufacturer	Honor Device Co., Ltd. (Huntkey/Salcomp)
AE2-3	
Model	HW-100225E00
Manufacturer	Honor Device Co., Ltd. (Huntkey)
AE2-4	
Model	HW-100225U00
Manufacturer	Honor Device Co., Ltd. (Huntkey)
AE2-5	
Model	HW-100225B00
Manufacturer	Honor Device Co., Ltd. (Huntkey)
AE2-6	
Model	HN-100225B00
Manufacturer	Honor Device Co., Ltd. (Huntkey/Salcomp)
AE3-1	
Model	CUDU01B-HC451-EH
Manufacturer	04072295(FF)
AE3-2	
Model	AU2-CRO013HF
Manufacturer	04072295(LJ)
AE3-3	
Model	L125UC007-CS-H
Manufacturer	04072295(LX)
AE3-4	
Model	2120-00001-0
Manufacturer	04072295(MG)
AE3-5	
Model	RY0002
Manufacturer	04072295(NB)
AE4-1	
Model	1331-3301-6001-TC-347
Manufacturer	22070347 (QC)
AE4-2	
Model	MEND1532B528C00
Manufacturer	22040339 (LC)
AE4-3	
Model	1293-3283-3.5MM-339
Manufacturer	22040339 (QC)
AE5	
Model	USB042020090AW7
Manufacturer	22040348(LC)

*AE ID: is used to identify the test sample in the lab internally.
AE: ancillary equipment.



AE2: The circuit boards of AE2-2 and AE2-6 are the same, the circuit boards of AE2-4 and AE2-5 are the same.

3.4. General Description

The Equipment Under Test (EUT) is a model of Smart Phone with internal antenna.

It consists of normal options: Battery, Adapter, Data Cable, Headset.

Manual and specifications of the EUT were provided to fulfill the test.

Samples (EUT+AE) undergoing test were selected by the Client. Relevant information is provided by the client.

4. REFERENCE DOCUMENTS

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	(10-1-2020 Edition)
FCC Part 2	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS	(10-1-2020 Edition)
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	(10-1-2020 Edition)
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	(10-1-2020 Edition)
ANSI C63.26	American National Standard of Procedures for Compliance Testing of Licensed Transmitters Used in Licensed Radio Service	2015
KDB971168 D01	Power Meas License Digital Systems	v03r01

5. LABORATORY ENVIRONMENT

Anechoic chamber (FACT3-2.0) did not exceed following limits along the EMC testing:

9.10m×6.10m×5.60m (L×W×H)

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ±4 dB, 3 m distance, from 30 to 1000 MHz
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	F	Fail
	NA	Not applicable
	NM	Not measured
Location Column	A/B/C/D	The test is performed in test location A, B, C or D which are described in section 1.1 of this report

WCDMA Band II

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	24.232	A.1	P
2	Field Strength of Spurious Radiation	24.238	A.2	P

WCDMA Band V

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	22.913	A.1	P
2	Field Strength of Spurious Radiation	22.917	A.2	P

WCDMA Band IV

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(d)	A.1	P
2	Field Strength of Spurious Radiation	27.53(h)	A.2	P

7. STATEMENT

Since the information of samples in this report is provided by the client, the laboratory is not responsible for the authenticity of sample information.

This report takes measured values as criterion of test conclusion. The test conclusion meets the limit requirements.

8. TEST EQUIPMENTS UTILIZED

NO.	Description	TYPE	Manufacture	Series number	Calibration Due date
1	Test Receiver	ESR7	R&S	101676	2023.11.23
2	BiLog Antenna	3142E	ETS-Lindgren	0224831	2024.05.27
3	Horn Antenna	3117	ETS-Lindgren	00066577	2025.04.17
4	Horn Antenna	QSH-SL-18 -26-S-20	Q-par	17013	2023-01-06
5	Antenna	BBHA 9120D	Schwarzbeck	1593	2023-12-04
6	Antenna	VUBA 9117	Schwarzbeck	207	2023-07-15
7	Antenna	QWH-SL-18 -40-K-SG	Q-par	15979	2023-01-06
8	preamplifier	83017A	Agilent	MY39501110	/
9	Signal Generator	SMB100A	R&S	179725	2023-11-23
10	Anechoic Chamber	FACT3-2.0	ETS-Lindgren	1285	2023.05.29
11	Spectrum Analyzer	FSV40	R&S	101192	2023-01-12
12	Universal Radio Communication Tester	CMU200	R&S	114545	2023-01-12

Test software

Item	Name	Vesion
Radiated	EMC32	V10.50.40

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

Reference

FCC: CFR Part 22.913, 24.232, 27.50(d)

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200 or CMW500) to ensure max power transmission and proper modulation.

This result contains max output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Radiated


A.1.2.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. "Rule Part 22.913(a) specifies the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.2.2 Method of Measurement

1. For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, EUT was placed on a 80 cm high non-conductive stand at a 3 meter test distance from the receive antenna. For radiated measurements performed at frequencies above 1 GHz, EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. Receiving antenna was placed on the antenna mast 3 meters from the EUT. For emission measurements. The receiving antenna shall be varied from 1 m to 4 m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.
The cable loss (P_{cl}), the Substitution Antenna Gain(dBi) (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dB}$.

WCDMA Band II-EIRP
Limits

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

Measurement result
QPSK-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1852.40	-15.82	-29.30	8.10	21.58	33.00	H
1880.00	-15.82	-29.40	8.10	21.68	33.00	H
1907.60	-15.44	-29.30	8.10	21.96	33.00	H

QPSK-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1852.40	-16.05	-29.30	8.10	21.35	33.00	H
1880.00	-16.33	-29.40	8.10	21.17	33.00	H
1907.60	-16.12	-29.30	8.10	21.28	33.00	H

16QAM-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1852.40	-15.87	-29.30	8.10	21.53	33.00	H
1880.00	-15.89	-29.40	8.10	21.61	33.00	H
1907.60	-15.50	-29.30	8.10	21.90	33.00	H

16QAM-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1852.40	-16.06	-29.30	8.10	21.34	33.00	H
1880.00	-16.42	-29.40	8.10	21.08	33.00	H
1907.60	-16.17	-29.30	8.10	21.23	33.00	H

Frequency: 1907.60MHz

Peak EIRP(dBm)= P_{Mea}(-15.44dBm)-(P_{cl}+P_{Ag})(-29.30dB)+Ga (8.10dB) =21.96dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

WCDMA Band V-ERP
Limits

	Burst Peak ERP (dBm)
WCDMA Band V	≤38.45dBm

Measurement result
QPSK-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	Correction(dB)	ERP(dBm)	Limit(dBm)	Polarization
826.40	-9.09	-33.60	-0.84	2.15	21.52	38.45	H
836.60	-9.12	-33.50	-0.74	2.15	21.49	38.45	H
846.60	-9.87	-33.50	-0.73	2.15	20.75	38.45	H

QPSK-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	Correction(dB)	ERP(dBm)	Limit(dBm)	Polarization
826.40	-9.66	-33.60	-0.84	2.15	20.95	38.45	H
836.60	-9.84	-33.50	-0.74	2.15	20.77	38.45	H
846.60	-10.38	-33.50	-0.73	2.15	20.24	38.45	H

16QAM-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Polarization
826.40	-9.13	-33.60	-0.84	2.15	21.48	38.45	V
836.60	-9.50	-33.50	-0.74	2.15	21.12	38.45	V
846.60	-9.93	-33.50	-0.73	2.15	20.69	38.45	V

16QAM-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Polarization
826.40	-9.71	-33.60	-0.84	2.15	20.90	38.45	V
836.60	-9.89	-33.50	-0.74	2.15	20.72	38.45	V
846.60	-10.43	-33.50	-0.73	2.15	20.19	38.45	V

Frequency: 826.40MHz

Peak ERP(dBm)= P_{Mea}(-9.09dBm)-(P_{cl}+P_{Ag})(-33.60dB)+Ga (-0.84dB)-2.15dB=21.52dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

WCDMA Band IV-EIRP

Limits

	Burst Peak EIRP (dBm)
WCDMA Band IV	≤30.00dBm

Measurement result

QPSK-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1712.40	-15.71	-29.60	8.10	22.00	30.00	H
1732.60	-16.26	-29.50	8.10	21.34	30.00	H
1752.60	-16.01	-29.50	8.10	21.59	30.00	H

QPSK-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1712.40	-16.22	-29.60	8.10	21.48	30.00	H
1732.60	-16.35	-29.50	8.10	21.26	30.00	H
1752.60	-16.25	-29.50	8.10	21.35	30.00	H

16QAM-UP

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1712.40	-15.79	-29.60	8.10	21.91	30.00	H
1732.60	-16.33	-29.50	8.10	21.27	30.00	H
1752.60	-16.08	-29.50	8.10	21.52	30.00	H

16QAM-DOWN

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Polarization
1712.40	-16.30	-29.60	8.10	21.40	30.00	H
1732.60	-16.41	-29.50	8.10	21.19	30.00	H
1752.60	-16.27	-29.50	8.10	21.33	30.00	H

Frequency: 1732.60MHz

Peak EIRP(dBm)= P_{Mea}(-16.35dBm)-(P_{cl}+P_{Ag})(-29.50dB)+Ga (8.10dB)=21.91dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

Note: The maximum value of expanded measurement uncertainty for this test item is U = 2.72dB(30MHz-3GHz)/3.60dB(3GHz-18GHz)/3.58dB(18GHz-40GHz), k = 2

Note: Both of Vertical and Horizontal polarizations are evaluated, but only the worst case is recorded in this report.

A.2 FIELD STRENGTH OF SPURIOUS RADIATION

Reference


FCC: CFR 22.917, 24.238, 27.53(h).

A.2.1 Measurement Method


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238, Part 22.917 and Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V and WCDMA Band IV.

The procedure of radiated spurious emissions is as follows:

1. For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, EUT was placed on a 80 cm high non-conductive stand at a 3 meter test distance from the receive antenna. For radiated measurements performed at frequencies above 1 GHz, EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. Receiving antenna was placed on the antenna mast 3 meters from the EUT. For emission measurements. The receiving antenna shall be varied from 1 m to 4 m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain(dBi) (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dB}$.

A.2.2 Measurement Limit

Part 24.238 , Part 22.917 and Part 27.50 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz), WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz) and WCDMA Band IV (1712.4MHz, 1740.0MHz and 1752.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	3

WCDMA BAND II Mode Channel 9662/1932.4MHz (QPSK) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16954.38	-45.94	2.90	16.50	-32.34	-13.00	H
17098.75	-43.93	2.90	14.50	-32.33	-13.00	H
17288.75	-43.52	3.20	14.50	-32.22	-13.00	H
17448.13	-41.71	2.90	14.50	-30.11	-13.00	H
17619.38	-39.97	3.30	12.80	-30.47	-13.00	H
17718.75	-40.63	3.30	12.80	-31.13	-13.00	H

WCDMA BAND II Mode Channel 9800/1960MHz (QPSK) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16966.88	-45.70	2.90	16.50	-32.10	-13.00	H
17190.63	-44.54	2.90	14.50	-32.94	-13.00	H
17279.38	-43.32	3.20	14.50	-32.02	-13.00	H
17522.50	-39.47	2.90	12.80	-29.57	-13.00	H
17566.88	-39.76	3.30	12.80	-30.26	-13.00	H
17811.88	-40.45	3.60	12.80	-31.25	-13.00	H

WCDMA BAND II Mode Channel 9938/1987.6MHz (QPSK) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16938.13	-45.02	2.90	16.50	-31.42	-13.00	H
17117.50	-43.63	2.90	14.50	-32.03	-13.00	H
17287.50	-43.89	3.20	14.50	-32.59	-13.00	H
17520.63	-39.90	2.90	12.80	-30.00	-13.00	H
17525.63	-41.01	2.90	12.80	-31.11	-13.00	H
17834.38	-40.79	3.60	12.80	-31.59	-13.00	H

WCDMA BAND II Mode Channel 9662/1932.4MHz (QPSK) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16943.13	-45.62	2.90	16.50	-32.02	-13.00	H
17210.00	-43.78	2.90	14.50	-32.18	-13.00	H
17297.50	-43.58	3.20	14.50	-32.28	-13.00	H
17443.13	-41.91	2.90	14.50	-30.31	-13.00	H
17622.50	-39.52	3.30	12.80	-30.02	-13.00	H
17816.88	-39.81	3.60	12.80	-30.61	-13.00	H

WCDMA BAND II Mode Channel 9800/1960MHz (QPSK) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16942.50	-45.71	2.90	16.50	-32.11	-13.00	H
17207.50	-43.81	2.90	14.50	-32.21	-13.00	H
17250.00	-43.70	3.20	14.50	-32.40	-13.00	H
17448.13	-42.09	2.90	14.50	-30.49	-13.00	H
17592.50	-39.95	3.30	12.80	-30.45	-13.00	H
17768.75	-39.52	3.60	12.80	-30.32	-13.00	H

WCDMA BAND II Mode Channel 9938/1987.6MHz (QPSK) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16979.38	-45.40	2.90	16.50	-31.80	-13.00	H
17195.63	-44.21	2.90	14.50	-32.61	-13.00	H
17298.75	-42.79	3.20	14.50	-31.49	-13.00	H
17501.25	-39.44	2.90	12.80	-29.54	-13.00	H
17615.63	-40.21	3.30	12.80	-30.71	-13.00	H
17773.13	-40.04	3.60	12.80	-30.84	-13.00	H

WCDMA BAND II Mode Channel 9662/1932.4MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16981.25	-45.75	2.90	16.50	-32.15	-13.00	H
17170.63	-44.46	2.90	14.50	-32.86	-13.00	H
17302.50	-43.59	3.20	14.50	-32.29	-13.00	H
17521.88	-40.65	2.90	12.80	-30.75	-13.00	H
17586.88	-40.04	3.30	12.80	-30.54	-13.00	H
17833.13	-40.38	3.60	12.80	-31.18	-13.00	H

WCDMA BAND II Mode Channel 9800/1960MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16939.38	-45.77	2.90	16.50	-32.17	-13.00	H
17118.75	-43.86	2.90	14.50	-32.26	-13.00	H
17300.00	-43.49	3.20	14.50	-32.19	-13.00	H
17417.50	-41.79	2.90	14.50	-30.19	-13.00	H
17610.00	-40.13	3.30	12.80	-30.63	-13.00	H
17840.00	-40.17	3.60	12.80	-30.97	-13.00	H

WCDMA BAND II Mode Channel 9938/1987.6MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16997.50	-45.11	2.90	16.50	-31.51	-13.00	H
17195.00	-44.28	2.90	14.50	-32.68	-13.00	H
17366.88	-44.03	3.20	14.50	-32.73	-13.00	H
17434.38	-42.70	2.90	14.50	-31.10	-13.00	H
17610.63	-39.70	3.30	12.80	-30.20	-13.00	H
17803.13	-39.95	3.60	12.80	-30.75	-13.00	H

WCDMA BAND II Mode Channel 9662/1932.4MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16982.50	-45.38	2.90	16.50	-31.78	-13.00	H
17195.63	-43.40	2.90	14.50	-31.80	-13.00	H
17358.13	-42.42	3.20	14.50	-31.12	-13.00	H
17499.38	-41.84	2.90	14.50	-30.24	-13.00	H
17624.38	-40.20	3.30	12.80	-30.70	-13.00	H
17764.38	-40.38	3.60	12.80	-31.18	-13.00	H

WCDMA BAND II Mode Channel 9800/1960MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16954.38	-45.20	2.90	16.50	-31.60	-13.00	H
17096.88	-44.19	2.90	14.50	-32.59	-13.00	H
17293.75	-43.77	3.20	14.50	-32.47	-13.00	H
17506.25	-39.95	2.90	12.80	-30.05	-13.00	H
17583.75	-39.90	3.30	12.80	-30.40	-13.00	H
17694.38	-40.68	3.30	12.80	-31.18	-13.00	H

WCDMA BAND II Mode Channel 9938/1987.6MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16995.63	-44.41	2.90	16.50	-30.81	-13.00	H
17123.13	-44.36	2.90	14.50	-32.76	-13.00	H
17349.38	-43.71	3.20	14.50	-32.41	-13.00	H
17481.25	-42.19	2.90	14.50	-30.59	-13.00	H
17574.38	-39.68	3.30	12.80	-30.18	-13.00	H
17757.50	-39.63	3.60	12.80	-30.43	-13.00	H

WCDMA BAND V Mode Channel 4357/871.4 MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7206.75	-52.98	1.80	12.00	-44.93	-13.00	H
9107.50	-52.15	2.10	11.60	-44.80	-13.00	H
9304.63	-50.43	2.00	11.60	-42.98	-13.00	H
9475.63	-50.99	2.10	11.60	-43.64	-13.00	V
9738.25	-51.23	2.20	11.20	-44.38	-13.00	H
9885.50	-50.68	2.20	11.20	-43.83	-13.00	H

WCDMA BAND V Mode Channel 4408/881.6MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8473.13	-52.24	1.80	11.30	-44.89	-13.00	H
9105.13	-51.66	2.20	11.60	-44.41	-13.00	H
9291.88	-50.87	2.00	11.60	-43.42	-13.00	H
9471.00	-50.75	2.10	11.60	-43.40	-13.00	V
9728.13	-50.95	2.20	11.20	-44.10	-13.00	H
9911.25	-51.13	2.20	11.20	-44.28	-13.00	H

WCDMA BAND V Mode Channel 4458/891.6MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8451.00	-52.17	1.80	11.30	-44.82	-13.00	H
9093.13	-50.70	2.20	11.60	-43.45	-13.00	H
9304.63	-50.72	2.00	11.60	-43.27	-13.00	H
9472.88	-50.98	2.10	11.60	-43.63	-13.00	V
9740.13	-51.16	2.20	11.20	-44.31	-13.00	H
9800.00	-51.12	2.30	11.20	-44.37	-13.00	H

WCDMA BAND V Mode Channel 4357/871.4 MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8525.63	-53.08	2.10	12.00	-45.33	-13.00	H
9101.13	-52.04	2.20	11.60	-44.79	-13.00	H
9222.75	-50.77	2.10	11.60	-43.42	-13.00	H
9342.13	-51.38	2.00	11.60	-43.93	-13.00	V
9754.25	-50.96	2.20	11.20	-44.11	-13.00	H
9804.63	-51.11	2.30	11.20	-44.36	-13.00	H

WCDMA BAND V Mode Channel 4408/881.6MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7222.13	-52.94	1.80	12.00	-44.89	-13.00	V
8418.75	-51.70	1.80	11.30	-44.35	-13.00	H
9096.00	-50.97	2.20	11.60	-43.72	-13.00	H
9223.50	-50.44	2.10	11.60	-43.09	-13.00	H
9475.50	-51.28	2.10	11.60	-43.93	-13.00	V
9735.13	-50.86	2.20	11.20	-44.01	-13.00	H

WCDMA BAND V Mode Channel 4458/891.6MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7184.63	-52.48	1.80	12.00	-44.43	-13.00	H
8655.38	-52.60	2.00	12.00	-44.75	-13.00	H
9105.38	-51.61	2.20	11.60	-44.36	-13.00	H
9302.00	-50.55	2.00	11.60	-43.10	-13.00	H
9472.88	-51.27	2.10	11.60	-43.92	-13.00	V
9732.00	-50.66	2.20	11.20	-43.81	-13.00	H

WCDMA BAND V Mode Channel 4357/871.4 MHz (16QAM) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8809.88	-53.04	1.90	12.00	-45.09	-13.00	H
9110.38	-51.82	2.10	11.60	-44.47	-13.00	H
9306.75	-49.85	2.00	11.60	-42.40	-13.00	H
9478.38	-50.98	2.10	11.60	-43.63	-13.00	V
9727.38	-50.70	2.20	11.20	-43.85	-13.00	H
9802.88	-50.99	2.30	11.20	-44.24	-13.00	H

WCDMA BAND V Mode Channel 4408/881.6MHz (16QAM) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8457.38	-51.52	1.80	11.30	-44.17	-13.00	H
8833.50	-53.14	1.90	12.00	-45.19	-13.00	H
9101.75	-51.50	2.20	11.60	-44.25	-13.00	H
9223.25	-50.21	2.10	11.60	-42.86	-13.00	H
9474.38	-51.08	2.10	11.60	-43.73	-13.00	V
9754.00	-51.18	2.20	11.20	-44.33	-13.00	H

WCDMA BAND V Mode Channel 4458/891.6MHz (16QAM) -UP

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7325.63	-52.66	1.70	12.00	-44.51	-13.00	H
9096.88	-50.86	2.20	11.60	-43.61	-13.00	H
9304.38	-50.12	2.00	11.60	-42.67	-13.00	H
9475.25	-50.87	2.10	11.60	-43.52	-13.00	V
9744.75	-50.59	2.20	11.20	-43.74	-13.00	H
9799.75	-50.68	2.30	11.20	-43.93	-13.00	H

WCDMA BAND V Mode Channel 4357/871.4 MHz (16QAM) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7320.38	-52.85	1.70	12.00	-44.70	-13.00	H
8715.75	-52.39	2.00	12.00	-44.54	-13.00	V
9104.75	-50.50	2.20	11.60	-43.25	-13.00	H
9299.50	-49.54	2.00	11.60	-42.09	-13.00	H
9473.50	-50.32	2.10	11.60	-42.97	-13.00	V
9729.38	-50.86	2.20	11.20	-44.01	-13.00	H

WCDMA BAND V Mode Channel 4408/881.6MHz (16QAM) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
7140.38	-53.06	1.90	12.00	-45.11	-13.00	H
8436.38	-51.97	1.80	11.30	-44.62	-13.00	H
9104.50	-51.90	2.20	11.60	-44.65	-13.00	H
9224.13	-49.89	2.10	11.60	-42.54	-13.00	H
9474.13	-50.86	2.10	11.60	-43.51	-13.00	V
9747.38	-51.11	2.20	11.20	-44.26	-13.00	H

WCDMA BAND V Mode Channel 4458/891.6MHz (16QAM) -DOWN

Frequency(MHz)	PMea(dBm)	Path loss	Antenna Gain(dBi)	Peak ERP(dBm)	Limit(dBm)	Polarization
8442.75	-52.37	1.80	11.30	-45.02	-13.00	H
9094.13	-51.55	2.20	11.60	-44.30	-13.00	H
9225.25	-49.63	2.10	11.60	-42.28	-13.00	H
9479.00	-50.93	2.10	11.60	-43.58	-13.00	V
9731.63	-50.71	2.20	11.20	-43.86	-13.00	H
9791.75	-51.02	2.30	11.20	-44.27	-13.00	H

WCDMA BAND IV Mode Channel 1537/1753.4MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16970.63	-44.93	2.90	16.50	-31.33	-13.00	H
17210.00	-43.99	2.90	14.50	-32.39	-13.00	H
17296.25	-43.82	3.20	14.50	-32.52	-13.00	H
17455.00	-42.22	2.90	14.50	-30.62	-13.00	H
17546.25	-40.19	2.90	12.80	-30.29	-13.00	H
17761.25	-40.29	3.60	12.80	-31.09	-13.00	H

WCDMA BAND IV Mode Channel 1638/1777.6MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16966.88	-45.64	2.90	16.50	-32.04	-13.00	H
17210.00	-44.25	2.90	14.50	-32.65	-13.00	H
17365.63	-43.19	3.20	14.50	-31.89	-13.00	H
17460.63	-42.23	2.90	14.50	-30.63	-13.00	H
17589.38	-40.10	3.30	12.80	-30.60	-13.00	H
17781.25	-40.50	3.60	12.80	-31.30	-13.00	H

WCDMA BAND IV Mode Channel 1738/1797.6MHz (QPSK) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16988.75	-45.12	2.90	16.50	-31.52	-13.00	H
17177.50	-44.37	2.90	14.50	-32.77	-13.00	H
17364.38	-43.85	3.20	14.50	-32.55	-13.00	H
17513.13	-39.51	2.90	12.80	-29.61	-13.00	H
17536.88	-40.24	2.90	12.80	-30.34	-13.00	H
17786.25	-39.94	3.60	12.80	-30.74	-13.00	H

WCDMA BAND IV Mode Channel 1537/1753.4MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16947.50	-45.18	2.90	16.50	-31.58	-13.00	H
17110.00	-43.65	2.90	14.50	-32.05	-13.00	H
17346.25	-42.98	3.20	14.50	-31.68	-13.00	H
17523.75	-40.48	2.90	12.80	-30.58	-13.00	H
17619.38	-39.52	3.30	12.80	-30.02	-13.00	H
17823.13	-40.63	3.60	12.80	-31.43	-13.00	H

WCDMA BAND IV Mode Channel 1638/1777.6MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16951.25	-45.29	2.90	16.50	-31.69	-13.00	H
17169.38	-43.55	2.90	14.50	-31.95	-13.00	H
17343.75	-43.67	3.20	14.50	-32.37	-13.00	H
17438.13	-41.36	2.90	14.50	-29.76	-13.00	H
17613.13	-39.71	3.30	12.80	-30.21	-13.00	H
17816.25	-40.17	3.60	12.80	-30.97	-13.00	H

WCDMA BAND IV Mode Channel 1738/1797.6MHz (QPSK) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16983.75	-45.21	2.90	16.50	-31.61	-13.00	H
17213.13	-44.23	2.90	14.50	-32.63	-13.00	H
17285.63	-43.27	3.20	14.50	-31.97	-13.00	H
17522.50	-40.22	2.90	12.80	-30.32	-13.00	H
17631.88	-40.44	3.30	12.80	-30.94	-13.00	H
17699.38	-40.34	3.30	12.80	-30.84	-13.00	H

WCDMA BAND IV Mode Channel 1537/1753.4MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16981.25	-45.75	2.90	16.50	-32.15	-13.00	H
17170.63	-44.46	2.90	14.50	-32.86	-13.00	H
17302.50	-43.59	3.20	14.50	-32.29	-13.00	H
17521.88	-40.65	2.90	12.80	-30.75	-13.00	H
17586.88	-40.04	3.30	12.80	-30.54	-13.00	H
17833.13	-40.38	3.60	12.80	-31.18	-13.00	H

WCDMA BAND IV Mode Channel 1638/1777.6MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16939.38	-45.77	2.90	16.50	-32.17	-13.00	H
17118.75	-43.86	2.90	14.50	-32.26	-13.00	H
17300.00	-43.49	3.20	14.50	-32.19	-13.00	H
17417.50	-41.79	2.90	14.50	-30.19	-13.00	H
17610.00	-40.13	3.30	12.80	-30.63	-13.00	H
17840.00	-40.17	3.60	12.80	-30.97	-13.00	H

WCDMA BAND IV Mode Channel 1738/1797.6MHz (16QAM) -UP

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16997.50	-45.11	2.90	16.50	-31.51	-13.00	H
17195.00	-44.28	2.90	14.50	-32.68	-13.00	H
17366.88	-44.03	3.20	14.50	-32.73	-13.00	H
17434.38	-42.70	2.90	14.50	-31.10	-13.00	H
17610.63	-39.70	3.30	12.80	-30.20	-13.00	H
17803.13	-39.95	3.60	12.80	-30.75	-13.00	H

WCDMA BAND IV Mode Channel 1537/1753.4MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16991.88	-45.75	2.90	16.50	-32.15	-13.00	H
17190.00	-43.79	2.90	14.50	-32.19	-13.00	H
17356.88	-43.69	3.20	14.50	-32.39	-13.00	H
17515.63	-39.92	2.90	12.80	-30.02	-13.00	H
17587.50	-40.47	3.30	12.80	-30.97	-13.00	H
17830.63	-40.55	3.60	12.80	-31.35	-13.00	H

WCDMA BAND IV Mode Channel 1638/1777.6MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16964.38	-45.55	2.90	16.50	-31.95	-13.00	H
17210.63	-43.47	2.90	14.50	-31.87	-13.00	H
17306.25	-43.81	3.20	14.50	-32.51	-13.00	H
17521.25	-39.28	2.90	12.80	-29.38	-13.00	H
17598.13	-39.67	3.30	12.80	-30.17	-13.00	H
17838.75	-40.50	3.60	12.80	-31.30	-13.00	H

WCDMA BAND IV Mode Channel 1738/1797.6MHz (16QAM) -DOWN

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Polarization
16985.00	-45.42	2.90	16.50	-31.82	-13.00	H
17115.00	-44.08	2.90	14.50	-32.48	-13.00	H
17275.63	-43.24	3.20	14.50	-31.94	-13.00	H
17508.75	-40.53	2.90	12.80	-30.63	-13.00	H
17606.88	-39.65	3.30	12.80	-30.15	-13.00	H
17770.00	-40.23	3.60	12.80	-31.03	-13.00	H

Note: The maximum value of expanded measurement uncertainty for this test item is U =

2.72dB(30MHz-3GHz)/3.60dB(3GHz-18GHz)/3.58dB(18GHz-40GHz), k = 2

*****END OF REPORT*****