



Shenzhen Free Walk Technology Co. LTD

ADD: Third floor, building 2, industrial park, Hezhou
West District, Baoan Xixiang, Shenzhen

Email: zyx_sz@yeah.net

TEL: 86-0755-29955983 FAX: 86-0755-29955983

APPROVAL SHEET

Customer: Fang Nuo

Product: 5G External Antenna (L=95mm)/ IPEX-1

Model: R1200A4

Part Number: Z02-50615-R01

Written By: Hu Tao

Issued Date: 2025-07-16

CUSTOMER

ENGINEER R&D DEPT	QUALITY DEPT	APPROVED

Free Walk

R&D DEPT	ENGINEER R&D DEPT	APPROVED
Li Wen Ke	Gu Zhenghua	Deng Kai





Document Change Resume

Form number:QR-ZYX-084 APPROVAL REV: A0

Product model		Document change record					
No	Change the type	File number	Date of change	Description of change content	Production / revision	edition	remark



Index

1. Cover	1
2. Document Change Resume	2
3. Index	3
4. The basic parameters	4
5. Product Drawing	5
6. Test Equipment & Conditions	6
7. Test Data	7-10
8. RoHS report list	11
9. TEE PACKING WAY	12

The basic parameters

A. Electrical Characteristics	
Frequency	5150 MHz ~5850MHz
VSWR	≤ 2
Efficiency	>50%
Impedance	50 Ohm
Polarization	Linear
Gain	5G 5dBi
B. Material & Mechanical Characteristics	
Material of Radiator	
Cable Type	Φ 1.13mm Black
Connector Type	IPEX-1
Dimension	
C. Environmental	
Operation Temperature	- 20 °C ~ + 60 °C
Storage Temperature	- 40 °C ~ + 80 °C

NO	Name	Material	Colour	Amount	Remark
①	RF line	ø1.13 line	black	1	
②	Bottom Solid	PC	black	1	
③	Rod sleeve	ABS	black	1	
④	PCB	FR-4	black	1	
⑤	Spring	carbon steel	silver	1	
⑥	Rivet	POM	black	2	
⑦	IPEX	IPEX-1	golden	1	




NOTE:

- Mark * as the key dimension for inspection, and for unmarked tolerance dimensions, check within ± 0.15 .
- Reference drawings without specified dimensions; Other dimensions are subject to actual configuration.
- Plastic must not have any sharp edges, deformation, oil stains, shrinkage, severe imprinting, or other phenomena.
- There should be no virtual soldering, soldering or other phenomena at the finished solder pads, and the conductivity of the finished product should be tested to be OK.
- The material complies with environmental regulations such as ROHS 2.0

Shenzhen free travel communication technology Co., LTD

The third Angle method		Machine type	R1200M4	date	2025-07-15	page number	1/2
①	②	Product name	5G-External antenna	design	audit	audit	Guidog
10以下	± 0.10	Pact number	Z02-50615-R01	audit	FR	MR LI	
10~20	± 0.12	Customer P/N					
20~40	± 0.15	Material quality	N/A	affirm			
40以上	± 0.20	appearance treatment					
Do not observe drawing							



Test Equipment & Conditions


1. Network Analyzers :

Agilent 8753D 5071B


2. Communications Test Set:

Agilent 8960


3. 3D Chamber Test System



(Testing by 3D anechoic chamber)




Phi axis test




Theta axis test

TEST DATA

SWR



Smith




Efficiency&Gain

test data


Freq (MHz)	Effi (%)	Gain (dBi)
5150	73. 11	5. 12
5200	73. 28	5. 29
5250	74. 3	5. 31
5300	75. 86	5. 41
5350	73. 96	5. 35
5400	77. 31	5. 52
5450	75. 99	5. 38
5500	75. 85	5. 27
5550	75. 47	5. 24
5600	76. 04	5. 63
5650	77. 98	5. 6
5700	74. 99	5. 17
5750	77. 45	5. 29
5800	74. 13	5. 26
5850	76. 21	5. 18

3D Patten


5150MHz



5550MHz




5850MHz




2D Patten


XOY 面



ZOX 面



ZOY 面



Shenzhen free travel communication technology Co., LTD

ROHS Report List for WIFI Antenna Material Components

Number	Raw Material Name	Raw material supplier (manufacturer)	Testing agency	Report Number	Test date	Detect expiration date	Notes
1	PC/PBT	yubang	CTI	A2240057268112001	2025/3/5	2026/3/5	 PCPBT.pdf
2	PCB	junxuan	CTI	A2240256191101002E	2025/5/9	2026/5/9	 FR-4 A2 ROHS.pdf
3	ABS	lejing	SGS	CANPC24004074902	2025/3/14	2026/3/14	 ABS HP171-本色 ROHS_CN_240314.pdf
4	Tinned round copper wire	mingxing	CTI	A2240182175102001E	2025/4/12	2026/4/12	 镀锡圆铜线A2240182175102001E (铜线) 2024.04.12.pdf
5	TIN	taiyuan	SGS	CANEC24003588604	2025/3/8	2026/3/8	 CANEC24003588604(锡线).pdf
6	FEP BLUE	jianlong	CTI	A2240269286101007C	2025/5/21	2026/5/21	 见龙 (护套) ROHS 蓝色中文.pdf
7	FEP Whine	jianlong	SGS	A2240269286101002C	2025/5/21	2026/5/21	 见龙 (护套) ROHS 白色中文.pdf
8	Silk screen ink	Xinzheng Chemical	WT	WTH24F12305415C	2025/1/2	2026/1/2	 丝网油墨WTH24F12305415C-2024.01.02.pdf
9	Solder MaskSolder Mask	Xinzheng Chemical	WT	WTH24F12305406C	2025/1/2	2026/1/2	 锡膏WTH24F12305406C-2024.01.02.pdf
10	Nickel-Plated Steel	huapu	SGS	XMNPC24000170702	2025/3/6	2026/3/6	 弹簧-XMNP2403000390PC01_CN.pdf

require:

1. The submission of component material reports must be in accordance with EU implementation requirements, including testing reports for indivisible care methods and named materials, as well as testing for other environmental regulations and requirements
2. If the submitted component materials are to be tested, they must include the composition of the original piece, all materials according to the department's packaging materials, social metal and other materials. No form of control report is accepted. Humorous acceptance of mixed testing reports within three types is accepted, and reports exceeding three types are not accepted
3. The company recognizes the reports provided by the following nine testing institutions, SGS, CTI , ITS, Saibao, Noni, CCIC, bv, STS, set
4. If the first page of the testing report needs to be stamped with our company's official seal and the side needs to be stamped with a saddle stitch seal, each report must be provided. It is not allowed to alter or forge the price report. The supplier must first review the report themselves to ensure that the submitted report is valid, correct, complete, and the content is clear and distinguishable

Provide electronic copies of report requirements: the report can be scanned together with the list; It can also be scanned separately, but with corresponding numbers for easy querying



Product packaging specification


page: 1 of 1

Product Name: antenna




Rea : A00

Except for others



一: Antenna



二: Put them in PE bags, quantity
is packed in (50 100pcs)
Subject to the actual situation



三: Put the antenna in the carton



四: Seal the box and paste the
production label and RoHS
label on the outer box(actual
situation shall prevail)