OBW NVNT ac20 5240MHz Ant B



OBW NVNT ac40 5190MHz Ant B



OBW NVNT ac40 5230MHz Ant B



OBW NVNT ac80 5210MHz Ant B



Test Graphs

-6dB Bandwidth NVNT a 5745MHz Ant B



-6dB Bandwidth NVNT a 5785MHz Ant B



-6dB Bandwidth NVNT a 5825MHz Ant B



-6dB Bandwidth NVNT n20 5745MHz Ant B



-6dB Bandwidth NVNT n20 5785MHz Ant B



-6dB Bandwidth NVNT n20 5825MHz Ant B



-6dB Bandwidth NVNT n40 5755MHz Ant B



-6dB Bandwidth NVNT n40 5795MHz Ant B



-6dB Bandwidth NVNT ac20 5745MHz Ant B



-6dB Bandwidth NVNT ac20 5785MHz Ant B



-6dB Bandwidth NVNT ac20 5825MHz Ant B



-6dB Bandwidth NVNT ac40 5755MHz Ant B



-6dB Bandwidth NVNT ac40 5795MHz Ant B



-6dB Bandwidth NVNT ac80 5775MHz Ant B



Test Graphs

OBW NVNT a 5745MHz Ant B



OBW NVNT a 5785MHz Ant B



OBW NVNT a 5825MHz Ant B



OBW NVNT n20 5745MHz Ant B



OBW NVNT n20 5785MHz Ant B



OBW NVNT n20 5825MHz Ant B



OBW NVNT n40 5755MHz Ant B



OBW NVNT n40 5795MHz Ant B



OBW NVNT ac20 5745MHz Ant B



OBW NVNT ac20 5785MHz Ant B



OBW NVNT ac20 5825MHz Ant B



OBW NVNT ac40 5755MHz Ant B



OBW NVNT ac40 5795MHz Ant B



OBW NVNT ac80 5775MHz Ant B



10. Maximum Conducted Output Power

10.1 Block Diagram Of Test Setup



10.2 Limit

According to FCC §15.407

The maximum conduced output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	1W
5725~5850	1W

10.3 Test procedure

Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.1 However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

• The EUT transmits continuously (or with a duty cycle ≥ 98 percent).

• Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the

transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

10.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

10.5 Test Result

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC120V/60Hz
Test Mode:	(5180-5240MHz); (5745-5825MHz)		

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)		Total(dBm)	Limit (dBm)	Verdict
			Ant A	Ant B			
NVNT	a	5180	2.68	5.22	/	24	Pass
NVNT	a	5200	5.41	4.63	/	24	Pass
NVNT	a	5240	4.9	4.47	/	24	Pass
NVNT	n20	5180	2.73	2.51	5.63	24	Pass
NVNT	n20	5200	2.34	2.13	5.25	24	Pass
NVNT	n20	5240	1.07	2.05	4.60	24	Pass
NVNT	n40	5190	2.46	3.04	5.77	24	Pass
NVNT	n40	5230	1.29	2.5	4.95	24	Pass
NVNT	ac20	5180	2.55	2.71	5.64	24	Pass
NVNT	ac20	5200	2.26	2.45	5.37	24	Pass
NVNT	ac20	5240	1.1	2.32	4.76	24	Pass
NVNT	ac40	5190	2.58	2.94	5.77	24	Pass
NVNT	ac40	5230	1.37	2.44	4.95	24	Pass
NVNT	ac80	5210	1.41	1.27	4.35	24	Pass

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)		Total(dBm)	Limit (dBm)	Verdict
			Ant A	Ant B			
NVNT	a	5745	3.32	2.94	/	30	Pass
NVNT	a	5785	3.08	0.42	/	30	Pass
NVNT	a	5825	2.96	2.74	/	30	Pass
NVNT	n20	5745	0.71	0.57	3.65	30	Pass
NVNT	n20	5785	0.57	0.37	3.48	30	Pass
NVNT	n20	5825	0.42	0.21	3.33	30	Pass
NVNT	n40	5755	0.69	0.55	3.63	30	Pass
NVNT	n40	5795	0.43	0.19	3.32	30	Pass
NVNT	ac20	5745	0.68	0.39	3.55	30	Pass
NVNT	ac20	5785	0.52	0.23	3.39	30	Pass
NVNT	ac20	5825	0.37	-0.12	3.14	30	Pass
NVNT	ac40	5755	0.71	0.55	3.64	30	Pass
NVNT	ac40	5795	0.55	0.22	3.40	30	Pass
NVNT	ac80	5775	0.22	-0.01	3.12	30	Pass

11. Out Of Band Emissions

11.1 Block Diagram Of Test Setup

11.2 Limit

According to FCC §15.407(b)
Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:
(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

11.3 Test procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data

11.5 Test Result

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

Test Graphs

Band Edge NVNT a 5180MHz Low Ant A



Band Edge NVNT a 5240MHz High Ant A



Band Edge NVNT n20 5180MHz Low Ant A



Band Edge NVNT n20 5240MHz High Ant A



Band Edge NVNT n40 5190MHz Low Ant A



Band Edge NVNT n40 5230MHz High Ant A



Band Edge NVNT ac20 5180MHz Low Ant A



Band Edge NVNT ac20 5240MHz High Ant A



Band Edge NVNT ac40 5190MHz Low Ant A



Band Edge NVNT ac40 5230MHz High Ant A



Band Edge NVNT ac80 5210MHz High Ant A



Band Edge NVNT ac80 5210MHz Low Ant A



Test Graphs

Band Edge NVNT a 5745MHz Low Ant A



Band Edge NVNT a 5825MHz High Ant A



Band Edge NVNT n20 5745MHz Low Ant A



Band Edge NVNT n20 5825MHz High Ant A



Band Edge NVNT n40 5755MHz Low Ant A



Band Edge NVNT n40 5795MHz High Ant A



Band Edge NVNT ac20 5745MHz Low Ant A



Band Edge NVNT ac20 5825MHz High Ant A



Band Edge NVNT ac40 5755MHz Low Ant A



Band Edge NVNT ac40 5795MHz High Ant A



Band Edge NVNT ac80 5775MHz High Ant A



Band Edge NVNT ac80 5775MHz Low Ant A



12. Spurious RF Conducted Emissions

12.1 Block Diagram Of Test Setup



12.2 Limit

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:
(1)For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2)For transmitters operating in the 5.725-5.85 GHz band(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

12.3 Test procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

12.4 Test Result

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

About:26.5GHz-40GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

Test Graphs

Tx. Spurious NVNT a 5180MHz Ant A Emission



Tx. Spurious NVNT a 5200MHz Ant A Emission



Tx. Spurious NVNT a 5240MHz Ant A Emission



Tx. Spurious NVNT n20 5180MHz Ant A Emission



Tx. Spurious NVNT n20 5200MHz Ant A Emission



Tx. Spurious NVNT n20 5240MHz Ant A Emission



Tx. Spurious NVNT n40 5190MHz Ant A Emission



Tx. Spurious NVNT n40 5230MHz Ant A Emission



Tx. Spurious NVNT ac20 5180MHz Ant A Emission



Tx. Spurious NVNT ac20 5200MHz Ant A Emission



Tx. Spurious NVNT ac20 5240MHz Ant A Emission



Tx. Spurious NVNT ac40 5190MHz Ant A Emission



Tx. Spurious NVNT ac40 5230MHz Ant A Emission



Tx. Spurious NVNT ac80 5210MHz Ant A Emission



Test Graphs

Tx. Spurious NVNT a 5745MHz Ant A Emission



Tx. Spurious NVNT a 5785MHz Ant A Emission



Tx. Spurious NVNT a 5825MHz Ant A Emission



Tx. Spurious NVNT n20 5745MHz Ant A Emission



Tx. Spurious NVNT n20 5785MHz Ant A Emission



Tx. Spurious NVNT n20 5825MHz Ant A Emission



Tx. Spurious NVNT n40 5755MHz Ant A Emission



Tx. Spurious NVNT n40 5795MHz Ant A Emission



Tx. Spurious NVNT ac20 5745MHz Ant A Emission



Tx. Spurious NVNT ac20 5785MHz Ant A Emission



Tx. Spurious NVNT ac20 5825MHz Ant A Emission



Tx. Spurious NVNT ac40 5755MHz Ant A Emission



Tx. Spurious NVNT ac40 5795MHz Ant A Emission



Tx. Spurious NVNT ac80 5775MHz Ant A Emission



13. Frequency Stability Measurement

13.1 Block Diagram Of Test Setup



13.2 Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

13.3 Test procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc × 106 ppm and he limit is less than ±20ppm (IEEE 802.11nspecification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is -20°C~70°C.

13.4 Test Result

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC120V/60Hz
Test Mode:	TX (5.1G) Mode Frequency U-NII-1 (5180-5240MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5180.0209	5180	0.0209	4.0322
		V max (V)	138.00	5180.0025	5180	0.0025	0.4792
		V min (V)	102.00	5180.0042	5180	0.0042	0.8139
Limits				5150-5250 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5180.0131	5180	0.0131	2.5256
		T (°C)	-10	5180.0089	5180	0.0089	1.7123
		T (°C)	0	5180.0083	5180	0.0083	1.5984
		T (°C)	10	5180.0007	5180	0.0007	0.1390
		T (°C)	20	5180.0121	5180	0.0121	2.3359
		T (°C)	30	5180.0091	5180	0.0091	1.7600
		T (°C)	40	5180.0030	5180	0.0030	0.5729
		T (°C)	50	5180.0030	5180	0.0030	0.5815
		T (°C)	60	5180.0059	5180	0.0059	1.1379
		T (°C)	70	5180.0081	5180	0.0081	1.5647
Limits				5150-5250 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5200.0071	5200	0.0071	1.3663
		V max (V)	138.00	5200.0135	5200	0.0135	2.5884
		V min (V)	102.00	5200.0079	5200	0.0079	1.5237
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5200.01316	5200	0.01316	2.5310
		T (°C)	-10	5200.01023	5200	0.01023	1.9677
		T (°C)	0	5200.00241	5200	0.00241	0.4630
		T (°C)	10	5200.00093	5200	0.00093	0.1783
		T (°C)	20	5200.00807	5200	0.00807	1.5524
		T (°C)	30	5200.00107	5200	0.00107	0.2065
		T (°C)	40	5200.00030	5200	0.00030	0.0579
		T (°C)	50	5200.01322	5200	0.01322	2.5430
		T (°C)	60	5200.01243	5200	0.01243	2.3905
		T (°C)	70	5200.01214	5200	0.01214	2.3343
Limits				5150-5250 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5240.0065	5240	0.0065	1.2348
		V max (V)	138.00	5240.0060	5240	0.0060	1.1420
		V min (V)	102.00	5240.0103	5240	0.0103	1.9570
Limits				5150-5250 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5240.0130	5240	0.0130	2.4823
		T (°C)	-10	5240.0028	5240	0.0028	0.5285
		T (°C)	0	5240.0019	5240	0.0019	0.3614
		T (°C)	10	5240.0028	5240	0.0028	0.5368
		T (°C)	20	5240.0105	5240	0.0105	1.9982
		T (°C)	30	5240.0027	5240	0.0027	0.5246
		T (°C)	40	5240.0102	5240	0.0102	1.9440
		T (°C)	50	5240.0049	5240	0.0049	0.9439
		T (°C)	60	5240.0118	5240	0.0118	2.2454
		T (°C)	70	5240.0012	5240	0.0012	0.2366
Limits				5150-5250 MHz			
Result				Complies			

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC120V/60Hz
Test Mode:	TX (5.8G) Mode Frequency U-NII-3 (5745-5825MHz)		

Voltage vs. Frequency Stabilit

TEST CONDITIONS				Reference Frequency:5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5745.00511	5745	0.00511	0.8903
		V max (V)	138.00	5745.00019	5745	0.00019	0.0332
		V min (V)	102.00	5745.00934	5745	0.00934	1.6255
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5745.00778	5745	0.00778	1.3549
		T (°C)	-10	5745.00912	5745	0.00912	1.5879
		T (°C)	0	5745.00740	5745	0.00740	1.2883
		T (°C)	10	5745.00966	5745	0.00966	1.6818
		T (°C)	20	5745.01039	5745	0.01039	1.8086
		T (°C)	30	5745.01232	5745	0.01232	2.1446
		T (°C)	40	5745.00293	5745	0.00293	0.5099
		T (°C)	50	5745.01057	5745	0.01057	1.8395
		T (°C)	60	5745.01279	5745	0.01279	2.2271
		T (°C)	70	5745.00983	5745	0.00983	1.7113
Limits				5725-5850 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5785.01002	5785	0.01002	1.7324
		V max (V)	138.00	5785.00801	5785	0.00801	1.3844
		V min (V)	102.00	5785.01268	5785	0.01268	2.1923
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5785.00287	5785	0.00287	0.4963
		T (°C)	-10	5785.00459	5785	0.00459	0.7938
		T (°C)	0	5785.01281	5785	0.01281	2.2139
		T (°C)	10	5785.01049	5785	0.01049	1.8133
		T (°C)	20	5785.00227	5785	0.00227	0.3931
		T (°C)	30	5785.00414	5785	0.00414	0.7162
		T (°C)	40	5785.00928	5785	0.00928	1.6035
		T (°C)	50	5785.01196	5785	0.01196	2.0683
		T (°C)	60	5785.00246	5785	0.00246	0.4258
		T (°C)	70	5785.00412	5785	0.00412	0.7124
Limits				5725-5850 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5825.00104	5825	0.00104	0.1787
		V max (V)	138.00	5825.00368	5825	0.00368	0.6326
		V min (V)	102.00	5825.00472	5825	0.00472	0.8097
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency:5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5825.00433	5825	0.00433	0.7434
		T (°C)	-10	5825.00814	5825	0.00814	1.3970
		T (°C)	0	5825.00138	5825	0.00138	0.2367
		T (°C)	10	5825.00716	5825	0.00716	1.2297
		T (°C)	20	5825.00811	5825	0.00811	1.3930
		T (°C)	30	5825.00594	5825	0.00594	1.0204
		T (°C)	40	5825.00225	5825	0.00225	0.3863
		T (°C)	50	5825.00916	5825	0.00916	1.5727
		T (°C)	60	5825.01052	5825	0.01052	1.8053
		T (°C)	70	5825.00640	5825	0.00640	1.0994
Limits				5725-5850 MHz			
Result				Complies			

14. Antenna Requirement

14.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.2 Test Antenna

The EUT antenna is External antenna. It comply with the standard requirement.

15. EUT Photographs

Appendix-Photographs Of EUT Constructional Details

16. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos





STATEMENT

1.The equipment lists are traceable to the national reference standards.

2.The test report can not be partially copied unless prior written approval is issued from our lab.

3.The test report is invalid without stamp of laboratory.

4.The test report is invalid without signature of person(s) testing and authorizing.

5.The test process and test result is only related to the Unit Under Test.

6.The quality system of our laboratory is in accordance with ISO/IEC17025.

7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:
1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL：400-788-9558

P.C.: 518103

FAX：0755-33229357

Website：http://www.chnbctc.com

E-Mail：bctc@bctc-lab.com.cn

※※※※※ **END** ※※※※※