



APPROVAL SHEET

承认书

CUSTOMER NAME 客户名称	Xiamen Milesight IoT Co., Ltd.	
CUSTOMER P/N 客户料号	23.001.000008	
PART NAME 品 名	WIFI-2 黑色 FPC 内置天线 TO SMB 公针 L=100MM WIFI-2 black FPC built-in antenna TO SMB standard pin L = 100MM	
P/ N 料 号	YJC-6N100-S02	
APPROVAL REV. 版 次	A0	
DELIVERY DATE 送样日期	2024 年 06 月 17 日 June 17th, 2024	
PREPARED BY 承 办	殷飞杰 Yin Feijie	
CHECKED BY 审 核	方文锋 Fang Wenfeng	
APPROVED BY 核 准	肖 汉 Xiao Han	
Customer Approved 客 户 承 认		
Prepared By 承 办	Checked By 审 核	Approved By 核 准

总部地址：深圳市光明区马田街道油麻岗路 11 号宏域光明谷 C 栋

Headquarters Address: Building C, Hongyu Guangming Valley, No. 11 Youmaigang Road,
Ma Tian Subdistrict, Guangming District, Shenzhen City

东莞分厂：东莞市桥头镇石水口银河三路 2 号英佳创产业园

Dongguan Branch Factory: No. 2, Hegang Third Road, Shishui Kou, Qiaotou Town, Dongguan
City, Guangdong Province, China, Yingjia Chuang Industrial Park

杭州办事处：杭州滨江区浦沿街道至仁街 5 号滨润科创园 1 栋 509



深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

Hangzhou Office: No. 5, Zhirong Street, Pu'an Subdistrict, Binjiang District, Hangzhou.
Building 1, Binrun Science and Technology Park, Room 509

绵阳办事处: 四川省绵阳市高新区绵兴东路 35 号万向高新国际 4F-34 号

Mianyang Office: No. 34, 4th Floor, Wanxiang High-tech International Building, 35th
Avenue of Mianxing Road, High-tech Zone, Mianyang City, Sichuan Province

电话 Telephone: 0755-27810060

传真 Fax: 0755-27810057

网址 Website: <http://www.szsyjc.com>

目 录 Table of Contents

1、	封面 Cover。	1
2、	目录 Table of Contents。	2
3、	履历表 Curriculum Vitae。	3
4、	天线平面图 Antenna plan view。	4
5、	天线技术参数及环境性能测试 Antenna technical parameters and environmental performance testing。	5-6
6、	天线实物图 Antenna physical diagram。	7
7、	天线性能测试图 Antenna performance test chart。	7
8、	2D.3D (2.4G/5G) 测试数据 2D. 3D (2.4G/5G) Test Data。	8-10
9、	ROHS 物料控制报告 ROHS Material Control Report。	11-12




深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

履历表 Curriculum Vitae:

版本 Version	变更内容及更改原因 Change content and reasons for the change	日期 Date	发行 Release
A/0	初版发行 First edition release	2024 年 06 月 17 日 June 17, 2024	



Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

天线平面图 Antenna plan view:





深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

天线技术参数及环境测试 Antenna technical parameters and environmental testing:

电气技术参数 Electrical technical parameters			
电 性 能 指 标		Electrical Specifications	
频率范围	2400-2500/5150-5850MHz	Frequency Range	2400-2500/5150-5850MHz
电压驻波比	<1.92	VSWR	<1.92
输入阻抗	50 Ω	Input Impedance	50 Ω
方向	全向	Direction	All
增益	3.0 $\pm$ 1dBi	Gain	3.0 $\pm$ 1dBi
机 械 指 标		Mechanical Specifications	
线材颜色	棕色	Wire color	brown
接口形式	SMB	Input connector	SMB
线材长度	100mm	Wire length	100mm
工作温度	-20 $^{\circ}$ C~+70 $^{\circ}$ C	Working Temperature	-20 $^{\circ}$ C~+70 $^{\circ}$ C
工作湿度	20%~80%	Working Humidity	20%~80%



深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

环境性能测试(Environmental performance testing):

项目 (Project)	测试条件 (Test condition)	规格 (Specification)
储存环境 Storage Conditions	In the absence of specified test temperature, humidity, air pressure is as follows: 在没有指定的情况下测试温度、湿度、气压如下: 1. Temperature is $-45^{\circ}\text{C} \sim +85^{\circ}\text{C}$ 1. 温度为 $-45^{\circ}\text{C} \sim +85^{\circ}\text{C}$ 2. Relative humidity of 20~80% 2. 相对湿度为20~80% 3. Air pressure is 86 kpa to 106 kpa 3. 气压为86kpa-106kpa	Electrical and mechanical properties is normal 电气机械性能正常
高低温试验 high and low temperature test	Between 85°C and -45°C for 5 loops, then 1-2 h under normal conditions, check the appearance quality. 在 85°C 与 -45°C 之间进行5次循环,然后在正常条件下1-2H, 检查外观质量。	Size should meet the requirements and should satisfy the content with the electrical and mechanical properties 尺寸应满足规定并应满足于机械、电气性能
耐恒定 湿热试验 Constant damp and hot resistance test	$80 \pm 3\%$ relative humidity, temperature test: 40°C . Lasts 2 h after, try to take out the determination of electrical properties, within 5 min after try 1-2 h under article normal thing, check the appearance quality 相对湿度 $80 \pm 3\%$, 试验温度: 40°C . 持续2H作用后, 试品取出后5min之内测定电气性能, 试品在正常条件下1-2H, 检查外观质量	Size should meet the requirements and should satisfy the content with the electrical and mechanical properties 尺寸应满足规定并应满足于机械、电气性能
振动试验 vibration test	10-55 hz, vibration frequency range of displacement amplitude: 0.35 MM, acceleration amplitude: 50.0 M/S, sweep cycles: 30 times 振频范围10-55HZ, 位移幅值: 0.35MM, 加速度幅值: 50.0M/S, 扫频循环次数: 30次	Electrical and mechanical properties is normal 电气机械性能正常
跌落试验 fall down test	1 m high altitude in accordance with the perpendicular axis free drop 3 times 1M高空按照互相垂直的轴方向自由跌落3次	Electrical and mechanical properties is normal 电气机械性能正常



深圳市英佳创电子科技有限公司
Shenzhen Yingjichuang Electronic Technology Co., Ltd.
<http://www.szsyjc.com>

天线实物图 Antenna physical diagram:



天线性能测试图 Antenna performance test chart:





深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>




2D、3D 测试数据(2.4G/5G)2D and 3D test data (2.4G/5G):

Frequency	Efficiency (%)	Gain. (dBi)
2400MHz	55.16	2.09
2410MHz	55.86	2.15
2420MHz	54.82	2.29
2430MHz	54.99	2.18
2440MHz	54.64	2.14
2450MHz	52.61	2.24
2460MHz	51.45	2.11
2470MHz	50.47	2.03
2480MHz	56.71	2.01
2490MHz	59.18	2.25
2500MHz	51.09	2.12
5150MHz	47.61	3.42
5250MHz	42.78	3.46
5350MHz	43.31	3.33
5450MHz	47.78	3.66
5550MHz	44.82	3.55
5650MHz	46.18	3.39
5750MHz	45.29	3.10
5850MHz	48.87	3.42




Phi 0 2D:

Phi 90 2D

Theta 90 2D




3D 2400:







3D 2450:




3D 2500:



3D 5150:



3D 5550:








深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

3D 5850:





深圳市英佳创电子科技有限公司
 Shenzhen Yingjichuang Electronic Technology Co., Ltd.
<http://www.szsyjc.com>

ROHS 物料控制报告 ROHS Material Control Report											
兹证明向贵司交货的零组件、辅助材料所使用的原材料、以及生产工程中的添加剂等均符合 RoHS 限制使用有害物质指令的环保要求 (RoHS 指令 2011/65/EC) This is to certify that the raw materials used for the components and auxiliary materials delivered to your company, as well as the additives used in the production process, all comply with the environmental protection requirements of the Restriction of Hazardous Substances Directive (RoHS Directive 2011/65/EC). 关于零组件、辅助材料所使用的原材料、包装材料以及和产过程中使用的添加剂等的构成成份报告如下: The composition of the raw materials, packaging materials used for components and auxiliary materials, as well as the additives used in the production process, is as follows:											
组成物料名称 Component /Part Name	组成材料 Material Composition	ICP 报告编号 ICP report #	测试机构 Test Org.	测试时间 Test Date	有 害 物 质 含 量(ppm)						是否合格? PASS?
					Cd	Pb	Hg	Cr ⁶⁺	PBB	PBDE	PASS
线材 Wire material	同轴线缆 Coaxial cable	CANEC25018034403	SGS	25/07/30	ND	ND	ND	ND	ND	ND	PASS
SMB	胶芯 O-ring	TAOEC25007265701	SGS	25/08/06	ND	ND	ND	ND	ND	ND	PASS
	黄铜 Brass	CANEC25032508610	SGS	26/01/06	33	23495	ND	ND	ND	ND	PASS
	金镀层 Gold coating	CANPC26004541501	SGS	26/03/09	ND	49	ND	ND	ND	ND	PASS
环保锡丝 Environmental -friendly tin wire	环保锡丝 Environment al-friendly tin wire	SZXPC26000658916	SGS	26/02/26	ND	22	ND	ND	ND	ND	PASS
FPC	油墨 Ink	ETR25901252M01	SGS	25/09/11	ND	4.78	ND	ND	ND	ND	PASS
	3M9471LE	SHAEC25032493501-1	SGS	26/01/06	ND	ND	ND	ND	ND	ND	PASS



深圳市英佳创电子科技有限公司

Shenzhen Yingjichuang Electronic Technology Co., Ltd.

<http://www.szsyjc.com>

	基材 Base material	A22600588471010004E	CTI	26/04/02	ND	ND	ND	ND	ND	ND	PASS
热缩套管 Heat shrink tubing	热缩套管 Heat shrink tubing	CANEC25021146402	SGS	25/09/01	ND	ND	ND	ND	ND	ND	PASS