



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Xiamen Milesight IoT Co., Ltd.

Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China

FCC ID: 2AYHY-UG63V2

Product Name: LoRaWAN Gateway

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231167606-00B

Date Of Issue: 2024/3/27

Reviewed By: Julie Tan

Julie Tan

Title: RF Engineer

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 20 DB BANDWIDTH.....	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 CHANNEL SEPARATION	20
3.4.1 Applicable Standard.....	20
3.4.2 EUT Setup.....	20
3.4.3 Test Procedure	20
3.5 NUMBER OF HOPPING FREQUENCY	21
3.5.1 Applicable Standard.....	21
3.5.2 EUT Setup.....	21
3.5.3 Test Procedure	21
3.6 TIME OF OCCUPANCY (DWELL TIME)	22
3.6.1 Applicable Standard.....	22
3.6.2 EUT Setup.....	22
3.6.3 Test Procedure	22
3.7 MAXIMUM CONDUCTED OUTPUT POWER.....	24
3.7.1 Applicable Standard.....	24
3.7.2 EUT Setup.....	24

3.7.3 Test Procedure	24
3.8 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	25
3.8.1 Applicable Standard.....	25
3.8.2 EUT Setup.....	25
3.8.3 Test Procedure	25
3.9 ANTENNA REQUIREMENT.....	26
3.9.1 Applicable Standard.....	26
3.9.2 Judgment.....	26
4. TEST DATA AND RESULTS	27
4.1 AC LINE CONDUCTED EMISSIONS.....	27
4.2 RADIATION SPURIOUS EMISSIONS.....	30
4.3 20 dB EMISSION BANDWIDTH:	45
4.4 CHANNEL SEPARATION:	47
4.5 NUMBER OF HOPPING FREQUENCY:	49
4.6 TIME OF OCCUPANCY (DWELL TIME):.....	51
4.7 MAXIMUM CONDUCTED OUTPUT POWER:	53
4.8 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	55
5. EUT PHOTOGRAPHS	58
6. TEST SETUP PHOTOGRAPHS	59

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231167606-00B	Original Report	2024/3/27

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	LoRaWAN Gateway
EUT Model:	UG63-L09NA-915M
Operation Frequency:	902.3-927.6 MHz
Maximum Peak Output Power (Conducted):	20.39dBm
Modulation Type:	Chirp Spread Spectrum (CSS)
Rated Input Voltage:	DC 12V from Adapter or DC 5V from Adapter by USB or DC 5V from PoE Splitter
Serial Number:	2DY0-3(For RF Conducted Test) 2DY0-1(For RE/CE Test)
EUT Received Date:	2023/11/21
EUT Received Status:	Good

Operation Frequency Detail:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	902.3	65	915.2
2	902.5	66	915.4
...	...	...	...
...	...	...	...
...	...	126	927.4
63	914.7	127	927.6
64	914.9	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		902.3	
Middle		914.9	
Highest		927.6	

Antenna Information Detail▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Dongguan Zhongchi Electronic Technology Co.,Ltd	Dipole	50	902-928MHz	-1.87dBi

The Method of §15.203 Compliance:

- ☒ Antenna was permanently attached to the unit.
☐ Antenna use a unique type of connector to attach to the EUT.
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter #1	DONG GUAN ORIENTAL HERO ELECTRICAL FACTORY	OH-1015A0502000U4U- UL	Input: 100-240Vac~50/60Hz 0.5A Output: DC5V, 2A
Adapter #2	HUIZHOU FUJIAAPPLIANCE TECH,CO.,LTD.	FJ-SW2120502000U	Input: 100-240Vac~50/60Hz 0.4A Max Output: DC5V, 2A
Adapter #3	HUIZHOU FUJIAAPPLIANCE TECH,CO.,LTD.	FJ-SW2050501000U	Input: 100-240Vac~50/60Hz 0.25A Max Output: DC5V, 1A
PoE Splitter	Unknown	TYPEC0502	Input: DC37-57V Output: DC5V, 2.4A

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer. Per 2.4G Wifi test report, Powered by Adapter 2# was the worst.		
Equipment Modifications:	No		
EUT Exercise Software:	SecureCRT		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲：			
Test Modes	Power Level Setting		
	Lowest	Middle	Highest
Lora-FHSS	18	19	20

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	G510	CB30920865

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.2	Adapter #2	EUT
RJ45 Cable	No	No	10	Laptop	EUT

1.2.4 Block Diagram of Test Setup

AC Line Conducted Emissions :



Radiation Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9k~30MHz:4.12dB, 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC line conducted emissions	Compliant
FCC §15.205, §15.209, §15.247(d)	Radiated Spurious emissions	Compliant
FCC §15.247(a)(1)	20 dB bandwidth	Compliant
FCC §15.247(a)(1)	Channel separation	Compliant
FCC §15.247(a)(1)(i)	Number of hopping Frequency	Compliant
FCC §15.247(a)(1)(i)	Time of occupancy (dwell time)	Compliant
FCC §15.247(b)(2)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	Band edges	Compliant
FCC §15.203	Antenna requirement	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 10 GHz

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9 - 90 kHz, 110 - 490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 20 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(1)(i)

For frequency hopping systems operating in the 902 – 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude”

determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.4 Channel Separation

3.4.1 Applicable Standard

FCC §15.247 (a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.


3.5 Number Of Hopping Frequency

3.5.1 Applicable Standard

FCC §15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.


3.6 Time Of Occupancy (Dwell Time)

3.6.1 Applicable Standard

FCC §15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} & \text{(Number of hops in the period specified in the requirements)} = \\ & \text{(number of hops on spectrum analyzer)} \times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.


3.7 Maximum Conducted Output Power

3.7.1 Applicable Standard

FCC §15.247 (b)(2)

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

3.7.2 EUT Setup



3.7.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.


3.8 100 kHz Bandwidth of Frequency Band Edge

3.8.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.8.2 EUT Setup



3.8.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.6

For band-edge measurements, use the band-edge procedure in 6.10. Band-edge measurements shall be tested both on single channels, and with the EUT hopping.

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2DY0-1	Test Date:	2023/12/28
Test Site:	CE	Test Mode:	Transmitting (maximum output power mode(Middle channel) was tested)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	21.6	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/3/31	2024/3/30
R&S	EMI Test Receiver	ESR3	102726	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/8/6	2024/8/5
Audix	Test Software	E3	190306 (V9)	N/A	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No.: CR231167606 -RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(125K Adapter 2#)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.158	15.48	9.61	25.09	55.58	30.49	Average
2	0.158	35.60	9.61	45.21	65.58	20.37	QP
3	0.183	14.96	9.61	24.57	54.34	29.77	Average
4	0.183	34.38	9.61	43.99	64.34	20.35	QP
5	0.245	11.86	9.61	21.47	51.91	30.44	Average
6	0.245	30.14	9.61	39.75	61.91	22.16	QP
7	0.532	19.81	9.61	29.42	46.00	16.58	Average
8	0.532	31.06	9.61	40.67	56.00	15.33	QP
9	1.052	8.27	9.62	17.89	46.00	28.11	Average
10	1.052	17.34	9.62	26.96	56.00	29.04	QP
11	13.418	15.44	9.68	25.12	50.00	24.88	Average
12	13.418	25.78	9.68	35.46	60.00	24.54	QP

Project No.: CR231167606 -RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(125K Adapter 2#)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.165	14.72	9.61	24.33	55.20	30.87	Average
2	0.165	35.23	9.61	44.84	65.20	20.36	QP
3	0.212	10.99	9.61	20.60	53.14	32.54	Average
4	0.212	30.70	9.61	40.31	63.14	22.83	QP
5	0.530	19.79	9.61	29.40	46.00	16.60	Average
6	0.530	31.10	9.61	40.71	56.00	15.29	QP
7	1.154	14.97	9.62	24.59	46.00	21.41	Average
8	1.154	22.18	9.62	31.80	56.00	24.20	QP
9	1.584	6.85	9.63	16.48	46.00	29.52	Average
10	1.584	17.62	9.63	27.25	56.00	28.75	QP
11	10.793	13.87	9.67	23.54	50.00	26.46	Average
12	10.793	28.63	9.67	38.30	60.00	21.70	QP

4.2 Radiation Spurious Emissions

Serial Number:	2DY0-1	Test Date:	2024/1/2~2024/1/20
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Vic Du, coco Tian	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25~25.5	Relative Humidity: (%)	43~47	ATM Pressure: (kPa)	101.1~101.5
----------------------	---------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1A	3110611	2023/12/4	2026/12/3
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:


1) 9kHz-30MHz(maximum output power mode(High channel) was tested):

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Parallel
Note: Transmitting SRD




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	35.38	35.23	70.61	128.15	57.54	Peak
2	0.010	34.77	34.24	69.01	127.27	58.26	Peak
3	0.012	34.95	33.39	68.34	125.93	57.59	Peak
4	0.014	36.35	32.45	68.80	124.66	55.86	Peak
5	0.016	34.13	31.59	65.72	123.63	57.91	Peak
6	0.024	32.74	27.52	60.26	119.97	59.71	Peak

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Parallel
Note: Transmitting SRD




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.163	35.89	11.70	47.59	103.35	55.76	Peak
2	0.217	36.24	9.18	45.42	100.86	55.44	Peak
3	0.369	35.95	3.83	39.78	96.26	56.48	Peak
4	0.661	36.01	-0.91	35.10	71.14	36.04	Peak
5	1.043	39.31	-4.36	34.95	67.10	32.15	Peak
6	28.755	38.79	-7.31	31.48	69.54	38.06	Peak

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Ground-parallel
Note: Transmitting SRD




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.010	34.61	34.70	69.31	127.79	58.48	Peak
2	0.011	35.51	34.04	69.55	126.93	57.38	Peak
3	0.013	35.26	33.11	68.37	125.54	57.17	Peak
4	0.016	37.68	31.59	69.27	123.63	54.36	Peak
5	0.024	31.73	27.52	59.25	119.97	60.72	Peak
6	0.033	24.69	23.94	48.63	117.16	68.53	Peak

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Ground-parallel
Note: Transmitting SRD




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.166	34.15	11.58	45.73	103.21	57.48	Peak
2	0.491	36.69	1.15	37.84	73.77	35.93	Peak
3	0.651	38.69	-0.79	37.90	71.28	33.38	Peak
4	0.938	38.28	-3.68	34.60	68.04	33.44	Peak
5	1.071	38.49	-4.47	34.02	66.86	32.84	Peak
6	30.000	38.60	-7.11	31.49	69.54	38.05	Peak

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Perpendicular
Note: Transmitting SRD



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	35.32	35.43	70.75	128.30	57.55	Peak
2	0.010	34.86	34.66	69.52	127.76	58.24	Peak
3	0.013	35.88	32.92	68.80	125.27	56.47	Peak
4	0.015	37.52	31.99	69.51	124.10	54.59	Peak
5	0.018	32.74	30.32	63.06	122.31	59.25	Peak
6	0.024	29.10	27.62	56.72	120.04	63.32	Peak


Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: Perpendicular
Note: Transmitting SRD



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.173	34.11	11.24	45.35	102.84	57.49	Peak
2	0.222	34.05	8.97	43.02	100.68	57.66	Peak
3	0.592	35.86	-0.10	35.76	72.13	36.37	Peak
4	0.708	36.33	-1.46	34.87	70.53	35.66	Peak
5	1.043	39.64	-4.36	35.28	67.10	31.82	Peak
6	29.216	39.01	-7.24	31.77	69.54	37.77	Peak


2) 30MHz-1GHz(maximum output power mode(High channel) was tested):

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: horizontal
Note: Transmitting SRD



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.105	-2.56	27.49	24.93	40.00	15.07	QP
2	150.011	13.50	19.34	32.84	43.50	10.66	Peak
3	325.596	16.80	20.68	37.48	46.00	8.52	Peak
4	375.939	19.83	21.64	41.47	46.00	4.53	QP
5	501.179	13.34	25.02	38.36	46.00	7.64	QP
6	857.025	-1.66	29.17	27.51	46.00	18.49	QP

Project No.: CR231167606 -RF
Tester: Vic Du
Polarization: vertical
Note: Transmitting SRD



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	-2.27	27.16	24.89	40.00	15.11	QP
2	72.847	15.76	14.49	30.25	40.00	9.75	Peak
3	133.619	9.35	19.80	29.15	43.50	14.35	Peak
4	375.939	15.77	21.64	37.41	46.00	8.59	Peak
5	501.179	16.20	25.02	41.22	46.00	4.78	QP
6	958.794	-1.12	29.93	28.81	46.00	17.19	QP

3) Band edge and 1-10GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				902.3	MHz		
902.30	79.36	QP	H	29.46	108.82	N/A	N/A
902.30	85.14	QP	V	29.46	114.60	N/A	N/A
902.00	31.80	QP	V	29.46	61.26	94.60	33.34
1804.600	43.45	PK	H	0.59	44.04	74.00	29.96
1804.600	37.64	AV	H	0.59	38.23	54.00	15.77
1804.600	42.32	PK	V	0.59	42.91	74.00	31.09
1804.600	35.19	AV	V	0.59	35.78	54.00	18.22
2706.900	38.24	PK	H	4.82	43.06	74.00	30.94
2706.900	31.98	AV	H	4.82	36.80	54.00	17.20
2706.900	39.75	PK	V	4.82	44.57	74.00	29.43
2706.900	32.15	AV	V	4.82	36.97	54.00	17.03
3609.200	35.69	PK	H	7.18	42.87	74.00	31.13
3609.200	29.73	AV	H	7.18	36.91	54.00	17.09
3609.200	36.67	PK	V	7.18	43.85	74.00	30.15
3609.200	30.15	AV	V	7.18	37.33	54.00	16.67

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				914.9	MHz		
914.90	80.48	QP	H	29.62	110.10	N/A	N/A
914.90	88.21	QP	V	29.62	117.83	N/A	N/A
1829.800	42.65	PK	H	0.67	43.32	74.00	30.68
1829.800	36.15	AV	H	0.67	36.82	54.00	17.18
1829.800	43.86	PK	V	0.67	44.53	74.00	29.47
1829.800	37.48	AV	V	0.67	38.15	54.00	15.85
2744.700	37.43	PK	H	4.87	42.30	74.00	31.70
2744.700	31.29	AV	H	4.87	36.16	54.00	17.84
2744.700	38.54	PK	V	4.87	43.41	74.00	30.59
2744.700	32.23	AV	V	4.87	37.10	54.00	16.90
3659.600	35.35	PK	H	7.26	42.61	74.00	31.39
3659.600	29.27	AV	H	7.26	36.53	54.00	17.47
3659.600	35.39	PK	V	7.26	42.65	74.00	31.35
3659.600	29.08	AV	V	7.26	36.34	54.00	17.66


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
High Channel:				927.6	MHz		
927.60	82.15	QP	H	29.70	111.85	N/A	N/A
927.60	88.29	QP	V	29.70	117.99	N/A	N/A
928.00	39.30	QP	V	29.70	69.00	97.99	28.99
1855.200	41.46	PK	H	0.77	42.23	74.00	31.77
1855.200	35.68	AV	H	0.77	36.45	54.00	17.55
1855.200	44.79	PK	V	0.77	45.56	74.00	28.44
1855.200	38.26	AV	V	0.77	39.03	54.00	14.97
2782.800	36.42	PK	H	4.91	41.33	74.00	32.67
2782.800	30.09	AV	H	4.91	35.00	54.00	19.00
2782.800	38.64	PK	V	4.91	43.55	74.00	30.45
2782.800	32.19	AV	V	4.91	37.10	54.00	16.90
3710.400	35.47	PK	H	7.47	42.94	74.00	31.06
3710.400	29.11	AV	H	7.47	36.58	54.00	17.42
3710.400	35.26	PK	V	7.47	42.73	74.00	31.27
3710.400	29.47	AV	V	7.47	36.94	54.00	17.06

Worst Test plots (High channel)

1-4GHz:

Project No.: CR231167606 -RF
Tester: coco Tian
Polarization: horizontal
Note:


Date: 2024-01-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1855.200	41.46	0.77	42.23	74.00	31.77	Peak
2	1855.200	35.68	0.77	36.45	54.00	17.55	Average
3	2782.800	36.42	4.91	41.33	74.00	32.67	Peak
4	2782.800	30.09	4.91	35.00	54.00	19.00	Average
5	3710.400	35.47	7.47	42.94	74.00	31.06	Peak
6	3710.400	29.11	7.47	36.58	54.00	17.42	Average


Project No.: CR231167606 -RF
Tester: coco Tian
Polarization: vertical
Note:

Date: 2024-01-20




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1855.200	44.79	0.77	45.56	74.00	28.44	Peak
2	1855.200	38.26	0.77	39.03	54.00	14.97	Average
3	2782.800	38.64	4.91	43.55	74.00	30.45	Peak
4	2782.800	32.19	4.91	37.10	54.00	16.90	Average
5	3710.400	35.26	7.47	42.73	74.00	31.27	Peak
6	3710.400	29.47	7.47	36.94	54.00	17.06	Average

4-10GHz:



Project No.: CR231167606 -RF
Tester: coco Tian
Polarization: vertical
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	6688.000	34.68	14.55	49.23	74.00	24.77	Peak
2	6688.000	28.12	14.55	42.67	54.00	11.33	Average
3	8417.200	32.39	17.18	49.57	74.00	24.43	Peak
4	8417.200	24.88	17.18	42.06	54.00	11.94	Average
5	9173.200	32.40	18.53	50.93	74.00	23.07	Peak
6	9173.200	25.23	18.53	43.76	54.00	10.24	Average

4.3 20 dB Emission Bandwidth:

Serial Number:	2DY0-3	Test Date:	2023/12/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	63	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Channel	Test Frequency (MHz)	20 dB Bandwidth (MHz)	Limit (MHz)
Lowest	902.3	0.138	<0.25
Middle	914.9	0.138	<0.25
Highest	927.6	0.138	<0.25


20 dB Bandwidth

Lowest Channel




ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 00:01:09

Middle Channel



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 00:03:45

Highest Channel



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 00:05:46

4.4 Channel Separation:

Serial Number:	2DY0-3	Test Date:	2023/12/14~2024/2/3
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.5~26.2	Relative Humidity: (%)	50~63	ATM Pressure: (kPa)	101.1~101.4
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Channel	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
Lowest	902.3	0.193	0.138
Middle	914.9	0.319	0.138
Highest	927.6	0.212	0.138


Channel Separation

Lowest Channel




ProjectNo.:CR231167606 Tester:Jim Wei
Date: 3.FEB.2024 07:40:23

Middle Channel



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 3.FEB.2024 07:46:25

Highest Channel



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 21:02:04

4.5 Number Of Hopping Frequency:

Serial Number:	2DY0-3	Test Date:	2023/12/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	63	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Frequency Range (MHz)	Number of Hopping Channel	Limits
902-928	127	≥ 50


Number Of Hopping Frequency

902-915
MHz



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 18:09:10

915-928
MHz



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 19:27:01

4.6 Time Of Occupancy (Dwell Time):

Serial Number:	2DY0-3	Test Date:	2023/12/14-2024/3/27
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei, Jeff Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2-26.9	Relative Humidity: (%)	56-63	ATM Pressure: (kPa)	101.4-102
----------------------	-----------	------------------------------	-------	------------------------	-----------





Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Frequency (MHz)	Pulse width (ms)	Observation time (s)	Hopping Numbers in Observation time	Dwell Time (s)	Limit (s)
914.9	36.981	20	1	0.037	0.400
Note: Observation time= 20s					

	Dwell Time  ProjectNo.:CR231167606 Tester:Jim Wei Date: 14.DEC.2023 00:54:32
Pulse width	 ProjectNo.:CR231167606 Tester:Jim Wei Date: 14.DEC.2023 01:10:21
Hopping Numbers in Observation time 20S	 ProjectNo.:CR231167606 Tester:Jeff Wei Date: 27.MAR.2024 15:28:09
Hopping Numbers in Observation time 60S	 ProjectNo.:CR231167606 Tester:Jeff Wei Date: 27.MAR.2024 15:28:09

4.7 Maximum Conducted Output Power:

Serial Number:	2DY0-3	Test Date:	2023/12/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	63	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Test Channel	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
Lowest	902.3	19.91	30
Middle	914.9	20.39	30
Highest	927.6	20.19	30

Maximum Conducted Output Power


Lowest Channel



Middle Channel



Highest Channel



4.8 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	2DY0-3	Test Date:	2023/12/14~2024/2/3
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jim Wei	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.5~26.2	Relative Humidity: (%)	50~63	ATM Pressure: (kPa)	101.1~101.4
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


100 kHz Bandwidth of Frequency Band Edge-Single Mode

Band Edge,
Left Side



ProjectNo.:CR231167606 Tester:Jim Wei
Date: 14.DEC.2023 00:13:54


Band Edge,
Right Side




ProjectNo.:CR231167606 Tester:Jim Wei
Date: 3.FEB.2024 07:54:00

100 kHz Bandwidth of Frequency Band Edge-Hopping Mode

Band Edge,
Left Side



Band Edge,
Right Side



5. EUT PHOTOGRAPHS

Please refer to the attachment CR231167606-EXP EUT EXTERNAL PHOTOGRAPHS and
CR231167606-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR231167606-00B-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====