

**FCC ID: 2AYJD-DZ07****Portable device**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**2.4G WIFI:**

| Modulation    | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| 802.11b       | 2.412               | 7.521                  | 5.65                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.46728            | 3.00                    | YES                |
|               | 2.442               | 7.646                  | 5.82                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.48258            | 3.00                    | YES                |
|               | 2.462               | 7.542                  | 5.68                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.49272            | 3.00                    | YES                |
| 802.11g       | 2.412               | 6.687                  | 4.66                  | 7±1                 | 8.00                    | 6.31                   | <5            | 1.95983            | 3.00                    | YES                |
|               | 2.442               | 6.1                    | 4.07                  | 7±1                 | 8.00                    | 6.31                   | <5            | 1.97198            | 3.00                    | YES                |
|               | 2.462               | 6.817                  | 4.81                  | 7±1                 | 8.00                    | 6.31                   | <5            | 1.98004            | 3.00                    | YES                |
| 802.11n(HT20) | 2.412               | 6.656                  | 4.63                  | 7±1                 | 8.00                    | 6.31                   | <5            | 1.95983            | 3.00                    | YES                |
|               | 2.442               | 5.411                  | 3.48                  | 6±1                 | 7.00                    | 5.01                   | <5            | 1.56640            | 3.00                    | YES                |
|               | 2.462               | 5.408                  | 3.47                  | 6±1                 | 7.00                    | 5.01                   | <5            | 1.57280            | 3.00                    | YES                |
| 802.11n(HT40) | 2.412               | 3.433                  | 2.20                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.98224            | 3.00                    | YES                |
|               | 2.442               | 3.843                  | 2.42                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.98833            | 3.00                    | YES                |
|               | 2.462               | 3.528                  | 2.25                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.99237            | 3.00                    | YES                |

**Conclusion:**

For the max result :  $2.49272 \leq \text{FCC Limit } 3.0$  for 1g SAR.