RAYLEIGH LABS
Address: 3rd Floor, Block A, Coolpad Building, Intersection of Keyuan Avenue and Baoshen Road, Nanshan Hi-Tech North District, Songpingshan Community, Xili Subdistrict, Nanshan District, Shenzhen

PCB 板载蓝牙天线测试报告

PCB BT Antenna Test Report

一、天线简介/ Introduction of antenna

我司的蓝牙音箱的蓝牙天线直接采用做在主板 PCB 板上的方式，天线为铜泊加喷锡工艺，铜箔厚度：1OZ，板材为 FR－4 厚度 1.6mm 材料。

Our Bluetooth speaker's antenna is directly made on the Main PCB board. The antenna is copper potable tin injection process, copper foil thickness: 1OZ, sheet material is FR - 4 thickness 1.6mm material.

二、天线外形/ Antenna shape

1. 尺寸图/ Size ：





三、天线参数/ Antenna parameters

蓝牙天线工作频率在2402-2480MHz，在此频段产生谐振。下表为天线的主要参数。

The Bluetooth antenna operates at 2402-2480MHz and generates resonance in this frequency band. The next table is the main parameter of the antenna.

蓝牙内置天线/Bluetooth built-in antenna	
Frequency(MHz)	2402 ~ 2480 MHz
VSWR	≤ 1.92
Impedance	50 Ohm Nominal
Return Loss	-8.5 dB Max
Radiation	Omni-directional
Gain (Peak)	1.78 dBi
Polarization	Linear, Vertical
Admitted Power	2W
Connector	Tin

四、天线增益检测报告/ Antenna gain detection report

Spectrum Detector: Test	Agilent E5071B Tang	Test Date : Temperatur	Mar 15, 2019
Test Result:	PA SS	Humidity :	65 %
Modulati on:	GF SK		

最大增益值/ Maximum gain value

Frequency VNA (MHz)	Max Gain(dB)
2400	1.07
2410	1.21
2420	1.1.2
2430	1.09
2440	1.23
2450	1.46
2460	1.78
2470	1.68
2480	1.58
2490	1.52
2500	1.31

方向图/ Directional map：













驻波比图/ Bobbi map：