FCC TEST REPORT

FOR

WAN ZHAO SHENG XUE TECHNOLOGY (SHENZHEN) CO., LTD

Gaming Headset

Test Model: E910

Prepared for	:	WAN ZHAO SHENG XUE TECHNOLOGY (SHENZHEN) CO., LTD
Address	:	#603, Jiazhaona BLDG, 5010 Baoan Avenue, Shenzhen, China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	December 24, 2020
Number of tested samples	:	2
Sample No.	:	201208213A-1,201208213A-2
Date of Test	:	December 24, 2020 ~ January 14, 2021
Date of Report	:	January 14, 2021

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

FCC TEST REPORT

FCC CFR 47 PART 15 C (15.249)

Report Reference No.	**:**	**LCS201208213AEA**
Date of Issue.....	:	January 14, 2021
Testing Laboratory Name.....	**:**	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address.....	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Testing Location/ Procedure.....	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name.....	**:**	**WAN ZHAO SHENG XUE TECHNOLOGY (SHENZHEN) CO., LTD**
Address.....	:	#603, Jiazhaona BLDG, 5010 Baoan Avenue, Shenzhen, China
Test Specification		
Standard.....	:	FCC CFR 47 PART 15 C(15.249) / ANSI C63.10: 2013
Test Report Form No.....	:	LCSEMC-1.0
TRF Originator.....	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	:	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.....	**:**	**Gaming Headset**
Trade Mark.....	:	EKSA
Test Model.....	:	E910
Ratings.....	:	Transmitter: Input: DC 5V, 68mA Receiver: Input: DC 3.5-4.2V,55mA DC 3.7V by Li-ion Battery(600mAh)
Result	**:**	**Positive**

Compiled by:	**Supervised by:**	**Approved by:**
Jack Liu	Jin Wang	Gavin Liang
Jack Liu/ File administrators	Jin Wang/ Technique principal	Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. :	**LCS201208213AEA**	January 14, 2021 Date of issue

Test Model.....	: E910
EUT.....	: Gaming Headset
Applicant.....	**: WAN ZHAO SHENG XUE TECHNOLOGY (SHENZHEN) CO., LTD**
Address.....	: #603, Jiazhaona BLDG, 5010 Baoan Avenue, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: YIZHAO SHENG XUE TECHNOLOGY (SHENZHEN) CO., LTD.**
Address.....	: Room 609-610, 6 / F, T3 Creative Building, Shenzhen Colorful Huiwei Cultural And Creative Expo City, No. 5010, Baoan Avenue, Caowei Community, Hangcheng Street, Bao 'an District, Shenzhen
Telephone.....	: /
Fax.....	: /
Factory.....	**: /**
Address.....	: /
Telephone.....	: /
Fax.....	: /

Test Result	**Positive**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	January 14, 2021	Initial Issue	Gavin Liang

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION....6
1.1 Description of Device (EUT)....6
1.2. Support Equipment List....6
1.3. External I/O....6
1.4. Description of Test Facility....7
1.5. Statement of the measurement uncertainty....7
1.6. Measurement Uncertainty....7
1.7. Description of Test Modes....8
2. TEST METHODOLOGY....9
2.1. EUT Configuration....9
2.2. EUT Exercise....9
2.3. General Test Procedures....9
3. CONNECTION DIAGRAM OF TEST SYSTEM....10
3.1. Justification....10
3.2. EUT Exercise Software....10
3.3. Special Accessories....10
3.4. Block Diagram/Schematics....10
3.5. Equipment Modifications....10
3.6. Test Setup....10
4. SUMMARY OF TEST RESULTS....11
5. ANTENNA REQUIREMENT....12
6. POWER LINE CONDUCTED EMISSIONS....13
7. RADIATED EMISSION MEASUREMENT....16
8. RESULTS FOR BAND EDGE TESTING....24
9. 99% OCCUPIED BANDWIDTH AND 20 DB BANDWIDTH MEASUREMENT....34
10. LIST OF MEASURING EQUIPMENT....37
11. TEST SETUP PHOTOGRAPHS OF THE EUT....38
12. EXTERIOR PHOTOGRAPHS OF THE EUT....38
13. INTERIOR PHOTOGRAPHS OF THE EUT....38

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT	:	Gaming Headset
Test Model	:	E910
Power Supply	:	Transmitter: Input: DC 5V, 68mA Receiver: Input: DC 3.5-4.2V,55mA DC 3.7V by Li-ion Battery(600mAh)
Hardware Version	:	/
Software Version	:	/
SRD	:	
Frequency Range	:	5729MHz~5849MHz
Channel Number	:	31channels
Modulation Type	:	GFSK
Antenna Description	:	PCB Antenna, 0dBi

1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O

I/O Port Description	Quantity	Cable
--	--	--

1.4. Description of Test Facility

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier: CN0071.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	±3.10dB	(1)
		30MHz~200MHz	±2.96dB	(1)
		200MHz~1000MHz	±3.10dB	(1)
		1GHz~26.5GHz	±3.80dB	(1)
		26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	±1.63dB	(1)
Power disturbance	:	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

Operates in the unlicensed Band at 5725MHz~5875MHz. With basic data rate feature, by modulating the RF carrier using ASK techniques. The EUT works in the X-axis, Y-axis, Z-axis. The following operating modes were applied for the related test items. All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Modulation	Frequency Range (MHz)	Data Rate (Mbps)
GFSK	5729MHz~5849MHz	/
For Conducted Emission		
Test Mode	TX Mode	
For Radiated Emission		
Test Mode	TX Mode	

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX.

Channel List:

Channel No.	Channel Frequency (MHz)
1	**5729**
2	5733
3	5737
4	5741
5	5745
6	5749
7	5753
8	5757
9	5761
10	5765
11	5769
12	5773
13	5777
14	5781
15	5785
16	**5789**
17	5793
--	--
--	--
--	-
31	**5849**

Note:Channel Frequency=5729+4*i（i=0,1,2....31）

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is directly placed on the ground. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turntable, which is directly placed on the ground. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

3. CONNECTION DIAGRAM OF TEST SYSTEM

3.1. Justification

The system was configured for testing in a continuous transmit condition. Continuous transmitting was pre-programmed. It'll keep transmitting with modulated signal at the lowest channel by installing the batter. When press the "up" button, it'll move to the next channel. Repeat press "up" button, it'll transmitting at each of the channel used.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by (adb tool input code) provided by application.

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C §15.249		
FCC Rules	**Description Of Test**	**Result**
§15.203	Antenna Requirement	Compliant
§15.207(a)	Power Line Conducted Emissions	Compliant
§15.205(a), §15.209(a), §15.249(a), §15.249(c)	Radiated Emissions Measurement	Compliant
§15.249 (d)	Band Edges Measurement	Compliant
§2.1049	99% and 20 dB Bandwidth	Compliant

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

5. ANTENNA REQUIREMENT

5.1. Standard Applicable

According to § 15.203 and RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.2. Antenna Connected Construction

The EUT use Internal Antenna(PCB Antenna) and maximum antenna gain is 0.0dBi, antenna cannot replacement, meets FCC Part §15.203 antenna requirement. Please see EUT photo for details.

5.3. Results

Compliance

6. POWER LINE CONDUCTED EMISSIONS

6.1. Standard Applicable

According to §15.207 (a) & RSS-Gen § 8.8: For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

6.2. Block Diagram of Test Setup



6.3. Test Results

PASS.

The test data please refer to following page.

Temperature	24.8℃	Humidity	53.7%
Test Engineer	Ken He		

AC Conducted Emission of power adapter @ AC 120V/60Hz

Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1859	31.40	19.17	50.57	64.22	-13.65	QP
2	0.1912	9.84	19.17	29.01	53.98	-24.97	AVG
3	0.7890	10.45	19.30	29.75	56.00	-26.25	QP
4	0.8114	-0.49	19.30	18.81	46.00	-27.19	AVG
5	3.3540	11.78	19.46	31.24	56.00	-24.76	QP
6	3.4756	1.12	19.46	20.58	46.00	-25.42	AVG
7	6.3285	16.66	19.55	36.21	60.00	-23.79	QP
8	6.5716	5.28	19.55	24.83	50.00	-25.17	AVG
9	10.7926	14.56	19.76	34.32	60.00	-25.68	QP
10	11.0806	1.07	19.79	20.86	50.00	-29.14	AVG
11	24.5851	25.28	20.12	45.40	60.00	-14.60	QP
12	24.8551	13.20	20.13	33.33	50.00	-16.67	AVG

Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1860	31.40	19.17	50.57	64.21	-13.64	QP
2	0.1892	11.95	19.17	31.12	54.07	-22.95	AVG
3	0.4335	14.04	19.32	33.36	57.19	-23.83	QP
4	0.4425	1.81	19.32	21.13	47.01	-25.88	AVG
5	1.4190	9.43	19.32	28.75	56.00	-27.25	QP
6	1.4683	-2.70	19.33	16.63	46.00	-29.37	AVG
7	6.3285	16.66	19.55	36.21	60.00	-23.79	QP
8	6.5041	4.19	19.55	23.74	50.00	-26.26	AVG
9	10.7926	14.56	19.76	34.32	60.00	-25.68	QP
10	11.0806	1.07	19.79	20.86	50.00	-29.14	AVG
11	29.0580	26.18	20.14	46.32	60.00	-13.68	QP
12	29.4945	12.04	20.14	32.18	50.00	-17.82	AVG

Notes：

1）Result(dBuv)=Reading Level +Correct Factor;

2）Margin(dB)=Result-Limit;

3）Pre-scan all modes and recorded the worst case results in this report.

7. RADIATED EMISSION MEASUREMENT

7.1. Standard Applicable

According to FCC § 15.249: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) and 15.249 limit in the table below has to be followed.

Fundamental Frequency	Field Strength of fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

According to RSS-210 B.10:

The field strength of fundamental and harmonic emissions, measured at 3 m, shall not exceed 50 mV/m and 0.5 mV/m respectively.

The field strength limits shall be measured using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using an International Special Committee on Radio Interference (CISPR) quasi-peak detector.

Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

7.2. Instruments Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP
Start ~ Stop Frequency	1GHz~10GHz / RB/VB 1MHz/3MHz for PK 1MHz/10Hz for AV

7.3. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 0.8 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height scan range is 1 meter to 2.5 meter.

--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

--- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.4. Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1.5m]) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

7.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

7.6. Test Results of Radiated Emissions (9 KHz~30 MHz)

Temperature	22.3℃	Humidity	54.4%
Test Engineer	Ken He		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:
The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.

7.7. Test Results of Radiated Emissions (30 MHz – 1000 MHz)

Temperature	22.3℃	Humidity	54.4%
Test Engineer	Ken He		

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	48.8427	55.86	-28.82	27.04	40.00	-12.96	QP
2 *	68.3906	61.61	-31.61	30.00	40.00	-10.00	QP
3	118.6012	55.14	-29.30	25.84	43.50	-17.66	QP
4	277.0935	57.80	-28.72	29.08	46.00	-16.92	QP
5	599.3211	50.22	-21.78	28.44	46.00	-17.56	QP
6	796.1829	50.05	-19.61	30.44	46.00	-15.56	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	46.8301	59.64	-28.87	30.77	40.00	-9.23	QP
2	71.5805	57.16	-32.02	25.14	40.00	-14.86	QP
3	169.0053	55.13	-32.56	22.57	43.50	-20.93	QP
4	303.5437	52.76	-28.14	24.62	46.00	-21.38	QP
5	584.7894	50.97	-22.11	28.86	46.00	-17.14	QP
6	755.3872	47.14	-20.14	27.00	46.00	-19.00	QP

Note:

1). Pre-scan all modes and recorded the worst case results in this report ((Low Channel)).

2). Emission level (dBuV/m) = 20 log Emission level (uV/m).

3). Corrected Reading: Factor + Readingl = Level；Factor=Antenna+Cable-Preamplifier。

7.8. Results for Radiated Emissions (1 – 40GHz)

Lower Channel 5729MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.459	42.53	33.24	35.82	9.52	49.47	74.00	-24.53	Peak	Horizontal
11.459	35.42	33.24	35.82	9.52	42.36	54.00	-11.64	Average	Horizontal
11.459	50.32	32.24	35.82	9.52	56.26	74.00	-17.74	Peak	Vertical
11.459	36.52	32.24	35.82	9.52	42.46	54.00	-11.54	Average	Vertical

Middle Channel 5791MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.583	44.69	33.53	35.82	9.58	51.98	74.00	-22.02	Peak	Horizontal
11.583	36.58	33.53	35.82	9.58	43.87	54.00	-10.13	Average	Horizontal
11.583	49.32	32.53	35.82	9.58	55.61	74.00	-18.39	Peak	Vertical
11.583	38.52	32.53	35.82	9.58	44.81	54.00	-9.19	Average	Vertical

High Channel 5849MHz

Freq GHz	Read Level dBuV	Ant. Fac dB/m	Pre. Fac dB	Cab.Los dB	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11.699	44.63	33.01	35.82	9.60	51.42	74.00	-22.58	Peak	Horizontal
11.699	37.52	33.01	35.82	9.60	44.31	54.00	-9.69	Average	Horizontal
11.699	48.52	32.01	35.82	9.60	54.31	74.00	-19.69	Peak	Vertical
11.699	36.34	32.01	35.82	9.60	42.13	54.00	-11.87	Average	Vertical

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

Notes:

1). Measuring frequencies from 9 KHz - 10th harmonic (ex. 40GHz), No emission found between lowest internal used/generated frequency to 30 MHz.

2). Radiated emissions measured in frequency range from 9 KHz - 10th harmonic (ex. 40GHz) were made with an instrument using Peak detector mode.

3).*Margin=Reading level+Cab loss+Ant Fac-Pre Fac-Limit.*

8. RESULTS FOR BAND EDGE TESTING

8.1. Standard Applicable

According to FCC §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to RSS-210 B.10 (b): Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

8.2. Test Setup Layout



Above 1GHz

8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

8.4. Test Procedures

3) Sequence of testing 30MHz to 1000 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

8.5. Measuring Instruments and Setting

Temperature	22.9℃	Humidity	54.2%
Test Engineer	Ken He		

PASS

Remark:

1. *The other emission levels were very low against the limit.*
2. *PK is setting spectrum/receiver. RBW=1MHz/VBW=3MHz/Sweep time=Auto/Detector=Peak;*
3. *AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak*
4. *Please refer to following test plots;*

Test Frequency 5729MHZ

PK Plot（Vertical）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5667.325	51.37	-1.31	50.06	74.00	-23.94	peak
2	5687.575	51.35	-1.31	50.04	74.00	-23.96	peak
3	5728.750	75.82	-1.31	74.51	114.00	-39.49	peak
4	5771.275	50.88	-1.30	49.58	114.00	-64.42	peak
5	5841.025	51.14	-1.30	49.84	114.00	-64.16	peak
6	5860.825	50.90	-1.29	49.61	114.00	-64.39	peak

AV Plot（Vertical）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5678.800	41.71	-1.30	40.41	54.00	-13.59	peak
2	5729.425	63.51	-1.31	62.20	94.00	-31.80	peak
3	5770.600	45.09	-1.30	43.79	94.00	-50.21	peak
4	5804.800	43.11	-1.30	41.81	94.00	-52.19	peak
5	5841.700	40.04	-1.30	38.74	94.00	-55.26	peak
6	5857.000	40.96	-1.29	39.67	94.00	-54.33	peak

PK Plot（Horizontal）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5657.425	50.94	-1.30	49.64	74.00	-24.36	peak
2	5703.100	50.17	-1.31	48.86	74.00	-25.14	peak
3	5728.075	78.71	-1.31	77.40	114.00	-36.60	peak
4	5785.900	49.32	-1.31	48.01	114.00	-65.99	peak
5	5839.225	49.77	-1.31	48.46	114.00	-65.54	peak
6	5863.975	50.70	-1.29	49.41	114.00	-64.59	peak

AV Plot（Horizontal）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5665.975	43.41	-1.31	42.10	54.00	-11.90	peak
2	5698.375	40.31	-1.31	39.00	54.00	-15.00	peak
3	5729.875	65.86	-1.31	64.55	94.00	-29.45	peak
4	5766.325	41.61	-1.30	40.31	94.00	-53.69	peak
5	5814.250	41.37	-1.30	40.07	94.00	-53.93	peak
6	5847.775	38.12	-1.30	36.82	94.00	-57.18	peak

Test Frequency 5849MHZ

PK Plot（Vertical）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	5673.850	50.25	-1.30	48.95	74.00	-25.05	peak
2 *	5722.000	51.28	-1.30	49.98	74.00	-24.02	peak
3	5758.675	50.42	-1.30	49.12	114.00	-64.88	peak
4	5803.225	50.46	-1.30	49.16	114.00	-64.84	peak
5	5849.575	80.47	-1.31	79.16	114.00	-34.84	peak
6	5861.050	50.30	-1.29	49.01	114.00	-64.99	peak

AV Plot（Vertical）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5670.700	42.30	-1.31	40.99	54.00	-13.01	peak
2	5713.225	40.45	-1.31	39.14	54.00	-14.86	peak
3	5762.950	40.93	-1.30	39.63	94.00	-54.37	peak
4	5786.125	43.18	-1.31	41.87	94.00	-52.13	peak
5	5836.975	38.04	-1.30	36.74	94.00	-57.26	peak
6	5849.800	71.03	-1.30	69.73	94.00	-24.27	peak

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

PK Plot（Horizontal）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1 *	5670.700	42.30	-1.31	40.99	54.00	-13.01	peak
2	5713.225	40.45	-1.31	39.14	54.00	-14.86	peak
3	5762.950	40.93	-1.30	39.63	94.00	-54.37	peak
4	5786.125	43.18	-1.31	41.87	94.00	-52.13	peak
5	5836.975	38.04	-1.30	36.74	94.00	-57.26	peak
6	5849.800	71.03	-1.30	69.73	94.00	-24.27	peak

AV Plot（Horizontal）



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	5676.100	42.15	-1.31	40.84	54.00	-13.16	peak
2 *	5709.175	43.97	-1.31	42.66	54.00	-11.34	peak
3	5752.825	45.11	-1.30	43.81	94.00	-50.19	peak
4	5802.550	45.00	-1.31	43.69	94.00	-50.31	peak
5	5819.650	37.98	-1.30	36.68	94.00	-57.32	peak
6	5850.475	68.50	-1.29	67.21	94.00	-26.79	peak

Notes:

1）Level（dBuv/m）=Reading+Factor;

2）Margin(dB)=Level-Limit;

3）Factor=Ant Fac-Pre Fac+Cab Loss.

9. 99% OCCUPIED BANDWIDTH AND 20 DB BANDWIDTH MEASUREMENT

9.1. Standard Applicable

According to § 2.1049 and RSS-Gen section 6.7 "The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs."

In some cases, the "x dB bandwidth" is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

9.2. Block Diagram of Test Setup



9.3. Test Procedure

Use the following spectrum analyzer settings:

Span = 5MHz

RBW = 100KHz

VBW = 300KHz

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

9.4. Test Results

Temperature	22.9℃	Humidity	54.2%
Test Engineer	Ken He		

Test Result of 99% and 20dB Bandwidth Measurement			
Test Frequency (MHz)	99% Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
5729	2.2574	2.597	Non-Specified
5789	2.1313	2.710	Non-Specified
5849	2.2613	2.634	Non-Specified

Remark:

1. *Test results including cable loss;*
2. *Please refer following test plots;*



5729MHz



5789MHz


Keysight Spectrum Analyzer - Occupied BW
Center Freq 5.849000000 GHz
Center Freq: 5.849000000 GHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 20 dB
Radio Std: None
Radio Device: BTS
10 dB/div
Ref 10.00 dBm
Center 5.849 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 5 MHz
Sweep 1 ms
Occupied Bandwidth
2.2613 MHz
Total Power 8.86 dBm
Transmit Freq Error -46.895 kHz
OBW Power 99.00 %
x dB Bandwidth 2.634 MHz
x dB -20.00 dB
Frequency
Center Freq
5.849000000 GHz
CF Step
500.000 kHz
Auto Man
Freq Offset
0 Hz

5849MHz

10. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2020-11-21	2021-11-20
2	DC Power Supply	Agilent	E3642A	N/A	2020-11-13	2021-11-12
3	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2020-10-08	2021-10-07
4	EMI Test Software	Farad	EZ	/	N/A	N/A
5	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2020-06-11	2021-06-10
6	Positioning Controller	MF	MF-7082	/	2020-06-11	2021-06-10
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2018-07-26	2021-07-25
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
10	EMI Test Receiver	R&S	ESR 7	101181	2020-06-11	2021-06-10
11	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2020-11-13	2021-11-12
12	Broadband Preamplifier	/	BP-01M18G	P190501	2020-06-30	2021-06-29
13	RF Cable-R03m	Jye Bao	RG142	CB021	2020-06-11	2021-06-10
14	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2020-06-11	2021-06-10
15	EMI Test Receiver	R&S	ESPI	101840	2020-06-10	2021-06-09
16	Artificial Mains	R&S	ENV216	101288	2020-06-11	2021-06-10
17	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2020-06-10	2021-06-09
18	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2020-09-20	2023-09-19
19	Broadband Preamplifier	SCHWARZBECK	BBV 9719	9719-025	2020-06-22	2021-06-21
Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.						

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.

11. TEST SETUP PHOTOGRAPHS OF THE EUT

Please refer to separated files for Test Setup Photos of the EUT.

12. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

13. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF REPORT----------

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.