

TEST REPORT

Applicant: HANSHOW TECHNOLOGY CO.,LTD.

Address of Applicant: Building 1(IF podium building and 4F) and Building 5 (7F) in Jiaxing Photovolta High-tech Park, No. 1288 Kanghe Rd., Xiuzhou District, Jiaxing, Zhejiang, China

Manufacturer: HANSHOW TECHNOLOGY CO.,LTD.

Address of Manufacturer: Building 1(IF podium building and 4F) and Building 5 (7F) in Jiaxing Photovolta High-tech Park, No. 1288 Kanghe Rd., Xiuzhou District, Jiaxing, Zhejiang, China

Equipment Under Test (EUT)

Product Name: ESL Controller

Model No.: HS_C09961

FCC ID: 2AYMH-C09961

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: May 31, 2024

Date of Test: June 01-20, 2024

Date of report issued: June 20, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	June 20, 2024	Original

Prepared By:




Date:

June 20, 2024

Project Engineer

Check By:



Date:

June 20, 2024

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	8
5.3 DESCRIPTION OF SUPPORT UNITS	8
5.4 DEVIATION FROM STANDARDS	8
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	8
5.6 TEST FACILITY	8
5.7 TEST LOCATION	8
5.8 ADDITIONAL INSTRUCTIONS	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA	11
7.1 ANTENNA REQUIREMENT	11
7.2 CONDUCTED EMISSIONS	12
7.3 RADIATED EMISSION METHOD	15
7.3.1 Field Strength of The Fundamental Signal	17
7.3.2 Spurious emissions	20
7.3.3 Bandedge emissions	45
7.4 20dB OCCUPY BANDWIDTH	50
8 TEST SETUP PHOTO	54
9 EUT CONSTRUCTIONAL DETAILS	54

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10:2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	ESL Controller
Model No.:	HS_C09961
S/N:	N/A
Test sample(s) ID:	GTS2024050431-1
Sample(s) Status	Engineered sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	157
Channel Separation:	0.5MHz
Modulation Type:	GFSK
Antenna Type:	Internal Antenna
Antenna gain:	ANT1:4.07dBi ANT2:4.27dBi ANT3:3.91dBi ANT4:4.17dBi ANT5:4.19dBi
Power supply:	DC 12.0V Or DC 36V~57V by POE

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.
3. All 5 antennas transmitters were work in asynchronous status.
4. Both two power supply modes were tested and only reported the worst case adapter.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402.0	41	2422.0	81	2442.0	121	2462.0
2	2402.5	42	2422.5	82	2442.5	122	2462.5
3	2403.0	43	2423.0	83	2443.0	123	2463.0
4	2403.5	44	2423.5	84	2443.5	124	2463.5
5	2404.0	45	2424.0	85	2444.0	125	2464.0
6	2404.5	46	2424.5	86	2444.5	126	2464.5
7	2405.0	47	2425.0	87	2445.0	127	2465.0
8	2405.5	48	2425.5	88	2445.5	128	2465.5
9	2406.0	49	2426.0	89	2446.0	129	2466.0
10	2406.5	50	2426.5	90	2446.5	130	2466.5
11	2407.0	51	2427.0	91	2447.0	131	2467.0
12	2407.5	52	2427.5	92	2447.5	132	2467.5
13	2408.0	53	2428.0	93	2448.0	133	2468.0
14	2408.5	54	2428.5	94	2448.5	134	2468.5
15	2409.0	55	2429.0	95	2449.0	135	2469.0
16	2409.5	56	2429.5	96	2449.5	136	2469.5
17	2410.0	57	2430.0	97	2450.0	137	2470.0
18	2410.5	58	2430.5	98	2450.5	138	2470.5
19	2411.0	59	2431.0	99	2451.0	139	2471.0
20	2411.5	60	2431.5	100	2451.5	140	2471.5
21	2412.0	61	2432.0	101	2452.0	141	2472.0
22	2412.5	62	2432.5	102	2452.5	142	2472.5
23	2413.0	63	2433.0	103	2453.0	143	2473.0
24	2413.5	64	2433.5	104	2453.5	144	2473.5
25	2414.0	65	2434.0	105	2454.0	145	2474.0
26	2414.5	66	2434.5	106	2454.5	146	2474.5
27	2415.0	67	2435.0	107	2455.0	147	2475.0
28	2415.5	68	2435.5	108	2455.5	148	2475.5
29	2416.0	69	2436.0	109	2456.0	149	2476.0
30	2416.5	70	2436.5	110	2456.5	150	2476.5
31	2417.0	71	2437.0	111	2457.0	151	2477.0
32	2417.5	72	2437.5	112	2457.5	152	2477.5
33	2418.0	73	2438.0	113	2458.0	153	2478.0
34	2418.5	74	2438.5	114	2458.5	154	2478.5
35	2419.0	75	2439.0	115	2459.0	155	2479.0
36	2419.5	76	2439.5	116	2459.5	156	2479.5
37	2420.0	77	2440.0	117	2460.0	157	2480.0
38	2420.5	78	2440.5	118	2460.5		
39	2421.0	79	2441.0	119	2461.0		
40	2421.5	80	2441.5	120	2461.5		

The test frequencies are below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	78.58	78.90	78.01

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
GTS	Adapter	K651-1205000D	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	June 23, 2021	June 22, 2024
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 11, 2024	April 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 19, 2023	March 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	April 17, 2023	April 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 11, 2024	April 10, 2025
8	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 13, 2023	Nov.12, 2024
9	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 11, 2024	April 10, 2025
10	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 11, 2024	April 10, 2025
11	Horn Antenna (18-26.5GHz)	/	UG-598A/U	GTS664	Oct. 29, 2023	Oct. 28, 2024
12	Horn Antenna (26.5-40GHz)	A.H Systems	SAS-573	GTS665	Oct. 29, 2023	Oct. 28, 2024
13	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	March 12, 2024	March 11, 2025
14	Amplifier	/	LNA-1000-30S	GTS650	April 11, 2024	April 10, 2025
15	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 08, 2023	Nov.07, 2024
16	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	April 11, 2024	April 10, 2025
17	Thermo meter	JINCHUANG	GSP-8A	GTS643	April 18, 2024	April 17, 2025
18	RE cable 1	GTS	N/A	GTS675	July 31. 2023	July 30. 2024
19	RE cable 2	GTS	N/A	GTS676	July 31. 2023	July 30. 2024
20	RE cable 3	GTS	N/A	GTS677	July 31. 2023	July 30. 2024
21	RE cable 4	GTS	N/A	GTS678	July 31. 2023	July 30. 2024
22	RE cable 5	GTS	N/A	GTS679	July 31. 2023	July 30. 2024
23	RE cable 6	GTS	N/A	GTS680	July 31. 2023	July 30. 2024
24	RE cable 7	GTS	N/A	GTS681	July 31. 2023	July 30. 2024
25	RE cable 8	GTS	N/A	GTS682	July 31. 2023	July 30. 2024

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 11, 2024	April 10, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 11, 2024	April 10, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	April 11, 2024	April 10, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 11, 2024	April 10, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 11, 2024	April 10, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 11, 2024	April 10, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 11, 2024	April 10, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 11, 2024	April 10, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	April 18, 2024	April 17, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	April 18, 2024	April 17, 2025

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is internal antenna, reference to the appendix II for details.	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
	* Decreases with the logarithm of the frequency.					
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:


Pre-scan all test modes, found worst case at 2402MHz@ ANT 1, and so only show the test result of it.

Line:



Freq	Reading	LISN/ISN	Cable		Limit	Over	
	level	factor	loss	Level	level	limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	48.72	9.56	0.01	58.29	65.74	-7.45	QP
0.15	27.94	9.56	0.01	37.51	55.74	-18.23	Average
0.18	45.11	9.54	0.01	54.66	64.68	-10.02	QP
0.18	24.75	9.54	0.01	34.30	54.68	-20.38	Average
0.60	33.08	9.50	0.02	42.60	56.00	-13.40	QP
0.60	21.06	9.50	0.02	30.58	46.00	-15.42	Average
1.18	23.82	9.52	0.03	33.37	56.00	-22.63	QP
1.18	13.85	9.52	0.03	23.40	46.00	-22.60	Average
11.20	34.34	9.38	0.12	43.84	60.00	-16.16	QP
11.20	22.08	9.38	0.12	31.58	50.00	-18.42	Average
14.67	35.89	9.56	0.16	45.61	60.00	-14.39	QP
14.67	25.87	9.56	0.16	35.59	50.00	-14.41	Average

Neutral:




Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	48.72	9.55	0.01	58.28	65.87	-7.59	QP
0.15	29.23	9.55	0.01	38.79	55.87	-17.08	Average
0.17	45.26	9.56	0.01	54.83	64.77	-9.94	QP
0.17	25.33	9.56	0.01	34.90	54.77	-19.87	Average
0.61	33.61	9.56	0.02	43.19	56.00	-12.81	QP
0.61	22.20	9.56	0.02	31.78	46.00	-14.22	Average
1.20	21.46	9.55	0.03	31.04	56.00	-24.96	QP
1.20	13.27	9.55	0.03	22.85	46.00	-23.15	Average
11.20	33.03	9.55	0.12	42.70	60.00	-17.30	QP
11.20	21.16	9.55	0.12	30.83	50.00	-19.17	Average
14.67	35.40	9.66	0.16	45.22	60.00	-14.78	QP
14.67	25.55	9.66	0.16	35.37	50.00	-14.63	Average



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.

Final Level = Receiver Read level + LISN Factor + Cable Loss

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
			5000 @3m		Peak Value
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				

	 For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test voltage:	DC 3V
Test results:	Pass

Measurement data:**7.3.1 Field Strength of The Fundamental Signal****ANT1****Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	84.05	27.43	2.93	38.88	75.53	114.00	-38.47	Vertical
2402.00	81.40	27.43	2.93	38.88	72.88	114.00	-41.12	Horizontal
2441.00	87.37	27.55	2.96	38.98	78.90	114.00	-35.10	Vertical
2441.00	81.91	27.55	2.96	38.98	73.44	114.00	-40.56	Horizontal
2480.00	86.24	27.64	2.99	39.05	77.82	114.00	-36.18	Vertical
2480.00	78.91	27.64	2.99	39.05	70.49	114.00	-43.51	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	71.63	27.43	2.93	38.88	63.11	94.00	-30.89	Vertical
2402.00	69.63	27.43	2.93	38.88	61.11	94.00	-32.89	Horizontal
2441.00	73.07	27.55	2.96	38.98	64.60	94.00	-29.40	Vertical
2441.00	69.98	27.55	2.96	38.98	61.51	94.00	-32.49	Horizontal
2480.00	71.99	27.64	2.99	39.05	63.57	94.00	-30.43	Vertical
2480.00	70.93	27.64	2.99	39.05	62.51	94.00	-31.49	Horizontal

ANT2**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	84.01	27.43	2.93	38.88	75.49	114.00	-38.51	Vertical
2402.00	81.37	27.43	2.93	38.88	72.85	114.00	-41.15	Horizontal
2441.00	87.33	27.55	2.96	38.98	78.86	114.00	-35.14	Vertical
2441.00	81.87	27.55	2.96	38.98	73.40	114.00	-40.60	Horizontal
2480.00	86.21	27.64	2.99	39.05	77.79	114.00	-36.21	Vertical
2480.00	78.88	27.64	2.99	39.05	70.46	114.00	-43.54	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	71.60	27.43	2.93	38.88	63.08	94.00	-30.92	Vertical
2402.00	69.60	27.43	2.93	38.88	61.08	94.00	-32.92	Horizontal
2441.00	73.03	27.55	2.96	38.98	64.56	94.00	-29.44	Vertical
2441.00	69.94	27.55	2.96	38.98	61.47	94.00	-32.53	Horizontal
2480.00	71.95	27.64	2.99	39.05	63.53	94.00	-30.47	Vertical
2480.00	70.93	27.64	2.99	39.05	62.51	94.00	-31.49	Horizontal

ANT3**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	83.82	27.43	2.93	38.88	75.30	114.00	-38.70	Vertical
2402.00	81.24	27.43	2.93	38.88	72.72	114.00	-41.28	Horizontal
2441.00	87.15	27.55	2.96	38.98	78.68	114.00	-35.32	Vertical
2441.00	81.71	27.55	2.96	38.98	73.24	114.00	-40.76	Horizontal
2480.00	86.07	27.64	2.99	39.05	77.65	114.00	-36.35	Vertical
2480.00	78.76	27.64	2.99	39.05	70.34	114.00	-43.66	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	71.44	27.43	2.93	38.88	62.92	94.00	-31.08	Vertical
2402.00	69.46	27.43	2.93	38.88	60.94	94.00	-33.06	Horizontal
2441.00	72.84	27.55	2.96	38.98	64.37	94.00	-29.63	Vertical
2441.00	69.77	27.55	2.96	38.98	61.30	94.00	-32.70	Horizontal
2480.00	71.75	27.64	2.99	39.05	63.33	94.00	-30.67	Vertical
2480.00	70.71	27.64	2.99	39.05	62.29	94.00	-31.71	Horizontal

ANT4**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	83.80	27.43	2.93	38.88	75.28	114.00	-38.72	Vertical
2402.00	81.23	27.43	2.93	38.88	72.71	114.00	-41.29	Horizontal
2441.00	87.14	27.55	2.96	38.98	78.67	114.00	-35.33	Vertical
2441.00	81.70	27.55	2.96	38.98	73.23	114.00	-40.77	Horizontal
2480.00	86.06	27.64	2.99	39.05	77.64	114.00	-36.36	Vertical
2480.00	78.75	27.64	2.99	39.05	70.33	114.00	-43.67	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	71.43	27.43	2.93	38.88	62.91	94.00	-31.09	Vertical
2402.00	69.44	27.43	2.93	38.88	60.92	94.00	-33.08	Horizontal
2441.00	72.83	27.55	2.96	38.98	64.36	94.00	-29.64	Vertical
2441.00	69.76	27.55	2.96	38.98	61.29	94.00	-32.71	Horizontal
2480.00	71.74	27.64	2.99	39.05	63.32	94.00	-30.68	Vertical
2480.00	70.70	27.64	2.99	39.05	62.28	94.00	-31.72	Horizontal

ANT5**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	83.56	27.43	2.93	38.88	75.04	114.00	-38.96	Vertical
2402.00	81.07	27.43	2.93	38.88	72.55	114.00	-41.45	Horizontal
2441.00	86.92	27.55	2.96	38.98	78.45	114.00	-35.55	Vertical
2441.00	81.49	27.55	2.96	38.98	73.02	114.00	-40.98	Horizontal
2480.00	85.89	27.64	2.99	39.05	77.47	114.00	-36.53	Vertical
2480.00	78.59	27.64	2.99	39.05	70.17	114.00	-43.83	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	71.23	27.43	2.93	38.88	62.71	94.00	-31.29	Vertical
2402.00	69.27	27.43	2.93	38.88	60.75	94.00	-33.25	Horizontal
2441.00	72.59	27.55	2.96	38.98	64.12	94.00	-29.88	Vertical
2441.00	69.55	27.55	2.96	38.98	61.08	94.00	-32.92	Horizontal
2480.00	71.49	27.64	2.99	39.05	63.07	94.00	-30.93	Vertical
2480.00	70.47	27.64	2.99	39.05	62.05	94.00	-31.95	Horizontal

Note: For fundamental frequency , RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value

7.3.2 Spurious emissions

■ Below 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at 2402MHz, and so only show the test result of it


ANT 1:

Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
325.596	52.02	13.34	2.49	32.59	35.26	46.00	-10.74	QP
375.939	49.61	14.99	2.75	32.39	34.96	46.00	-11.04	QP
475.499	51.50	17.17	3.21	32.07	39.81	46.00	-6.19	QP
526.397	46.29	18.08	3.43	31.94	35.86	46.00	-10.14	QP
675.208	38.11	20.45	4.00	31.64	30.92	46.00	-15.08	QP
875.247	39.03	23.62	4.76	31.04	36.37	46.00	-9.63	QP

Vertical




ANT 2:

Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.576	37.74	13.44	0.66	33.73	18.11	40.00	-21.89	QP
92.787	35.60	8.92	1.13	33.60	12.05	43.50	-31.45	QP
104.536	33.56	10.06	1.23	33.55	11.30	43.50	-32.20	QP
186.441	31.92	9.93	1.77	32.88	10.74	43.50	-32.76	QP
499.425	28.15	17.59	3.30	32.00	17.04	46.00	-28.96	QP
916.069	27.15	24.03	4.91	30.92	25.17	46.00	-20.83	QP

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
45.695	35.64	13.32	0.73	33.70	15.99	40.00	-24.01	QP
93.768	36.65	9.03	1.14	33.60	13.22	43.50	-30.28	QP
167.824	38.67	11.67	1.67	33.00	19.01	43.50	-24.49	QP
322.189	29.51	13.22	2.48	32.60	12.61	46.00	-33.39	QP
501.179	26.34	17.62	3.31	32.00	15.27	46.00	-30.73	QP
642.861	26.68	19.97	3.88	31.70	18.83	46.00	-27.17	QP

ANT 3:
Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.715	37.43	13.46	0.66	33.73	17.82	40.00	-22.18	QP
103.442	33.68	9.98	1.22	33.56	11.32	43.50	-32.18	QP
186.441	30.92	9.93	1.77	32.88	9.74	43.50	-33.76	QP
346.809	30.40	14.06	2.61	32.50	14.57	46.00	-31.43	QP
593.050	29.88	19.19	3.70	31.80	20.97	46.00	-25.03	QP
922.516	26.47	24.09	4.93	30.90	24.59	46.00	-21.41	QP

Vertical




ANT 4:
Horizontal




Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
39.994	36.63	13.50	0.66	33.73	17.06	40.00	-22.94	QP
95.427	36.07	9.21	1.16	33.60	12.84	43.50	-30.66	QP
119.436	32.14	11.16	1.36	33.40	11.26	43.50	-32.24	QP
186.441	31.92	9.93	1.77	32.88	10.74	43.50	-32.76	QP
245.951	30.67	11.51	2.10	32.75	11.53	46.00	-34.47	QP
962.162	27.51	24.41	5.09	30.80	26.21	54.00	-27.79	QP

Vertical




ANT 5:
Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.994	35.63	13.50	0.66	33.73	16.06	40.00	-23.94	QP
95.093	35.36	9.17	1.15	33.60	12.08	43.50	-31.42	QP
141.826	29.88	12.42	1.52	33.20	10.62	43.50	-32.88	QP
186.441	31.92	9.93	1.77	32.88	10.74	43.50	-32.76	QP
346.809	27.40	14.06	2.61	32.50	11.57	46.00	-34.43	QP
729.358	25.92	21.38	4.19	31.50	19.99	46.00	-26.01	QP

Vertical



■ Above 1GHz

ANT 1

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.61	31.22	4.63	37.68	33.78	74.00	-40.22	Vertical
7206.00	30.70	36.25	6.52	37.81	35.66	74.00	-38.34	Vertical
9608.00	30.47	37.97	7.98	37.93	38.49	74.00	-35.51	Vertical
4804.00	39.55	31.22	4.63	37.68	37.72	74.00	-36.28	Horizontal
7206.00	32.31	36.25	6.52	37.81	37.27	74.00	-36.73	Horizontal
9608.00	29.73	37.97	7.98	37.93	37.75	74.00	-36.25	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.74	31.22	4.63	37.68	22.91	54.00	-31.09	Vertical
7206.00	19.58	36.25	6.52	37.81	24.54	54.00	-29.46	Vertical
9608.00	18.77	37.97	7.98	37.93	26.79	54.00	-27.21	Vertical
4804.00	28.78	31.22	4.63	37.68	26.95	54.00	-27.05	Horizontal
7206.00	21.64	36.25	6.52	37.81	26.60	54.00	-27.40	Horizontal
9608.00	18.35	37.97	7.98	37.93	26.37	54.00	-27.63	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.52	31.33	4.69	37.62	33.92	74.00	-40.08	Vertical
7323.00	30.64	36.43	6.63	37.77	35.93	74.00	-38.07	Vertical
9764.00	30.41	38.10	8.03	37.95	38.59	74.00	-35.41	Vertical
4882.00	39.44	31.33	4.69	37.62	37.84	74.00	-36.16	Horizontal
7323.00	32.24	36.43	6.63	37.77	37.53	74.00	-36.47	Horizontal
9764.00	29.67	38.10	8.03	37.95	37.85	74.00	-36.15	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.67	31.33	4.69	37.62	23.07	54.00	-30.93	Vertical
7323.00	19.54	36.43	6.63	37.77	24.83	54.00	-29.17	Vertical
9764.00	18.72	38.10	8.03	37.95	26.90	54.00	-27.10	Vertical
4882.00	28.70	31.33	4.69	37.62	27.10	54.00	-26.90	Horizontal
7323.00	21.59	36.43	6.63	37.77	26.88	54.00	-27.12	Horizontal
9764.00	18.31	38.10	8.03	37.95	26.49	54.00	-27.51	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.74	31.41	4.77	37.56	34.36	74.00	-39.64	Vertical
7440.00	30.79	36.62	6.73	37.73	36.41	74.00	-37.59	Vertical
9920.00	30.54	38.27	8.08	37.98	38.91	74.00	-35.09	Vertical
4960.00	39.70	31.41	4.77	37.56	38.32	74.00	-35.68	Horizontal
7440.00	32.41	36.62	6.73	37.73	38.03	74.00	-35.97	Horizontal
9920.00	29.82	38.27	8.08	37.98	38.19	74.00	-35.81	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.89	31.41	4.77	37.56	23.51	54.00	-30.49	Vertical
7440.00	19.68	36.62	6.73	37.73	25.30	54.00	-28.70	Vertical
9920.00	18.85	38.27	8.08	37.98	27.22	54.00	-26.78	Vertical
4960.00	28.95	31.41	4.77	37.56	27.57	54.00	-26.43	Horizontal
7440.00	21.75	36.62	6.73	37.73	27.37	54.00	-26.63	Horizontal
9920.00	18.46	38.27	8.08	37.98	26.83	54.00	-27.17	Horizontal

ANT 2

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.59	31.22	4.63	37.68	33.76	74.00	-40.24	Vertical
7206.00	30.69	36.25	6.52	37.81	35.65	74.00	-38.35	Vertical
9608.00	30.45	37.97	7.98	37.93	38.47	74.00	-35.53	Vertical
4804.00	39.52	31.22	4.63	37.68	37.69	74.00	-36.31	Horizontal
7206.00	32.29	36.25	6.52	37.81	37.25	74.00	-36.75	Horizontal
9608.00	29.71	37.97	7.98	37.93	37.73	74.00	-36.27	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.73	31.22	4.63	37.68	22.90	54.00	-31.10	Vertical
7206.00	19.57	36.25	6.52	37.81	24.53	54.00	-29.47	Vertical
9608.00	18.75	37.97	7.98	37.93	26.77	54.00	-27.23	Vertical
4804.00	28.76	31.22	4.63	37.68	26.93	54.00	-27.07	Horizontal
7206.00	21.63	36.25	6.52	37.81	26.59	54.00	-27.41	Horizontal
9608.00	18.34	37.97	7.98	37.93	26.36	54.00	-27.64	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.64	31.33	4.69	37.62	34.04	74.00	-39.96	Vertical
7323.00	30.72	36.43	6.63	37.77	36.01	74.00	-37.99	Vertical
9764.00	30.48	38.10	8.03	37.95	38.66	74.00	-35.34	Vertical
4882.00	39.58	31.33	4.69	37.62	37.98	74.00	-36.02	Horizontal
7323.00	32.33	36.43	6.63	37.77	37.62	74.00	-36.38	Horizontal
9764.00	29.75	38.10	8.03	37.95	37.93	74.00	-36.07	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.77	31.33	4.69	37.62	23.17	54.00	-30.83	Vertical
7323.00	19.60	36.43	6.63	37.77	24.89	54.00	-29.11	Vertical
9764.00	18.78	38.10	8.03	37.95	26.96	54.00	-27.04	Vertical
4882.00	28.81	31.33	4.69	37.62	27.21	54.00	-26.79	Horizontal
7323.00	21.66	36.43	6.63	37.77	26.95	54.00	-27.05	Horizontal
9764.00	18.37	38.10	8.03	37.95	26.55	54.00	-27.45	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.13	31.41	4.77	37.56	34.75	74.00	-39.25	Vertical
7440.00	31.05	36.62	6.73	37.73	36.67	74.00	-37.33	Vertical
9920.00	30.78	38.27	8.08	37.98	39.15	74.00	-34.85	Vertical
4960.00	40.18	31.41	4.77	37.56	38.80	74.00	-35.20	Horizontal
7440.00	32.70	36.62	6.73	37.73	38.32	74.00	-35.68	Horizontal
9920.00	30.09	38.27	8.08	37.98	38.46	74.00	-35.54	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.22	31.41	4.77	37.56	23.84	54.00	-30.16	Vertical
7440.00	19.91	36.62	6.73	37.73	25.53	54.00	-28.47	Vertical
9920.00	19.05	38.27	8.08	37.98	27.42	54.00	-26.58	Vertical
4960.00	29.32	31.41	4.77	37.56	27.94	54.00	-26.06	Horizontal
7440.00	22.01	36.62	6.73	37.73	27.63	54.00	-26.37	Horizontal
9920.00	18.69	38.27	8.08	37.98	27.06	54.00	-26.94	Horizontal

ANT 3

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	36.03	31.22	4.63	37.68	34.20	74.00	-39.80	Vertical
7206.00	30.99	36.25	6.52	37.81	35.95	74.00	-38.05	Vertical
9608.00	30.72	37.97	7.98	37.93	38.74	74.00	-35.26	Vertical
4804.00	40.06	31.22	4.63	37.68	38.23	74.00	-35.77	Horizontal
7206.00	32.63	36.25	6.52	37.81	37.59	74.00	-36.41	Horizontal
9608.00	30.02	37.97	7.98	37.93	38.04	74.00	-35.96	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	25.09	31.22	4.63	37.68	23.26	54.00	-30.74	Vertical
7206.00	19.82	36.25	6.52	37.81	24.78	54.00	-29.22	Vertical
9608.00	18.97	37.97	7.98	37.93	26.99	54.00	-27.01	Vertical
4804.00	29.17	31.22	4.63	37.68	27.34	54.00	-26.66	Horizontal
7206.00	21.91	36.25	6.52	37.81	26.87	54.00	-27.13	Horizontal
9608.00	18.60	37.97	7.98	37.93	26.62	54.00	-27.38	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.40	31.33	4.69	37.62	33.80	74.00	-40.20	Vertical
7323.00	30.57	36.43	6.63	37.77	35.86	74.00	-38.14	Vertical
9764.00	30.34	38.10	8.03	37.95	38.52	74.00	-35.48	Vertical
4882.00	39.30	31.33	4.69	37.62	37.70	74.00	-36.30	Horizontal
7323.00	32.15	36.43	6.63	37.77	37.44	74.00	-36.56	Horizontal
9764.00	29.59	38.10	8.03	37.95	37.77	74.00	-36.23	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.58	31.33	4.69	37.62	22.98	54.00	-31.02	Vertical
7323.00	19.47	36.43	6.63	37.77	24.76	54.00	-29.24	Vertical
9764.00	18.67	38.10	8.03	37.95	26.85	54.00	-27.15	Vertical
4882.00	28.60	31.33	4.69	37.62	27.00	54.00	-27.00	Horizontal
7323.00	21.52	36.43	6.63	37.77	26.81	54.00	-27.19	Horizontal
9764.00	18.24	38.10	8.03	37.95	26.42	54.00	-27.58	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.31	31.41	4.77	37.56	33.93	74.00	-40.07	Vertical
7440.00	30.50	36.62	6.73	37.73	36.12	74.00	-37.88	Vertical
9920.00	30.29	38.27	8.08	37.98	38.66	74.00	-35.34	Vertical
4960.00	39.18	31.41	4.77	37.56	37.80	74.00	-36.20	Horizontal
7440.00	32.08	36.62	6.73	37.73	37.70	74.00	-36.30	Horizontal
9920.00	29.52	38.27	8.08	37.98	37.89	74.00	-36.11	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.52	31.41	4.77	37.56	23.14	54.00	-30.86	Vertical
7440.00	19.43	36.62	6.73	37.73	25.05	54.00	-28.95	Vertical
9920.00	18.63	38.27	8.08	37.98	27.00	54.00	-27.00	Vertical
4960.00	28.53	31.41	4.77	37.56	27.15	54.00	-26.85	Horizontal
7440.00	21.48	36.62	6.73	37.73	27.10	54.00	-26.90	Horizontal
9920.00	18.20	38.27	8.08	37.98	26.57	54.00	-27.43	Horizontal

ANT 4

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.70	31.22	4.63	37.68	33.87	74.00	-40.13	Vertical
7206.00	30.77	36.25	6.52	37.81	35.73	74.00	-38.27	Vertical
9608.00	30.52	37.97	7.98	37.93	38.54	74.00	-35.46	Vertical
4804.00	39.66	31.22	4.63	37.68	37.83	74.00	-36.17	Horizontal
7206.00	32.38	36.25	6.52	37.81	37.34	74.00	-36.66	Horizontal
9608.00	29.79	37.97	7.98	37.93	37.81	74.00	-36.19	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.82	31.22	4.63	37.68	22.99	54.00	-31.01	Vertical
7206.00	19.63	36.25	6.52	37.81	24.59	54.00	-29.41	Vertical
9608.00	18.81	37.97	7.98	37.93	26.83	54.00	-27.17	Vertical
4804.00	28.87	31.22	4.63	37.68	27.04	54.00	-26.96	Horizontal
7206.00	21.70	36.25	6.52	37.81	26.66	54.00	-27.34	Horizontal
9608.00	18.41	37.97	7.98	37.93	26.43	54.00	-27.57	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.40	31.33	4.69	37.62	33.80	74.00	-40.20	Vertical
7323.00	30.57	36.43	6.63	37.77	35.86	74.00	-38.14	Vertical
9764.00	30.35	38.10	8.03	37.95	38.53	74.00	-35.47	Vertical
4882.00	39.30	31.33	4.69	37.62	37.70	74.00	-36.30	Horizontal
7323.00	32.16	36.43	6.63	37.77	37.45	74.00	-36.55	Horizontal
9764.00	29.59	38.10	8.03	37.95	37.77	74.00	-36.23	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.58	31.33	4.69	37.62	22.98	54.00	-31.02	Vertical
7323.00	19.47	36.43	6.63	37.77	24.76	54.00	-29.24	Vertical
9764.00	18.67	38.10	8.03	37.95	26.85	54.00	-27.15	Vertical
4882.00	28.60	31.33	4.69	37.62	27.00	54.00	-27.00	Horizontal
7323.00	21.52	36.43	6.63	37.77	26.81	54.00	-27.19	Horizontal
9764.00	18.24	38.10	8.03	37.95	26.42	54.00	-27.58	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.07	31.41	4.77	37.56	34.69	74.00	-39.31	Vertical
7440.00	31.01	36.62	6.73	37.73	36.63	74.00	-37.37	Vertical
9920.00	30.74	38.27	8.08	37.98	39.11	74.00	-34.89	Vertical
4960.00	40.10	31.41	4.77	37.56	38.72	74.00	-35.28	Horizontal
7440.00	32.65	36.62	6.73	37.73	38.27	74.00	-35.73	Horizontal
9920.00	30.04	38.27	8.08	37.98	38.41	74.00	-35.59	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.16	31.41	4.77	37.56	23.78	54.00	-30.22	Vertical
7440.00	19.87	36.62	6.73	37.73	25.49	54.00	-28.51	Vertical
9920.00	19.02	38.27	8.08	37.98	27.39	54.00	-26.61	Vertical
4960.00	29.26	31.41	4.77	37.56	27.88	54.00	-26.12	Horizontal
7440.00	21.96	36.62	6.73	37.73	27.58	54.00	-26.42	Horizontal
9920.00	18.65	38.27	8.08	37.98	27.02	54.00	-26.98	Horizontal

ANT 5

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.86	31.22	4.63	37.68	34.03	74.00	-39.97	Vertical
7206.00	30.87	36.25	6.52	37.81	35.83	74.00	-38.17	Vertical
9608.00	30.62	37.97	7.98	37.93	38.64	74.00	-35.36	Vertical
4804.00	39.85	31.22	4.63	37.68	38.02	74.00	-35.98	Horizontal
7206.00	32.50	36.25	6.52	37.81	37.46	74.00	-36.54	Horizontal
9608.00	29.90	37.97	7.98	37.93	37.92	74.00	-36.08	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.95	31.22	4.63	37.68	23.12	54.00	-30.88	Vertical
7206.00	19.72	36.25	6.52	37.81	24.68	54.00	-29.32	Vertical
9608.00	18.89	37.97	7.98	37.93	26.91	54.00	-27.09	Vertical
4804.00	29.02	31.22	4.63	37.68	27.19	54.00	-26.81	Horizontal
7206.00	21.80	36.25	6.52	37.81	26.76	54.00	-27.24	Horizontal
9608.00	18.50	37.97	7.98	37.93	26.52	54.00	-27.48	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.64	31.33	4.69	37.62	34.04	74.00	-39.96	Vertical
7323.00	30.73	36.43	6.63	37.77	36.02	74.00	-37.98	Vertical
9764.00	30.48	38.10	8.03	37.95	38.66	74.00	-35.34	Vertical
4882.00	39.58	31.33	4.69	37.62	37.98	74.00	-36.02	Horizontal
7323.00	32.33	36.43	6.63	37.77	37.62	74.00	-36.38	Horizontal
9764.00	29.75	38.10	8.03	37.95	37.93	74.00	-36.07	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.77	31.33	4.69	37.62	23.17	54.00	-30.83	Vertical
7323.00	19.60	36.43	6.63	37.77	24.89	54.00	-29.11	Vertical
9764.00	18.78	38.10	8.03	37.95	26.96	54.00	-27.04	Vertical
4882.00	28.82	31.33	4.69	37.62	27.22	54.00	-26.78	Horizontal
7323.00	21.67	36.43	6.63	37.77	26.96	54.00	-27.04	Horizontal
9764.00	18.38	38.10	8.03	37.95	26.56	54.00	-27.44	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.08	31.41	4.77	37.56	34.70	74.00	-39.30	Vertical
7440.00	31.02	36.62	6.73	37.73	36.64	74.00	-37.36	Vertical
9920.00	30.75	38.27	8.08	37.98	39.12	74.00	-34.88	Vertical
4960.00	40.12	31.41	4.77	37.56	38.74	74.00	-35.26	Horizontal
7440.00	32.67	36.62	6.73	37.73	38.29	74.00	-35.71	Horizontal
9920.00	30.05	38.27	8.08	37.98	38.42	74.00	-35.58	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.18	31.41	4.77	37.56	23.80	54.00	-30.20	Vertical
7440.00	19.88	36.62	6.73	37.73	25.50	54.00	-28.50	Vertical
9920.00	19.03	38.27	8.08	37.98	27.40	54.00	-26.60	Vertical
4960.00	29.28	31.41	4.77	37.56	27.90	54.00	-26.10	Horizontal
7440.00	21.97	36.62	6.73	37.73	27.59	54.00	-26.41	Horizontal
9920.00	18.66	38.27	8.08	37.98	27.03	54.00	-26.97	Horizontal

Remarks:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

7.3.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

ANT 1

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.25	27.14	2.81	38.64	35.56	74.00	-38.44	Horizontal
2390.00	48.24	27.37	2.91	38.84	39.68	74.00	-34.32	Horizontal
2400.00	49.96	27.41	2.92	38.86	41.43	74.00	-32.57	Horizontal
2310.00	44.93	27.14	2.81	38.64	36.24	74.00	-37.76	Vertical
2390.00	49.42	27.37	2.91	38.84	40.86	74.00	-33.14	Vertical
2400.00	50.90	27.41	2.92	38.86	42.37	74.00	-31.63	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.49	27.14	2.81	38.64	25.80	54.00	-28.20	Horizontal
2390.00	35.81	27.37	2.91	38.84	27.25	54.00	-26.75	Horizontal
2400.00	36.91	27.41	2.92	38.86	28.38	54.00	-25.62	Horizontal
2310.00	34.54	27.14	2.81	38.64	25.85	54.00	-28.15	Vertical
2390.00	36.59	27.37	2.91	38.84	28.03	54.00	-25.97	Vertical
2400.00	37.69	27.41	2.92	38.86	29.16	54.00	-24.84	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.52	27.82	2.99	39.05	38.28	74.00	-35.72	Horizontal
2500.00	45.43	27.70	3.01	39.10	37.04	74.00	-36.96	Horizontal
2483.50	47.59	27.82	2.99	39.05	39.35	74.00	-34.65	Vertical
2500.00	46.56	27.70	3.01	39.10	38.17	74.00	-35.83	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.34	27.82	2.99	39.05	27.10	54.00	-26.90	Horizontal
2500.00	35.14	27.70	3.01	39.10	26.75	54.00	-27.25	Horizontal
2483.50	35.65	27.82	2.99	39.05	27.41	54.00	-26.59	Vertical
2500.00	35.18	27.70	3.01	39.10	26.79	54.00	-27.21	Vertical

Remark:

Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

ANT 2

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	43.80	27.14	2.81	38.64	35.11	74.00	-38.89	Horizontal
2390.00	47.72	27.37	2.91	38.84	39.16	74.00	-34.84	Horizontal
2400.00	49.44	27.41	2.92	38.86	40.91	74.00	-33.09	Horizontal
2310.00	44.43	27.14	2.81	38.64	35.74	74.00	-38.26	Vertical
2390.00	48.85	27.37	2.91	38.84	40.29	74.00	-33.71	Vertical
2400.00	50.29	27.41	2.92	38.86	41.76	74.00	-32.24	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.14	27.14	2.81	38.64	25.45	54.00	-28.55	Horizontal
2390.00	35.43	27.37	2.91	38.84	26.87	54.00	-27.13	Horizontal
2400.00	36.45	27.41	2.92	38.86	27.92	54.00	-26.08	Horizontal
2310.00	34.15	27.14	2.81	38.64	25.46	54.00	-28.54	Vertical
2390.00	36.17	27.37	2.91	38.84	27.61	54.00	-26.39	Vertical
2400.00	37.28	27.41	2.92	38.86	28.75	54.00	-25.25	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.01	27.82	2.99	39.05	37.77	74.00	-36.23	Horizontal
2500.00	45.01	27.70	3.01	39.10	36.62	74.00	-37.38	Horizontal
2483.50	47.01	27.82	2.99	39.05	38.77	74.00	-35.23	Vertical
2500.00	46.09	27.70	3.01	39.10	37.70	74.00	-36.30	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.98	27.82	2.99	39.05	26.74	54.00	-27.26	Horizontal
2500.00	34.85	27.70	3.01	39.10	26.46	54.00	-27.54	Horizontal
2483.50	35.42	27.82	2.99	39.05	27.18	54.00	-26.82	Vertical
2500.00	34.85	27.70	3.01	39.10	26.46	54.00	-27.54	Vertical

Remark:

Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

ANT 3

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	43.91	27.14	2.81	38.64	35.22	74.00	-38.78	Horizontal
2390.00	47.84	27.37	2.91	38.84	39.28	74.00	-34.72	Horizontal
2400.00	49.56	27.41	2.92	38.86	41.03	74.00	-32.97	Horizontal
2310.00	44.55	27.14	2.81	38.64	35.86	74.00	-38.14	Vertical
2390.00	48.99	27.37	2.91	38.84	40.43	74.00	-33.57	Vertical
2400.00	50.44	27.41	2.92	38.86	41.91	74.00	-32.09	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.22	27.14	2.81	38.64	25.53	54.00	-28.47	Horizontal
2390.00	35.52	27.37	2.91	38.84	26.96	54.00	-27.04	Horizontal
2400.00	36.56	27.41	2.92	38.86	28.03	54.00	-25.97	Horizontal
2310.00	34.24	27.14	2.81	38.64	25.55	54.00	-28.45	Vertical
2390.00	36.27	27.37	2.91	38.84	27.71	54.00	-26.29	Vertical
2400.00	37.38	27.41	2.92	38.86	28.85	54.00	-25.15	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.13	27.82	2.99	39.05	37.89	74.00	-36.11	Horizontal
2500.00	45.11	27.70	3.01	39.10	36.72	74.00	-37.28	Horizontal
2483.50	47.15	27.82	2.99	39.05	38.91	74.00	-35.09	Vertical
2500.00	46.21	27.70	3.01	39.10	37.82	74.00	-36.18	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.06	27.82	2.99	39.05	26.82	54.00	-27.18	Horizontal
2500.00	34.92	27.70	3.01	39.10	26.53	54.00	-27.47	Horizontal
2483.50	35.47	27.82	2.99	39.05	27.23	54.00	-26.77	Vertical
2500.00	34.93	27.70	3.01	39.10	26.54	54.00	-27.46	Vertical

Remark:

$$\text{Final Level} = \text{Receiver Read level} + \text{Antenna Factor} + \text{Cable Loss} - \text{Preamplifier Factor}$$

ANT 4

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.05	27.14	2.81	38.64	35.36	74.00	-38.64	Horizontal
2390.00	48.00	27.37	2.91	38.84	39.44	74.00	-34.56	Horizontal
2400.00	49.73	27.41	2.92	38.86	41.20	74.00	-32.80	Horizontal
2310.00	44.71	27.14	2.81	38.64	36.02	74.00	-37.98	Vertical
2390.00	49.17	27.37	2.91	38.84	40.61	74.00	-33.39	Vertical
2400.00	50.62	27.41	2.92	38.86	42.09	74.00	-31.91	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.33	27.14	2.81	38.64	25.64	54.00	-28.36	Horizontal
2390.00	35.64	27.37	2.91	38.84	27.08	54.00	-26.92	Horizontal
2400.00	36.70	27.41	2.92	38.86	28.17	54.00	-25.83	Horizontal
2310.00	34.36	27.14	2.81	38.64	25.67	54.00	-28.33	Vertical
2390.00	36.40	27.37	2.91	38.84	27.84	54.00	-26.16	Vertical
2400.00	37.51	27.41	2.92	38.86	28.98	54.00	-25.02	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.29	27.82	2.99	39.05	38.05	74.00	-35.95	Horizontal
2500.00	45.24	27.70	3.01	39.10	36.85	74.00	-37.15	Horizontal
2483.50	47.33	27.82	2.99	39.05	39.09	74.00	-34.91	Vertical
2500.00	46.35	27.70	3.01	39.10	37.96	74.00	-36.04	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.18	27.82	2.99	39.05	26.94	54.00	-27.06	Horizontal
2500.00	35.01	27.70	3.01	39.10	26.62	54.00	-27.38	Horizontal
2483.50	35.55	27.82	2.99	39.05	27.31	54.00	-26.69	Vertical
2500.00	35.03	27.70	3.01	39.10	26.64	54.00	-27.36	Vertical

Remark:

$$\text{Final Level} = \text{Receiver Read level} + \text{Antenna Factor} + \text{Cable Loss} - \text{Preamplifier Factor}$$

ANT 5

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	43.92	27.14	2.81	38.64	35.23	74.00	-38.77	Horizontal
2390.00	47.86	27.37	2.91	38.84	39.30	74.00	-34.70	Horizontal
2400.00	49.58	27.41	2.92	38.86	41.05	74.00	-32.95	Horizontal
2310.00	44.57	27.14	2.81	38.64	35.88	74.00	-38.12	Vertical
2390.00	49.01	27.37	2.91	38.84	40.45	74.00	-33.55	Vertical
2400.00	50.46	27.41	2.92	38.86	41.93	74.00	-32.07	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.24	27.14	2.81	38.64	25.55	54.00	-28.45	Horizontal
2390.00	35.54	27.37	2.91	38.84	26.98	54.00	-27.02	Horizontal
2400.00	36.57	27.41	2.92	38.86	28.04	54.00	-25.96	Horizontal
2310.00	34.26	27.14	2.81	38.64	25.57	54.00	-28.43	Vertical
2390.00	36.28	27.37	2.91	38.84	27.72	54.00	-26.28	Vertical
2400.00	37.40	27.41	2.92	38.86	28.87	54.00	-25.13	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.15	27.82	2.99	39.05	37.91	74.00	-36.09	Horizontal
2500.00	45.12	27.70	3.01	39.10	36.73	74.00	-37.27	Horizontal
2483.50	47.17	27.82	2.99	39.05	38.93	74.00	-35.07	Vertical
2500.00	46.22	27.70	3.01	39.10	37.83	74.00	-36.17	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.08	27.82	2.99	39.05	26.84	54.00	-27.16	Horizontal
2500.00	34.93	27.70	3.01	39.10	26.54	54.00	-27.46	Horizontal
2483.50	35.48	27.82	2.99	39.05	27.24	54.00	-26.76	Vertical
2500.00	34.94	27.70	3.01	39.10	26.55	54.00	-27.45	Vertical

Remark:

$$\text{Final Level} = \text{Receiver Read level} + \text{Antenna Factor} + \text{Cable Loss} - \text{Preamplifier Factor}$$


7.4 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Antenna	Frequency[MHz]	20dB bandwidth(KHz)	Result
ANT 1	2402	892.87	Pass
ANT 1	2441	936.03	Pass
ANT 1	2480	908.08	Pass
ANT 2	2402	922.85	Pass
ANT 2	2441	942.95	Pass
ANT 2	2480	924.22	Pass
ANT 3	2402	913.75	Pass
ANT 3	2441	922.67	Pass
ANT 3	2480	915.34	Pass
ANT 4	2402	913.35	Pass
ANT 4	2441	942.64	Pass
ANT 4	2480	915.36	Pass
ANT 5	2402	916.56	Pass
ANT 5	2441	917.44	Pass
ANT 5	2480	927.32	Pass

Test plot as follows:







8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----