

RF EXPOSURE REPORT

Applicant:	Luxottica Group S.p.A
Address:	One Icon Foothill Ranch California
Manufacturer:	Luxottica Group S.p.A
Address:	One Icon Foothill Ranch California
Product Description:	Nuance Audio Plus
Brand Name:	Nuance Audio Plus
Tested Model	AW5005
FCC ID:	2AYOA-4008
Report No.:	JCF251205081-002
Received Date:	Dec. 05, 2025
Tested Date:	Dec. 05, 2025 ~ Mar. 10, 2026
Issued Date:	Mar. 10, 2026
Test Standards:	KDB 447498 D01 General RF Exposure Guidance v06
Test Result:	Pass

Prepared By:




Roger Li/Engineer **Date:** Mar. 10, 2026

Reviewed By:



Kennys Zhang/Engineer **Date:** Mar. 10, 2026

Approved By:



Talent Zhang/Engineer **Date:** Mar. 10, 2026

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
--	/	Mar. 10, 2026	Original Report	/

Table of Contents

1. Test Report Declare	4
2. Equipment Under Test	5
2.1. Description of EUT	5
2.2. Description of Available Antennas	5
3. Test Laboratory	5
4. RF Exposure Measurement	6
4.1. Requirement	6
4.2. Limits for Maximum Permissible Exposure (MPE)	6
4.3. Conducted Power	6
5. RF Exposure Calculation	6

1. Test Report Declare

Applicant:	Luxottica Group S.p.A
Address:	One Icon Foothill Ranch California
Manufacturer:	Luxottica Group S.p.A
Address:	One Icon Foothill Ranch California
Product Name	Nuance Audio Plus
Brand Name:	Nuance Audio Plus
Model Name:	AW5005, AW5006, AW5007, AW5009, AW5010
Difference Description:	The differences in color and lens size among the products do not affect their electromagnetic compatibility characteristics.

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

2. Equipment Under Test

2.1. Description of EUT

EUT* Name:	Nuance Audio Plus
Model Number:	AW5005
EUT Function Description:	Please refer to the user manual of this device
Power Supply:	DC 3.4V-4.45V
Sample No.	251205081-01-01
Hardware Version:	NA
Software Version:	NA
Radio Specification:	Bluetooth V5.3
Operation Frequency:	2402 MHz - 2480 MHz
Modulation:	GFSK
Antenna Type:	FPC Antenna, MAX. Gain: 2.66 dBi
Product Type:	☒ Portable device ☐ Mobile device ☐ Fixed device

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

2.2. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

4. RF Exposure Measurement

4.1. Requirement

According to 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where: $f(\text{GHz})$ is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation The result is rounded to one decimal place for comparison

4.2. Limits for Maximum Permissible Exposure (MPE)

Band	Channel Frequency (MHz)	Limit (mW)	Limit (dBm)
BLE	2402	9.68	9.86

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Limit = $[3.0 \cdot (\text{min. test separation distance, mm})] / [\sqrt{f(\text{GHz})}] = (3 \cdot 5) / [\sqrt{2.402(\text{GHz})}] = 9.60\text{mW}$

4.3. Conducted Power

Band	Channel Frequency (MHz)	Average Power (dBm)
BLE	2402	0.51

5. RF Exposure Calculation

We used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

Band	Channel Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	PASS/FAIL
BLE	2402	0.51	2.66	3.17	9.86	PASS

Then SAR evaluation is not required.

--END--