FCC RADIO TEST REPORT

FCC ID	:	**2AYOA-4010**
Equipment	:	**AI GLASSES**
Brand Name	:	**Ray-Ban Meta or Ray-Ban**
Model Name	:	**RW7001, RW7002**
Applicant	:	**Luxottica Group S.p.A. Piazzale Cadorna 3 20123 Milan, Italy**
Manufacturer	:	**Luxottica Group S.p.A. Piazzale Cadorna 3 20123 Milan, Italy**
Standard	:	**FCC Part 15 Subpart E §15.407**

The product was received on Oct. 22, 2025 and testing was performed from Oct. 22, 2025 to Nov. 27, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory
No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 5
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 26dB & 99% Occupied Bandwidth Measurement 11
3.2 Maximum Conducted Output Power Measurement 12
3.3 Power Spectral Density Measurement 14
3.4 Unwanted Emissions Measurement 16
3.5 AC Conducted Emission Measurement 20
3.6 Antenna Requirements 22
4 List of Measuring Equipment **23**
5 Measurement Uncertainty **25**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR5O1534D	01	Initial issue of report	Dec. 24, 2025
FR5O1534D	02	Revised Product Feature of Equipment Under Test, Maximum Conducted Output Power Measurement, Power Spectral Density Measurement, and appendix D. This report is an updated version, replacing the report issued on Dec. 24, 2025.	Dec. 31, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403	26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	-
3.5	15.207	AC Conducted Emission	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Shiori Chen

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Bluetooth-LE, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax and Wi-Fi 6GHz 802.11a/ax. **Antenna Type** WLAN: IFA Antenna

Antenna information		
5150 MHz ~ 5250 MHz	Peak Gain (dBi)	0.20
5250 MHz ~ 5350 MHz	Peak Gain (dBi)	0.25
5470 MHz ~ 5725 MHz	Peak Gain (dBi)	1.74

Sample	Model Name	Product Marketing Name
Sample 1	RW7002	RayBan Meta Scriber
Sample 2	RW7001	RayBan Meta Blazer Large
Sample 3	RW7001	RayBan Meta Blazer

Remark:

1. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
2. There are three samples of EUT. The manufacturer declares that all the equipment share the same radio characteristics and Software/Firmware, the only differences between each of them are color of frames, lenses, and sizes which certainly do not affect the test results. Therefore, only Sample 1 was tested.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- FCC Part 15 Subpart E
- ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42#	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5250-5350 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58#	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5470-5725 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106#	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)
5150-5350 MHz	50@	5250
5470-5725 MHz	114@	5570

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122#	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138#	5690	144	5720
	142*	5710		

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "#" are 802.11ac VHT80 and 802.11ax HE80.
3. The above Frequency and Channel with "@" are 802.11ac VHT160 and 802.11ax HE160.

2.2 Test Mode

This device support 26/52/106/242/484/996/2x996-tone RU.

The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11a	**6 Mbps**
802.11n HT20 (Covered by VHT20)	**MCS0**
802.11n HT40 (Covered by VHT40)	**MCS0**
802.11ac VHT20	**MCS0**
802.11ac VHT40	**MCS0**
802.11ac VHT80	**MCS0**
802.11ac VHT160	**MCS0**
802.11ax HE20	**MCS0**
802.11ax HE40	**MCS0**
802.11ax HE80	**MCS0**
802.11ax HE160	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + Charging from Charging case (USB Cable with Adapter)

Remark:

1. The detailed Radiated test modes are shown in Appendix C.
2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	Netgear	RAXE500	PY320300508	N/A	Unshielded,1.8m
2.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P： Unshielded, 1.2m DC O/P： Shielded, 1.8m
3.	Mobile Phone	Asus	Zenfone5	MSQX00QSA	N/A	N/A
4.	DC Power Supply	KEYSIGHT	E3610A	NA	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Version 4.0.211.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules **v02r01**, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<CFR 15.407>

For the 5.15–5.25 GHz bands:

■ For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For the 5.25–5.725 GHz bands:

■ The maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<CFR 15.407>

For the 5.15–5.25 GHz bands:

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1.0 MHz band.

For the 5.25–5.725 GHz bands:

The maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of –27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

(2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of −27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Unique (non-standard) antenna connector.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 18, 2024	Nov. 01, 2025~ Nov. 26, 2025	Dec. 17, 2025	Radiation (03CH23-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N -06	47020 & 06	30MHz~1GHz	Oct. 04, 2025	Nov. 01, 2025~ Nov. 26, 2025	Oct. 03, 2026	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421582	9kHz~1GHz	Jul. 13, 2025	Nov. 01, 2025~ Nov. 26, 2025	Jul. 12 2026	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	1GHz~18GHz	Sep. 26, 2025	Nov. 01, 2025~ Nov. 26, 2025	Sep. 25, 2026	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18E N	1GHz~18GHz	Jul. 02, 2025	Nov. 01, 2025~ Nov. 26, 2025	Jul. 01, 2026	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1225	18GHz-40GHz	Jul. 02, 2025	Nov. 01, 2025~ Nov. 26, 2025	Jul. 01, 2026	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz-40GHz	Aug. 26, 2025	Nov. 01, 2025~ Nov. 26, 2025	Aug. 25, 2026	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	10Hz~44GHz	Aug. 26, 2025	Nov. 01, 2025~ Nov. 26, 2025	Aug. 25, 2026	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Nov. 01, 2025~ Nov. 26, 2025	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Nov. 01, 2025~ Nov. 26, 2025	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Nov. 01, 2025~ Nov. 26, 2025	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019 122	RK-002348	N/A	N/A	Nov. 01, 2025~ Nov. 26, 2025	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	30MHz~40GHz	Nov. 26, 2024	Nov. 01, 2025~ Nov. 24, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	30MHz~40GHz	Nov. 25, 2025	Nov. 25, 2025~ Nov. 26, 2025	Nov. 24, 2026	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/23111 9/231122	30MHz~40GHz	Nov. 26, 2024	Nov. 01, 2025~ Nov. 24, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/23111 9/231122	30MHz~40GHz	Nov. 25, 2025	Nov. 25, 2025~ Nov. 26, 2025	Nov. 24, 2026	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303B	TP200735	N/A	Mar. 13, 2025	Oct. 22, 2025~ Nov. 27, 2025	Mar. 12, 2026	Conducted (TH05-HY)
USB RF Power Sensor	Raditeq	RPR3008W	RPR8W-2301 001(NO:146)	10MHz~8GHz	Jan. 17, 2025	Oct. 22, 2025~ Nov. 27, 2025	Jan. 16, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Oct. 22, 2025~ Nov. 27, 2025	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Oct. 22, 2025~ Nov. 27, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_20240 823	N/A	Conducted Other Test Item	N/A	Oct. 22, 2025~ Nov. 27, 2025	N/A	Conducted (TH05-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Nov. 26, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Nov. 26, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Nov. 26, 2025	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Nov. 26, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Nov. 26, 2025	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	Nov. 26, 2025	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI7	100724	9kHz~7GHz	Feb. 13, 2025	Nov. 26, 2025	Feb. 12, 2026	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.6 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.4 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.7 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Joseph Hu/Sylvia Li	Temperature:	21~25	°C
Test Date:	2025/10/22~2025/11/27	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

U-NII-1 single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)			Note
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	17.54	-	23.39	-	-		22.44	-	-	
11a	6Mbps	1	44	5220	17.57	-	23.87	-	-		22.45	-		
11a	6Mbps	1	48	5240	17.48	-	23.19	-	-		22.42	-		
VHT20	MCS0	1	36	5180	18.60	-	23.92	-	-		22.70	-		
VHT20	MCS0	1	44	5220	18.70	-	24.28	-	-		22.72	-		
VHT20	MCS0	1	48	5240	18.64	-	23.98	-	-		22.71	-		
VHT40	MCS0	1	38	5190	37.74	-	48.03	-	-		23.01	-		
VHT40	MCS0	1	46	5230	37.71	-	47.97	-	-		23.01	-		
VHT80	MCS0	1	42	5210	78.09	-	96.32	-	-		23.01	-		
VHT160	MCS0	1	50	5250	155.89	-	177.65	-	-		23.01	-		

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	16.18	-	-	24.00	-	0.20	-	-	Pass
11a	6Mbps	1	44	5220	16.49	-		24.00	-	0.20	-		Pass
11a	6Mbps	1	48	5240	16.21	-		24.00	-	0.20	-		Pass
HT20	MCS0	1	36	5180	15.87	-		24.00	-	0.20	-		Pass
HT20	MCS0	1	44	5220	16.26	-		24.00	-	0.20	-		Pass
HT20	MCS0	1	48	5240	16.21	-		24.00	-	0.20	-		Pass
HT40	MCS0	1	38	5190	15.67	-		24.00	-	0.20	-		Pass
HT40	MCS0	1	46	5230	15.98	-		24.00	-	0.20	-		Pass
VHT20	MCS0	1	36	5180	15.97	-		24.00	-	0.20	-		Pass
VHT20	MCS0	1	44	5220	16.36	-		24.00	-	0.20	-		Pass
VHT20	MCS0	1	48	5240	16.31	-		24.00	-	0.20	-		Pass
VHT40	MCS0	1	38	5190	15.77	-		24.00	-	0.20	-		Pass
VHT40	MCS0	1	46	5230	16.08	-		24.00	-	0.20	-		Pass
VHT80	MCS0	1	42	5210	15.57	-		24.00	-	0.20	-		Pass
VHT160	MCS0	1	50	5250	15.67	-		24.00	-	0.20	-		Pass

TEST RESULTS DATA
Power Spectral Density

FCC U-NII-1 single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	0.04	-	4.55	-	-	11.00	-	0.20	-	-	Pass
11a	6Mbps	1	44	5220	0.04	-	5.05	-		11.00	-	0.20	-		Pass
11a	6Mbps	1	48	5240	0.04	-	4.44	-		11.00	-	0.20	-		Pass
VHT20	MCS0	1	36	5180	0.02	-	3.79	-		11.00	-	0.20	-		Pass
VHT20	MCS0	1	44	5220	0.02	-	4.31	-		11.00	-	0.20	-		Pass
VHT20	MCS0	1	48	5240	0.02	-	4.29	-		11.00	-	0.20	-		Pass
VHT40	MCS0	1	38	5190	0.00	-	-0.01	-		11.00	-	0.20	-		Pass
VHT40	MCS0	1	46	5230	0.00	-	0.98	-		11.00	-	0.20	-		Pass
VHT80	MCS0	1	42	5210	0.02	-	-2.92	-		11.00	-	0.20	-		Pass
VHT160	MCS0	1	50	5250	0.00	-	-5.18	-		11.00	-	0.20	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2A single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	52	5260	17.51	-	23.33	-	23.43	-	29.43	-	23.98	-	-
11a	6Mbps	1	60	5300	17.51	-	23.27	-	23.43	-	29.43	-	23.98	-	
11a	6Mbps	1	64	5320	17.50	-	23.16	-	23.43	-	29.43	-	23.98	-	
VHT20	MCS0	1	52	5260	18.62	-	24.21	-	23.70	-	29.70	-	23.98	-	
VHT20	MCS0	1	60	5300	18.59	-	24.29	-	23.69	-	29.69	-	23.98	-	
VHT20	MCS0	1	64	5320	18.60	-	24.18	-	23.69	-	29.69	-	23.98	-	
VHT40	MCS0	1	54	5270	37.66	-	48.05	-	23.98	-	30.00	-	23.98	-	
VHT40	MCS0	1	62	5310	37.78	-	48.05	-	23.98	-	30.00	-	23.98	-	
VHT80	MCS0	1	58	5290	77.91	-	96.77	-	23.98	-	30.00	-	23.98	-	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	52	5260	16.43	-	-	23.98	-	0.25	-	26.99	Pass
11a	6Mbps	1	60	5300	16.42	-		23.98	-	0.25	-	26.99	Pass
11a	6Mbps	1	64	5320	16.31	-		23.98	-	0.25	-	26.99	Pass
HT20	MCS0	1	52	5260	16.01	-		23.98	-	0.25	-	26.99	Pass
HT20	MCS0	1	60	5300	16.10	-		23.98	-	0.25	-	26.99	Pass
HT20	MCS0	1	64	5320	15.57	-		23.98	-	0.25	-	26.99	Pass
HT40	MCS0	1	54	5270	16.25	-		23.98	-	0.25	-	26.99	Pass
HT40	MCS0	1	62	5310	15.57	-		23.98	-	0.25	-	26.99	Pass
VHT20	MCS0	1	52	5260	16.09	-		23.98	-	0.25	-	26.99	Pass
VHT20	MCS0	1	60	5300	16.06	-		23.98	-	0.25	-	26.99	Pass
VHT20	MCS0	1	64	5320	15.67	-		23.98	-	0.25	-	26.99	Pass
VHT40	MCS0	1	54	5270	16.35	-		23.98	-	0.25	-	26.99	Pass
VHT40	MCS0	1	62	5310	15.67	-		23.98	-	0.25	-	26.99	Pass
VHT80	MCS0	1	58	5290	15.87	-		23.98	-	0.25	-	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2A single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	52	5260	0.04	-	4.76	-		11.00	-	0.25	-		Pass
11a	6Mbps	1	60	5300	0.04	-	4.68	-		11.00	-	0.25	-		Pass
11a	6Mbps	1	64	5320	0.04	-	4.21	-		11.00	-	0.25	-		Pass
VHT20	MCS0	1	52	5260	0.02	-	4.25	-		11.00	-	0.25	-		Pass
VHT20	MCS0	1	60	5300	0.02	-	4.01	-	-	11.00	-	0.25	-	-	Pass
VHT20	MCS0	1	64	5320	0.02	-	3.55	-		11.00	-	0.25	-		Pass
VHT40	MCS0	1	54	5270	0.00	-	1.51	-		11.00	-	0.25	-		Pass
VHT40	MCS0	1	62	5310	0.00	-	0.04	-		11.00	-	0.25	-		Pass
VHT80	MCS0	1	58	5290	0.02	-	-2.63	-		11.00	-	0.25	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2C single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
11a	6Mbps	1	100	5500	17.49	-	23.42	-	23.43	-	29.43	-	23.98	-	----	----
11a	6Mbps	1	120	5600	17.56	-	23.31	-	23.44	-	29.44	-	23.98	-	----	----
11a	6Mbps	1	140	5700	17.50	-	23.24	-	23.43	-	29.43	-	23.98	-	----	----
VHT20	MCS0	1	100	5500	18.64	-	24.09	-	23.71	-	29.71	-	23.98	-	----	----
VHT20	MCS0	1	120	5600	18.65	-	24.42	-	23.71	-	29.71	-	23.98	-	----	----
VHT20	MCS0	1	140	5700	18.60	-	23.93	-	23.69	-	29.69	-	23.98	-	----	----
VHT40	MCS0	1	102	5510	37.88	-	48.32	-	23.98	-	30.00	-	23.98	-	----	----
VHT40	MCS0	1	118	5590	37.87	-	48.69	-	23.98	-	30.00	-	23.98	-	----	----
VHT40	MCS0	1	134	5670	37.88	-	48.19	-	23.98	-	30.00	-	23.98	-	----	----
VHT80	MCS0	1	106	5530	77.94	-	95.90	-	23.98	-	30.00	-	23.98	-	----	----
VHT80	MCS0	1	122	5610	77.97	-	96.86	-	23.98	-	30.00	-	23.98	-	----	----
VHT160	MCS0	1	114	5570	155.91	-	176.74	-	23.98	-	30.00	-	23.98	-	----	----

U-NII-2C straddle channel single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
11a	6Mbps	1	144	5720	13.95	-	16.94	-	23.43	-	29.43	-	23.98	-	3.165	-
VHT20	MCS0	1	144	5720	14.38	-	17.17	-	23.70	-	29.70	-	23.98	-	3.78	-
VHT40	MCS0	1	142	5710	33.97	-	39.46	-	23.98	-	30.00	-	23.98	-	3.18	-
VHT80	MCS0	1	138	5690	73.76	-	83.00	-	23.98	-	30.00	-	23.98	-	3.192	-

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	100	5500	16.31	-	-	23.98	-	1.74	-	26.99	Pass
11a	6Mbps	1	120	5600	16.44	-		23.98	-	1.74	-	26.99	Pass
11a	6Mbps	1	140	5700	15.87	-		23.98	-	1.74	-	26.99	Pass
HT20	MCS0	1	100	5500	16.01	-		23.98	-	1.74	-	26.99	Pass
HT20	MCS0	1	120	5600	16.11	-		23.98	-	1.74	-	26.99	Pass
HT20	MCS0	1	140	5700	15.17	-		23.98	-	1.74	-	26.99	Pass
HT40	MCS0	1	102	5510	16.21	-		23.98	-	1.74	-	26.99	Pass
HT40	MCS0	1	118	5590	16.27	-		23.98	-	1.74	-	26.99	Pass
HT40	MCS0	1	134	5670	16.06	-		23.98	-	1.74	-	26.99	Pass
VHT20	MCS0	1	100	5500	16.05	-		23.98	-	1.74	-	26.99	Pass
VHT20	MCS0	1	120	5600	16.21	-		23.98	-	1.74	-	26.99	Pass
VHT20	MCS0	1	140	5700	15.27	-		23.98	-	1.74	-	26.99	Pass
VHT40	MCS0	1	102	5510	16.31	-		23.98	-	1.74	-	26.99	Pass
VHT40	MCS0	1	118	5590	16.37	-		23.98	-	1.74	-	26.99	Pass
VHT40	MCS0	1	134	5670	16.16	-		23.98	-	1.74	-	26.99	Pass
VHT80	MCS0	1	106	5530	15.87	-		23.98	-	1.74	-	26.99	Pass
VHT80	MCS0	1	122	5610	16.34	-		23.98	-	1.74	-	26.99	Pass
VHT160	MCS0	1	114	5570	16.34	-		23.98	-	1.74	-	26.99	Pass

FCC U-NII-2C straddle channel single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	144	5720	16.24	-	-	23.98	-	1.74	-	26.99	Pass
HT20	MCS0	1	144	5720	16.02	-		23.98	-	1.74	-	26.99	Pass
HT40	MCS0	1	142	5710	16.20	-		23.98	-	1.74	-	26.99	Pass
VHT20	MCS0	1	144	5720	16.03	-		23.98	-	1.74	-	26.99	Pass
VHT40	MCS0	1	142	5710	16.30	-		23.98	-	1.74	-	26.99	Pass
VHT80	MCS0	1	138	5690	16.29	-		23.98	-	1.74	-	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2C single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	100	5500	0.04	-	4.15	-	-	11.00	-	1.74	-	-	Pass
11a	6Mbps	1	120	5600	0.04	-	4.26	-		11.00	-	1.74	-		Pass
11a	6Mbps	1	140	5700	0.04	-	3.58	-		11.00	-	1.74	-		Pass
VHT20	MCS0	1	100	5500	0.02	-	3.55	-		11.00	-	1.74	-		Pass
VHT20	MCS0	1	120	5600	0.02	-	4.07	-		11.00	-	1.74	-		Pass
VHT20	MCS0	1	140	5700	0.02	-	3.03	-		11.00	-	1.74	-		Pass
VHT40	MCS0	1	102	5510	0.00	-	0.75	-		11.00	-	1.74	-		Pass
VHT40	MCS0	1	118	5590	0.00	-	1.24	-		11.00	-	1.74	-		Pass
VHT40	MCS0	1	134	5670	0.00	-	1.04	-		11.00	-	1.74	-		Pass
VHT80	MCS0	1	106	5530	0.02	-	-2.86	-		11.00	-	1.74	-		Pass
VHT80	MCS0	1	122	5610	0.02	-	-1.80	-		11.00	-	1.74	-		Pass
VHT160	MCS0	1	114	5570	0.00	-	-5.03	-		11.00	-	1.74	-		Pass

U-NII-2C straddle channel single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	144	5720	0.04	-	3.93	-	-	11.00	-	1.74	-	-	Pass
VHT20	MCS0	1	144	5720	0.02	-	3.75	-		11.00	-	1.74	-		Pass
VHT40	MCS0	1	142	5710	0.00	-	0.94	-		11.00	-	1.74	-		Pass
VHT80	MCS0	1	138	5690	0.02	-	-1.56	-		11.00	-	1.74	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-1 single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)			Note
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	19.31	-	23.44	-	-		22.86	-	-	-
HE20	MCS0	1	44	5220	Full	19.29	-	23.31	-	-		22.85	-		
HE20	MCS0	1	48	5240	Full	19.27	-	23.16	-	-		22.85	-		
HE40	MCS0	1	38	5190	Full	38.54	-	46.02	-	-		23.01	-		
HE40	MCS0	1	46	5230	Full	38.51	-	46.06	-	-		23.01	-		
HE80	MCS0	1	42	5210	Full	78.90	-	93.70	-	-		23.01	-		
HE160	MCS0	1	50	5250	Full	157.45	-	186.62	-	-		23.01	-		

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	16.46	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	26/0	9.87	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	52/37	12.87	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	106/53	15.37	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	242/61	15.37	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	Full	16.46	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	26/4	9.97	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	52/38	12.67	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	106/53	15.37	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	242/61	15.27	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	Full	16.41	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	26/8	9.77	-	-	24.00	-	0.20	-	-	Pass
HE20	MCS0	1	48	5240	52/40	12.77	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	106/54	15.27	-		24.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	242/61	15.27	-		24.00	-	0.20	-		Pass
HE40	MCS0	1	38	5190	Full	16.23	-		24.00	-	0.20	-		Pass
HE40	MCS0	1	38	5190	484/65	15.47	-		24.00	-	0.20	-		Pass
HE40	MCS0	1	46	5230	Full	16.18	-		24.00	-	0.20	-		Pass
HE40	MCS0	1	46	5230	484/65	15.47	-		24.00	-	0.20	-		Pass
HE80	MCS0	1	42	5210	Full	15.67	-		24.00	-	0.20	-		Pass
HE80	MCS0	1	42	5210	996/67	15.47	-		24.00	-	0.20	-		Pass
HE160	MCS0	1	50	5250	Full	16.36	-		24.00	-	0.20	-		Pass
HE160	MCS0	1	50	5250	1992/68	15.47	-		24.00	-	0.20	-		Pass

TEST RESULTS DATA
Power Spectral Density

FCC U-NII-1 single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	0.02	-	4.02	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	26/0	0.02	-	7.05	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	52/37	0.02	-	6.87	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	106/53	0.02	-	6.30	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	36	5180	242/61	0.05	-	2.71	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	Full	0.02	-	3.93	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	26/4	0.02	-	5.90	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	52/38	0.02	-	6.58	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	106/53	0.02	-	6.10	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	44	5220	242/61	0.05	-	2.64	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	Full	0.02	-	3.80	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	26/8	0.02	-	6.80	-	-	11.00	-	0.20	-	-	Pass
HE20	MCS0	1	48	5240	52/40	0.02	-	6.76	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	106/54	0.02	-	6.26	-		11.00	-	0.20	-		Pass
HE20	MCS0	1	48	5240	242/61	0.05	-	2.64	-		11.00	-	0.20	-		Pass
HE40	MCS0	1	38	5190	Full	0.00	-	0.55	-		11.00	-	0.20	-		Pass
HE40	MCS0	1	38	5190	484/65	0.08	-	-0.23	-		11.00	-	0.20	-		Pass
HE40	MCS0	1	46	5230	Full	0.00	-	0.52	-		11.00	-	0.20	-		Pass
HE40	MCS0	1	46	5230	484/65	0.08	-	-0.40	-		11.00	-	0.20	-		Pass
HE80	MCS0	1	42	5210	Full	0.00	-	-2.80	-		11.00	-	0.20	-		Pass
HE80	MCS0	1	42	5210	996/67	0.11	-	-2.91	-		11.00	-	0.20	-		Pass
HE160	MCS0	1	50	5250	Full	0.02	-	-4.26	-		11.00	-	0.20	-		Pass
HE160	MCS0	1	50	5250	1992/68	0.12	-	-5.47	-		11.00	-	0.20	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2A single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	1	52	5260	Full	19.28	-	23.22	-	23.85	-	29.85	-	23.98	-	
HE20	MCS0	1	60	5300	Full	19.29	-	23.14	-	23.85	-	29.85	-	23.98	-	
HE20	MCS0	1	64	5320	Full	19.27	-	23.30	-	23.85	-	29.85	-	23.98	-	
HE40	MCS0	1	54	5270	Full	38.52	-	45.81	-	23.98	-	30.00	-	23.98	-	
HE40	MCS0	1	62	5310	Full	38.50	-	45.52	-	23.98	-	30.00	-	23.98	-	
HE80	MCS0	1	58	5290	Full	78.83	-	93.34	-	23.98	-	30.00	-	23.98	-	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	52	5260	Full	16.19	-	-	23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	52	5260	26/0	11.27	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	52	5260	52/37	14.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	52	5260	106/53	15.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	52	5260	242/61	15.37	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	60	5300	Full	16.16	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	60	5300	26/4	11.37	-		23.80	-	0.25	-	26.99	Pass
HE20	MCS0	1	60	5300	52/38	14.37	-		23.90	-	0.25	-	26.99	Pass
HE20	MCS0	1	60	5300	106/53	15.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	60	5300	242/61	15.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	64	5320	Full	16.14	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	64	5320	26/8	11.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	64	5320	52/40	14.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	64	5320	106/54	15.47	-		23.98	-	0.25	-	26.99	Pass
HE20	MCS0	1	64	5320	242/61	15.47	-		23.98	-	0.25	-	26.99	Pass
HE40	MCS0	1	54	5270	Full	16.45	-		23.98	-	0.25	-	26.99	Pass
HE40	MCS0	1	54	5270	484/65	15.37	-		23.98	-	0.25	-	26.99	Pass
HE40	MCS0	1	62	5310	Full	16.15	-		23.98	-	0.25	-	26.99	Pass
HE40	MCS0	1	62	5310	484/65	15.47	-		23.98	-	0.25	-	26.99	Pass
HE80	MCS0	1	58	5290	Full	15.97	-		23.98	-	0.25	-	26.99	Pass
HE80	MCS0	1	58	5290	996/67	15.27	-		23.98	-	0.25	-	26.99	Pass
HE160	MCS0	1	50	5250	Full	16.36	-		23.98	-	0.25	-	26.99	Pass
HE160	MCS0	1	50	5250	1992/68	15.47	-		23.98	-	0.25	-	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2A single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	52	5260	Full	0.02	-	3.68	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	52	5260	26/0	0.02	-	8.37	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	52	5260	52/37	0.02	-	8.57	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	52	5260	106/53	0.02	-	6.58	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	52	5260	242/61	0.05	-	3.01	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	60	5300	Full	0.02	-	3.61	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	60	5300	26/4	0.02	-	7.28	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	60	5300	52/38	0.02	-	8.38	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	60	5300	106/53	0.02	-	6.45	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	60	5300	242/61	0.05	-	2.86	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	64	5320	Full	0.02	-	3.63	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	64	5320	26/8	0.02	-	8.38	-	-	11.00	-	0.25	-	-	Pass
HE20	MCS0	1	64	5320	52/40	0.02	-	8.48	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	64	5320	106/54	0.02	-	6.56	-		11.00	-	0.25	-		Pass
HE20	MCS0	1	64	5320	242/61	0.05	-	2.97	-		11.00	-	0.25	-		Pass
HE40	MCS0	1	54	5270	Full	0.00	-	1.03	-		11.00	-	0.25	-		Pass
HE40	MCS0	1	54	5270	484/65	0.08	-	-0.27	-		11.00	-	0.25	-		Pass
HE40	MCS0	1	62	5310	Full	0.00	-	0.30	-		11.00	-	0.25	-		Pass
HE40	MCS0	1	62	5310	484/65	0.08	-	-0.16	-		11.00	-	0.25	-		Pass
HE80	MCS0	1	58	5290	Full	0.00	-	-2.50	-		11.00	-	0.25	-		Pass
HE80	MCS0	1	58	5290	996/67	0.11	-	-3.15	-		11.00	-	0.25	-		Pass
HE160	MCS0	1	50	5250	Full	0.02	-	-4.26	-		11.00	-	0.25	-		Pass
HE160	MCS0	1	50	5250	1992/68	0.12	-	-5.47	-		11.00	-	0.25	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2C single antenna																	
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
HE20	MCS0	1	100	5500	Full	19.27	-	23.35	-	23.85	-	29.85	-	23.98	-	----	----
HE20	MCS0	1	120	5600	Full	19.30	-	23.18	-	23.86	-	29.86	-	23.98	-	----	----
HE20	MCS0	1	140	5700	Full	19.26	-	23.10	-	23.85	-	29.85	-	23.98	-	----	----
HE40	MCS0	1	102	5510	Full	38.54	-	45.20	-	23.98	-	30.00	-	23.98	-	----	----
HE40	MCS0	1	118	5590	Full	38.52	-	45.42	-	23.98	-	30.00	-	23.98	-	----	----
HE40	MCS0	1	134	5670	Full	38.59	-	45.89	-	23.98	-	30.00	-	23.98	-	----	----
HE80	MCS0	1	106	5530	Full	78.80	-	92.93	-	23.98	-	30.00	-	23.98	-	----	----
HE80	MCS0	1	122	5610	Full	78.84	-	92.03	-	23.98	-	30.00	-	23.98	-	----	----
HE160	MCS0	1	114	5570	Full	157.54	-	176.98	-	23.98	-	30.00	-	23.98	-	----	----

U-NII-2C straddle channel single antenna																	
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
HE20	MCS0	1	144	5720	Full	14.68	-	16.81	-	23.85	-	29.85	-	23.98	-	4.48	-
HE40	MCS0	1	142	5710	Full	34.31	-	37.74	-	23.98	-	30.00	-	23.98	-	4.026	-
HE80	MCS0	1	138	5690	Full	74.30	-	81.62	-	23.98	-	30.00	-	23.98	-	3.976	-

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	100	5500	Full	16.15	-	-	23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	100	5500	26/0	11.47	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	100	5500	52/37	14.27	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	100	5500	106/53	15.27	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	100	5500	242/61	15.47	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	120	5600	Full	16.31	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	120	5600	26/4	11.47	-		23.80	-	1.74	-	26.99	Pass
HE20	MCS0	1	120	5600	52/38	14.47	-		23.89	-	1.74	-	26.99	Pass
HE20	MCS0	1	120	5600	106/53	15.37	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	120	5600	242/61	15.37	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	140	5700	Full	14.37	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	140	5700	26/8	11.47	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	140	5700	52/40	14.47	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	140	5700	106/54	15.17	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	140	5700	242/61	15.07	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	102	5510	Full	16.41	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	102	5510	484/65	15.47	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	118	5590	Full	16.47	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	118	5590	484/65	15.27	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	134	5670	Full	16.26	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	134	5670	484/65	15.17	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	106	5530	Full	15.97	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	106	5530	996/67	15.27	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	122	5610	Full	16.44	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	122	5610	996/67	15.27	-		23.98	-	1.74	-	26.99	Pass
HE160	MCS0	1	114	5570	Full	16.44	-		23.98	-	1.74	-	26.99	Pass

FCC U-NII-2C straddle channel single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	144	5720	Full	16.13	-	-	23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	144	5720	26/8	11.17	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	144	5720	52/40	14.37	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	144	5720	106/54	15.47	-		23.98	-	1.74	-	26.99	Pass
HE20	MCS0	1	144	5720	242/61	15.47	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	142	5710	Full	16.40	-		23.98	-	1.74	-	26.99	Pass
HE40	MCS0	1	142	5710	484/65	15.27	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	138	5690	Full	16.39	-		23.98	-	1.74	-	26.99	Pass
HE80	MCS0	1	138	5690	996/67	15.37	-		23.98	-	1.74	-	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2C single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	100	5500	Full	0.02	-	3.56	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	100	5500	26/0	0.02	-	8.19	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	100	5500	52/37	0.02	-	7.89	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	100	5500	106/53	0.02	-	5.69	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	100	5500	242/61	0.05	-	2.57	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	120	5600	Full	0.02	-	3.76	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	120	5600	26/4	0.02	-	7.36	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	120	5600	52/38	0.02	-	8.60	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	120	5600	106/53	0.02	-	6.22	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	120	5600	242/61	0.05	-	2.66	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	140	5700	Full	0.02	-	1.45	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	140	5700	26/8	0.02	-	8.10	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	140	5700	52/40	0.02	-	8.16	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	140	5700	106/54	0.02	-	5.62	-	-	11.00	-	1.74	-	-	Pass
HE20	MCS0	1	140	5700	242/61	0.05	-	1.94	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	102	5510	Full	0.00	-	0.53	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	102	5510	484/65	0.08	-	-0.04	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	118	5590	Full	0.00	-	0.77	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	118	5590	484/65	0.08	-	-0.02	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	134	5670	Full	0.00	-	0.64	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	134	5670	484/65	0.08	-	-0.83	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	106	5530	Full	0.00	-	-2.92	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	106	5530	996/67	0.11	-	-3.39	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	122	5610	Full	0.00	-	-1.86	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	122	5610	996/67	0.11	-	-3.39	-		11.00	-	1.74	-		Pass
HE160	MCS0	1	114	5570	Full	0.02	-	-4.69	-		11.00	-	1.74	-		Pass
HE160	MCS0	1	114	5570	1992/68	0.12	-	-6.67	-		11.00	-	1.74	-		Pass

U-NII-2C straddle channel single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	144	5720	Full	0.02	-	3.34	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	144	5720	26/8	0.02	-	7.45	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	144	5720	52/40	0.02	-	7.71	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	144	5720	106/54	0.02	-	5.69	-		11.00	-	1.74	-		Pass
HE20	MCS0	1	144	5720	242/61	0.05	-	2.33	-	-	11.00	-	1.74	-	-	Pass
HE40	MCS0	1	142	5710	Full	0.00	-	0.65	-		11.00	-	1.74	-		Pass
HE40	MCS0	1	142	5710	484/65	0.08	-	-0.74	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	138	5690	Full	0.00	-	-1.70	-		11.00	-	1.74	-		Pass
HE80	MCS0	1	138	5690	996/67	0.11	-	-3.15	-		11.00	-	1.74	-		Pass

Test Result of 26dB & 99% Occupied Bandwidth

<802.11a>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT20>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT40>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT80>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT160>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE20>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE40>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE80>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE160>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Test Result of Power Spectral Density

<802.11a>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ac VHT20>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ac VHT40>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ac VHT80>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ac VHT160>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ax HE20>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ax HE40>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ax HE80>

Maximum Power Density Plot Trace 1 (Ant 1)



<802.11ax HE160>

Maximum Power Density Plot Trace 1 (Ant 1)



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	**Temperature :**	21.3~25.5℃
		Relative Humidity :	41.2~46.6%

EUT Information

Report NO :	5O1534
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.170000	---	30.56	54.96	24.40	L1	FLO	20.2
0.170000	46.36	---	64.96	18.60	L1	FLO	20.2
0.186000	---	24.87	54.21	29.34	L1	FLO	20.2
0.186000	40.66	---	64.21	23.55	L1	FLO	20.2
0.218000	---	30.42	52.90	22.48	L1	FLO	20.1
0.218000	45.00	---	62.90	17.90	L1	FLO	20.1
0.266000	---	27.26	51.24	23.98	L1	FLO	20.1
0.266000	41.06	---	61.24	20.18	L1	FLO	20.1
0.342000	---	16.78	49.16	32.38	L1	FLO	20.0
0.342000	30.70	---	59.16	28.46	L1	FLO	20.0
0.502000	---	29.26	46.00	16.74	L1	FLO	20.0
0.502000	36.39	---	56.00	19.61	L1	FLO	20.0
12.582000	---	25.62	50.00	24.38	L1	FLO	20.5
12.582000	33.05	---	60.00	26.95	L1	FLO	20.5

EUT Information

Report NO :	5O1534
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.162000	---	32.29	55.36	23.07	N	FLO	20.2
0.162000	48.55	---	65.36	16.81	N	FLO	20.2
0.194000	---	29.82	53.86	24.04	N	FLO	20.2
0.194000	44.86	---	63.86	19.00	N	FLO	20.2
0.218000	---	31.24	52.90	21.66	N	FLO	20.1
0.218000	45.72	---	62.90	17.18	N	FLO	20.1
0.242000	---	30.16	52.03	21.87	N	FLO	20.1
0.242000	44.08	---	62.03	17.95	N	FLO	20.1
0.274000	---	22.22	51.00	28.78	N	FLO	20.1
0.274000	38.89	---	61.00	22.11	N	FLO	20.1
0.522000	---	32.67	46.00	13.33	N	FLO	20.0
0.522000	39.14	---	56.00	16.86	N	FLO	20.0
12.206000	---	21.29	50.00	28.71	N	FLO	20.5
12.206000	29.38	---	60.00	30.62	N	FLO	20.5

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Leo Li , Karl Hou, and Lucifer Jiang	**Temperature :**	20.9~22.4°C
		Relative Humidity :	58.0~63.7%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU
Mode 1	U-NII-1	5.15-5.25	0	802.11a	36	5180	6Mbps	-
Mode 2	U-NII-1	5.15-5.25	0	802.11a	44	5220	6Mbps	-
Mode 3	U-NII-1	5.15-5.25	0	802.11a	48	5240	6Mbps	-
Mode 4	U-NII-1	5.15-5.25	0	802.11ac VHT20	36	5180	MCS0	-
Mode 5	U-NII-1	5.15-5.25	0	802.11ac VHT20	44	5220	MCS0	-
Mode 6	U-NII-1	5.15-5.25	0	802.11ac VHT20	48	5240	MCS0	-
Mode 7	U-NII-1	5.15-5.25	0	802.11ac VHT40	38	5190	MCS0	-
Mode 8	U-NII-1	5.15-5.25	0	802.11ac VHT40	46	5230	MCS0	-
Mode 9	U-NII-1	5.15-5.25	0	802.11ac VHT80	42	5210	MCS0	-
Mode 10	U-NII-1	5.15-5.25	0	802.11ac VHT160	50	5250	MCS0	-
Mode 11	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	Full RU
Mode 12	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	Partial RU 26/0
Mode 13	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	Partial RU 52/37
Mode 14	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	Partial RU 106/53
Mode 15	U-NII-1	5.15-5.25	0	802.11ax HE20	44	5220	MCS0	Full RU
Mode 16	U-NII-1	5.15-5.25	0	802.11ax HE20	48	5240	MCS0	Full RU
Mode 17	U-NII-1	5.15-5.25	0	802.11ax HE20	48	5240	MCS0	Partial RU 26/8

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU
Mode 18	U-NII-1	5.15-5.25	0	802.11ax HE20	48	5240	MCS0	Partial RU 52/40
Mode 19	U-NII-1	5.15-5.25	0	802.11ax HE40	38	5190	MCS0	Full RU
Mode 20	U-NII-1	5.15-5.25	0	802.11ax HE40	46	5230	MCS0	Full RU
Mode 21	U-NII-1	5.15-5.25	0	802.11ax HE80	42	5210	MCS0	Full RU
Mode 22	U-NII-1	5.15-5.25	0	802.11ax HE160	50	5250	MCS0	Full RU
Mode 23	U-NII-2A	5.25-5.35	0	802.11a	52	5260	6Mbps	-
Mode 24	U-NII-2A	5.25-5.35	0	802.11a	60	5300	6Mbps	-
Mode 25	U-NII-2A	5.25-5.35	0	802.11a	64	5320	6Mbps	-
Mode 26	U-NII-2A	5.25-5.35	0	802.11ac VHT20	52	5260	MCS0	-
Mode 27	U-NII-2A	5.25-5.35	0	802.11ac VHT20	60	5300	MCS0	-
Mode 28	U-NII-2A	5.25-5.35	0	802.11ac VHT20	64	5320	MCS0	-
Mode 29	U-NII-2A	5.25-5.35	0	802.11ac VHT40	54	5270	MCS0	-
Mode 30	U-NII-2A	5.25-5.35	0	802.11ac VHT40	62	5310	MCS0	-
Mode 31	U-NII-2A	5.25-5.35	0	802.11ac VHT80	58	5290	MCS0	-
Mode 32	U-NII-2A	5.25-5.35	0	802.11ax HE20	52	5260	MCS0	Full RU
Mode 33	U-NII-2A	5.25-5.35	0	802.11ax HE20	52	5260	MCS0	Partial RU 26/0
Mode 34	U-NII-2A	5.25-5.35	0	802.11ax HE20	52	5260	MCS0	Partial RU 52/37
Mode 35	U-NII-2A	5.25-5.35	0	802.11ax HE20	60	5300	MCS0	Full RU
Mode 36	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Full RU
Mode 37	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Partial RU 26/8
Mode 38	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Partial RU 52/40
Mode 39	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Partial RU 106/54
Mode 40	U-NII-2A	5.25-5.35	0	802.11ax HE40	54	5270	MCS0	Full RU
Mode 41	U-NII-2A	5.25-5.35	0	802.11ax HE40	62	5310	MCS0	Full RU
Mode 42	U-NII-2A	5.25-5.35	0	802.11ax HE80	58	5290	MCS0	Full RU

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU
Mode 43	U-NII-2C	5.47-5.725	0	802.11a	100	5500	6Mbps	-
Mode 44	U-NII-2C	5.47-5.725	0	802.11a	120	5600	6Mbps	-
Mode 45	U-NII-2C	5.47-5.725	0	802.11a	140	5700	6Mbps	-
Mode 46	U-NII-2C	5.47-5.725	0	802.11a	144	5720	6Mbps	-
Mode 47	U-NII-2C	5.47-5.725	0	802.11ac VHT20	100	5500	MCS0	-
Mode 48	U-NII-2C	5.47-5.725	0	802.11ac VHT20	120	5600	MCS0	-
Mode 49	U-NII-2C	5.47-5.725	0	802.11ac VHT20	140	5700	MCS0	-
Mode 50	U-NII-2C	5.47-5.725	0	802.11ac VHT20	144	5720	MCS0	-
Mode 51	U-NII-2C	5.47-5.725	0	802.11ac VHT40	102	5510	MCS0	-
Mode 52	U-NII-2C	5.47-5.725	0	802.11ac VHT40	118	5590	MCS0	-
Mode 53	U-NII-2C	5.47-5.725	0	802.11ac VHT40	134	5670	MCS0	-
Mode 54	U-NII-2C	5.47-5.725	0	802.11ac VHT40	142	5710	MCS0	-
Mode 55	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Partial RU 106/54
Mode 40	U-NII-2A	5.25-5.35	0	802.11ax HE40	54	5270	MCS0	Full RU
Mode 41	U-NII-2A	5.25-5.35	0	802.11ax HE40	62	5310	MCS0	Full RU
Mode 42	U-NII-2A	5.25-5.35	0	802.11ax HE80	58	5290	MCS0	Full RU
Mode 43	U-NII-2C	5.47-5.725	0	802.11a	100	5500	6Mbps	-
Mode 44	U-NII-2C	5.47-5.725	0	802.11a	120	5600	6Mbps	-
Mode 45	U-NII-2C	5.47-5.725	0	802.11a	140	5700	6Mbps	-
Mode 46	U-NII-2C	5.47-5.725	0	802.11a	144	5720	6Mbps	-
Mode 47	U-NII-2C	5.47-5.725	0	802.11ac VHT20	100	5500	MCS0	-
Mode 48	U-NII-2C	5.47-5.725	0	802.11ac VHT20	120	5600	MCS0	-
Mode 49	U-NII-2C	5.47-5.725	0	802.11ac VHT20	140	5700	MCS0	-
Mode 50	U-NII-2C	5.47-5.725	0	802.11ac VHT80	106	5530	MCS0	-
Mode 56	U-NII-2C	5.47-5.725	0	802.11ac VHT80	122	5610	MCS0	-
Mode 57	U-NII-2C	5.47-5.725	0	802.11ac VHT80	138	5690	MCS0	-

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU
Mode 58	U-NII-2C	5.47-5.725	0	802.11ac VHT160	114	5570	MCS0	-
Mode 59	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	Full RU
Mode 60	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	Partial RU 26/0
Mode 61	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	Partial RU 52/37
Mode 62	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	Partial RU 106/53
Mode 63	U-NII-2C	5.47-5.725	0	802.11ax HE20	120	5600	MCS0	Full RU
Mode 64	U-NII-2C	5.47-5.725	0	802.11ax HE20	120	5600	MCS0	Partial RU 26/4
Mode 65	U-NII-2C	5.47-5.725	0	802.11ax HE20	120	5600	MCS0	Partial RU 52/38
Mode 66	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Full RU
Mode 67	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Partial RU 26/8
Mode 68	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Partial RU 52/40
Mode 69	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Partial RU 106/54
Mode 70	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Partial RU 242/61
Mode 71	U-NII-2C	5.47-5.725	0	802.11ax HE20	144	5720	MCS0	Full RU
Mode 72	U-NII-2C	5.47-5.725	0	802.11ax HE20	144	5720	MCS0	Partial RU 26/8
Mode 73	U-NII-2C	5.47-5.725	0	802.11ax HE20	144	5720	MCS0	Partial RU 52/40
Mode 74	U-NII-2C	5.47-5.725	0	802.11ax HE20	144	5720	MCS0	Partial RU 106/54
Mode 75	U-NII-2C	5.47-5.725	0	802.11ax HE40	102	5510	MCS0	Full RU
Mode 76	U-NII-2C	5.47-5.725	0	802.11ax HE40	118	5590	MCS0	Full RU
Mode 77	U-NII-2C	5.47-5.725	0	802.11ax HE40	134	5670	MCS0	Full RU
Mode 78	U-NII-2C	5.47-5.725	0	802.11ax HE40	142	5710	MCS0	Full RU
Mode 79	U-NII-2C	5.47-5.725	0	802.11ax HE80	106	5530	MCS0	Full RU
Mode 80	U-NII-2C	5.47-5.725	0	802.11ax HE80	122	5610	MCS0	Full RU
Mode 81	U-NII-2C	5.47-5.725	0	802.11ax HE80	138	5690	MCS0	Full RU
Mode 82	U-NII-2C	5.47-5.725	0	802.11ax HE160	114	5570	MCS0	Full RU
Mode 83	SHF (Above 18GHz)							
Mode 84	LF (Below 1GHz)							

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	802.11a	36	5149.94	50.96	54.00	-3.04	H	Avg.	Pass	-	Band Edge
	802.11a	36	15540.00	44.06	54.00	-9.94	V	Avg.	Pass	-	Harmonic
2	802.11a	44	5006.16	43.14	54.00	-10.86	H	Avg.	Pass	-	Band Edge
	802.11a	44	15660.00	44.03	54.00	-9.97	V	Avg.	Pass	-	Harmonic
3	802.11a	48	5003.36	43.16	54.00	-10.84	H	Avg.	Pass	-	Band Edge
	802.11a	48	15720.00	44.07	54.00	-9.93	H	Avg.	Pass	-	Harmonic
4	802.11ac VHT20	36	5149.94	48.90	54.00	-5.10	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	36	15540.00	44.09	54.00	-9.91	V	Avg.	Pass	-	Harmonic
5	802.11ac VHT20	44	5002.86	43.08	54.00	-10.92	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	44	15660.00	43.96	54.00	-10.04	V	Avg.	Pass	-	Harmonic
6	802.11ac VHT20	48	5004.32	43.09	54.00	-10.91	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	48	15720.00	43.90	54.00	-10.10	H	Avg.	Pass	-	Harmonic
7	802.11ac VHT40	38	5148.77	48.82	54.00	-5.18	H	Avg.	Pass	-	Band Edge
8	802.11ac VHT40	46	5149.96	44.35	54.00	-9.65	H	Avg.	Pass	-	Band Edge
9	802.11ac VHT80	42	5137.97	50.10	54.00	-3.90	H	Avg.	Pass	-	Band Edge
10	802.11ac VHT160	50	5148.75	50.44	54.00	-3.56	H	Avg.	Pass	-	Band Edge
11	802.11ax HE20	36	5149.94	50.08	54.00	-3.92	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	36	15540.00	44.09	54.00	-9.91	H	Avg.	Pass	Full	Harmonic
12	802.11ax HE20	36	5008.46	43.03	54.00	-10.97	V	Avg.	Pass	26/0	Band Edge
	802.11ax HE20	36	15540.00	45.03	54.00	-8.97	H	Avg.	Pass	26/0	Harmonic
13	802.11ax HE20	36	5001.80	43.03	54.00	-10.97	H	Avg.	Pass	52/37	Band Edge
	802.11ax HE20	36	15540.00	45.00	54.00	-9.00	V	Avg.	Pass	52/37	Harmonic
14	802.11ax HE20	36	5149.94	43.36	54.00	-10.64	H	Avg.	Pass	106/53	Band Edge
15	802.11ax HE20	44	5001.54	43.00	54.00	-11.00	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	44	15660.00	43.96	54.00	-10.04	V	Avg.	Pass	Full	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
16	802.11ax HE20	48	5003.36	43.03	54.00	-10.97	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	48	15720.00	43.91	54.00	-10.09	V	Avg.	Pass	Full	Harmonic
17	802.11ax HE20	48	15720.00	44.73	54.00	-9.27	V	Avg.	Pass	26/8	Harmonic
18	802.11ax HE20	48	15720.00	44.64	54.00	-9.36	H	Avg.	Pass	52/40	Harmonic
19	802.11ax HE40	38	5149.53	49.15	54.00	-4.85	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	38	15570.00	45.80	54.00	-8.20	V	Avg.	Pass	Full	Harmonic
20	802.11ax HE40	46	5149.96	45.42	54.00	-8.58	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	46	15690.00	43.82	54.00	-10.18	H	Avg.	Pass	Full	Harmonic
21	802.11ax HE80	42	5130.20	49.41	54.00	-4.59	H	Avg.	Pass	Full	Band Edge
	802.11ax HE80	42	15630.00	44.17	54.00	-9.83	H	Avg.	Pass	Full	Harmonic
22	802.11ax HE160	50	5149.50	50.50	54.00	-3.50	H	Avg.	Pass	Full	Band Edge
	802.11ax HE160	50	15750.00	44.12	54.00	-9.88	H	Avg.	Pass	Full	Harmonic
23	802.11a	52	5006.50	43.34	54.00	-10.66	H	Avg.	Pass	-	Band Edge
	802.11a	52	15780.00	44.31	54.00	-9.69	H	Avg.	Pass	-	Harmonic
24	802.11a	60	5001.50	43.24	54.00	-10.76	H	Avg.	Pass	-	Band Edge
	802.11a	60	15900.00	44.22	54.00	-9.78	H	Avg.	Pass	-	Harmonic
25	802.11a	64	5350.10	49.12	54.00	-4.88	H	Avg.	Pass	-	Band Edge
	802.11a	64	15960.00	43.94	54.00	-10.06	V	Avg.	Pass	-	Harmonic
26	802.11ac VHT20	52	5002.08	43.23	54.00	-10.77	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	52	15780.00	44.06	54.00	-9.94	V	Avg.	Pass	-	Harmonic
27	802.11ac VHT20	60	5004.50	43.21	54.00	-10.79	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	60	15900.00	44.16	54.00	-9.84	H	Avg.	Pass	-	Harmonic
28	802.11ac VHT20	64	5350.10	48.66	54.00	-5.34	H	Avg.	Pass	-	Band Edge

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
28	802.11ac VHT20	64	15960.00	44.52	54.00	-9.48	V	Avg.	Pass	-	Harmonic
29	802.11ac VHT40	54	5002.70	43.25	54.00	-10.75	H	Avg.	Pass	-	Band Edge
30	802.11ac VHT40	62	5353.50	49.02	54.00	-4.98	H	Avg.	Pass	-	Band Edge
31	802.11ac VHT80	58	5373.30	49.64	54.00	-4.36	H	Avg.	Pass	-	Band Edge
32	802.11ax HE20	52	5001.30	43.30	54.00	-10.70	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	52	15780.00	44.16	54.00	-9.84	H	Avg.	Pass	Full	Harmonic
34	802.11ax HE20	52	15780.00	44.98	54.00	-9.02	V	Avg.	Pass	52/37	Harmonic
35	802.11ax HE20	60	5006.00	43.30	54.00	-10.70	V	Avg.	Pass	Full	Band Edge
	802.11ax HE20	60	15900.00	44.59	54.00	-9.41	H	Avg.	Pass	Full	Harmonic
36	802.11ax HE20	64	5350.10	50.02	54.00	-3.98	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	64	15960.00	43.93	54.00	-10.07	H	Avg.	Pass	Full	Harmonic
37	802.11ax HE20	64	5362.42	41.65	54.00	-12.35	H	Avg.	Pass	26/8	Band Edge
	802.11ax HE20	64	15960.00	44.86	54.00	-9.14	H	Avg.	Pass	26/8	Harmonic
38	802.11ax HE20	64	5351.92	41.43	54.00	-12.57	H	Avg.	Pass	52/40	Band Edge
	802.11ax HE20	64	15960.00	44.76	54.00	-9.24	H	Avg.	Pass	52/40	Harmonic
39	802.11ax HE20	64	5350.38	41.72	54.00	-12.28	H	Avg.	Pass	106/54	Band Edge
40	802.11ax HE40	54	5351.32	43.42	54.00	-10.58	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	54	15810.00	44.29	54.00	-9.71	H	Avg.	Pass	Full	Harmonic
41	802.11ax HE40	62	5356.65	49.22	54.00	-4.78	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	62	15930.00	44.15	54.00	-9.85	H	Avg.	Pass	Full	Harmonic
42	802.11ax HE80	58	5371.26	50.69	54.00	-3.31	H	Avg.	Pass	Full	Band Edge
	802.11ax HE80	58	15870.00	45.97	54.00	-8.03	V	Avg.	Pass	Full	Harmonic
43	802.11a	100	5470.00	64.12	68.20	-4.08	H	Peak	Pass	-	Band Edge
	802.11a	100	16500.00	56.16	68.20	-12.04	H	Peak	Pass	-	Harmonic
44	802.11a	120	5459.75	40.99	54.00	-13.01	H	Avg.	Pass	-	Band Edge
	802.11a	120	11200.00	40.51	54.00	-13.49	H	Avg.	Pass	-	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
45	802.11a	140	5728.21	64.65	68.20	-3.55	H	Peak	Pass	-	Band Edge
	802.11a	140	11400.00	40.68	54.00	-13.32	H	Avg.	Pass	-	Harmonic
46	802.11a	144	5455.69	40.64	54.00	-13.36	H	Avg.	Pass	-	Band Edge
	802.11a	144	11440.00	40.72	54.00	-13.28	V	Avg.	Pass	-	Harmonic
47	802.11ac VHT20	100	5469.40	62.81	68.20	-5.39	H	Peak	Pass	-	Band Edge
	802.11ac VHT20	100	11000.00	39.97	54.00	-14.03	H	Avg.	Pass	-	Harmonic
48	802.11ac VHT20	120	5445.25	40.83	54.00	-13.17	V	Avg.	Pass	-	Band Edge
	802.11ac VHT20	120	11200.00	40.41	54.00	-13.59	V	Avg.	Pass	-	Harmonic
49	802.11ac VHT20	140	5725.35	62.97	68.20	-5.23	H	Peak	Pass	-	Band Edge
	802.11ac VHT20	140	11400.00	40.69	54.00	-13.31	V	Avg.	Pass	-	Harmonic
50	802.11ac VHT20	144	5456.86	40.64	54.00	-13.36	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	144	11440.00	40.82	54.00	-13.18	V	Avg.	Pass	-	Harmonic
51	802.11ac VHT40	102	5465.36	64.27	68.20	-3.93	H	Peak	Pass	-	Band Edge
52	802.11ac VHT40	118	5459.92	41.26	54.00	-12.74	H	Avg.	Pass	-	Band Edge
53	802.11ac VHT40	134	5725.10	60.36	68.20	-7.84	H	Peak	Pass	-	Band Edge
54	802.11ac VHT40	142	5459.20	40.83	54.00	-13.17	V	Avg.	Pass	-	Band Edge
55	802.11ac VHT80	106	5445.04	49.74	54.00	-4.26	H	Avg.	Pass	-	Band Edge
56	802.11ac VHT80	122	5725.63	57.54	68.20	-10.66	H	Peak	Pass	-	Band Edge
57	802.11ac VHT80	138	5459.59	41.27	54.00	-12.73	H	Avg.	Pass	-	Band Edge
58	802.11ac VHT160	114	5460.00	50.53	54.00	-3.47	H	Avg.	Pass	-	Band Edge
59	802.11ax HE20	100	5466.40	61.34	68.20	-6.86	H	Peak	Pass	Full	Band Edge
	802.11ax HE20	100	16500.00	60.13	68.20	-8.07	V	Peak	Pass	Full	Harmonic
60	802.11ax HE20	100	5456.95	41.92	54.00	-12.08	H	Avg.	Pass	26/0	Band Edge
	802.11ax HE20	100	11000.00	41.01	54.00	-12.99	V	Avg.	Pass	26/0	Harmonic
61	802.11ax HE20	100	5459.50	41.91	54.00	-12.09	H	Avg.	Pass	52/37	Band Edge
	802.11ax HE20	100	11000.00	40.94	54.00	-13.06	H	Avg.	Pass	52/37	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
62	802.11ax HE20	100	5459.95	42.09	54.00	-11.91	H	Avg.	Pass	106/53	Band Edge
63	802.11ax HE20	120	5457.75	40.85	54.00	-13.15	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	120	16800.00	54.80	68.20	-13.40	V	Peak	Pass	Full	Harmonic
64	802.11ax HE20	120	11200.00	41.20	54.00	-12.80	V	Avg.	Pass	26/4	Harmonic
65	802.11ax HE20	120	11200.00	41.58	54.00	-12.42	H	Avg.	Pass	52/38	Harmonic
66	802.11ax HE20	140	5725.68	64.72	68.20	-3.48	H	Peak	Pass	Full	Band Edge
	802.11ax HE20	140	11400.00	42.43	54.00	-11.57	H	Avg.	Pass	Full	Harmonic
67	802.11ax HE20	140	5726.20	53.93	68.20	-14.27	H	Peak	Pass	26/8	Band Edge
	802.11ax HE20	140	11400.00	41.67	54.00	-12.33	H	Avg.	Pass	26/8	Harmonic
68	802.11ax HE20	140	5726.85	54.25	68.20	-13.95	H	Peak	Pass	52/40	Band Edge
	802.11ax HE20	140	11400.00	41.43	54.00	-12.57	V	Avg.	Pass	52/40	Harmonic
69	802.11ax HE20	140	5729.32	57.21	68.20	-10.99	H	Peak	Pass	106/54	Band Edge
70	802.11ax HE20	140	5726.07	64.49	68.20	-3.71	H	Peak	Pass	242/61	Band Edge
71	802.11ax HE20	144	5458.42	40.72	54.00	-13.28	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	144	11440.00	40.77	54.00	-13.23	H	Avg.	Pass	Full	Harmonic
72	802.11ax HE20	144	5459.20	40.62	54.00	-13.38	H	Avg.	Pass	26/8	Band Edge
73	802.11ax HE20	144	5458.81	40.61	54.00	-13.39	H	Avg.	Pass	52/40	Band Edge
74	802.11ax HE20	144	5459.98	40.67	54.00	-13.33	H	Avg.	Pass	106/54	Band Edge
75	802.11ax HE40	102	5459.92	50.84	54.00	-3.16	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	102	16530.00	55.30	68.20	-12.90	H	Peak	Pass	Full	Harmonic
76	802.11ax HE40	118	5459.44	41.23	54.00	-12.77	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	118	11180.00	41.54	54.00	-12.46	H	Avg.	Pass	Full	Harmonic
77	802.11ax HE40	134	5727.95	59.43	68.20	-8.77	H	Peak	Pass	Full	Band Edge
	802.11ax HE40	134	17010.00	55.24	68.20	-12.96	H	Peak	Pass	Full	Harmonic
78	802.11ax HE40	142	5459.20	40.70	54.00	-13.30	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	142	11420.00	40.93	54.00	-13.07	H	Avg.	Pass	Full	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
79	802.11ax HE80	106	5444.86	50.31	54.00	-3.69	H	Avg.	Pass	Full	Band Edge
	802.11ax HE80	106	16590.00	55.52	68.20	-12.68	V	Peak	Pass	Full	Harmonic
80	802.11ax HE80	122	5459.98	42.10	54.00	-11.90	H	Avg.	Pass	Full	Band Edge
	802.11ax HE80	122	11220.00	40.56	54.00	-13.44	H	Avg.	Pass	Full	Harmonic
81	802.11ax HE80	138	5459.98	41.09	54.00	-12.91	H	Avg.	Pass	Full	Band Edge
	802.11ax HE80	138	17070.00	55.21	68.20	-12.99	V	Peak	Pass	Full	Harmonic
82	802.11ax HE160	114	5460.00	50.54	54.00	-3.46	H	Avg.	Pass	Full	Band Edge
	802.11ax HE160	114	16710.00	55.59	68.20	-12.61	V	Peak	Pass	Full	Harmonic
83	SHF		39573.65	47.60	74.00	-26.40	H	Peak	Pass	-	-
84	LF		721.61	36.12	46.00	-9.88	V	Peak	Pass	-	-

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 62.99 74.00 -11.01 48.76 32.90 10.56 32.65 3.42 104 321 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 108.72 ------ ------ 94.65 32.82 10.59 32.76 3.42 104 321 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 50.96 54.00 -3.04 36.73 32.90 10.56 32.65 3.42 104 321 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 101.35 ------ ------ 87.28 32.82 10.59 32.76 3.42 104 321 Average

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5147.24 58.50 74.00 -15.50 44.26 32.90 10.56 32.64 3.42 400 209 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 102.69 ------ ------ 88.56 32.85 10.58 32.72 3.42 400 209 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 47.59 54.00 -6.41 33.36 32.90 10.56 32.65 3.42 400 209 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 95.56 ------ ------ 81.43 32.85 10.58 32.72 3.42 400 209 Average

Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.94 68.20 -18.26 34.27 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.34 74.00 -19.66 37.23 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.03 54.00 -9.97 26.92 41.00 18.34 44.69 2.46 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.72 68.20 -18.48 34.05 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.69 74.00 -19.31 37.58 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.06 54.00 -9.94 26.95 41.00 18.34 44.69 2.46 -- -- Average

Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	2	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5077.88 53.33 74.00 -20.67 38.95 32.90 10.51 32.44 3.41 198 320 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 106.84 ------ ------ 92.86 32.78 10.61 32.83 3.42 198 320 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5006.16 43.14 54.00 -10.86 28.53 32.99 10.45 32.24 3.41 198 320 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 99.73 ------ ------ 85.78 32.75 10.63 32.86 3.43 198 320 Average

Mode	2	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5425.68 50.88 74.00 -23.12 37.31 32.65 10.85 33.44 3.51 198 320 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5454.48 40.69 54.00 -13.31 27.08 32.71 10.91 33.52 3.51 198 320 Average	Blank

Mode	2	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5122.98 53.05 74.00 -20.95 38.76 32.90 10.54 32.57 3.42 122 187 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5220.00 104.25 ------ ------ 90.27 32.78 10.61 32.83 3.42 122 187 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5000.66 43.11 54.00 -10.89 28.47 33.00 10.45 32.22 3.41 122 187 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5220.00 97.19 ------ ------ 83.24 32.75 10.63 32.86 3.43 122 187 Average

Mode	2	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5412.00 50.59 74.00 -23.41 37.04 32.62 10.83 33.40 3.50 122 187 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5458.56 40.64 54.00 -13.36 27.03 32.72 10.91 33.53 3.51 122 187 Average	Blank

Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 49.79 68.20 -18.41 34.36 37.42 14.94 39.07 2.14 -- -- Peak 2 15660.00 54.07 74.00 -19.93 37.14 40.88 18.41 44.83 2.47 -- -- Peak 3 15660.00 43.90 54.00 -10.10 26.97 40.88 18.41 44.83 2.47 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 49.99 68.20 -18.21 34.56 37.42 14.94 39.07 2.14 -- -- Peak 2 15660.00 53.71 74.00 -20.29 36.78 40.88 18.41 44.83 2.47 -- -- Peak 3 15660.00 44.03 54.00 -9.97 27.10 40.88 18.41 44.83 2.47 -- -- Average

Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	3	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5135.12 53.14 74.00 -20.86 38.88 32.90 10.55 32.61 3.42 188 347 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 107.06 ------ ------ 93.20 32.70 10.65 32.93 3.44 188 347 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5003.36 43.16 54.00 -10.84 28.54 32.99 10.45 32.23 3.41 188 347 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 100.02 ------ ------ 86.11 32.73 10.64 32.89 3.43 188 347 Average

Mode	3	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5455.16 50.79 74.00 -23.21 37.18 32.71 10.91 33.52 3.51 188 347 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5446.58 40.72 54.00 -13.28 27.13 32.69 10.89 33.50 3.51 188 347 Average	Blank

Mode	3	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5037.68 53.84 74.00 -20.16 39.36 32.92 10.48 32.33 3.41 399 221 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5240.00 104.97 ------ ------ 91.08 32.72 10.64 32.91 3.44 399 221 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5002.88 43.10 54.00 -10.90 28.48 32.99 10.45 32.23 3.41 399 221 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5240.00 98.05 ------ ------ 84.19 32.70 10.65 32.93 3.44 399 221 Average

Mode	3	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5389.82 50.21 74.00 -23.79 36.66 32.58 10.80 33.33 3.50 399 221 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.78 40.61 54.00 -13.39 27.00 32.72 10.91 33.53 3.51 399 221 Average	Blank

Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10480.00 50.57 68.20 -17.63 35.09 37.46 14.97 39.10 2.15 -- -- Peak 2 15720.00 54.82 74.00 -19.18 37.96 40.84 18.44 44.90 2.48 -- -- Peak 3 15720.00 44.07 54.00 -9.93 27.21 40.84 18.44 44.90 2.48 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10480.00 50.34 68.20 -17.86 34.86 37.46 14.97 39.10 2.15 -- -- Peak 2 15720.00 54.58 74.00 -19.42 37.72 40.84 18.44 44.90 2.48 -- -- Peak 3 15720.00 43.96 54.00 -10.04 27.10 40.84 18.44 44.90 2.48 -- -- Average

Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5147.42 61.30 74.00 -12.70 47.06 32.90 10.56 32.64 3.42 100 320 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 107.46 ------ ------ 93.33 32.85 10.58 32.72 3.42 100 320 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 48.90 54.00 -5.10 34.67 32.90 10.56 32.65 3.42 100 320 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 100.09 ------ ------ 85.94 32.86 10.58 32.71 3.42 100 320 Average

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH36_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5149.76 57.87 74.00 -16.13 43.64 32.90 10.56 32.65 3.42 108 196 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5180.00 103.67 ------ ------ 89.56 32.84 10.59 32.74 3.42 108 196 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5149.94 46.30 54.00 -7.70 32.07 32.90 10.56 32.65 3.42 108 196 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5180.00 96.15 ------ ------ 82.08 32.82 10.59 32.76 3.42 108 196 Average

Mode	4	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 50.51 68.20 -17.69 34.84 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.60 74.00 -19.40 37.49 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.09 54.00 -9.91 26.98 41.00 18.34 44.69 2.46 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 50.22 68.20 -17.98 34.55 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.43 74.00 -19.57 37.32 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.09 54.00 -9.91 26.98 41.00 18.34 44.69 2.46 -- -- Average

Mode	4	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	5	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5005.50 52.82 74.00 -21.18 38.21 32.99 10.45 32.24 3.41 102 321 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 108.34 ------ ------ 94.39 32.75 10.63 32.86 3.43 102 321 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5002.86 43.08 54.00 -10.92 28.46 32.99 10.45 32.23 3.41 102 321 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 101.41 ------ ------ 87.49 32.74 10.63 32.88 3.43 102 321 Average

Mode	5	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5418.24 50.70 74.00 -23.30 37.14 32.64 10.84 33.42 3.50 102 321 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5447.04 40.68 54.00 -13.32 27.09 32.69 10.89 33.50 3.51 102 321 Average	Blank

Mode	5	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5056.10 52.44 74.00 -21.56 38.02 32.90 10.49 32.38 3.41 116 200 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 105.14 ------ ------ 91.16 32.78 10.61 32.83 3.42 116 200 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5003.96 43.03 54.00 -10.97 28.41 32.99 10.45 32.23 3.41 116 200 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 97.65 ------ ------ 83.68 32.76 10.62 32.84 3.43 116 200 Average

Mode	5	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5407.44 51.18 74.00 -22.82 37.64 32.61 10.82 33.39 3.50 116 200 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5460.00 40.55 54.00 -13.45 26.95 32.72 10.91 33.54 3.51 116 200 Average	Blank

Mode	5	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 49.90 68.20 -18.30 34.47 37.42 14.94 39.07 2.14 -- -- Peak 2 15660.00 55.07 74.00 -18.93 38.14 40.88 18.41 44.83 2.47 -- -- Peak 3 15660.00 43.95 54.00 -10.05 27.02 40.88 18.41 44.83 2.47 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 50.48 68.20 -17.72 35.05 37.42 14.94 39.07 2.14 -- -- Peak 2 15660.00 54.63 74.00 -19.37 37.70 40.88 18.41 44.83 2.47 -- -- Peak 3 15660.00 43.96 54.00 -10.04 27.03 40.88 18.41 44.83 2.47 -- -- Average

Mode	5	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	6	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5039.12 53.97 74.00 -20.03 39.49 32.92 10.48 32.33 3.41 100 344 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 108.22 ------ ------ 94.31 32.73 10.64 32.89 3.43 100 344 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5004.32 43.09 54.00 -10.91 28.47 32.99 10.45 32.23 3.41 100 344 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 101.16 ------ ------ 87.27 32.72 10.64 32.91 3.44 100 344 Average

Mode	6	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5405.22 51.17 74.00 -22.83 37.62 32.61 10.82 33.38 3.50 100 344 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5457.36 40.75 54.00 -13.25 27.15 32.71 10.91 33.53 3.51 100 344 Average	Blank

Mode	6	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5034.56 53.36 74.00 -20.64 38.86 32.93 10.48 32.32 3.41 100 167 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 104.18 ------ ------ 90.27 32.73 10.64 32.89 3.43 100 167 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5001.44 43.00 54.00 -11.00 28.36 33.00 10.45 32.22 3.41 100 167 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5240.00 96.81 ------ ------ 82.92 32.72 10.64 32.91 3.44 100 167 Average

Mode	6	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5409.84 51.33 74.00 -22.67 37.77 32.62 10.83 33.39 3.50 100 167 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.56 40.54 54.00 -13.46 26.93 32.72 10.91 33.53 3.51 100 167 Average	Blank

Mode	6	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL 1 10480.00 49.75 68.20 -18.45 34.27 37.46 14.97 39.10 2.15 -- -- Peak 2 15720.00 54.32 74.00 -19.68 37.46 40.84 18.44 44.90 2.48 -- -- Peak 3 15720.00 43.90 54.00 -10.10 27.04 40.84 18.44 44.90 2.48 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL 1 10480.00 49.93 68.20 -18.27 34.45 37.46 14.97 39.10 2.15 -- -- Peak 2 15720.00 54.76 74.00 -19.24 37.90 40.84 18.44 44.90 2.48 -- -- Peak 3 15720.00 43.89 54.00 -10.11 27.03 40.84 18.44 44.90 2.48 -- -- Average

Mode	6	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	7	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH38_5190MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5141.36 59.60 74.00 -14.40 45.34 32.90 10.56 32.62 3.42 100 321 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5190.00 104.63 ------ ------ 90.56 32.82 10.59 32.76 3.42 100 321 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.77 48.82 54.00 -5.18 34.59 32.90 10.56 32.65 3.42 100 321 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5190.00 97.22 ------ ------ 83.09 32.85 10.58 32.72 3.42 100 321 Average

Mode	7	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH38_5190MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5439.75 50.73 74.00 -23.27 37.14 32.68 10.88 33.48 3.51 100 321 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5444.88 40.71 54.00 -13.29 27.11 32.69 10.89 33.49 3.51 100 321 Average	Blank

Mode	7	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH38_5190MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5145.35 57.46 74.00 -16.54 43.22 32.90 10.56 32.64 3.42 108 188 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5190.00 100.50 ------ ------ 86.39 32.84 10.59 32.74 3.42 108 188 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.34 46.43 54.00 -7.57 32.20 32.90 10.56 32.65 3.42 108 188 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5190.00 92.97 ------ ------ 78.84 32.85 10.58 32.72 3.42 108 188 Average

Mode	7	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH38_5190MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5407.08 50.30 74.00 -23.70 36.75 32.61 10.82 33.38 3.50 108 188 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.73 40.50 54.00 -13.50 26.89 32.72 10.91 33.53 3.51 108 188 Average	Blank

Mode	8	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH46_5230MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.58 53.77 74.00 -20.23 39.53 32.90 10.56 32.64 3.42 100 321 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5230.00 105.65 ------ ------ 91.79 32.70 10.65 32.93 3.44 100 321 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.96 44.35 54.00 -9.65 30.12 32.90 10.56 32.65 3.42 100 321 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5230.00 98.22 ------ ------ 84.27 32.75 10.63 32.86 3.43 100 321 Average

Mode	8	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH46_5230MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5410.09 50.80 74.00 -23.20 37.24 32.62 10.83 33.39 3.50 100 321 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5350.06 41.09 54.00 -12.91 27.57 32.50 10.76 33.22 3.48 100 321 Average	Blank

Mode	8	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH46_5230MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5144.44 54.57 74.00 -19.43 40.32 32.90 10.56 32.63 3.42 100 197 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5230.00 101.29 ------ ------ 87.34 32.75 10.63 32.86 3.43 100 197 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5149.96 43.12 54.00 -10.88 28.89 32.90 10.56 32.65 3.42 100 197 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5230.00 94.15 ------ ------ 80.20 32.75 10.63 32.86 3.43 100 197 Average

Mode	8	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT40_CH46_5230MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5418.60 51.17 74.00 -22.83 37.61 32.64 10.84 33.42 3.50 100 197 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.54 40.52 54.00 -13.48 26.91 32.72 10.91 33.53 3.51 100 197 Average	Blank

Mode	9
	Band Edge - L
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_5210MHz
ANT	0

Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5127.26 61.05 74.00 -12.95 46.76 32.90 10.55 32.58 3.42 100 318 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5210.00 101.40 ------ ------ 87.54 32.70 10.65 32.93 3.44 100 318 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5137.97 50.10 54.00 -3.90 35.84 32.90 10.55 32.61 3.42 100 318 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5210.00 93.71 ------ ------ 79.82 32.72 10.64 32.91 3.44 100 318 Average

Mode	9	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_5210MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5435.25 52.19 74.00 -21.81 38.60 32.67 10.87 33.46 3.51 100 318 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5350.25 41.75 54.00 -12.25 28.23 32.50 10.76 33.22 3.48 100 318 Average	Blank

Mode	9	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_5210MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5115.08 60.52 74.00 -13.48 46.21 32.90 10.54 32.55 3.42 121 191 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5210.00 96.77 ------ ------ 82.80 32.76 10.62 32.84 3.43 121 191 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5131.04 48.86 54.00 -5.14 34.58 32.90 10.55 32.59 3.42 121 191 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto 1 5210.00 89.26 ------ ------ 75.11 32.86 10.58 32.71 3.42 121 191 Average

Mode	9	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_5210MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5454.00 51.19 74.00 -22.81 37.59 32.71 10.90 33.52 3.51 121 191 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.50 40.61 54.00 -13.39 27.00 32.72 10.91 33.53 3.51 121 191 Average	Blank

Mode	10	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT160_CH50_5250MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5134.25 61.25 74.00 -12.75 46.98 32.90 10.55 32.60 3.42 100 308 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5250.00 98.99 ------ ------ 85.15 32.69 10.66 32.95 3.44 100 308 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.75 50.44 54.00 -3.56 36.21 32.90 10.56 32.65 3.42 100 308 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5250.00 91.42 ------ ------ 77.58 32.69 10.66 32.95 3.44 100 308 Average

Mode	10	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT160_CH50_5250MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5357.10 64.23 74.00 -9.77 50.72 32.51 10.76 33.24 3.48 100 308 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5350.17 48.78 54.00 -5.22 35.26 32.50 10.76 33.22 3.48 100 308 Average	Blank

Mode	10	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT160_CH50_5250MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5140.00 57.59 74.00 -16.41 43.33 32.90 10.56 32.62 3.42 100 265 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5250.00 96.40 ------ ------ 82.51 32.72 10.64 32.91 3.44 100 265 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.25 48.62 54.00 -5.38 34.38 32.90 10.56 32.64 3.42 100 265 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5250.00 87.90 ------ ------ 74.06 32.69 10.66 32.95 3.44 100 265 Average

Mode	10	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT160_CH50_5250MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5371.59 58.50 74.00 -15.50 44.97 32.54 10.78 33.28 3.49 100 265 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5350.17 45.83 54.00 -8.17 32.31 32.50 10.76 33.22 3.48 100 265 Average	Blank

Mode	11	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Full RU_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5144.72 62.51 74.00 -11.49 48.26 32.90 10.56 32.63 3.42 100 320 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 109.47 ------ ------ 95.34 32.85 10.58 32.72 3.42 100 320 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 50.08 54.00 -3.92 35.85 32.90 10.56 32.65 3.42 100 320 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 100.69 ------ ------ 86.54 32.86 10.58 32.71 3.42 100 320 Average

Mode	11	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Full RU_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.50 58.10 74.00 -15.90 43.86 32.90 10.56 32.64 3.42 106 162 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 105.22 ------ ------ 91.09 32.85 10.58 32.72 3.42 106 162 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 46.65 54.00 -7.35 32.42 32.90 10.56 32.65 3.42 106 162 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 96.48 ------ ------ 82.33 32.86 10.58 32.71 3.42 106 162 Average

Mode	11	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Full RU_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.77 68.20 -18.43 34.10 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.90 74.00 -19.10 37.79 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.09 54.00 -9.91 26.98 41.00 18.34 44.69 2.46 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.83 68.20 -18.37 34.16 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 54.93 74.00 -19.07 37.82 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.06 54.00 -9.94 26.95 41.00 18.34 44.69 2.46 -- -- Average

Mode	11	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Full RU_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	12	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Partial RU 26/0_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5076.14 54.19 74.00 -19.81 39.81 32.90 10.51 32.44 3.41 100 300 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 110.89 ------ ------ 96.74 32.86 10.58 32.71 3.42 100 300 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5004.14 43.03 54.00 -10.97 28.41 32.99 10.45 32.23 3.41 100 300 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 103.82 ------ ------ 89.67 32.86 10.58 32.71 3.42 100 300 Average

Mode	12	
	Band Edge	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Partial RU 26/0_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Level Read Factor Ant Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5127.62 53.68 74.00 -20.32 39.39 32.90 10.55 32.58 3.42 105 173 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Level Read Factor Ant Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 109.96 ------ ------ 95.81 32.86 10.58 32.71 3.42 105 173 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Level Read Factor Ant Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5008.46 43.03 54.00 -10.97 28.42 32.98 10.46 32.24 3.41 105 173 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Level Read Factor Ant Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 103.13 ------ ------ 88.98 32.86 10.58 32.71 3.42 105 173 Average

Mode	12	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Partial RU 26/0_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 50.76 68.20 -17.44 35.09 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 55.20 74.00 -18.80 38.09 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 45.03 54.00 -8.97 27.92 41.00 18.34 44.69 2.46 -- -- Average	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.43 68.20 -18.77 33.76 37.66 14.88 39.00 2.13 -- -- Peak 2 15540.00 53.95 74.00 -20.05 36.84 41.00 18.34 44.69 2.46 -- -- Peak 3 15540.00 44.73 54.00 -9.27 27.62 41.00 18.34 44.69 2.46 -- -- Average

Mode	12	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ax HE20_CH36_Partial RU 26/0_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg