



FCC RF Test Report

APPLICANT : Luxottica Group S.p.A.
EQUIPMENT : AI GLASSES
BRAND NAME : Ray-Ban Meta or Ray-Ban
MODEL NAME : RW4011, RW4011V, RW4015,
RW4015V, RW4016, RW4016V
FCC ID : 2AYOA-4010
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : Apr. 14, 2026 ~ May 20, 2026

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
3 TEST RESULT	11
3.1 Output Power Measurement.....	11
3.2 Radiated Band Edges and Spurious Emission Measurement	12
4 LIST OF MEASURING EQUIPMENT.....	16
5 MEASUREMENT UNCERTAINTY.....	17
APPENDIX A. RADIATED SPURIOUS EMISSION	
APPENDIX B. DUTY CYCLE PLOTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O1706-01A	Rev. 01	Initial issue of report	Apr. 30, 2026
FR5O1706-01A	Rev. 02	1. Added verified conducted power 2. Added descriptions of samples 1234 and the worst LF mode to the table. This report is an updated version, replacing the report issued on Apr. 30, 2026	May 20, 2026



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(b)(1)	Conducted Output Power	≤ 125 mW	Pass	-
3.2	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 18.96 dB at 635.28 MHz

Note: This is a variant report. The change note could be referred to Product Equality Declaration which is exhibit separately. According to the change, only the related test cases were verified from original report (Sporton Report Number FR5O1534A).

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Luxottica Group S.p.A.

Piazzale Cadorna 3 20123 Milan, Italy

1.2 Manufacturer

Luxottica Group S.p.A.

Piazzale Cadorna 3 20123 Milan, Italy

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	AI GLASSES
Brand Name	Ray-Ban Meta or Ray-Ban
Model Name	RW4011, RW4011V, RW4015, RW4015V, RW4016, RW4016V
FCC ID	2AYOA-4010
SN Code	Conducted/Radiation:4237X05J1L001W/4337W06J21001G/ 4337V16J22000P/4337T05J2Y0009
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are four samples of EUT. The manufacturer declares that all the equipment share the same radio characteristics and Software/Firmware, the only differences between each of them are color of frames, lenses, and sizes.

Sample	Model Name
Sample 1	RW4016
Sample 1	RW4016V
Sample 2	RW4015
Sample 2	RW4015V
Sample 3	RW4011
Sample 3	RW4011V
Sample 4	RW4011
Sample 4	RW4011V

3. Differences between model numbers RW4011, RW4015, RW4016 and RW4011V, RW4015V, RW4016V: The glasses are 100% the same between V models and the others without V at the end of model code. Only difference is the eyeglasses lenses that will be mounted on the frame.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03-SZ TH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020+Cor.1-2023

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated:, radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y/Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH39_2441 MHz		
Remark:			
1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			

2.3 Connection Diagram of Test System





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8m

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

3 Test Result

3.1 Output Power Measurement

3.1.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of Peak Output Power

DH	CH.	NTX	Peak Power (dBm)	Power Level	Power Limit (dBm)	Test Result
DH5	0	1	9.08	Default	20.97	Pass

3.1.6 Test Result of Average Output Power (Reporting Only)

DH	CH.	NTX	Average Power (dBm)
DH5	0	1	8.90



3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5 and 6.6.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1\text{GHz}$; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
8. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
9. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.2.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix A.

3.2.8 Duty cycle correction factor for average measurement

Please refer to Appendix B.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 02, 2026	Apr. 14, 2026	Apr. 01, 2027	Radiation (03CH03-SZ)
EXA Signal Analyzer	KEYSIGHT	N9010B	MY59071191	10KHz~44GHz	Mar. 27, 2026	Apr. 14, 2026	Mar. 26, 2027	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 25, 2025	Apr. 14, 2026	Dec. 24, 2026	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Sep. 13, 2025	Apr. 14, 2026	Sep. 12, 2026	Radiation (03CH03-SZ)
Double Ridge Guide Antenna	ETS-Lindgren	Burgeon-3117	00240107	1GHz~18GHz	Jul. 13, 2025	Apr. 14, 2026	Jul. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Apr. 14, 2026	Jul. 02, 2026	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 03, 2025	Apr. 14, 2026	Apr. 02, 2027	Radiation (03CH03-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz~3000MHz	Apr. 02, 2026	Apr. 14, 2026	Apr. 01, 2027	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 13, 2025	Apr. 14, 2026	Oct. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	Keysight	83017A	MY53270357	500MHz~26.5GHz	Apr. 02, 2026	Apr. 14, 2026	Apr. 01, 2027	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Oct. 13, 2026	Apr. 14, 2026	Oct. 12, 2027	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Apr. 14, 2026	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Apr. 14, 2026	NCR	Radiation (03CH03-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Mar. 26, 2026	May 20, 2026	Mar. 25, 2027	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 24, 2025	May 20, 2026	Dec. 23, 2026	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct.13, 2025	May 20, 2026	Oct. 12, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 1.34 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

----- THE END -----



Appendix A. Radiated Spurious Emission Test Data

Test Engineer :	Reid Huang	Relative Humidity :	48~49%
		Temperature :	24~25°C

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth BR_GFSK	39	2441	1DH5	-	1
Mode 4	2400-2483.5	1	Bluetooth BR_GFSK	39	2441	1DH5	-	2
Mode 7	2400-2483.5	1	Bluetooth BR_GFSK	39	2441	1DH5	-	3
Mode 10	2400-2483.5	1	Bluetooth BR_GFSK	39	2441	1DH5	-	4
Mode 13	2400-2483.5	1	Bluetooth BR_GFSK_LF	39	2441	1DH5	-	3

Only the worst-case LF mode shall be reflected in the report.


Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	39	2389.11	49.77	74.00	-24.23	V	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	39	7323.00	45.28	74.00	-28.72	H	Peak	Pass	Harmonic
4	Bluetooth BR_GFSK	39	2486.44	47.69	74.00	-26.31	V	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	39	7323.00	46.09	74.00	-27.91	H	Peak	Pass	Harmonic
7	Bluetooth BR_GFSK	39	2388.71	52.17	74.00	-21.83	H	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	39	7323.00	45.24	74.00	-28.76	H	Peak	Pass	Harmonic
10	Bluetooth BR_GFSK	39	2488.18	48.40	74.00	-25.60	H	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	39	7323.00	46.99	74.00	-27.01	V	Peak	Pass	Harmonic
13	Bluetooth BR_GFSK_LF	39	635.28	27.04	46.00	-18.96	H	Peak	Pass	LF





Mode	1																																																																																																													
	Band Edge - L																																																																																																													
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																													
ANT	1																																																																																																													
Pol.	Horizontal	Fundamental																																																																																																												
Peak																																																																																																														
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2388.98</td><td>48.40</td><td>74.00</td><td>-25.60</td><td>41.91</td><td>31.69</td><td>8.31</td><td>33.51</td><td>100</td><td>137 PEAK</td></tr><tr><td>2</td><td>2388.98</td><td>23.61</td><td>54.00</td><td>-30.39</td><td>17.12</td><td>31.69</td><td>8.31</td><td>33.51</td><td>100</td><td>137 AVERAGE</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2388.98	48.40	74.00	-25.60	41.91	31.69	8.31	33.51	100	137 PEAK	2	2388.98	23.61	54.00	-30.39	17.12	31.69	8.31	33.51	100	137 AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>97.13</td><td>-----</td><td>90.35</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>137</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>72.34</td><td>-----</td><td>65.56</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>137</td><td>AVERAGE</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	97.13	-----	90.35	31.89	8.38	33.49	100	137	PEAK	2	2441.00	72.34	-----	65.56	31.89	8.38	33.49	100	137	AVERAGE
			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2388.98	48.40	74.00	-25.60	41.91	31.69	8.31	33.51	100	137 PEAK																																																																																																				
2	2388.98	23.61	54.00	-30.39	17.12	31.69	8.31	33.51	100	137 AVERAGE																																																																																																				
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2441.00	97.13	-----	90.35	31.89	8.38	33.49	100	137	PEAK																																																																																																				
2	2441.00	72.34	-----	65.56	31.89	8.38	33.49	100	137	AVERAGE																																																																																																				




Mode	1																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																							
ANT	1																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2500.00</td><td>48.26</td><td>74.00</td><td>-25.74</td><td>41.15</td><td>32.10</td><td>8.46</td><td>33.45</td><td>100</td><td>137 PEAK</td></tr><tr><td>2</td><td>2500.00</td><td>23.47</td><td>54.00</td><td>-30.53</td><td>16.36</td><td>32.10</td><td>8.46</td><td>33.45</td><td>100</td><td>137 AVERAGE</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2500.00	48.26	74.00	-25.74	41.15	32.10	8.46	33.45	100	137 PEAK	2	2500.00	23.47	54.00	-30.53	16.36	32.10	8.46	33.45	100	137 AVERAGE	Blank
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																															
1	2500.00	48.26	74.00	-25.74	41.15	32.10	8.46	33.45	100	137 PEAK																																														
2	2500.00	23.47	54.00	-30.53	16.36	32.10	8.46	33.45	100	137 AVERAGE																																														





Mode	1																																																																																																																																	
	Band Edge - L																																																																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																	
ANT	1																																																																																																																																	
Pol.	Vertical						Fundamental																																																																																																																											
Peak																																																																																																																																		
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.11</td><td>49.77</td><td>74.00</td><td>-24.23</td><td>43.28</td><td>31.69</td><td>8.31</td><td>33.51</td><td>100</td><td>138</td><td>PEAK</td></tr><tr><td>2</td><td>2389.11</td><td>24.98</td><td>54.00</td><td>-29.02</td><td>18.49</td><td>31.69</td><td>8.31</td><td>33.51</td><td>100</td><td>138</td><td>AVERAGE</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2389.11	49.77	74.00	-24.23	43.28	31.69	8.31	33.51	100	138	PEAK	2	2389.11	24.98	54.00	-29.02	18.49	31.69	8.31	33.51	100	138	AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>94.53</td><td>-----</td><td>-----</td><td>87.75</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>138</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>69.74</td><td>-----</td><td>-----</td><td>62.96</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>138</td><td>AVERAGE</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	94.53	-----	-----	87.75	31.89	8.38	33.49	100	138	PEAK	2	2441.00	69.74	-----	-----	62.96	31.89	8.38	33.49	100	138	AVERAGE
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																						
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																								
1	2389.11	49.77	74.00	-24.23	43.28	31.69	8.31	33.51	100	138	PEAK																																																																																																																							
2	2389.11	24.98	54.00	-29.02	18.49	31.69	8.31	33.51	100	138	AVERAGE																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																								
1	2441.00	94.53	-----	-----	87.75	31.89	8.38	33.49	100	138	PEAK																																																																																																																							
2	2441.00	69.74	-----	-----	62.96	31.89	8.38	33.49	100	138	AVERAGE																																																																																																																							



Mode	1																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Vertical	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2490.64</td><td>47.97</td><td>74.00</td><td>-26.03</td><td>40.90</td><td>32.08</td><td>8.44</td><td>33.45</td><td>100</td><td>138</td><td>PEAK</td></tr><tr><td>2</td><td>2490.64</td><td>23.18</td><td>54.00</td><td>-30.82</td><td>16.11</td><td>32.08</td><td>8.44</td><td>33.45</td><td>100</td><td>138</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	2490.64	47.97	74.00	-26.03	40.90	32.08	8.44	33.45	100	138	PEAK	2	2490.64	23.18	54.00	-30.82	16.11	32.08	8.44	33.45	100	138	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																				
1	2490.64	47.97	74.00	-26.03	40.90	32.08	8.44	33.45	100	138	PEAK																																																		
2	2490.64	23.18	54.00	-30.82	16.11	32.08	8.44	33.45	100	138	AVERAGE																																																		




Mode	1																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal					Vertical																																																																																																																			
Peak Avg																																																																																																																									
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr></thead><tbody><tr><td>1</td><td>4882.00</td><td>44.38</td><td>74.00</td><td>-29.62</td><td>57.35</td><td>33.71</td><td>9.87</td></tr><tr><td>2</td><td>4882.00</td><td>19.59</td><td>54.00</td><td>-34.41</td><td>32.56</td><td>33.71</td><td>9.87</td></tr><tr><td>3</td><td>7323.00</td><td>45.28</td><td>74.00</td><td>-28.72</td><td>57.44</td><td>35.62</td><td>11.45</td></tr><tr><td>4</td><td>7323.00</td><td>20.49</td><td>54.00</td><td>-33.51</td><td>32.65</td><td>35.62</td><td>11.45</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4882.00	44.38	74.00	-29.62	57.35	33.71	9.87	2	4882.00	19.59	54.00	-34.41	32.56	33.71	9.87	3	7323.00	45.28	74.00	-28.72	57.44	35.62	11.45	4	7323.00	20.49	54.00	-33.51	32.65	35.62	11.45	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr></thead><tbody><tr><td>1</td><td>4882.00</td><td>44.08</td><td>74.00</td><td>-29.92</td><td>57.05</td><td>33.71</td><td>9.87</td></tr><tr><td>2</td><td>4882.00</td><td>19.29</td><td>54.00</td><td>-34.71</td><td>32.26</td><td>33.71</td><td>9.87</td></tr><tr><td>3</td><td>7323.00</td><td>45.19</td><td>74.00</td><td>-28.81</td><td>57.35</td><td>35.62</td><td>11.45</td></tr><tr><td>4</td><td>7323.00</td><td>20.40</td><td>54.00</td><td>-33.60</td><td>32.56</td><td>35.62</td><td>11.45</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4882.00	44.08	74.00	-29.92	57.05	33.71	9.87	2	4882.00	19.29	54.00	-34.71	32.26	33.71	9.87	3	7323.00	45.19	74.00	-28.81	57.35	35.62	11.45	4	7323.00	20.40	54.00	-33.60	32.56	35.62
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																		
1	4882.00	44.38	74.00	-29.62	57.35	33.71	9.87																																																																																																																		
2	4882.00	19.59	54.00	-34.41	32.56	33.71	9.87																																																																																																																		
3	7323.00	45.28	74.00	-28.72	57.44	35.62	11.45																																																																																																																		
4	7323.00	20.49	54.00	-33.51	32.65	35.62	11.45																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																		
1	4882.00	44.08	74.00	-29.92	57.05	33.71	9.87																																																																																																																		
2	4882.00	19.29	54.00	-34.71	32.26	33.71	9.87																																																																																																																		
3	7323.00	45.19	74.00	-28.81	57.35	35.62	11.45																																																																																																																		
4	7323.00	20.40	54.00	-33.60	32.56	35.62	11.45																																																																																																																		





Mode	4																																																																																																																						
	Band Edge - L																																																																																																																						
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																						
ANT	1																																																																																																																						
Pol.	Horizontal						Fundamental																																																																																																																
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2355.36</td><td>47.32</td><td>74.00</td><td>-26.68</td><td>41.00</td><td>31.62</td><td>8.23</td><td>33.53</td><td>179</td><td>209 PEAK</td></tr><tr><td>2</td><td>2355.36</td><td>22.53</td><td>54.00</td><td>-31.47</td><td>16.21</td><td>31.62</td><td>8.23</td><td>33.53</td><td>179</td><td>209 AVERAGE</td></tr></table>								Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2355.36	47.32	74.00	-26.68	41.00	31.62	8.23	33.53	179	209 PEAK	2	2355.36	22.53	54.00	-31.47	16.21	31.62	8.23	33.53	179	209 AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>98.08</td><td>-----</td><td>91.30</td><td>31.89</td><td>8.38</td><td>33.49</td><td>179</td><td>209</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>73.29</td><td>-----</td><td>66.51</td><td>31.89</td><td>8.38</td><td>33.49</td><td>179</td><td>209</td><td>AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	98.08	-----	91.30	31.89	8.38	33.49	179	209	PEAK	2	2441.00	73.29	-----	66.51	31.89	8.38	33.49	179	209	AVERAGE
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2355.36	47.32	74.00	-26.68	41.00	31.62	8.23	33.53	179	209 PEAK																																																																																																													
2	2355.36	22.53	54.00	-31.47	16.21	31.62	8.23	33.53	179	209 AVERAGE																																																																																																													
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2441.00	98.08	-----	91.30	31.89	8.38	33.49	179	209	PEAK																																																																																																													
2	2441.00	73.29	-----	66.51	31.89	8.38	33.49	179	209	AVERAGE																																																																																																													




Mode	4																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Horizontal	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2485.90</td><td>47.48</td><td>74.00</td><td>-26.52</td><td>40.44</td><td>32.06</td><td>8.44</td><td>33.46</td><td>179</td><td>209</td><td>PEAK</td></tr><tr><td>2</td><td>2485.90</td><td>22.69</td><td>54.00</td><td>-31.31</td><td>15.65</td><td>32.06</td><td>8.44</td><td>33.46</td><td>179</td><td>209</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2485.90	47.48	74.00	-26.52	40.44	32.06	8.44	33.46	179	209	PEAK	2	2485.90	22.69	54.00	-31.31	15.65	32.06	8.44	33.46	179	209	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																			
1	2485.90	47.48	74.00	-26.52	40.44	32.06	8.44	33.46	179	209	PEAK																																																		
2	2485.90	22.69	54.00	-31.31	15.65	32.06	8.44	33.46	179	209	AVERAGE																																																		





Mode	4																																																																																																													
	Band Edge - L																																																																																																													
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																													
ANT	1																																																																																																													
Pol.	Vertical	Fundamental																																																																																																												
Peak	 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2365.76</td><td>47.49</td><td>74.00</td><td>-26.51</td><td>41.12</td><td>31.64</td><td>8.26</td><td>33.53</td><td>348</td><td>4 PEAK</td></tr><tr><td>2</td><td>2365.76</td><td>22.70</td><td>54.00</td><td>-31.30</td><td>16.33</td><td>31.64</td><td>8.26</td><td>33.53</td><td>348</td><td>4 AVERAGE</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2365.76	47.49	74.00	-26.51	41.12	31.64	8.26	33.53	348	4 PEAK	2	2365.76	22.70	54.00	-31.30	16.33	31.64	8.26	33.53	348	4 AVERAGE	 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>91.20</td><td>-----</td><td>84.42</td><td>31.89</td><td>8.38</td><td>33.49</td><td>348</td><td></td><td>4 PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>66.41</td><td>-----</td><td>59.63</td><td>31.89</td><td>8.38</td><td>33.49</td><td>348</td><td></td><td>4 AVERAGE</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	91.20	-----	84.42	31.89	8.38	33.49	348		4 PEAK	2	2441.00	66.41	-----	59.63	31.89	8.38	33.49	348		4 AVERAGE
			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																			
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2365.76	47.49	74.00	-26.51	41.12	31.64	8.26	33.53	348	4 PEAK																																																																																																				
2	2365.76	22.70	54.00	-31.30	16.33	31.64	8.26	33.53	348	4 AVERAGE																																																																																																				
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	2441.00	91.20	-----	84.42	31.89	8.38	33.49	348		4 PEAK																																																																																																				
2	2441.00	66.41	-----	59.63	31.89	8.38	33.49	348		4 AVERAGE																																																																																																				





Mode	4																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Vertical	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2486.44</td><td>47.69</td><td>74.00</td><td>-26.31</td><td>40.65</td><td>32.06</td><td>8.44</td><td>33.46</td><td>348</td><td>4</td><td>PEAK</td></tr><tr><td>2</td><td>2486.44</td><td>22.90</td><td>54.00</td><td>-31.10</td><td>15.86</td><td>32.06</td><td>8.44</td><td>33.46</td><td>348</td><td>4</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2486.44	47.69	74.00	-26.31	40.65	32.06	8.44	33.46	348	4	PEAK	2	2486.44	22.90	54.00	-31.10	15.86	32.06	8.44	33.46	348	4	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																			
1	2486.44	47.69	74.00	-26.31	40.65	32.06	8.44	33.46	348	4	PEAK																																																		
2	2486.44	22.90	54.00	-31.10	15.86	32.06	8.44	33.46	348	4	AVERAGE																																																		




Mode	4																																																																																												
	Harmonic																																																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																												
ANT	1																																																																																												
Pol.	Horizontal																																																																																												
Peak Avg																																																																																													
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4882.00</td><td>43.49</td><td>74.00</td><td>-30.51</td><td>56.46</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>18.70</td><td>54.00</td><td>-35.30</td><td>31.67</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>46.09</td><td>74.00</td><td>-27.91</td><td>58.25</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>21.30</td><td>54.00</td><td>-32.70</td><td>33.46</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>													Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4882.00	43.49	74.00	-30.51	56.46	33.71	9.87	56.55	--	--	Peak	2	4882.00	18.70	54.00	-35.30	31.67	33.71	9.87	56.55	--	--	Average	3	7323.00	46.09	74.00	-27.91	58.25	35.62	11.45	59.23	--	--	Peak	4	7323.00	21.30	54.00	-32.70	33.46	35.62	11.45	59.23	--	--
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	4882.00	43.49	74.00	-30.51	56.46	33.71	9.87	56.55	--	--	Peak																																																																																		
2	4882.00	18.70	54.00	-35.30	31.67	33.71	9.87	56.55	--	--	Average																																																																																		
3	7323.00	46.09	74.00	-27.91	58.25	35.62	11.45	59.23	--	--	Peak																																																																																		
4	7323.00	21.30	54.00	-32.70	33.46	35.62	11.45	59.23	--	--	Average																																																																																		
Peak Avg																																																																																													
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4882.00</td><td>43.26</td><td>74.00</td><td>-30.74</td><td>56.23</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>18.47</td><td>54.00</td><td>-35.53</td><td>31.44</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>45.31</td><td>74.00</td><td>-28.69</td><td>57.47</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>20.52</td><td>54.00</td><td>-33.48</td><td>32.68</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>													Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4882.00	43.26	74.00	-30.74	56.23	33.71	9.87	56.55	--	--	Peak	2	4882.00	18.47	54.00	-35.53	31.44	33.71	9.87	56.55	--	--	Average	3	7323.00	45.31	74.00	-28.69	57.47	35.62	11.45	59.23	--	--	Peak	4	7323.00	20.52	54.00	-33.48	32.68	35.62	11.45	59.23	--	--
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	4882.00	43.26	74.00	-30.74	56.23	33.71	9.87	56.55	--	--	Peak																																																																																		
2	4882.00	18.47	54.00	-35.53	31.44	33.71	9.87	56.55	--	--	Average																																																																																		
3	7323.00	45.31	74.00	-28.69	57.47	35.62	11.45	59.23	--	--	Peak																																																																																		
4	7323.00	20.52	54.00	-33.48	32.68	35.62	11.45	59.23	--	--	Average																																																																																		





Mode	7																																																																
	Band Edge - L																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																
ANT	1																																																																
Pol.	Horizontal																																																																
Peak																																																																	
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.71</td><td>52.17</td><td>74.00</td><td>-21.83</td><td>45.68</td><td>31.69</td><td>8.31</td><td>33.51</td><td>334</td><td>156 PEAK</td></tr><tr><td>2</td><td>2388.71</td><td>27.38</td><td>54.00</td><td>-26.62</td><td>20.89</td><td>31.69</td><td>8.31</td><td>33.51</td><td>334</td><td>156 AVERAGE</td></tr></table>													Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.71	52.17	74.00	-21.83	45.68	31.69	8.31	33.51	334	156 PEAK	2	2388.71	27.38	54.00	-26.62	20.89	31.69	8.31	33.51	334	156 AVERAGE
			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																						
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																							
1	2388.71	52.17	74.00	-21.83	45.68	31.69	8.31	33.51	334	156 PEAK																																																							
2	2388.71	27.38	54.00	-26.62	20.89	31.69	8.31	33.51	334	156 AVERAGE																																																							
																																																																	
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>96.43</td><td>-----</td><td>89.65</td><td>31.89</td><td>8.38</td><td>33.49</td><td>334</td><td>156</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>71.64</td><td>-----</td><td>64.86</td><td>31.89</td><td>8.38</td><td>33.49</td><td>334</td><td>156</td><td>AVERAGE</td></tr></table>													Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	96.43	-----	89.65	31.89	8.38	33.49	334	156	PEAK	2	2441.00	71.64	-----	64.86	31.89	8.38	33.49	334	156	AVERAGE	
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																							
1	2441.00	96.43	-----	89.65	31.89	8.38	33.49	334	156	PEAK																																																							
2	2441.00	71.64	-----	64.86	31.89	8.38	33.49	334	156	AVERAGE																																																							




Mode	7																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Horizontal	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2489.26</td><td>48.35</td><td>74.00</td><td>-25.65</td><td>41.30</td><td>32.07</td><td>8.44</td><td>33.46</td><td>334</td><td>156</td><td>PEAK</td></tr><tr><td>2</td><td>2489.26</td><td>23.56</td><td>54.00</td><td>-30.44</td><td>16.51</td><td>32.07</td><td>8.44</td><td>33.46</td><td>334</td><td>156</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2489.26	48.35	74.00	-25.65	41.30	32.07	8.44	33.46	334	156	PEAK	2	2489.26	23.56	54.00	-30.44	16.51	32.07	8.44	33.46	334	156	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																			
1	2489.26	48.35	74.00	-25.65	41.30	32.07	8.44	33.46	334	156	PEAK																																																		
2	2489.26	23.56	54.00	-30.44	16.51	32.07	8.44	33.46	334	156	AVERAGE																																																		



Mode	7																																																																																																																					
	Band Edge - L																																																																																																																					
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																					
ANT	1																																																																																																																					
Pol.	Vertical					Fundamental																																																																																																																
Peak																																																																																																																						
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2388.84</td><td>49.49</td><td>74.00</td><td>-24.51</td><td>43.00</td><td>31.69</td><td>8.31</td><td>33.51</td><td>218</td><td>310 PEAK</td></tr><tr><td>2</td><td>2388.84</td><td>24.70</td><td>54.00</td><td>-29.30</td><td>18.21</td><td>31.69</td><td>8.31</td><td>33.51</td><td>218</td><td>310 AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2388.84	49.49	74.00	-24.51	43.00	31.69	8.31	33.51	218	310 PEAK	2	2388.84	24.70	54.00	-29.30	18.21	31.69	8.31	33.51	218	310 AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>95.39</td><td>-----</td><td>88.61</td><td>31.89</td><td>8.38</td><td>33.49</td><td>218</td><td>310</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>70.60</td><td>-----</td><td>63.82</td><td>31.89</td><td>8.38</td><td>33.49</td><td>218</td><td>310</td><td>AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	95.39	-----	88.61	31.89	8.38	33.49	218	310	PEAK	2	2441.00	70.60	-----	63.82	31.89	8.38	33.49	218	310	AVERAGE
			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2388.84	49.49	74.00	-24.51	43.00	31.69	8.31	33.51	218	310 PEAK																																																																																																												
2	2388.84	24.70	54.00	-29.30	18.21	31.69	8.31	33.51	218	310 AVERAGE																																																																																																												
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2441.00	95.39	-----	88.61	31.89	8.38	33.49	218	310	PEAK																																																																																																												
2	2441.00	70.60	-----	63.82	31.89	8.38	33.49	218	310	AVERAGE																																																																																																												





Mode	7																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Vertical	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2484.16</td><td>47.79</td><td>74.00</td><td>-26.21</td><td>40.77</td><td>32.05</td><td>8.43</td><td>33.46</td><td>218</td><td>310</td><td>PEAK</td></tr><tr><td>2</td><td>2484.16</td><td>23.00</td><td>54.00</td><td>-31.00</td><td>15.98</td><td>32.05</td><td>8.43</td><td>33.46</td><td>218</td><td>310</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	2484.16	47.79	74.00	-26.21	40.77	32.05	8.43	33.46	218	310	PEAK	2	2484.16	23.00	54.00	-31.00	15.98	32.05	8.43	33.46	218	310	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																				
1	2484.16	47.79	74.00	-26.21	40.77	32.05	8.43	33.46	218	310	PEAK																																																		
2	2484.16	23.00	54.00	-31.00	15.98	32.05	8.43	33.46	218	310	AVERAGE																																																		




Mode	7																																																																																																																																																																															
	Harmonic																																																																																																																																																																															
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																																																															
ANT	1																																																																																																																																																																															
Pol.	Horizontal										Vertical																																																																																																																																																																					
Peak Avg																																																																																																																																																																																
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4882.00</td><td>44.45</td><td>74.00</td><td>-29.55</td><td>57.42</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>19.66</td><td>54.00</td><td>-34.34</td><td>32.63</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>45.24</td><td>74.00</td><td>-28.76</td><td>57.40</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>20.45</td><td>54.00</td><td>-33.55</td><td>32.61</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>												Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4882.00	44.45	74.00	-29.55	57.42	33.71	9.87	56.55	--	--	Peak	2	4882.00	19.66	54.00	-34.34	32.63	33.71	9.87	56.55	--	--	Average	3	7323.00	45.24	74.00	-28.76	57.40	35.62	11.45	59.23	--	--	Peak	4	7323.00	20.45	54.00	-33.55	32.61	35.62	11.45	59.23	--	--	Average	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4882.00</td><td>44.25</td><td>74.00</td><td>-29.75</td><td>57.22</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>19.46</td><td>54.00</td><td>-34.54</td><td>32.43</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>44.97</td><td>74.00</td><td>-29.03</td><td>57.13</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>20.18</td><td>54.00</td><td>-33.82</td><td>32.34</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4882.00	44.25	74.00	-29.75	57.22	33.71	9.87	56.55	--	--	Peak	2	4882.00	19.46	54.00	-34.54	32.43	33.71	9.87	56.55	--	--	Average	3	7323.00	44.97	74.00	-29.03	57.13	35.62	11.45	59.23	--	--	Peak	4	7323.00	20.18	54.00	-33.82	32.34	35.62	11.45	59.23	--	--
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	4882.00	44.45	74.00	-29.55	57.42	33.71	9.87	56.55	--	--	Peak																																																																																																																																																																					
2	4882.00	19.66	54.00	-34.34	32.63	33.71	9.87	56.55	--	--	Average																																																																																																																																																																					
3	7323.00	45.24	74.00	-28.76	57.40	35.62	11.45	59.23	--	--	Peak																																																																																																																																																																					
4	7323.00	20.45	54.00	-33.55	32.61	35.62	11.45	59.23	--	--	Average																																																																																																																																																																					
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	4882.00	44.25	74.00	-29.75	57.22	33.71	9.87	56.55	--	--	Peak																																																																																																																																																																					
2	4882.00	19.46	54.00	-34.54	32.43	33.71	9.87	56.55	--	--	Average																																																																																																																																																																					
3	7323.00	44.97	74.00	-29.03	57.13	35.62	11.45	59.23	--	--	Peak																																																																																																																																																																					
4	7323.00	20.18	54.00	-33.82	32.34	35.62	11.45	59.23	--	--	Average																																																																																																																																																																					





Mode	10																																																																																																																					
	Band Edge - L																																																																																																																					
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																					
ANT	1																																																																																																																					
Pol.	Horizontal					Fundamental																																																																																																																
Peak	 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2324.58</td><td>47.62</td><td>74.00</td><td>-26.38</td><td>41.45</td><td>31.56</td><td>8.16</td><td>33.55</td><td>100</td><td>107 PEAK</td></tr><tr><td>2</td><td>2324.58</td><td>22.83</td><td>54.00</td><td>-31.17</td><td>16.66</td><td>31.56</td><td>8.16</td><td>33.55</td><td>100</td><td>107 AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2324.58	47.62	74.00	-26.38	41.45	31.56	8.16	33.55	100	107 PEAK	2	2324.58	22.83	54.00	-31.17	16.66	31.56	8.16	33.55	100	107 AVERAGE	 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>100.09</td><td>-----</td><td>93.31</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>107</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>75.30</td><td>-----</td><td>68.52</td><td>31.89</td><td>8.38</td><td>33.49</td><td>100</td><td>107</td><td>AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	100.09	-----	93.31	31.89	8.38	33.49	100	107	PEAK	2	2441.00	75.30	-----	68.52	31.89	8.38	33.49	100	107	AVERAGE
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2324.58	47.62	74.00	-26.38	41.45	31.56	8.16	33.55	100	107 PEAK																																																																																																												
2	2324.58	22.83	54.00	-31.17	16.66	31.56	8.16	33.55	100	107 AVERAGE																																																																																																												
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																													
1	2441.00	100.09	-----	93.31	31.89	8.38	33.49	100	107	PEAK																																																																																																												
2	2441.00	75.30	-----	68.52	31.89	8.38	33.49	100	107	AVERAGE																																																																																																												




Mode	10																																																																				
	Band Edge - R																																																																				
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																				
ANT	1																																																																				
Pol.	Horizontal					Fundamental																																																															
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2488.18</td><td>48.40</td><td>74.00</td><td>-25.60</td><td>41.35</td><td>32.07</td><td>8.44</td><td>33.46</td><td>100</td><td>107</td><td>PEAK</td></tr><tr><td>2</td><td>2488.18</td><td>23.61</td><td>54.00</td><td>-30.39</td><td>16.56</td><td>32.07</td><td>8.44</td><td>33.46</td><td>100</td><td>107</td><td>AVERAGE</td></tr></table>							Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	2488.18	48.40	74.00	-25.60	41.35	32.07	8.44	33.46	100	107	PEAK	2	2488.18	23.61	54.00	-30.39	16.56	32.07	8.44	33.46	100	107	AVERAGE	Blank				
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																												
1	2488.18	48.40	74.00	-25.60	41.35	32.07	8.44	33.46	100	107	PEAK																																																										
2	2488.18	23.61	54.00	-30.39	16.56	32.07	8.44	33.46	100	107	AVERAGE																																																										





Mode	10																																																																																																																																	
	Band Edge - L																																																																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																	
ANT	1																																																																																																																																	
Pol.	Vertical						Fundamental																																																																																																																											
Peak																																																																																																																																		
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2345.10</td><td>47.51</td><td>74.00</td><td>-26.49</td><td>41.24</td><td>31.60</td><td>8.21</td><td>33.54</td><td>114</td><td>127</td><td>PEAK</td></tr><tr><td>2</td><td>2345.10</td><td>22.72</td><td>54.00</td><td>-31.28</td><td>16.45</td><td>31.60</td><td>8.21</td><td>33.54</td><td>114</td><td>127</td><td>AVERAGE</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	2345.10	47.51	74.00	-26.49	41.24	31.60	8.21	33.54	114	127	PEAK	2	2345.10	22.72	54.00	-31.28	16.45	31.60	8.21	33.54	114	127	AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2441.00</td><td>96.11</td><td>-----</td><td>-----</td><td>89.33</td><td>31.89</td><td>8.38</td><td>33.49</td><td>114</td><td>127</td><td>PEAK</td></tr><tr><td>2</td><td>2441.00</td><td>71.32</td><td>-----</td><td>-----</td><td>64.54</td><td>31.89</td><td>8.38</td><td>33.49</td><td>114</td><td>127</td><td>AVERAGE</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	2441.00	96.11	-----	-----	89.33	31.89	8.38	33.49	114	127	PEAK	2	2441.00	71.32	-----	-----	64.54	31.89	8.38	33.49	114	127	AVERAGE
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																						
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																									
1	2345.10	47.51	74.00	-26.49	41.24	31.60	8.21	33.54	114	127	PEAK																																																																																																																							
2	2345.10	22.72	54.00	-31.28	16.45	31.60	8.21	33.54	114	127	AVERAGE																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																									
1	2441.00	96.11	-----	-----	89.33	31.89	8.38	33.49	114	127	PEAK																																																																																																																							
2	2441.00	71.32	-----	-----	64.54	31.89	8.38	33.49	114	127	AVERAGE																																																																																																																							





Mode	10																																																												
	Band Edge - R																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																												
ANT	1																																																												
Pol.	Vertical	Fundamental																																																											
Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2491.00</td><td>48.19</td><td>74.00</td><td>-25.81</td><td>41.12</td><td>32.08</td><td>8.44</td><td>33.45</td><td>114</td><td>127</td><td>PEAK</td></tr><tr><td>2</td><td>2491.00</td><td>23.41</td><td>54.00</td><td>-30.59</td><td>16.34</td><td>32.08</td><td>8.44</td><td>33.45</td><td>114</td><td>127</td><td>AVERAGE</td></tr></table>			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2491.00	48.19	74.00	-25.81	41.12	32.08	8.44	33.45	114	127	PEAK	2	2491.00	23.41	54.00	-30.59	16.34	32.08	8.44	33.45	114	127	AVERAGE	Blank
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																			
1	2491.00	48.19	74.00	-25.81	41.12	32.08	8.44	33.45	114	127	PEAK																																																		
2	2491.00	23.41	54.00	-30.59	16.34	32.08	8.44	33.45	114	127	AVERAGE																																																		




Mode	10																																																																																																																																																																	
	Harmonic																																																																																																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																																																	
ANT	1																																																																																																																																																																	
Pol.	Horizontal					Vertical																																																																																																																																																												
Peak Avg																																																																																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>44.27</td><td>74.00</td><td>-29.73</td><td>57.24</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>19.48</td><td>54.00</td><td>-34.52</td><td>32.45</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>46.90</td><td>74.00</td><td>-27.10</td><td>59.06</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>22.11</td><td>54.00</td><td>-31.89</td><td>34.27</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	44.27	74.00	-29.73	57.24	33.71	9.87	56.55	--	--	Peak	2	4882.00	19.48	54.00	-34.52	32.45	33.71	9.87	56.55	--	--	Average	3	7323.00	46.90	74.00	-27.10	59.06	35.62	11.45	59.23	--	--	Peak	4	7323.00	22.11	54.00	-31.89	34.27	35.62	11.45	59.23	--	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>45.10</td><td>74.00</td><td>-28.90</td><td>58.07</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4882.00</td><td>20.31</td><td>54.00</td><td>-33.69</td><td>33.28</td><td>33.71</td><td>9.87</td><td>56.55</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7323.00</td><td>46.99</td><td>74.00</td><td>-27.01</td><td>59.15</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7323.00</td><td>22.20</td><td>54.00</td><td>-31.80</td><td>34.36</td><td>35.62</td><td>11.45</td><td>59.23</td><td>--</td><td>--</td><td>Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	45.10	74.00	-28.90	58.07	33.71	9.87	56.55	--	--	Peak	2	4882.00	20.31	54.00	-33.69	33.28	33.71	9.87	56.55	--	--	Average	3	7323.00	46.99	74.00	-27.01	59.15	35.62	11.45	59.23	--	--	Peak	4	7323.00	22.20	54.00	-31.80	34.36	35.62	11.45	59.23	--	--	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																										
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																								
1	4882.00	44.27	74.00	-29.73	57.24	33.71	9.87	56.55	--	--	Peak																																																																																																																																																							
2	4882.00	19.48	54.00	-34.52	32.45	33.71	9.87	56.55	--	--	Average																																																																																																																																																							
3	7323.00	46.90	74.00	-27.10	59.06	35.62	11.45	59.23	--	--	Peak																																																																																																																																																							
4	7323.00	22.11	54.00	-31.89	34.27	35.62	11.45	59.23	--	--	Average																																																																																																																																																							
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																									
1	4882.00	45.10	74.00	-28.90	58.07	33.71	9.87	56.55	--	--	Peak																																																																																																																																																							
2	4882.00	20.31	54.00	-33.69	33.28	33.71	9.87	56.55	--	--	Average																																																																																																																																																							
3	7323.00	46.99	74.00	-27.01	59.15	35.62	11.45	59.23	--	--	Peak																																																																																																																																																							
4	7323.00	22.20	54.00	-31.80	34.36	35.62	11.45	59.23	--	--	Average																																																																																																																																																							




Mode	13																																																																																																																																																																																																												
	LF																																																																																																																																																																																																												
	2400-2483.5_Bluetooth BR_GFSK_LF_CH39_2441MHz																																																																																																																																																																																																												
ANT	1																																																																																																																																																																																																												
Pol.	Horizontal					Vertical																																																																																																																																																																																																							
Peak Avg																																																																																																																																																																																																													
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>52.31</td><td>18.50</td><td>40.00</td><td>-21.50</td><td>33.23</td><td>19.53</td><td>0.74</td><td>35.00</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>150.28</td><td>18.95</td><td>43.50</td><td>-24.55</td><td>33.59</td><td>18.98</td><td>1.28</td><td>34.90</td><td>--</td><td>-- Peak</td></tr><tr><td>3</td><td>317.12</td><td>19.69</td><td>46.00</td><td>-26.31</td><td>33.04</td><td>19.50</td><td>1.85</td><td>34.70</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>408.30</td><td>21.96</td><td>46.00</td><td>-24.04</td><td>32.88</td><td>21.64</td><td>2.13</td><td>34.69</td><td>--</td><td>-- Peak</td></tr><tr><td>5</td><td>516.94</td><td>24.22</td><td>46.00</td><td>-21.78</td><td>32.68</td><td>23.64</td><td>2.40</td><td>34.50</td><td>--</td><td>-- Peak</td></tr><tr><td>6</td><td>635.28</td><td>27.04</td><td>46.00</td><td>-18.96</td><td>32.57</td><td>26.20</td><td>2.67</td><td>34.40</td><td>--</td><td>-- Peak</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	52.31	18.50	40.00	-21.50	33.23	19.53	0.74	35.00	--	-- Peak	2	150.28	18.95	43.50	-24.55	33.59	18.98	1.28	34.90	--	-- Peak	3	317.12	19.69	46.00	-26.31	33.04	19.50	1.85	34.70	--	-- Peak	4	408.30	21.96	46.00	-24.04	32.88	21.64	2.13	34.69	--	-- Peak	5	516.94	24.22	46.00	-21.78	32.68	23.64	2.40	34.50	--	-- Peak	6	635.28	27.04	46.00	-18.96	32.57	26.20	2.67	34.40	--	-- Peak	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>47.46</td><td>18.53</td><td>40.00</td><td>-21.47</td><td>33.14</td><td>19.62</td><td>0.69</td><td>34.92</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>175.50</td><td>18.85</td><td>43.50</td><td>-24.65</td><td>34.89</td><td>17.46</td><td>1.40</td><td>34.90</td><td>--</td><td>-- Peak</td></tr><tr><td>3</td><td>292.87</td><td>19.93</td><td>46.00</td><td>-26.07</td><td>33.95</td><td>18.91</td><td>1.78</td><td>34.71</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>358.83</td><td>21.03</td><td>46.00</td><td>-24.97</td><td>33.33</td><td>20.43</td><td>1.97</td><td>34.70</td><td>--</td><td>-- Peak</td></tr><tr><td>5</td><td>459.71</td><td>23.75</td><td>46.00</td><td>-22.25</td><td>33.20</td><td>22.87</td><td>2.26</td><td>34.58</td><td>--</td><td>-- Peak</td></tr><tr><td>6</td><td>543.13</td><td>25.95</td><td>46.00</td><td>-20.05</td><td>33.90</td><td>24.08</td><td>2.47</td><td>34.50</td><td>--</td><td>-- Peak</td></tr></table>							Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	47.46	18.53	40.00	-21.47	33.14	19.62	0.69	34.92	--	-- Peak	2	175.50	18.85	43.50	-24.65	34.89	17.46	1.40	34.90	--	-- Peak	3	292.87	19.93	46.00	-26.07	33.95	18.91	1.78	34.71	--	-- Peak	4	358.83	21.03	46.00	-24.97	33.33	20.43	1.97	34.70	--	-- Peak	5	459.71	23.75	46.00	-22.25	33.20	22.87	2.26	34.58	--	-- Peak	6	543.13	25.95	46.00	-20.05	33.90	24.08	2.47	34.50	--
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																				
1	52.31	18.50	40.00	-21.50	33.23	19.53	0.74	35.00	--	-- Peak																																																																																																																																																																																																			
2	150.28	18.95	43.50	-24.55	33.59	18.98	1.28	34.90	--	-- Peak																																																																																																																																																																																																			
3	317.12	19.69	46.00	-26.31	33.04	19.50	1.85	34.70	--	-- Peak																																																																																																																																																																																																			
4	408.30	21.96	46.00	-24.04	32.88	21.64	2.13	34.69	--	-- Peak																																																																																																																																																																																																			
5	516.94	24.22	46.00	-21.78	32.68	23.64	2.40	34.50	--	-- Peak																																																																																																																																																																																																			
6	635.28	27.04	46.00	-18.96	32.57	26.20	2.67	34.40	--	-- Peak																																																																																																																																																																																																			
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																				
1	47.46	18.53	40.00	-21.47	33.14	19.62	0.69	34.92	--	-- Peak																																																																																																																																																																																																			
2	175.50	18.85	43.50	-24.65	34.89	17.46	1.40	34.90	--	-- Peak																																																																																																																																																																																																			
3	292.87	19.93	46.00	-26.07	33.95	18.91	1.78	34.71	--	-- Peak																																																																																																																																																																																																			
4	358.83	21.03	46.00	-24.97	33.33	20.43	1.97	34.70	--	-- Peak																																																																																																																																																																																																			
5	459.71	23.75	46.00	-22.25	33.20	22.87	2.26	34.58	--	-- Peak																																																																																																																																																																																																			
6	543.13	25.95	46.00	-20.05	33.90	24.08	2.47	34.50	--	-- Peak																																																																																																																																																																																																			

Appendix B. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.