FCC RADIO TEST REPORT

FCC ID	:	**2AYOA-4012**
Equipment	:	**AI GLASSES**
Brand Name	:	**Ray-Ban Meta or Ray-Ban**
Model Name	:	**RW7004, RW7004V, RW7005, RW7005V**
Applicant	:	**Luxottica Group S.p.A. Piazzale Cadorna 3 20123 Milan, Italy**
Manufacturer	:	**Luxottica Group S.p.A. Piazzale Cadorna 3 20123 Milan, Italy**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on May 26, 2026 and testing was performed from Jul. 06, 2026 to Aug. 15, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory
No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

1 General Description 5
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test 7
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result 11
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Output Power Measurement 12
3.3 Power Spectral Density Measurement 13
3.4 Conducted Band Edges and Spurious Emission Measurement 14
3.5 Radiated Band Edges and Spurious Emission Measurement 15
3.6 AC Conducted Emission Measurement 19
3.7 Antenna Requirements 21
4 List of Measuring Equipment 22
5 Measurement Uncertainty 24
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR652603B	01	Initial issue of report	Aug. 20, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Avis Chuang

Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Bluetooth-LE **Antenna Type** Bluetooth: PIFA Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	4.0

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

Sample	Model Name
SKU1	RW7004, RW7004V
SKU2	RW7005, RW7005V
SKU3	RW7005, RW7005V

Remark:

1. SKU1 is different from the other SKUs in the design of the frames, lenses, and sizes.
2. The only difference between SKU2 and SKU3 is the size: SKU2 is Medium and SKU3 is Large.
3. Except for the above, all SKUs share the same antenna, RF circuitry, and PCB layout.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
Conducted Test Cases	**Bluetooth – LE / GFSK**
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: Bluetooth Link + Charging from Charging case (USB Cable with Adapter) + SKU1
Remark: 1. For Radiated Test Cases, the detailed test modes are shown in Appendix C. 2. For Radiation Spurious Emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	ideapad Gaming	PD9AX201NG	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m
2.	Mobile Phone	SAMSUNG	SM-A730F/DS	A3LSMA730F	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BlueTest3” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW ≥ 3 * RBW. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
   For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) ≥ 3 * RBW.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as "-".
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as "-".
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW = 100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW = 3 MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Unique (non-standard) antenna connector.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Jul. 14, 2026~ Aug. 15, 2026	Dec. 10, 2026	Radiation (03CH23-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D-06	62028 & 003	30MHz~1GHz	Nov. 26, 2025	Jul. 14, 2026~ Aug. 15, 2026	Nov. 25, 2026	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 18, 2025	Jul. 14, 2026~ Aug. 15, 2026	Dec. 17, 2026	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	1GHz~18GHz	Sep. 26, 2025	Jul. 14, 2026~ Aug. 15, 2026	Sep. 25, 2026	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	KV2D06A18ES	1GHz~18GHz	Nov. 05, 2025	Jul. 14, 2026~ Aug. 15, 2026	Nov. 04, 2026	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	10Hz~44GHz	Aug. 26, 2025	Jul. 14, 2026~ Aug. 15, 2026	Aug. 25, 2026	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Aug. 26, 2025	Jul. 14, 2026~ Aug. 15, 2026	Aug. 25, 2026	Radiation (03CH23-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	00993	18GHz~40GHz	Nov. 28, 2025	Jul. 14, 2026~ Aug. 15, 2026	Nov. 27, 2026	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303A	TP210001	N/A	Nov. 06, 2025	Jul. 14, 2026~ Aug. 15, 2026	Nov. 05, 2026	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 14, 2026~ Aug. 15, 2026	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 14, 2026~ Aug. 15, 2026	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 14, 2026~ Aug. 15, 2026	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019122	RK-002348	N/A	N/A	Jul. 14, 2026~ Aug. 15, 2026	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	805139/2	9kHz~30MHz	Mar. 04, 2026	Jul. 14, 2026~ Aug. 15, 2026	Mar. 03, 2027	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	30MHz~40GHz	Nov. 25, 2025	Jul. 14, 2026~ Aug. 15, 2026	Nov. 24, 2026	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/231119/25104238	30MHz~40GHz	May. 11, 2026	Jul. 14, 2026~ Aug. 15, 2026	May. 10, 2027	Radiation (03CH23-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 06, 2026~ Jul. 30, 2026	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 16, 2025	Jul. 06, 2026~ Jul. 30, 2026	Dec. 15, 2026	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 15, 2026	Jul. 06, 2026~ Jul. 30, 2026	Jun. 14, 2027	Conduction (CO05-HY)
Two-Line V-Network	Rohde & Schwarz	ENV 216 +EMCI-EXP-US-US S	100080+N-021	N/A	Apr. 22, 2026	Jul. 06, 2026~ Jul. 30, 2026	Apr. 21, 2027	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jul. 06, 2026~ Jul. 30, 2026	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 29, 2025	Jul. 06, 2026~ Jul. 30, 2026	Jul. 28, 2026	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00373	N/A	Oct. 20, 2025	Jul. 06, 2026~ Jul. 30, 2026	Oct. 19, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 14, 2025	Jul. 06, 2026~ Jul. 30, 2026	Oct. 13, 2026	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Jul. 08. 2026~ Jul. 31. 2026	Nov. 03, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Jul. 08. 2026~ Jul. 31. 2026	Aug. 28, 2026	Conducted (TH05-HY)
USB RF Power Sensor	DARE	RPR3006W	17I00015SNO37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Jul. 08. 2026~ Jul. 31. 2026	Nov. 13, 2026	Conducted (TH05-HY)
Switch Control Mainframe	EM Electronics	EMSW18SE	SW191204 (BOX8)	N/A	Dec. 29, 2025	Jul. 08. 2026~ Jul. 31. 2026	Dec. 28, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Jul. 08. 2026~ Jul. 31. 2026	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.7 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.7 dB

A1. Conducted Test Results

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2026/7/8~2026/7/31	Relative Humidity:	51~54	%

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2026/7/8~2026/7/31	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.025	0.664	0.50	Pass
BLE	1Mbps	1	19	2440	1.027	0.670	0.50	Pass
BLE	1Mbps	1	39	2480	1.027	0.669	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	9.11	30.00	4.00	13.11	36.00	Pass
BLE	1Mbps	1	19	2440	8.78	30.00	4.00	12.78	36.00	Pass
BLE	1Mbps	1	39	2480	8.86	30.00	4.00	12.86	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	9.20	-5.76	4.00	8.00	Pass
BLE	1Mbps	1	19	2440	8.85	-6.14	4.00	8.00	Pass
BLE	1Mbps	1	39	2480	8.85	-5.99	4.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2026/7/8~2026/7/31	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.034	1.316	0.50	Pass
BLE	2Mbps	1	19	2440	2.035	1.134	0.50	Pass
BLE	2Mbps	1	39	2480	2.029	1.132	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	9.09	30.00	4.00	13.09	36.00	Pass
BLE	2Mbps	1	19	2440	8.77	30.00	4.00	12.77	36.00	Pass
BLE	2Mbps	1	39	2480	8.81	30.00	4.00	12.81	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	9.07	-7.58	4.00	8.00	Pass
BLE	2Mbps	1	19	2440	8.78	-7.94	4.00	8.00	Pass
BLE	2Mbps	1	39	2480	8.78	-8.09	4.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

6dB Bandwidth

<1Mbps>

6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19



6 dB Bandwidth Plot on Channel 39



<2Mbps>

6 dB Bandwidth Plot on Channel 00	6 dB Bandwidth Plot on Channel 19
	
6 dB Bandwidth Plot on Channel 39	
	

99% Occupied Bandwidth

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19



99% Occupied Bandwidth Plot on Channel 39



<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19



99% Occupied Bandwidth Plot on Channel 39



Power Spectral Density (dBm/3kHz)

<1Mbps>

Power Density (dBm/3kHz) Plot Channel 00	Power Density (dBm/3kHz) Plot Channel 19
	
Power Density (dBm/3kHz) Plot Channel 39	
	

<2Mbps>

Power Density (dBm/3kHz) Plot Channel 00	Power Density (dBm/3kHz) Plot Channel 19
	
Power Density (dBm/3kHz) Plot Channel 39	
	

Band Edge and Conducted Spurious Emission

<1Mbps>

Channel 00	
100kHz PSD reference Level Plot	**Plot on Channel 00**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 19

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 39

100kHz PSD reference Level Plot



Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



<2Mbps>

Channel 00	
100kHz PSD reference Level Plot	**Plot on Channel 00**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 19

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 39

100kHz PSD reference Level Plot



Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	**Temperature :**	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO :	652603
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	37.43	55.63	18.20	L1	OFF	19.9
0.156750	54.52	---	65.63	11.11	L1	OFF	19.9
0.168000	---	28.76	55.06	26.30	L1	OFF	19.9
0.168000	47.91	---	65.06	17.15	L1	OFF	19.9
0.177000	---	31.67	54.63	22.96	L1	OFF	19.9
0.177000	51.12	---	64.63	13.51	L1	OFF	19.9
0.188250	---	34.26	54.11	19.85	L1	OFF	19.9
0.188250	51.27	---	64.11	12.84	L1	OFF	19.9
0.204000	---	28.94	53.45	24.51	L1	OFF	19.9
0.204000	47.78	---	63.45	15.67	L1	OFF	19.9
0.222000	---	30.61	52.74	22.13	L1	OFF	19.9
0.222000	47.60	---	62.74	15.14	L1	OFF	19.9
0.235500	---	27.08	52.25	25.17	L1	OFF	19.9
0.235500	45.77	---	62.25	16.48	L1	OFF	19.9
0.249000	---	28.36	51.79	23.43	L1	OFF	19.9
0.249000	44.97	---	61.79	16.82	L1	OFF	19.9
0.269250	---	23.24	51.14	27.90	L1	OFF	19.9
0.269250	40.09	---	61.14	21.05	L1	OFF	19.9
0.285000	---	26.42	50.67	24.25	L1	OFF	19.9
0.285000	42.65	---	60.67	18.02	L1	OFF	19.9
0.404250	---	25.90	47.77	21.87	L1	OFF	19.9

0.404250	37.72	---	57.77	20.05	L1	OFF	19.9
0.438000	---	27.03	47.10	20.07	L1	OFF	19.9
0.438000	36.79	---	57.10	20.31	L1	OFF	19.9
0.467250	---	25.68	46.56	20.88	L1	OFF	19.9
0.467250	38.70	---	56.56	17.86	L1	OFF	19.9
0.505500	---	34.03	46.00	11.97	L1	OFF	19.9
0.505500	43.65	---	56.00	12.35	L1	OFF	19.9
0.525750	---	24.35	46.00	21.65	L1	OFF	19.9
0.525750	36.14	---	56.00	19.86	L1	OFF	19.9
0.561750	---	27.01	46.00	18.99	L1	OFF	19.9
0.561750	37.76	---	56.00	18.24	L1	OFF	19.9
16.532250	---	20.49	50.00	29.51	L1	OFF	20.8
16.532250	29.69	---	60.00	30.31	L1	OFF	20.8

EUT Information

Report NO :	652603
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	39.67	55.63	15.96	N	OFF	19.9
0.156750	56.77	---	65.63	8.86	N	OFF	19.9
0.174750	---	32.50	54.73	22.23	N	OFF	19.9
0.174750	52.38	---	64.73	12.35	N	OFF	19.9
0.188250	---	36.29	54.11	17.82	N	OFF	19.9
0.188250	53.39	---	64.11	10.72	N	OFF	19.9
0.206250	---	30.50	53.36	22.86	N	OFF	19.9
0.206250	49.65	---	63.36	13.71	N	OFF	19.9
0.219750	---	33.11	52.83	19.72	N	OFF	19.9
0.219750	50.18	---	62.83	12.65	N	OFF	19.9
0.235500	---	28.24	52.25	24.01	N	OFF	19.9
0.235500	47.08	---	62.25	15.17	N	OFF	19.9
0.251250	---	30.38	51.72	21.34	N	OFF	19.9
0.251250	47.55	---	61.72	14.17	N	OFF	19.9
0.267000	---	25.38	51.21	25.83	N	OFF	19.9
0.267000	43.33	---	61.21	17.88	N	OFF	19.9
0.285000	---	27.32	50.67	23.35	N	OFF	19.9
0.285000	43.93	---	60.67	16.74	N	OFF	19.9
0.375000	---	24.60	48.39	23.79	N	OFF	19.9
0.375000	38.54	---	58.39	19.85	N	OFF	19.9
0.471750	---	25.92	46.48	20.56	N	OFF	19.9

0.471750	39.07	---	56.48	17.41	N	OFF	19.9
0.503250	---	31.11	46.00	14.89	N	OFF	19.9
0.503250	41.16	---	56.00	14.84	N	OFF	19.9
0.528000	---	24.27	46.00	21.73	N	OFF	19.9
0.528000	38.02	---	56.00	17.98	N	OFF	19.9
12.502500	---	23.62	50.00	26.38	N	OFF	20.7
12.502500	30.37	---	60.00	29.63	N	OFF	20.7

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Leo Li , Karl Hou,CHUN HAO LU	**Temperature :**	19~23°C
		Relative Humidity :	60~64.5%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1.Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	Main	Bluetooth-LE_GFSK	00	2402	1Mbps	-	SKU1
Mode 2	2400-2483.5	Main	Bluetooth-LE_GFSK	19	2440	1Mbps	-	SKU1
Mode 3	2400-2483.5	Main	Bluetooth-LE_GFSK	39	2480	1Mbps	-	SKU1
Mode 4	2400-2483.5	Main	Bluetooth-LE_GFSK	00	2402	2Mbps	-	SKU1
Mode 5	2400-2483.5	Main	Bluetooth-LE_GFSK	19	2440	2Mbps	-	SKU1
Mode 6	2400-2483.5	Main	Bluetooth-LE_GFSK	39	2480	2Mbps	-	SKU1
Mode 7	2400-2483.5	Main	Bluetooth-LE_GFSK	19	2440	1Mbps	-	SKU1 LF
Mode 8	2400-2483.5	Main	Bluetooth-LE_GFSK	19	2440	1Mbps	-	SKU1 SHF
Mode 9	2400-2483.5	Main	Bluetooth-LE_GFSK	39	2480	2Mbps	-	SKU2
Mode 10	2400-2483.5	Main	Bluetooth-LE_GFSK	39	2480	2Mbps	-	SKU3
Mode 11	2400-2483.5	Main	Bluetooth-LE_GFSK	19	2440	1Mbps	-	SKU1*
Mode 12	2400-2483.5	Main	Bluetooth-LE_GFSK	39	2480	2Mbps	-	SKU1*

Remark*: The evaluation was performed for SKU 1 together with its charging case.

C2.Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE_GFSK	00	4804.00	46.61	74.00	-27.39	V	Peak	Pass	-	Harmonic
2	Bluetooth-LE_GFSK	19	7320.00	39.82	54.00	-14.18	V	Avg.	Pass	-	Harmonic
3	Bluetooth-LE_GFSK	39	7440.00	38.88	54.00	-15.12	V	Avg.	Pass	-	Harmonic
4	Bluetooth-LE_GFSK	00	2336.50	42.31	54.00	-11.69	V	Avg.	Pass	-	Band Edge
5	Bluetooth-LE_GFSK	19	2349.26	42.21	54.00	-11.79	H	Avg.	Pass	-	Band Edge
6	Bluetooth-LE_GFSK	39	2483.52	50.74	54.00	-3.26	H	Avg.	Pass	-	Band Edge
7	Bluetooth-LE_GFSK	19	159.01	35.54	43.50	-7.96	H	Peak	Pass	-	LF
8	Bluetooth-LE_GFSK	19	21255.00	41.42	74.00	-32.58	V	Peak	Pass	-	SHF
9	Bluetooth-LE_GFSK	39	2483.52	46.41	54.00	-7.59	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	39	7440.00	41.36	54.00	-12.64	V	Avg.	Pass	-	Harmonic
10	Bluetooth-LE_GFSK	39	2483.52	50.42	54.00	-3.58	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	39	7440.00	40.12	54.00	-13.88	V	Avg.	Pass	-	Harmonic
11	Bluetooth-LE_GFSK	19	7320.00	39.68	54.00	-14.32	H	Avg.	Pass	-	Harmonic
12	Bluetooth-LE_GFSK	39	2483.52	48.41	54.00	-5.59	H	Avg.	Pass	-	Band Edge

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH00_2402MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 45.80 74.00 -28.20 33.68 32.21 10.53 32.33 1.71 -- -- Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 46.61 74.00 -27.39 34.49 32.21 10.53 32.33 1.71 -- -- Peak

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH00_2402MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 4880.00 47.08 74.00 -26.92 34.59 32.42 10.65 32.29 1.71 -- -- Peak 2 7320.00 50.25 74.00 -23.75 33.89 37.00 13.11 35.68 1.93 -- -- Peak 3 7320.00 39.69 54.00 -14.31 23.33 37.00 13.11 35.68 1.93 -- -- Average	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 4880.00 46.91 74.00 -27.09 34.42 32.42 10.65 32.29 1.71 -- -- Peak 2 7320.00 50.38 74.00 -23.62 34.02 37.00 13.11 35.68 1.93 -- -- Peak 3 7320.00 39.82 54.00 -14.18 23.46 37.00 13.11 35.68 1.93 -- -- Average

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 47.53 74.00 -26.47 34.56 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 49.63 74.00 -24.37 33.22 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 38.76 54.00 -15.24 22.35 37.02 13.23 35.78 1.94 -- -- Average	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 47.52 74.00 -26.48 34.55 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 50.00 74.00 -24.00 33.59 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 38.88 54.00 -15.12 22.47 37.02 13.23 35.78 1.94 -- -- Average

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH00_2402MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2386.45 51.83 74.00 -22.17 39.02 26.90 7.47 31.84 10.28 195 228 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 105.54 ------ ------ 92.81 26.80 7.49 31.84 10.28 195 228 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2354.44 42.21 54.00 -11.79 29.27 27.06 7.42 31.82 10.28 195 228 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 104.27 ------ ------ 91.54 26.80 7.49 31.84 10.28 195 228 Average

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH00_2402MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 2317.54 51.01 74.00 -22.99 38.14 27.02 7.37 31.80 10.28 136 349 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 2402.00 102.25 ------ ------ 89.52 26.80 7.49 31.84 10.28 136 349 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 2336.50 42.31 54.00 -11.69 29.35 27.10 7.39 31.81 10.28 136 349 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 2402.00 100.97 ------ ------ 88.24 26.80 7.49 31.84 10.28 136 349 Average

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2365.51 50.98 74.00 -23.02 38.15 26.94 7.44 31.83 10.28 228 227 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 105.12 ------ ------ 92.55 26.60 7.55 31.86 10.28 228 227 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2349.26 42.21 54.00 -11.79 29.24 27.10 7.41 31.82 10.28 228 227 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 103.81 ------ ------ 91.24 26.60 7.55 31.86 10.28 228 227 Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2485.72 51.33 74.00 -22.67 38.59 26.70 7.63 31.88 10.29 228 227 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.88 41.94 54.00 -12.06 29.20 26.70 7.63 31.88 10.29 228 227 Average	Blank

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 2332.75 51.17 74.00 -22.83 38.21 27.10 7.39 31.81 10.28 115 334 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 2440.00 102.59 ------ ------ 90.02 26.60 7.55 31.86 10.28 115 334 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto 1 2370.19 42.02 54.00 -11.98 29.22 26.90 7.45 31.83 10.28 115 334 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto 1 2440.00 101.31 ------ ------ 88.74 26.60 7.55 31.86 10.28 115 334 Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2498.26 50.77 74.00 -23.23 37.94 26.78 7.65 31.89 10.29 115 334 Peak	Blank
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2491.84 42.06 54.00 -11.94 29.30 26.72 7.64 31.89 10.29 115 334 Average	Blank

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.86 57.25 74.00 -16.75 44.52 26.70 7.62 31.88 10.29 211 220 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 104.63 ------ ------ 91.90 26.70 7.62 31.88 10.29 211 220 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 50.74 54.00 -3.26 38.01 26.70 7.62 31.88 10.29 211 220 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 103.34 ------ ------ 90.61 26.70 7.62 31.88 10.29 211 220 Average

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK_2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 55.98 74.00 -18.02 43.25 26.70 7.62 31.88 10.29 121 334 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 102.31 ------ ------ 89.58 26.70 7.62 31.88 10.29 121 334 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 48.88 54.00 -5.12 36.15 26.70 7.62 31.88 10.29 121 334 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 101.02 ------ ------ 88.29 26.70 7.62 31.88 10.29 121 334 Average

Mode	7	
	LF	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
QP/ Peak		

Site : 03CH23-HY
Condition: QP 3m CBL6111D_62028 & 003_251126 HORIZONTAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	85.29	28.73	40.00	-11.27	45.07	14.51	1.45	32.39	0.09	--	--	Peak
2	159.01	35.54	43.50	-7.96	48.82	16.88	1.98	32.37	0.23	--	--	Peak
3	238.55	32.41	46.00	-13.59	45.12	17.16	2.39	32.36	0.10	--	--	Peak
4	344.28	37.51	46.00	-8.49	46.37	20.21	2.95	32.27	0.25	--	--	Peak
5	745.86	37.71	46.00	-8.29	37.42	28.06	4.29	32.26	0.20	--	--	Peak
6	800.18	37.99	46.00	-8.01	37.30	28.07	4.44	32.04	0.22	--	--	Peak

Site : 03CH23-HY
Condition: QP 3m CBL6111D_62028 & 003_251126 VERTICAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	87.23	27.43	40.00	-12.57	43.45	14.81	1.47	32.39	0.09	--	--	Peak
2	159.01	34.17	43.50	-9.33	47.45	16.88	1.98	32.37	0.23	--	--	Peak
3	246.31	27.68	46.00	-18.32	39.44	18.08	2.43	32.37	0.10	--	--	Peak
4	480.08	30.79	46.00	-15.21	35.92	23.65	3.43	32.31	0.10	--	--	Peak
5	745.86	35.84	46.00	-10.16	35.55	28.06	4.29	32.26	0.20	--	--	Peak
6	913.67	34.08	46.00	-11.92	31.10	29.35	4.80	31.36	0.19	--	--	Peak

Mode	8	
	SHF	
	2400-2483.5_Bluetooth-LE_GFSK_1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak	 Site : Condition: PEAK_74 1m BBHA9170_1230_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 20289.00 40.89 74.00 -33.11 54.07 38.00 22.20 63.84 -9.54 -- -- Peak	 Site : Condition: PEAK_74 1m BBHA9170_1230_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 21255.00 41.42 74.00 -32.58 53.57 38.01 22.73 63.35 -9.54 -- -- Peak

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 54.26 74.00 -19.74 41.53 26.70 7.62 31.88 10.29 128 134 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.42 ------ ------ 87.69 26.70 7.62 31.88 10.29 128 134 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 46.41 54.00 -7.59 33.68 26.70 7.62 31.88 10.29 128 134 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 99.12 ------ ------ 86.39 26.70 7.62 31.88 10.29 128 134 Average

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 53.53 74.00 -20.47 40.80 26.70 7.62 31.88 10.29 398 194 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 99.60 ------ ------ 86.87 26.70 7.62 31.88 10.29 398 194 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 45.50 54.00 -8.50 32.77 26.70 7.62 31.88 10.29 398 194 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 98.31 ------ ------ 85.58 26.70 7.62 31.88 10.29 398 194 Average

Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 46.80 74.00 -27.20 33.83 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 49.74 74.00 -24.26 33.33 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 39.18 54.00 -14.82 22.77 37.02 13.23 35.78 1.94 -- -- Average	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 47.48 74.00 -26.52 34.51 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 51.92 74.00 -22.08 35.51 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 41.36 54.00 -12.64 24.95 37.02 13.23 35.78 1.94 -- -- Average

Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	10	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.62 57.10 74.00 -16.90 44.37 26.70 7.62 31.88 10.29 100 140 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 105.05 ------ ------ 92.32 26.70 7.62 31.88 10.29 100 140 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 50.42 54.00 -3.58 37.69 26.70 7.62 31.88 10.29 100 140 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 103.74 ------ ------ 91.01 26.70 7.62 31.88 10.29 100 140 Average

Mode	10	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.62 56.91 74.00 -17.09 44.18 26.70 7.62 31.88 10.29 394 195 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 104.67 ------ ------ 91.94 26.70 7.62 31.88 10.29 394 195 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 49.98 54.00 -4.02 37.25 26.70 7.62 31.88 10.29 394 195 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 103.29 ------ ------ 90.56 26.70 7.62 31.88 10.29 394 195 Average

Mode	10	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 46.56 74.00 -27.44 33.59 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 49.47 74.00 -24.53 33.06 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 39.97 54.00 -14.03 23.56 37.02 13.23 35.78 1.94 -- -- Average	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 47.98 74.00 -26.02 35.01 32.72 10.78 32.24 1.71 -- -- Peak 2 7440.00 50.57 74.00 -23.43 34.16 37.02 13.23 35.78 1.94 -- -- Peak 3 7440.00 40.12 54.00 -13.88 23.71 37.02 13.23 35.78 1.94 -- -- Average

Mode	10	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	11	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 4880.00 46.32 74.00 -27.68 34.12 32.42 10.64 32.29 1.43 -- -- Peak 2 7320.00 48.60 74.00 -25.40 32.61 37.00 13.27 35.68 1.40 -- -- Peak 3 7320.00 39.68 54.00 -14.32 23.69 37.00 13.27 35.68 1.40 -- -- Average	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 4880.00 46.39 74.00 -27.61 34.19 32.42 10.64 32.29 1.43 -- -- Peak 2 7320.00 48.93 74.00 -25.07 32.94 37.00 13.27 35.68 1.40 -- -- Peak 3 7320.00 39.50 54.00 -14.50 23.51 37.00 13.27 35.68 1.40 -- -- Average

Mode	11	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK _1Mbps_CH19_2440MHz	
ANT	Main	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	12	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.64 56.06 74.00 -17.94 43.30 26.70 7.65 31.88 10.29 102 60 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 101.98 ------ ------ 89.22 26.70 7.65 31.88 10.29 102 60 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 48.41 54.00 -5.59 35.65 26.70 7.65 31.88 10.29 102 60 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 HORIZONTAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.73 ------ ------ 87.97 26.70 7.65 31.88 10.29 102 60 Average

Mode	12	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GFSK _2Mbps_CH39_2480MHz	
ANT	Main	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.58 54.39 74.00 -19.61 41.63 26.70 7.65 31.88 10.29 400 73 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.22 ------ ------ 87.46 26.70 7.65 31.88 10.29 400 73 Peak
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 47.12 54.00 -6.88 34.36 26.70 7.65 31.88 10.29 400 73 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_KV2D06A18ES_251105 VERTICAL : RBW:1000.000kHz VBW:4.700kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 98.89 ------ ------ 86.13 26.70 7.65 31.88 10.29 400 73 Average

Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	32.37	404	2.48	2.7kHz
Bluetooth - LE for 2Mbps	17.63	220	4.55	4.7kHz

Bluetooth - LE for 1Mbps



Bluetooth - LE for 2Mbps