

RF Shenzhen Shuanghuaxin Technology Co., Ltd.

Antenna Certification Certificate Antenna specification for approval

Customer name	Cemho Medical Technology (Guangdong) Co., Ltd.		
Model	CZ-B801		
Antenna band	BT2.4G		
Antenna type	FPC		
Antenna material	electrolytic copper		
FPC color	black		
Material number	SHX-B801-V1		
Manufacturer address	Room D206, Huasheng Technology Building No. 36 Aviation Road, Hangcheng Street, Bao'an District, Shenzhen City		
Manufacturer Confirmation Signature Baren accepted the signature		Customer Confirmation Signature Client acknowledges signature	
structure		purchase	
Quality Control QC		structure	
radio frequency		engineering	
examine and verify To examine		Quality Control QC	
date	Seal Area	date	Seal Area

catalogue

1. Supported Equipment & Testable Antenna Types	1
II: Overview	2
3: Match the circuit diagram, machine image, and antenna image.....	3
4: Antenna Standing Wave Ratio & Antenna Efficiency (VSWR)	4
5: Structural Drawings	6

RF Shenzhen Shuanghuaxin Technology Co., Ltd.

1. Supported Equipment & Testable Antenna Types

Antenna Type	Frequency Range	Test Instruments	Test Methods	Test Standards
2G Antenna (GSM)	824MHz~960MHz, 1710MHz~1990MHz	5071B, 8960, OTA Chamber	Active Test, Passive Test	Soward Standard, Customer Requirements
3G Antenna (WCDMA/TD-SCDMA/CDMA-EVDO/2000)	824MHz~960MHz, 1710MHz~2170MHz	5071B, 8960, OTA Chamber	Active Test, Passive Test	Soward Standard, Customer Requirements
4G Antenna (LTE-FDD/LTE-TDD)	2.4GHz~2.48GHz, 5.15GHz~5.35GHz, 5.725GHz~5.825GHz	5071B, CMW500, SP8011, OTA Chamber	Active Test, Passive Test	Soward Standard, Customer Requirements
WiFi Antenna	2.4GHz~2.48GHz, 5.15GHz~5.35GHz, 5.725GHz~5.825GHz	5071B, CMW500, OTA Chamber, Router, PC	Active Test, Passive Test, APK Field Test, Throughput Test	Soward Standard, Customer Requirements
BT Antenna	2.4GHz~2.48GHz	5071B, OTA Chamber	Passive Test, Field Test (with Bluetooth speaker)	Soward Standard, Customer Requirements
GNSS Antenna (GPS, GLONASS, BeiDou, Galileo)	GPS: 1575.42MHz±10MHz; GLONASS: 1602MHz+0.5625MHz; BeiDou: 1561MHz+2.046MHz	5071B, OTA Chamber, APK	Passive Test, Field Test	Soward Standard, Customer Requirements
NFC Antenna	13.56MHz	5071B, Dedicated Test Fixture, OTA Chamber, APK	Passive Test, Field Test	Soward Standard, Customer Requirements
Remote Control Antenna	433MHz	5071B, OTA Chamber	Passive Test, Field Test	Soward Standard, Customer Requirements

RF Shenzhen Shuanghuaxin Technology Co., Ltd.

II: Overview

(1)Antenna performance

1.This approval sheet supports for MID project. FPC antennas include in this project. This report is for the performance of BT antenna.

2.Antenna shape size: Meet the requirement of MID

3.Antenna band: 2400MHz~2500MHz

4.Antenna material: Antenna material meet the requirement of MID

5.Adhesive performance: Adhesive performance meet the requirement of MID

6.Antenna performance meet the spec be low:


Description	BT2.4	Units
VSWR	≤ 3.0	
Average Antenna Gain	≥ -1	dB
Antenna Efficiency	≥ 30	%
Feed Impedance	50 ohms	
Operating Temperature	-40 to +85 deg C	
Polar ization / Azimuth	Linear / Omni-directional	

(2)Mechanical Information


Mechanical Dimension	
Cab le Length	NA
Description	BT2.4
Mater ial	FPC
Coaxial Cab le	NA
Environmental	
Operation Temperature	-40 to +85 deg C
Storage Temperature	-40 to +85 deg C

Three: Match the circuit diagram, machine image, and antenna 3D image

(1) Matching Circuit




(2) Machine image & Antenna 2D image



RF Shenzhen Shuanghuaxin Technology Co., Ltd.


Three: Match the circuit diagram, machine image, and antenna 3D image



1: Gold-finished surface; 3: Black matte ink coating; 4: Complies with latest environmental standards (RoHS & REACH);

RF Shenzhen Shuanghuaxin Technology Co., Ltd.

IV: BT 2.40G–2.48G (VSWR)



Frequency (MHz)	VSWR
2400	1.7
2440	1.3
2480	1.4

Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)
2400	30	-5.23	-1.23	-3.38
2410	31.81	-4.97	-0.96	-3.11
2420	28.81	-5.4	-1.27	-3.42
2430	36.76	-4.35	-0.16	-2.31
2440	32.05	-4.94	-0.72	-2.87
2450	38.96	-4.09	0.16	-1.99
2460	38.35	-4.16	0.14	-2.01
2470	34.05	-4.68	-0.25	-2.4
2480	44.24	-3.54	1.07	-1.08
2490	35.85	-4.46	0.25	-1.9
2500	37.39	-4.27	0.48	-1.67

5: Structural Drawings Unit: mm

