

RF EXPOSURE EVALUATION

According to FCC 1.1310 and KDB 447498 D01 V06, The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

Antenna gain:2.94dBi;

R=20cm

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	DH5	-1.82	-2±1	-1	0.794	2.94	1.97	0.0003	1
2441		-0.88	-1±1	0	1.000	2.94	1.97	0.0004	1
2480		-0.94	-1±1	0	1.000	2.94	1.97	0.0004	1
2402	2DH5	-2.56	-3±1	-2	0.631	2.94	1.97	0.0002	1
2441		-2.06	-2±1	-1	0.794	2.94	1.97	0.0003	1
2480		-1.7	-2±1	-1	0.794	2.94	1.97	0.0003	1
2402	3DH5	-2.54	-3±1	-2	0.631	2.94	1.97	0.0002	1
2441		-2.09	-2±1	-1	0.794	2.94	1.97	0.0003	1
2480		-1.71	-2±1	-1	0.794	2.94	1.97	0.0003	1

BLE:

Operation Frequency: 2402-2480MHz,

Power density limited: 1mW/ cm²

Power density limited: 1mW/cm

Antenna Type: PCB Antenna

Antenna : 2.94dBi

R=20cm

mW=10^(dBm/10)

Mode	Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
			(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
					(dBm)	(mW)	(dBi)	Numeric		
BLE1M	2402	GFSK	-2	-2±1	-1	0.794	2.94	1.97	0.0003	1
	2440		-1.14	-1±1	0	1.000	2.94	1.97	0.0004	1
	2480		-1.2	-1±1	0	1.000	2.94	1.97	0.0004	1
BLE 2M	2402	GFSK	-2.04	-2±1	-1	0.794	2.94	1.97	0.0003	1
	2440		-1.22	-1±1	0	1.000	2.94	1.97	0.0004	1
	2480		-1.39	-1±1	0	1.000	2.94	1.97	0.0004	1

Conclusion:

For the max result : 0.0004≤ 1.0, SAR is not required.

Signature:

Date: 2026-04-22

Alex Li

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China