Appendix B

RF Test Data for 5.2G WLAN (Conducted Measurement)

Product Name: projector

Trade Mark: N/A

Test Model: 530

Environmental Conditions

Temperature:	22.5 ° C
Relative Humidity:	53.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Diamond Lu
Supervised by:	Li Huan

B.1 Duty Cycle

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5200	100	0.00	0.01
11N20 SISO	5200	100	0.00	0.01
11N40 SISO	5190	100	0.00	0.01

On Time and Duty Cycle



IEEE 802.11a



IEEE 802.11n HT20


Agilent Spectrum Analyzer - Swept SA
Center Freq 5.190000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: RMS
04:23:19 PM Mar 30, 2021
10 dB/div Ref 20.00 dBm
Log
10.0
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
Center 5.190000000 GHz
Span 0 Hz
Res BW 8 MHz
#VBW 50 MHz*
Sweep 10.13 ms (8001 pts)
Frequency
Auto Tune
Center Freq
5.190000000 GHz
Start Freq
5.190000000 GHz
Stop Freq
5.190000000 GHz
CF Step
8.000000 MHz
Auto
Man
Freq Offset
0 Hz

B.2 Maximum Conduct Output Power

Test Mode	Channel	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	36	5180	10.42	0	10.42	24	Pass
	40	5200	9.91	0	9.91		Pass
	48	5240	9.96	0	9.96		Pass
11N20 SISO	36	5180	11.04	0	11.04	24	Pass
	40	5200	11.19	0	11.19		Pass
	48	5240	10.75	0	10.75		Pass
11N40 SISO	38	5190	10.34	0	10.34	24	Pass
	46	5230	9.66	0	9.66		Pass

B.3 Power Spectral Density

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor(dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	36	5180	-0.56	0	-0.56	11	Pass
	40	5200	-1.08	0	-1.08		Pass
	48	5240	-0.97	0	-0.97		Pass
11N20 SISO	36	5180	0.23	0	0.23	11	Pass
	40	5200	0.26	0	0.26		Pass
	48	5240	-0.51	0	-0.51		Pass
11N40 SISO	38	5190	-3.57	0	-3.57	11	Pass
	46	5230	-4.48	0	-4.48		Pass

Power Spectral Density



IEEE 802.11a / Channel 36 / 5180MHz



IEEE 802.11na / Channel 40 / 5200MHz



IEEE 802.11na / Channel 48 / 5240MHz

Power Spectral Density



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

Power Spectral Density



IEEE 802.11n40 / Channel 38 / 5190MHz



B.4 Emission Bandwidth

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	36	5180	19.72	No Limit	Pass
	40	5200	19.77		Pass
	48	5240	19.68		Pass
11N20 SISO	36	5180	19.93	No Limit	Pass
	40	5200	19.93		Pass
	48	5240	19.87		Pass
11N40 SISO	38	5190	40.07	No Limit	Pass
	46	5230	39.63		Pass

26dB Bandwidth



IEEE 802.11a / Channel 36 / 5180MHz



IEEE 802.11a / Channel 40 / 5200MHz



IEEE 802.11a / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n40 / Channel 38 / 5190MHz



B.5 Undesirable Emissions Measurement

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	36	4500.0	-50.55	2.00	0	46.68	Peak	68.20	Pass
		4500.0	-59.67	2.00	0	37.56	Average	54.00	Pass
		5150.0	-46.55	2.00	0	50.68	Peak	68.20	Pass
		5150.0	-55.65	2.00	0	41.58	Average	54.00	Pass
	48	5350.0	-48.58	2.00	0	48.65	Peak	68.20	Pass
		5350.0	-58.90	2.00	0	38.33	Average	54.00	Pass
		5460.0	-48.98	2.00	0	48.25	Peak	68.20	Pass
		5460.0	-59.42	2.00	0	37.81	Average	54.00	Pass
11N20 SISO	36	4500.0	-49.85	2.00	0	47.38	Peak	68.20	Pass
		4500.0	-59.72	2.00	0	37.51	Average	54.00	Pass
		5150.0	-46.10	2.00	0	51.13	Peak	68.20	Pass
		5150.0	-55.53	2.00	0	41.70	Average	54.00	Pass
	48	5350.0	-48.42	2.00	0	48.81	Peak	68.20	Pass
		5350.0	-58.90	2.00	0	38.33	Average	54.00	Pass
		5460.0	-49.20	2.00	0	48.03	Peak	68.20	Pass
		5460.0	-59.36	2.00	0	37.87	Average	54.00	Pass
11N40 SISO	38	4500.0	-50.46	2.00	0	46.77	Peak	68.20	Pass
		4500.0	-59.71	2.00	0	37.52	Average	54.00	Pass
		5150.0	-43.25	2.00	0	53.98	Peak	68.20	Pass
		5150.0	-54.66	2.00	0	42.57	Average	54.00	Pass
	46	5350.0	-47.91	2.00	0	49.32	Peak	68.20	Pass
		5350.0	-58.73	2.00	0	38.50	Average	54.00	Pass
		5460.0	-48.28	2.00	0	48.95	Peak	68.20	Pass
		5460.0	-59.08	2.00	0	38.15	Average	54.00	Pass

Undesirable Emissions Measurement



IEEE 802.11a / Channel 36 / 5180MHz / Peak



IEEE 802.11a / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11a / Channel 48 / 5240MHz / Peak



IEEE 802.11a / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 36 / 5180MHz / Peak



IEEE 802.11n20 / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 48 / 5240MHz / Peak



IEEE 802.11n20 / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 38 / 5190MHz / Peak



IEEE 802.11n40 / Channel 38 / 5190MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 46 / 5230MHz / Peak



IEEE 802.11n40 / Channel 46 / 5230MHz / Average