

TEST REPORT

Report No.: 8431EU012801W3

Applicant: Cheerlux (Shenzhen) Electronic Technology Co., Ltd.

Address: Room 201 2nd Floor Building 2 LongBi industrial Area
No.27 DaFa Rd. DaFaPu Community Bantian Street
Longgang District Shenzhen. Guangdong Province,
China

Product Name: Projector

Model No.: H2 (refer to clause 2.4)

Trademark: CHEERLUX, AUREON

FCC ID: 2AYQQ-H2

Test Standard(s): 47 CFR Part 15E

Test Result: Pass

Date of Receipt: May 28, 2026

Test Date: May 29, 2026 - Jul. 02, 2026

Date of Issue: Jul. 20, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Landon Qiu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Jul. 20, 2026	Original	Valid



Table of Contents

1	COVER PAGE	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION	5
2.2	MANUFACTURER INFORMATION	5
2.3	FACTORY INFORMATION	5
2.4	GENERAL DESCRIPTION OF E.U.T.	5
2.5	TECHNICAL INFORMATION OF E.U.T.	6
3	TEST SUMMARY	7
3.1	TEST STANDARD	7
3.2	TEST VERDICT	7
3.3	TEST LABORATORY	8
4	TEST CONFIGURATION	9
4.1	TEST ENVIRONMENT	9
4.2	TEST EQUIPMENT	9
4.3	DESCRIPTION OF SUPPORT UNIT	11
4.4	TEST MODE	11
4.5	DESCRIPTION OF CALCULATION	12
4.5.1	Field Strength Calculation	12
4.5.2	Disturbance Calculation	12
4.6	MEASUREMENT UNCERTAINTY	13
4.7	DEVIATION FROM STANDARDS	13
4.8	ABNORMALITIES FROM STANDARD CONDITION	13
5	EVALUATION RESULTS (EVALUATION)	14
5.1	ANTENNA REQUIREMENT	14
5.1.1	Test Specification	14
5.1.2	Test Data	14
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	15
6.1	CONDUCTED EMISSION AT AC POWER LINE	15
6.1.1	Test Specification	15
6.1.2	E.U.T. Operation	15
6.1.3	Test Setup Diagram	15
6.1.4	Test Data	15
6.2	DUTY CYCLE	18
6.2.1	Test Specification	18
6.2.2	E.U.T. Operation	18
6.2.3	Test Setup Diagram	18
6.2.4	Test Data	18
6.3	EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	19
6.3.1	Test Specification	19
6.3.2	E.U.T. Operation	20
6.3.3	Test Setup Diagram	20
6.3.4	Test Data	20
6.4	MAXIMUM CONDUCTED OUTPUT POWER	21
6.4.1	Test Specification	21
6.4.2	E.U.T. Operation	21
6.4.3	Test Setup Diagram	22

6.4.4	Test Data.....	22
6.5	POWER SPECTRAL DENSITY	23
6.5.1	Test Specification.....	23
6.5.2	E.U.T. Operation	23
6.5.3	Test Setup Diagram	24
6.5.4	Test Data.....	24
6.6	FREQUENCY STABILITY	25
6.6.1	Test Specification.....	25
6.6.2	E.U.T. Operation	25
6.6.3	Test Setup Diagram	25
6.6.4	Test Data.....	25
6.7	BAND EDGE EMISSIONS (RADIATED)	26
6.7.1	Test Specification.....	26
6.7.2	E.U.T. Operation	28
6.7.3	Test Setup Diagram	28
6.7.4	Test Data.....	28
6.8	UNDESIRABLE EMISSION LIMITS (BELOW 1GHz).....	36
6.8.1	Test Specification.....	36
6.8.2	E.U.T. Operation	37
6.8.3	Test Setup Diagram	38
6.8.4	Test Data.....	38
6.9	UNDESIRABLE EMISSION LIMITS (ABOVE 1GHz)	41
6.9.1	Test Specification.....	41
6.9.2	E.U.T. Operation	43
6.9.3	Test Setup Diagram	43
6.9.4	Test Data.....	43
ANNEX A	TEST SETUP PHOTOS	47
ANNEX B	EXTERNAL PHOTOS	47
ANNEX C	INTERNAL PHOTOS	47
ANNEX D	TEST DATA	48

2 General Information

2.1 Applicant Information

Applicant	Cheerlux (Shenzhen) Electronic Technology Co., Ltd.
Address	Room 201 2 nd Floor Building 2 LongBi industrial Area No.27 DaFa Rd. DaFaPu Community Bantian Street Longgang District Shenzhen. Guangdong Province, China

2.2 Manufacturer Information

Manufacturer	Cheerlux (Shenzhen) Electronic Technology Co., Ltd.
Address	Room 201 2 nd Floor Building 2 LongBi industrial Area No.27 DaFa Rd. DaFaPu Community Bantian Street Longgang District Shenzhen. Guangdong Province, China

2.3 Factory Information

Factory	Cheerlux (Shenzhen) Electronic Technology Co., Ltd.
Address	Room 201 2 nd Floor Building 2 LongBi industrial Area No.27 DaFa Rd. DaFaPu Community Bantian Street Longgang District Shenzhen. Guangdong Province, China

2.4 General Description of E.U.T.

Product Name	Projector
Model No. Under Test	H2
List Model No.	H3, H5, H6, H7, H8, H9, H10, AZ8600
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color and model name. (this information provided by the customer)
Rating(s)	Input: 100-240V~, 50-60Hz
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Test Sample No.	8431EU012801W-1/2(Normal), 8431EU012801W-2/2(Engineering)
Hardware Version	N/A
Software Version	N/A
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BDR+EDR) WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ax(HEW20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40) and 802.11ax(HEW20/40)
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Technology	5G WiFi
Operation Mode	a, n(HT20/40), ac(VHT20/40), ax(HEW20/40)
Operating Frequency	5150MHz to 5250MHz
Modulation Type	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Number of Channels	802.11a/n(HT20)/ac(HT20)/ax(HE20): U-NII Band 1: 4; 802.11n(HT40)/ac(HT40)/ax(HE40): U-NII Band 1: 2;
Antenna Type	FPC Antenna
Antenna Gain(Peak)	3.77 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	/	/
48	5240	/	/

802.11ax RU configuration table						
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242	RU_484
802.11ax(HEW20)	√	--	--	--	--	--
802.11ax(HEW40)	√	--	--	--	--	--

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Antenna requirement	47 CFR Part 15E	---	Part 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2	47 CFR Part 15.207(a)	Pass
Duty Cycle	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.2 (b)	---	Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.9 & 12.5	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use.	Pass
Maximum conducted output power	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.4	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv)	Pass
Power spectral density	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv)	Pass
Frequency stability	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.8	47 CFR Part 15.407(g)	Pass

Band edge emissions (Radiated)	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(10) 15.209, 15.205	Pass
Undesirable emission limits (below 1GHz)	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.5	47 CFR Part 15.407(b)(9) 15.209, 15.205	Pass
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(10) 15.209, 15.205	Pass
Note: (1) "N/A" denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15°C to +35°C
Working Voltage of the EUT	NV (Normal Voltage)	120VAC, 60Hz

4.2 Test Equipment

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Test Software	Farad	EZ-EMC	EE-014	/	/
EMI Test Receiver	Rohde & Schwarz	ESCI	EE-005	2026-04-07	2027-04-06
L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	EE-004	2026-05-10	2027-05-09
8-Wire ISN CAT6	Schwarzbeck	NTFM 8158	EE-219	2026-05-18	2027-05-17

Emission bandwidth and occupied bandwidth					
Maximum conducted output power					
Power spectral density					
Frequency stability					
Band edge emissions (Conducted)					
Duty Cycle					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026-04-11	2027-04-10
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2026-02-13	2027-02-12
Power Meter	Anritsu	ML2495A	EE-416	2026-02-13	2027-02-12
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025-07-29	2026-07-28
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06

Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-030	2026-04-07	2027-04-06

Band edge emissions (Radiated) Undesirable emission limits (above 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8449B	EE-010	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Spectrum Analyzer	ROHDE & SCHWARZ	FSV40-N	EE-029	2026-04-07	2027-04-06
40G Horn Antenna	HCT	HA-018040L	EE-031	2026-04-12	2027-04-11
40G Pre-amplifier	HCT	HC180400-50G25	EE-032	2026-04-07	2027-04-06

Undesirable emission limits (below 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8447D	EE-009	2026-04-08	2027-04-07

MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Band-Stop Filter	COM-MW	ZBSF6-C902-928-2389	EE-023	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	ZBSF6-C855-880-5938	EE-024	2026-04-07	2027-04-06

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Pink Notebook	ADOL	ADOL13F	EMC-PJ-030
2	Disney Speaker	XingRuiFeng	M1	EMC-PJ-048

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11a Mode	Keep the EUT in 802.11a transmitting mode.
TM2	802.11n(HT20) Mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM3	802.11n(HT40) Mode	Keep the EUT in 802.11n(HT40) transmitting mode.
TM4	802.11ac(VHT20) Mode	Keep the EUT in 802.11ac(VHT20) transmitting mode.
TM5	802.11ac(VHT40) Mode	Keep the EUT in 802.11ac(VHT40) transmitting mode.
TM6	802.11ax(HEW20) Mode	Keep the EUT in 802.11ax(HEW20) transmitting mode.
TM7	802.11ax(HEW40) Mode	Keep the EUT in 802.11ax(HEW40) transmitting mode.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{FS (dBuV/m)} = \text{RA (dBuV)} + \text{AF (dB/m)} + \text{CL (dB)} - \text{AG (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{CD (dBuV)} = \text{RA (dBuV)} + \text{PL (dB)} + \text{CL (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Conducted Emission	2.65 dB
Time of Occupancy (Dwell Time)	1.8 %
Occupied Channel Bandwidth	69 kHz
RF output power, conducted	1.07 dB
Power Spectral Density, conducted	0.94 dB
Unwanted Emissions, conducted	2.73 dB
Radiated Emission (1GHz- 18GHz)	Ur = 3.58 dB (Horizontal) Ur = 3.58 dB (Vertical)
Radiated Emission (9kHz- 30MHz)	Ur = 3.06 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.76 dB (Horizontal) Ur = 2.76 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.29 dB (Horizontal) Ur = 5.21 dB (Vertical)

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

5.1.1 Test Specification

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.2 Test Data

PASS.

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna-design is used.

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

6 Radio Spectrum Matter Test Results (RF)

6.1 Conducted Emission at AC power line


6.1.1 Test Specification

Test Requirement:	47 CFR Part 15.207(a)		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2		

6.1.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.1.3 Test Setup Diagram




6.1.4 Test Data

PASS.

Only the worst case data was showed in the report, please to see the following pages.

Conducted Emission at AC power line Test Data


TM1 / Line: Line / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.2175	46.73	9.97	56.70	62.91	-6.21	QP	P	
2	0.2175	33.73	9.97	43.70	52.91	-9.21	AVG	P	
3	0.2575	44.37	9.99	54.36	61.51	-7.15	QP	P	
4	0.2575	28.20	9.99	38.19	51.51	-13.32	AVG	P	
5	0.3840	39.63	10.01	49.64	58.19	-8.55	QP	P	
6	0.3840	23.88	10.01	33.89	48.19	-14.30	AVG	P	
7	0.7350	36.02	10.04	46.06	56.00	-9.94	QP	P	
8	0.7350	18.69	10.04	28.73	46.00	-17.27	AVG	P	
9	1.8555	29.34	10.02	39.36	56.00	-16.64	QP	P	
10	1.8555	16.32	10.02	26.34	46.00	-19.66	AVG	P	
11	6.9045	27.93	10.01	37.94	60.00	-22.06	QP	P	
12	6.9045	21.70	10.01	31.71	50.00	-18.29	AVG	P	

Conducted Emission at AC power line Test Data

TM1 / Line: Neutral / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.2130	46.01	9.99	56.00	63.09	-7.09	QP	P	
2	0.2130	32.18	9.99	42.17	53.09	-10.92	AVG	P	
3	0.3209	41.52	10.02	51.54	59.68	-8.14	QP	P	
4	0.3209	24.66	10.02	34.68	49.68	-15.00	AVG	P	
5	0.5370	35.25	10.07	45.32	56.00	-10.68	QP	P	
6	0.5370	21.11	10.07	31.18	46.00	-14.82	AVG	P	
7	1.9274	23.78	10.07	33.85	56.00	-22.15	QP	P	
8	1.9274	10.22	10.07	20.29	46.00	-25.71	AVG	P	
9	5.0954	31.64	10.05	41.69	60.00	-18.31	QP	P	
10	5.0954	24.92	10.05	34.97	50.00	-15.03	AVG	P	
11	10.0229	32.11	10.01	42.12	60.00	-17.88	QP	P	
12	10.0229	21.63	10.01	31.64	50.00	-18.36	AVG	P	

6.2 Duty Cycle


6.2.1 Test Specification

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

6.2.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.2.3 Test Setup Diagram



6.2.4 Test Data

PASS.

Please refer to Annex D for details.

6.3 Emission bandwidth and occupied bandwidth

6.3.1 Test Specification


Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use.
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.9 & 12.5
Procedure:	Emission bandwidth: a) Set RBW = approximately 1% of the emission bandwidth. b) Set the VBW > RBW. c) Detector = peak. d) Trace mode = max hold. e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. Occupied bandwidth: a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

	h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
--	---

6.3.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.3.3 Test Setup Diagram



6.3.4 Test Data

PASS.

Please refer to Annex D for details.

6.4 Maximum conducted output power


6.4.1 Test Specification

Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv)
Test Limit:	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm). For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.4
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.4

6.4.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.4.3 Test Setup Diagram



6.4.4 Test Data

PASS.

Please refer to Annex D for details.

6.5 Power spectral density


6.5.1 Test Specification

Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv)
Test Limit:	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations. For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6

6.5.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.5.3 Test Setup Diagram



6.5.4 Test Data

PASS.

Please refer to Annex D for details.

6.6 Frequency stability


6.6.1 Test Specification

Test Requirement:	47 CFR Part 15.407(g)
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.8
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.8

6.6.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.6.3 Test Setup Diagram



6.6.4 Test Data

PASS.

Please refer to Annex D for details.

6.7 Band edge emissions (Radiated)

6.7.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(10)		
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.		
	MHz	MHz	MHz
	0.090-0.110	16.42-16.423	399.9-410
	¹ 0.495-0.505	16.69475-16.69525	608-614
	2.1735-2.1905	16.80425-16.80475	960-1240
	4.125-4.128	25.5-25.67	1300-1427
	4.17725-4.17775	37.5-38.25	1435-1626.5
	4.20725-4.20775	73-74.6	1645.5-1646.5
	6.215-6.218	74.8-75.2	1660-1710
	6.26775-6.26825	108-121.94	1718.8-1722.2
	6.31175-6.31225	123-138	2200-2300
	8.291-8.294	149.9-150.05	2310-2390
	8.362-8.366	156.52475-156.52525	2483.5-2500
	8.37625-8.38675	156.7-156.9	2690-2900
	8.41425-8.41475	162.0125-167.17	3260-3267
	12.29-12.293	167.72-173.2	3332-3339
	12.51975-12.52025	240-285	3345.8-3358
	12.57675-12.57725	322-335.4	3600-4400
	13.36-13.41		(²)
	¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:		
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)


	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7		
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more		

	than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

6.7.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.7.3 Test Setup Diagram



6.7.4 Test Data

PASS.

Please refer to the following pages.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11a					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.11	5.79	53.90	68.23	-14.34	PK	PASS
H	5350.00	45.44	6.45	51.89	68.23	-16.34	PK	PASS
V	5150.00	48.73	5.79	54.52	68.23	-13.71	PK	PASS
V	5350.00	46.26	6.45	52.71	68.23	-15.53	PK	PASS
H	5150.00	34.64	5.79	40.43	54.00	-13.57	AV	PASS
H	5350.00	31.99	6.45	38.44	54.00	-15.56	AV	PASS
V	5150.00	35.69	5.79	41.48	54.00	-12.52	AV	PASS
V	5350.00	32.27	6.45	38.72	54.00	-15.29	AV	PASS

Test Mode: 802.11a					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.30	5.79	55.09	68.23	-13.15	PK	PASS
H	5350.00	45.62	6.45	52.07	68.23	-16.16	PK	PASS
V	5150.00	48.08	5.79	53.87	68.23	-14.37	PK	PASS
V	5350.00	44.63	6.45	51.08	68.23	-17.15	PK	PASS
H	5150.00	34.32	5.79	40.11	54.00	-13.89	AV	PASS
H	5350.00	31.11	6.45	37.56	54.00	-16.44	AV	PASS
V	5150.00	35.56	5.79	41.35	54.00	-12.65	AV	PASS
V	5350.00	32.39	6.45	38.84	54.00	-15.17	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.80	5.79	55.59	68.23	-12.64	PK	PASS
H	5350.00	45.69	6.45	52.14	68.23	-16.09	PK	PASS
V	5150.00	47.89	5.79	53.68	68.23	-14.55	PK	PASS
V	5350.00	45.34	6.45	51.79	68.23	-16.44	PK	PASS
H	5150.00	35.27	5.79	41.06	54.00	-12.94	AV	PASS
H	5350.00	33.91	6.45	40.36	54.00	-13.64	AV	PASS
V	5150.00	34.45	5.79	40.24	54.00	-13.77	AV	PASS
V	5350.00	33.29	6.45	39.74	54.00	-14.27	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.85	5.79	53.64	68.23	-14.59	PK	PASS
H	5350.00	45.15	6.45	51.60	68.23	-16.64	PK	PASS
V	5150.00	47.49	5.79	53.28	68.23	-14.96	PK	PASS
V	5350.00	46.33	6.45	52.78	68.23	-15.45	PK	PASS
H	5150.00	36.56	5.79	42.35	54.00	-11.66	AV	PASS
H	5350.00	33.56	6.45	40.01	54.00	-14.00	AV	PASS
V	5150.00	34.16	5.79	39.95	54.00	-14.06	AV	PASS
V	5350.00	33.10	6.45	39.55	54.00	-14.46	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.42	5.79	54.21	68.23	-14.03	PK	PASS
H	5350.00	44.41	6.45	50.86	68.23	-17.37	PK	PASS
V	5150.00	48.70	5.79	54.49	68.23	-13.75	PK	PASS
V	5350.00	45.24	6.45	51.69	68.23	-16.54	PK	PASS
H	5150.00	36.27	5.79	42.06	54.00	-11.94	AV	PASS
H	5350.00	32.03	6.45	38.48	54.00	-15.52	AV	PASS
V	5150.00	34.16	5.79	39.95	54.00	-14.05	AV	PASS
V	5350.00	33.01	6.45	39.46	54.00	-14.54	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.15	5.79	54.94	68.23	-13.29	PK	PASS
H	5350.00	44.59	6.45	51.04	68.23	-17.20	PK	PASS
V	5150.00	49.14	5.79	54.93	68.23	-13.30	PK	PASS
V	5350.00	46.20	6.45	52.65	68.23	-15.58	PK	PASS
H	5150.00	35.48	5.79	41.27	54.00	-12.74	AV	PASS
H	5350.00	31.93	6.45	38.38	54.00	-15.62	AV	PASS
V	5150.00	34.49	5.79	40.28	54.00	-13.72	AV	PASS
V	5350.00	32.08	6.45	38.53	54.00	-15.47	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ac(VHT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.94	5.79	53.73	68.23	-14.51	PK	PASS
H	5350.00	45.82	6.45	52.27	68.23	-15.96	PK	PASS
V	5150.00	49.25	5.79	55.04	68.23	-13.20	PK	PASS
V	5350.00	46.30	6.45	52.75	68.23	-15.48	PK	PASS
H	5150.00	34.12	5.79	39.91	54.00	-14.09	AV	PASS
H	5350.00	31.18	6.45	37.63	54.00	-16.38	AV	PASS
V	5150.00	35.48	5.79	41.27	54.00	-12.73	AV	PASS
V	5350.00	32.29	6.45	38.74	54.00	-15.27	AV	PASS

Test Mode: 802.11ac(VHT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.72	5.79	54.51	68.23	-13.73	PK	PASS
H	5350.00	45.16	6.45	51.61	68.23	-16.62	PK	PASS
V	5150.00	49.83	5.79	55.62	68.23	-12.62	PK	PASS
V	5350.00	46.58	6.45	53.03	68.23	-15.21	PK	PASS
H	5150.00	36.88	5.79	42.67	54.00	-11.33	AV	PASS
H	5350.00	33.55	6.45	40.00	54.00	-14.00	AV	PASS
V	5150.00	36.16	5.79	41.95	54.00	-12.06	AV	PASS
V	5350.00	32.93	6.45	39.38	54.00	-14.62	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11 ac(VHT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.45	5.79	54.24	68.23	-13.99	PK	PASS
H	5350.00	45.29	6.45	51.74	68.23	-16.50	PK	PASS
V	5150.00	47.13	5.79	52.92	68.23	-15.32	PK	PASS
V	5350.00	44.44	6.45	50.89	68.23	-17.34	PK	PASS
H	5150.00	35.46	5.79	41.25	54.00	-12.76	AV	PASS
H	5350.00	31.49	6.45	37.94	54.00	-16.07	AV	PASS
V	5150.00	35.40	5.79	41.19	54.00	-12.81	AV	PASS
V	5350.00	33.26	6.45	39.71	54.00	-14.29	AV	PASS

Test Mode: 802.11 ac(VHT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.43	5.79	53.22	68.23	-15.01	PK	PASS
H	5350.00	46.91	6.45	53.36	68.23	-14.88	PK	PASS
V	5150.00	48.73	5.79	54.52	68.23	-13.72	PK	PASS
V	5350.00	44.80	6.45	51.25	68.23	-16.98	PK	PASS
H	5150.00	35.74	5.79	41.53	54.00	-12.47	AV	PASS
H	5350.00	32.69	6.45	39.14	54.00	-14.86	AV	PASS
V	5150.00	36.74	5.79	42.53	54.00	-11.48	AV	PASS
V	5350.00	32.33	6.45	38.78	54.00	-15.22	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.94	5.79	54.73	68.23	-13.50	PK	PASS
H	5350.00	44.29	6.45	50.74	68.23	-17.50	PK	PASS
V	5150.00	49.69	5.79	55.48	68.23	-12.76	PK	PASS
V	5350.00	45.98	6.45	52.43	68.23	-15.80	PK	PASS
H	5150.00	36.41	5.79	42.20	54.00	-11.80	AV	PASS
H	5350.00	32.45	6.45	38.90	54.00	-15.11	AV	PASS
V	5150.00	35.69	5.79	41.48	54.00	-12.53	AV	PASS
V	5350.00	31.61	6.45	38.06	54.00	-15.95	AV	PASS

Test Mode: 802.11ax(HEW20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.03	5.79	52.82	68.23	-15.41	PK	PASS
H	5350.00	45.30	6.45	51.75	68.23	-16.49	PK	PASS
V	5150.00	49.43	5.79	55.22	68.23	-13.02	PK	PASS
V	5350.00	44.53	6.45	50.98	68.23	-17.26	PK	PASS
H	5150.00	36.22	5.79	42.01	54.00	-12.00	AV	PASS
H	5350.00	31.51	6.45	37.96	54.00	-16.04	AV	PASS
V	5150.00	35.47	5.79	41.26	54.00	-12.75	AV	PASS
V	5350.00	33.83	6.45	40.28	54.00	-13.72	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.79	5.79	55.58	68.23	-12.66	PK	PASS
H	5350.00	46.12	6.45	52.57	68.23	-15.67	PK	PASS
V	5150.00	49.36	5.79	55.15	68.23	-13.08	PK	PASS
V	5350.00	46.00	6.45	52.45	68.23	-15.78	PK	PASS
H	5150.00	36.83	5.79	42.62	54.00	-11.38	AV	PASS
H	5350.00	33.39	6.45	39.84	54.00	-14.16	AV	PASS
V	5150.00	36.10	5.79	41.89	54.00	-12.12	AV	PASS
V	5350.00	32.46	6.45	38.91	54.00	-15.10	AV	PASS

Test Mode: 802.11ax(HEW40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.67	5.79	54.46	68.23	-13.77	PK	PASS
H	5350.00	44.16	6.45	50.61	68.23	-17.62	PK	PASS
V	5150.00	47.12	5.79	52.91	68.23	-15.33	PK	PASS
V	5350.00	45.86	6.45	52.31	68.23	-15.92	PK	PASS
H	5150.00	34.69	5.79	40.48	54.00	-13.52	AV	PASS
H	5350.00	32.81	6.45	39.26	54.00	-14.75	AV	PASS
V	5150.00	36.11	5.79	41.90	54.00	-12.10	AV	PASS
V	5350.00	32.62	6.45	39.07	54.00	-14.94	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

6.8 Undesirable emission limits (below 1GHz)

6.8.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(9)																								
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.																								
	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:																								
	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																						
	0.009-0.490	2400/F(kHz)	300																						
	0.490-1.705	24000/F(kHz)	30																						
	1.705-30.0	30	30																						
	30-88	100 **	3																						
	88-216	150 **	3																						
	216-960	200 **	3																						
Above 960	500	3																							
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.																									
In the emission table above, the tighter limit applies at the band edges.																									
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																									
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.5																								
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel.																								

	h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

6.8.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
----------------	-----------------------------------

Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
------------------	-----------------------------------

6.8.3 Test Setup Diagram




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

6.8.4 Test Data

PASS.


Please to see the following pages.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

For test of 30MHz-1GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11a is worse case, the report only record this mode.

Undesirable emission limits (below 1GHz) Test Data


TM1 / Polarization: Horizontal / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	239.9873	54.32	-17.06	37.26	46.00	-8.74	QP	P	
2	284.9767	51.96	-15.95	36.01	46.00	-9.99	QP	P	
3 *	631.6884	47.88	-7.74	40.14	46.00	-5.86	QP	P	
4	694.4174	45.56	-7.06	38.50	46.00	-7.50	QP	P	
5	758.0408	39.89	-6.35	33.54	46.00	-12.46	QP	P	
6	884.5029	38.12	-4.85	33.27	46.00	-12.73	QP	P	

Undesirable emission limits (below 1GHz) Test Data

TM1 / Polarization: Vertical / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	42.8998	51.53	-17.85	33.68	40.00	-6.32	QP	P	
2	57.5939	48.99	-18.16	30.83	40.00	-9.17	QP	P	
3	239.1473	53.33	-17.23	36.10	46.00	-9.90	QP	P	
4	283.9791	48.75	-16.00	32.75	46.00	-13.25	QP	P	
5	413.2706	47.96	-12.51	35.45	46.00	-10.55	QP	P	
6	884.5029	37.51	-5.07	32.44	46.00	-13.56	QP	P	

6.9 Undesirable emission limits (above 1GHz)

6.9.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(10)		
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.		
	MHz	MHz	MHz
	0.090-0.110	16.42-16.423	399.9-410
	¹ 0.495-0.505	16.69475-16.69525	608-614
	2.1735-2.1905	16.80425-16.80475	960-1240
	4.125-4.128	25.5-25.67	1300-1427
	4.17725-4.17775	37.5-38.25	1435-1626.5
	4.20725-4.20775	73-74.6	1645.5-1646.5
	6.215-6.218	74.8-75.2	1660-1710
	6.26775-6.26825	108-121.94	1718.8-1722.2
	6.31175-6.31225	123-138	2200-2300
	8.291-8.294	149.9-150.05	2310-2390
	8.362-8.366	156.52475-156.52525	2483.5-2500
	8.37625-8.38675	156.7-156.9	2690-2900
	8.41425-8.41475	162.0125-167.17	3260-3267
	12.29-12.293	167.72-173.2	3332-3339
	12.51975-12.52025	240-285	3345.8-3358
	12.57675-12.57725	322-335.4	3600-4400
	13.36-13.41		(²)
	¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:		
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)


	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7		
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more		

	than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	--

6.9.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.9.3 Test Setup Diagram



6.9.4 Test Data

PASS.

Please to see the following pages.

For test of 1GHz-40GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) is worse case, the report only record this mode.

The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Emission level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector Type	Result
V	3200.95	47.16	0.00	47.16	68.23	-21.07	PK	PASS
V	7519.30	42.71	9.85	52.56	68.23	-15.67	PK	PASS
V	9515.76	36.57	13.20	49.77	68.23	-18.46	PK	PASS
V	10361.00	43.38	13.79	57.17	68.23	-11.06	PK	PASS
V	14016.23	36.29	17.35	53.64	68.23	-14.59	PK	PASS
V	15541.25	*	*	*	68.23	*	PK	PASS
H	3201.25	45.34	-0.87	44.48	68.23	-23.75	PK	PASS
H	7502.00	40.57	9.83	50.40	68.23	-17.83	PK	PASS
H	9501.75	36.02	13.15	49.17	68.23	-19.06	PK	PASS
H	10362.25	42.66	13.79	56.45	68.23	-11.78	PK	PASS
H	14018.52	37.57	17.35	54.92	68.23	-13.31	PK	PASS
H	15541.75	*	*	*	68.23	*	PK	PASS
V	3200.95	32.02	0.00	32.03	54.00	-21.97	AV	PASS
V	7519.30	30.24	9.85	40.09	54.00	-13.91	AV	PASS
V	9515.76	22.35	13.20	35.54	54.00	-18.46	AV	PASS
V	10361.00	31.41	13.79	45.20	54.00	-8.80	AV	PASS
V	14016.23	24.11	17.35	41.46	54.00	-12.54	AV	PASS
V	15541.25	*	*	*	54.00	*	AV	PASS
H	3201.25	33.92	-0.87	33.06	54.00	-20.94	AV	PASS
H	7502.00	29.75	9.83	39.59	54.00	-14.41	AV	PASS
H	9501.75	24.58	13.15	37.72	54.00	-16.28	AV	PASS
H	10362.25	31.13	13.79	44.92	54.00	-9.08	AV	PASS
H	14018.52	23.51	17.35	40.87	54.00	-13.13	AV	PASS
H	15541.75	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5200 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3408.35	45.14	-0.11	45.04	68.23	-23.19	PK	PASS
V	8019.14	42.17	10.37	52.54	68.23	-15.69	PK	PASS
V	9719.25	35.51	13.21	48.71	68.23	-19.52	PK	PASS
V	10400.75	44.28	13.91	58.19	68.23	-10.04	PK	PASS
V	14302.27	35.40	17.43	52.83	68.23	-15.40	PK	PASS
V	15602.25	*	*	*	68.23	*	PK	PASS
H	3413.51	45.96	-0.08	45.88	68.23	-22.35	PK	PASS
H	8002.85	42.27	10.33	52.60	68.23	-15.63	PK	PASS
H	9711.94	37.88	13.20	51.08	68.23	-17.15	PK	PASS
H	10401.75	42.87	13.91	56.78	68.23	-11.45	PK	PASS
H	14312.33	37.12	17.45	54.57	68.23	-13.66	PK	PASS
H	15600.75	*	*	*	68.23	*	PK	PASS
V	3408.35	32.39	-0.11	32.29	54.00	-21.71	AV	PASS
V	8019.14	29.82	10.37	40.19	54.00	-13.81	AV	PASS
V	9719.25	22.67	13.21	35.88	54.00	-18.12	AV	PASS
V	10400.75	30.72	13.91	44.63	54.00	-9.37	AV	PASS
V	14302.27	24.61	17.43	42.05	54.00	-11.95	AV	PASS
V	15602.25	*	*	*	54.00	*	AV	PASS
H	3413.51	33.98	-0.08	33.89	54.00	-20.11	AV	PASS
H	8002.85	29.62	10.33	39.95	54.00	-14.05	AV	PASS
H	9711.94	22.64	13.20	35.84	54.00	-18.16	AV	PASS
H	10401.75	30.24	13.91	44.15	54.00	-9.85	AV	PASS
H	14312.33	24.36	17.45	41.81	54.00	-12.19	AV	PASS
H	15600.75	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3711.90	45.21	1.10	46.31	68.23	-21.92	PK	PASS
V	8202.76	40.52	10.86	51.38	68.23	-16.85	PK	PASS
V	9815.86	35.47	13.23	48.70	68.23	-19.53	PK	PASS
V	10480.25	42.16	13.96	56.12	68.23	-12.11	PK	PASS
V	14702.02	35.81	17.56	53.38	68.23	-14.85	PK	PASS
V	15720.50	*	*	*	68.23	*	PK	PASS
H	3714.19	45.77	1.10	46.87	68.23	-21.36	PK	PASS
H	8218.32	42.35	10.90	53.25	68.23	-14.98	PK	PASS
H	9809.17	36.66	13.23	49.89	68.23	-18.34	PK	PASS
H	10481.25	43.93	13.96	57.89	68.23	-10.34	PK	PASS
H	14705.50	37.97	17.57	55.54	68.23	-12.69	PK	PASS
H	15722.50	*	*	*	68.23	*	PK	PASS
V	3711.90	34.38	1.10	35.48	54.00	-18.52	AV	PASS
V	8202.76	29.42	10.86	40.28	54.00	-13.72	AV	PASS
V	9815.86	24.89	13.23	38.12	54.00	-15.88	AV	PASS
V	10480.25	31.62	13.96	45.58	54.00	-8.42	AV	PASS
V	14702.02	22.75	17.56	40.31	54.00	-13.69	AV	PASS
V	15720.50	*	*	*	54.00	*	AV	PASS
H	3714.19	32.05	1.10	33.15	54.00	-20.85	AV	PASS
H	8218.32	29.86	10.90	40.76	54.00	-13.24	AV	PASS
H	9809.17	24.34	13.23	37.57	54.00	-16.43	AV	PASS
H	10481.25	31.12	13.96	45.08	54.00	-8.92	AV	PASS
H	14705.50	24.73	17.57	42.31	54.00	-11.69	AV	PASS
H	15722.50	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8431EU012801W1-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8431EU012801W1-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8431EU012801W1-ANNEX C.PDF"



ANNEX D TEST DATA

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	0.149	0.196	76.02	1.19	0.57
		5200	/	/	0.148	0.196	75.51	1.22	0.60
		5240	/	/	0.149	0.196	76.02	1.19	0.55
802.11n (HT20)	SISO	5180	/	/	0.177	0.224	79.02	1.02	0.25
		5200	/	/	0.176	0.223	78.92	1.03	0.32
		5240	/	/	0.177	0.224	79.02	1.02	0.17
802.11n (HT40)	SISO	5190	/	/	0.180	0.228	78.95	1.03	0.44
		5230	/	/	0.181	0.228	79.39	1.00	0.42
802.11ac (VHT20)	SISO	5180	/	/	0.165	0.212	77.83	1.09	0.49
		5200	/	/	0.164	0.211	77.73	1.09	0.23
		5240	/	/	0.165	0.211	78.20	1.07	0.25
802.11ac (VHT40)	SISO	5190	/	/	0.157	0.205	76.59	1.16	0.78
		5230	/	/	0.156	0.203	76.85	1.14	0.22
802.11ax (HEW20)	SISO	5180	SU	/	0.175	0.223	78.48	1.05	0.20
		5200	SU	/	0.175	0.222	78.83	1.03	0.21
		5240	SU	/	0.175	0.222	78.83	1.03	0.23
802.11ax (HEW40)	SISO	5190	SU	/	0.173	0.220	78.64	1.04	0.77
		5230	SU	/	0.171	0.218	78.44	1.05	0.23

1.2 Test Graph


1.2.1 Ant1




802.11a HCH 5240MHz Ant1 NTNV




802.11n(HT20) LCH 5180MHz Ant1 NTNV




802.11n(HT20) MCH 5200MHz Ant1 NTNV




802.11n(HT20) HCH 5240MHz Ant1 NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTNV




802.11n(HT40) HCH 5230MHz Ant1 NTNV




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTV



802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	16.652	/	Pass
		5200	/	/	1	16.497	/	Pass
		5240	/	/	1	16.462	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	17.661	/	Pass
		5200	/	/	1	17.637	/	Pass
		5240	/	/	1	17.614	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	36.207	/	Pass
		5230	/	/	1	36.239	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	17.603	/	Pass
		5200	/	/	1	17.640	/	Pass
		5240	/	/	1	17.635	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	36.178	/	Pass
		5230	/	/	1	36.228	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	18.819	/	Pass
		5200	SU	/	1	18.850	/	Pass
		5240	SU	/	1	18.852	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	37.563	/	Pass
		5230	SU	/	1	37.583	/	Pass

2.1.2 26dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	25.892	/	Pass
		5200	/	/	1	23.660	/	Pass
		5240	/	/	1	22.991	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	22.790	/	Pass
		5200	/	/	1	22.445	/	Pass
		5240	/	/	1	24.256	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	42.783	/	Pass
		5230	/	/	1	43.492	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	23.424	/	Pass
		5200	/	/	1	23.321	/	Pass
		5240	/	/	1	23.226	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	42.972	/	Pass
		5230	/	/	1	43.910	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	23.318	/	Pass
		5200	SU	/	1	22.058	/	Pass
		5240	SU	/	1	22.809	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	44.203	/	Pass
		5230	SU	/	1	42.510	/	Pass

2.2 Test Graph


2.2.1 OBW




802.11a HCH 5240MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20) HCH 5240MHz Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11ac(VHT20) LCH 5180MHz Ant1_NTNV




802.11ac(VHT20) MCH 5200MHz Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTV




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTV




2.2.2 26dB BW




802.11a HCH 5240MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20) HCH 5240MHz Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTNV




802.11n(HT40) HCH 5230MHz Ant1 NTNV




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTVN



802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTVN



3. Maximum Conducted Output Power


3.1 Test Result

3.1.1 Power


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11a	SISO	5180	/	/	11.73	<=23.98	Pass
		5200	/	/	11.93	<=23.98	Pass
		5240	/	/	12.00	<=23.98	Pass
802.11n (HT20)	SISO	5180	/	/	11.67	<=23.98	Pass
		5200	/	/	11.89	<=23.98	Pass
		5240	/	/	11.86	<=23.98	Pass
802.11n (HT40)	SISO	5190	/	/	11.89	<=23.98	Pass
		5230	/	/	12.18	<=23.98	Pass
802.11ac (VHT20)	SISO	5180	/	/	11.65	<=23.98	Pass
		5200	/	/	11.83	<=23.98	Pass
		5240	/	/	11.91	<=23.98	Pass
802.11ac (VHT40)	SISO	5190	/	/	11.85	<=23.98	Pass
		5230	/	/	12.16	<=23.98	Pass
802.11ax (HEW20)	SISO	5180	SU	/	11.42	<=23.98	Pass
		5200	SU	/	11.61	<=23.98	Pass
		5240	SU	/	11.73	<=23.98	Pass
802.11ax (HEW40)	SISO	5190	SU	/	11.58	<=23.98	Pass
		5230	SU	/	11.92	<=23.98	Pass
Note1: Antenna Gain: Ant1: 3.77dBi:							

3.2 Test Graph


3.2.1 Power




802.11a HCH 5240MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1 NTNV




802.11n(HT20) HCH 5240MHz Ant1 NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTNV



802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTNV



4. Maximum Power Spectral Density


4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)		Verdict
					ANT1	Limit	
802.11a	SISO	5180	/	/	1.48	<=11	Pass
		5200	/	/	1.48	<=11	Pass
		5240	/	/	1.68	<=11	Pass
802.11n (HT20)	SISO	5180	/	/	1.34	<=11	Pass
		5200	/	/	1.39	<=11	Pass
		5240	/	/	1.41	<=11	Pass
802.11n (HT40)	SISO	5190	/	/	-1.87	<=11	Pass
		5230	/	/	-1.69	<=11	Pass
802.11ac (VHT20)	SISO	5180	/	/	1.22	<=11	Pass
		5200	/	/	1.28	<=11	Pass
		5240	/	/	1.34	<=11	Pass
802.11ac (VHT40)	SISO	5190	/	/	-1.91	<=11	Pass
		5230	/	/	-1.81	<=11	Pass
802.11ax (HEW20)	SISO	5180	SU	/	0.73	<=11	Pass
		5200	SU	/	0.89	<=11	Pass
		5240	SU	/	0.99	<=11	Pass
802.11ax (HEW40)	SISO	5190	SU	/	-2.38	<=11	Pass
		5230	SU	/	-2.02	<=11	Pass

4.2 Test Graph


4.2.1 PSD




802.11a HCH 5240MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1 NTV




802.11n(HT20) HCH 5240MHz Ant1 NTV




802.11n(HT40) LCH 5190MHz Ant1 NTN




802.11n(HT40) HCH 5230MHz Ant1 NTN




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTN



802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTN



6. Frequency Stability

6.1 Test Result

6.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Temperature (°C)	Voltage	Measured Frequency (MHz)	Limit (MHz)	Verdict
Carrier Wave	SISO	5180	20	LV	5179.996	5150 to 5250	Pass
				NV	5179.996	5150 to 5250	Pass
				HV	5179.997	5150 to 5250	Pass
			-30	NV	5179.997	5150 to 5250	Pass
			-20	NV	5179.996	5150 to 5250	Pass
			-10	NV	5179.997	5150 to 5250	Pass
			0	NV	5179.996	5150 to 5250	Pass
			10	NV	5179.997	5150 to 5250	Pass
			30	NV	5179.997	5150 to 5250	Pass
			40	NV	5179.997	5150 to 5250	Pass
			50	NV	5179.997	5150 to 5250	Pass
		5200	20	LV	5199.997	5150 to 5250	Pass
				NV	5199.997	5150 to 5250	Pass
				HV	5199.997	5150 to 5250	Pass
			-30	NV	5199.997	5150 to 5250	Pass
			-20	NV	5199.997	5150 to 5250	Pass
			-10	NV	5199.997	5150 to 5250	Pass
			0	NV	5199.997	5150 to 5250	Pass
			10	NV	5199.997	5150 to 5250	Pass
			30	NV	5199.997	5150 to 5250	Pass
			40	NV	5199.997	5150 to 5250	Pass
			50	NV	5199.997	5150 to 5250	Pass
		5240	20	LV	5239.997	5150 to 5250	Pass
				NV	5239.997	5150 to 5250	Pass
				HV	5239.997	5150 to 5250	Pass
			-30	NV	5239.997	5150 to 5250	Pass
			-20	NV	5239.997	5150 to 5250	Pass
			-10	NV	5239.997	5150 to 5250	Pass
			0	NV	5239.997	5150 to 5250	Pass
			10	NV	5239.997	5150 to 5250	Pass
			30	NV	5239.998	5150 to 5250	Pass
			40	NV	5239.997	5150 to 5250	Pass
			50	NV	5239.998	5150 to 5250	Pass
		5190	20	LV	5189.997	5150 to 5250	Pass

				NV	5189.997	5150 to 5250	Pass
				HV	5189.997	5150 to 5250	Pass
			-30	NV	5189.997	5150 to 5250	Pass
			-20	NV	5189.997	5150 to 5250	Pass
			-10	NV	5189.997	5150 to 5250	Pass
			0	NV	5189.997	5150 to 5250	Pass
			10	NV	5189.997	5150 to 5250	Pass
			30	NV	5189.997	5150 to 5250	Pass
			40	NV	5189.997	5150 to 5250	Pass
			50	NV	5189.997	5150 to 5250	Pass
		5230	20	LV	5229.996	5150 to 5250	Pass
				NV	5229.997	5150 to 5250	Pass
				HV	5229.997	5150 to 5250	Pass
			-30	NV	5229.997	5150 to 5250	Pass
			-20	NV	5229.997	5150 to 5250	Pass
			-10	NV	5229.997	5150 to 5250	Pass
			0	NV	5229.997	5150 to 5250	Pass
			10	NV	5229.997	5150 to 5250	Pass
			30	NV	5229.997	5150 to 5250	Pass
			40	NV	5229.997	5150 to 5250	Pass
			50	NV	5229.997	5150 to 5250	Pass

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---