



RADIO TEST REPORT

FCC ID : 2AYRA-100025
Equipment : Linksys Velop Micro Mesh 7
Brand Name : Linksys
Model Name : LNM610, LNM610WH, LNM610MS, LNM610EC, SPNM61
Applicant : Linksys USA, Inc.
121 Theory, Irvine, CA. 92617, USA
Standard : 47 CFR FCC Part 15.247

The product was received on Sep. 17, 2025, and testing was started from Oct. 02, 2025 and completed on Oct. 14, 2025. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2020 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Information.....	5
1.2 Applicable Standards	10
1.3 Testing Location Information	10
1.4 Measurement Uncertainty	10
2 Test Configuration of EUT	11
2.1 The Worst Case Measurement Configuration	11
2.2 EUT Operation during Test	11
2.3 Accessories	12
2.4 Support Equipment.....	12
2.5 Test Setup Diagram	13
3 Transmitter Test Result	15
3.1 AC Power-line Conducted Emissions	15
3.2 Emissions in Restricted Frequency Bands.....	17
4 Test Equipment and Calibration Data	21
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of Emissions in Restricted Frequency Bands	
Appendix C. Test Photos	
Photographs of EUT v01	



History of this test report

TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A10_10 Ver1.3

Page Number : 3 of 21
Issued Date : Feb. 24, 2026
Report Version : 01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Sophia Shiung



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
2400-2483.5	b, g, n (HT20), VHT20, ax (HEW20), be (EHT20)	2412-2462	1-11 [11]
2400-2483.5	n (HT40), VHT40, ax (HEW40), be (EHT40)	2422-2452	3-9 [7]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	802.11b	20	2TX
2.4-2.4835GHz	802.11g	20	2TX
2.4-2.4835GHz	802.11n HT20	20	2TX
2.4-2.4835GHz	802.11n HT20-BF	20	2TX
2.4-2.4835GHz	VHT20	20	2TX
2.4-2.4835GHz	VHT20-BF	20	2TX
2.4-2.4835GHz	802.11ax HEW20	20	2TX
2.4-2.4835GHz	802.11ax HEW20-BF	20	2TX
2.4-2.4835GHz	802.11be EHT20	20	2TX
2.4-2.4835GHz	802.11be EHT20-BF	20	2TX
2.4-2.4835GHz	802.11n HT40	40	2TX
2.4-2.4835GHz	802.11n HT40-BF	40	2TX
2.4-2.4835GHz	VHT40	40	2TX
2.4-2.4835GHz	VHT40-BF	40	2TX
2.4-2.4835GHz	802.11ax HEW40	40	2TX
2.4-2.4835GHz	802.11ax HEW40-BF	40	2TX
2.4-2.4835GHz	802.11be EHT40	40	2TX
2.4-2.4835GHz	802.11be EHT40-BF	40	2TX

Note:

- ♦ 11b mode uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
- ♦ 11g, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- ♦ VHT20, VHT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- ♦ HEW20, HEW40 use a combination of OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- ♦ EHT20, EHT40 use a combination of OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM modulation.
- ♦ BWch is the nominal channel bandwidth.

**1.1.2 Antenna Information**

Ant.	Port				Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	2.4GHz	5GHz	6GHz	Bluetooth					
1	1	1	-	-	Galtronics	02102140-08200B-1	PCB Antenna	I-PEX	Note1
2	2	2	-	-	Galtronics	02102140-08200B-2	PCB Antenna	I-PEX	
3	-	-	1	1	Airgain	N08CBAUB-PK1-LG65U	PCB Antenna	I-PEX	
4	-	-	2	-	Airgain	N06CBAUA-T2M48-PK1-LA110U	PCB Antenna	I-PEX	

Note 1:

Ant.	Antenna Gain (dBi)									
	WLAN 2.4GHz	WLAN 5GHz				WLAN 6GHz				Bluetooth
		UNII 1	UNII 2A	UNII 2C	UNII 3	UNII 5	UNII 6	UNII 7	UNII 8	
1	2.34	2.30	2.30	2.40	2.40	-	-	-	-	-
2	2.42	2.77	2.77	2.46	2.59	-	-	-	-	-
3	-	-	-	-	-	2.80	2.20	2.60	4.00	2.70
4	-	-	-	-	-	4.00	4.20	4.20	4.20	-

Note 2: The above information was declared by manufacturer.

<For 2.4GHz function>**For IEEE 802.11b/g/n/VHT/ax/be (2TX/2RX):**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For 5GHz function>**For IEEE 802.11a/n/ac/ax/be (2TX/2RX):**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For 6GHz function>**For IEEE 802.11ax/be (2TX/2RX):**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For Bluetooth function> (1TX/1RX):

Only Port 1 can be used as transmitting/receiving antenna.

Port 1 could transmit/receive simultaneously.

Note 3: Directional gain information

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$
BF	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

Ex.

Directional Gain (NSS1) formula :

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

$$NSS1(g1,1) = 10^{G1/20} ; NSS1(g1,2) = 10^{G2/20};$$

$$g_{j,k} = (NSS1(g1,1) + NSS1(g1,2))^2$$

$$DG = 10 \log[(NSS1(g1,1) + NSS1(g1,2))^2 / N_{ANT}] \Rightarrow 10 \log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}]$$

Where;

2.4G G1= 2.34 dBi; G2= 2.42 dBi; DG= 5.39 dBi

5G UNII-1 G1= 2.3 dBi; G2= 2.77 dBi; DG= 5.55 dBi

5G UNII-2A G1= 2.3 dBi; G2= 2.77 dBi; DG= 5.55 dBi

5G UNII-2C G1= 2.4 dBi; G2= 2.46 dBi; DG= 5.44 dBi

5G UNII-3 G1= 2.4 dBi; G2= 2.59 dBi; DG= 5.51 dBi

6G UNII-5 G1= 2.8 dBi; G2= 4 dBi; DG= 6.43 dBi

6G UNII-6 G1= 2.2 dBi; G2= 4.2 dBi; DG= 6.27 dBi

6G UNII-7 G1= 2.6 dBi; G2= 4.2 dBi; DG= 6.45 dBi

6G UNII-8 G1= 4 dBi; G2= 4.2 dBi; DG= 7.11 dBi

1.1.3 EUT Operational Condition

EUT Power Type	From Power Adapter			
Beamforming Function	☒	With beamforming	☐	Without beamforming
	The product has beamforming function for 11n/VHT/ax/be in 2.4GHz, n/ac/ax/be in 5GHz and ax/be in 6GHz.			
Function	☒	Point-to-multipoint	☐	Point-to-point
Support RU	☒	Full RU	☐	Partial RU
Test Software Version	QRCT 4.0.170.1			

Note: The above information was declared by manufacturer.

1.1.4 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
LNM610	For retail
LNM610WH	For warehouse
LNM610MS	For superstore
LNM610EC	For e-commerce
SPNM61	For service provider

Note 1: From the above models, model: LNM610 was selected as representative model for the test and its data was recorded in this report.

Note 2: The above information was declared by manufacturer.

1.1.5 Table for EUT Support Function

Function	Support
AP Router	WLAN 2.4GHz, 5GHz UNII 1~3, 6GHz UNII 5~8 and Bluetooth
Mesh	WLAN 5GHz UNII 1~3 and 6GHz UNII 5~8

Note: The above information was declared by manufacturer.

1.1.6 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FR542105-01AA.

Below is the table for the change of the product with respect to the original one.

Modifications			Performance Checking
Add a new EUT that is equipped with different equipment name and model names. The differences between EUTs are listed below:			1. AC Power-line Conducted Emissions 2. Emissions in Restricted Frequency Bands < 1GHz
Sporton Project Number	542105-01	542105-02	
Equipment Name	Velop 7 Max	Linksys Velop Micro Mesh 7	
Model Name	LNM620, LNM620WH, LNM620MS, LNM620EC, SPNM62	LNM610, LNM610WH, LNM610MS, LNM610EC, SPNM61	
RJ-45 Transformer of port 3 (LAN) and Internet 1 port (WAN)	Brand: BS045-PULSE ELECTRONICS	Brand: HUIZHOU U&T ELETRONICS CO., LTD.	
	Model: JF0-7000NLT	Model: UTV36T06	
	Speed: 10G/2.5G/1G/100Mbps	Speed: 2.5G/1G/100Mbps	
	Related Circuit: -	Related Circuit: Changed	
	10G PHYS (Location: U13, U14): With	10G PHYS (Location: U13, U14): Without	
Components (Location: C4, C22, C135, CV13)	-	Moved the components to the backside of the PCB due to a process requirement.	
SW Version	1.0.4.25072110	1.0.2.25080515	



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15.247
- ♦ ANSI C63.10-2020

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ FCC KDB 558074 D01 v05r02
- ♦ FCC KDB 662911 D01 v02r01
- ♦ FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) TEL: 886-3-656-9065 FAX: 886-3-656-9085 Test site Designation No. TW3787 with FCC. Conformity Assessment Body Identifier (CABID) TW3787 with ISED.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
Radiated < 1GHz	03CH01-CB	Ian Hu	21.3~22.3 / 58~61	Oct. 14, 2025
AC Conduction	CO01-CB	Allen Chung	22~23 / 57~58	Oct. 02, 2025

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.8 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.8 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.7 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	CTX
	According to the original test report, "EUT + Adapter 2_Bluetooth" has been evaluated to be the worst case, so the measurement will follow this same test configuration.
1	EUT + Adapter 2_Bluetooth

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
	According to the original test report, "EUT in Y axis + Adapter 1 + US plug_WLAN 2.4GHz" has been evaluated to be the worst case, so the measurement will follow this same test configuration.
1	EUT in Y axis + Adapter 1 + US plug_WLAN 2.4GHz

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz + Bluetooth
Refer to Sporton Test Report No.: FA542105-02 for Co-location RF Exposure Evaluation.	

2.2 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



2.3 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
Adapter 1 (Interchangeable plug)	Ktec	KSA-45P-45W D5	INPUT: 100-240V~50/60Hz, 1.5A OUTPUT: 5.0V, 3.0A, 15.0W, 9.0V, 3.0A, 27.0W, 12.0V, 3.0A, 36.0W, 15.0V, 3.0A, 45.0W, 20.0V, 2.25A, 45.0W, 3.3-21.0V, 2.25A Max, 45.0w Max. 3.3-16.0V, 3.0A Max, 45.0w Max.
Adapter 2 (Fixed plug)	Frecom	FC045P13-150300U	INPUT: 100-240V~50/60Hz, 1.2A OUTPUT: 5.0V, 3.0A, 15.0W ; 9.0V, 3.0A, 27.0W ; 12.0V, 3.0A, 36.0W ; 15.0V, 3.0A, 45.0W
Others			
RJ-45 cable 1*1, non-shielded, 1.8m			
RJ-45 cable 2*1, non-shielded, 0.9m			
USB Type C cable*1, shielded, 1.5m (only for adapter 1 use)			
US plug*1 (only for adapter 1 use)			

2.4 Support Equipment


For AC Conduction:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Type-C Flash disk	Kingston	DT70	N/A
B	Port 3 (LAN)NB	DELL	E6430	N/A

For Radiated < 1GHz:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A
B	Client Device	Linksys	LN610	2AYRA-100025
C	NB	DELL	E4300	N/A

2.5 Test Setup Diagram



Test Setup Diagram - Radiated Test < 1GHz


Item	Connection	Shielded	Length
1	Power cable	Yes	1.5m
2	RJ-45 cable	No	0.9m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	1.8m
5	RJ-45 cable	No	1.8m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
☒ Refer as ANSI C63.10-2020, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Measurement Results Calculation

The measured Level is calculated using:

- Corrected Reading: LISN Factor (LISN) + Attenuator (AT/AUX) + Cable Loss (CL) + Read Level (Raw) = Level
- Margin = -Limit + Level

3.1.6 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A



3.2 Emissions in Restricted Frequency Bands

3.2.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.2.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.2.3 Test Procedures

Test Method	
▪ The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].	
▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
▪ For the transmitter unwanted emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$).
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$).
	☐ Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
	☐ Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
▪ For the transmitter band-edge emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074 clause 8.7 & C63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.2.4 Test Setup



3.2.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

3.2.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.



3.2.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix B



4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.4GHz	Mar. 06, 2025	Mar. 05, 2026	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Feb. 18, 2025	Feb. 17, 2026	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	May 10, 2025	May 09, 2026	Conduction (CO01-CB)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Sep. 14, 2025	Sep. 13, 2026	Conduction (CO01-CB)
COND Cable	Woken	Cable	CO01	9kHz ~ 30MHz	Sep. 14, 2025	Sep. 13, 2026	Conduction (CO01-CB)
Test Software	SPORTON	SENSE-EMI	V5.11	150kHz-30MHz	N.C.R.	N.C.R.	Conduction (CO01-CB)
Loop Antenna	Teseq	HLA 6121	65417	9kHz - 30MHz	Oct. 17, 2024	Oct. 16, 2025	Radiation (03CH01-CB)
3m Semi Anechoic Chamber NSA	TDK	SAC-3M	03CH01-CB	30 MHz ~ 1 GHz	Jan. 16, 2025	Jan. 15, 2026	Radiation (03CH01-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Feb. 17, 2025	Feb. 16, 2026	Radiation (03CH01-CB)
Pre-Amplifier	SGH	SGH0301	20230109-2	10M~1GHz	Jun. 21, 2025	Jun. 20, 2026	Radiation (03CH01-CB)
Signal Analyzer	R&S	FSV3044	101437	10kHz ~ 44GHz	Dec. 12, 2024	Dec. 11, 2025	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESR7	102172	9kHz ~ 7GHz	Oct. 21, 2024	Oct. 20, 2025	Radiation (03CH01-CB)
RF Cable-low	Woken	RG402	Low Cable-31+32	30 MHz ~ 1 GHz	Sep. 25, 2025	Sep. 24, 2026	Radiation (03CH01-CB)
Test Software	SPORTON	SENSE-EMI	V5.11.10	30MHz-40GHz	N.C.R.	N.C.R.	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.




Conducted Emissions at Powerline

Appendix A

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 1	Pass	QP	496.5k	45.80	56.06	-10.26	Line

Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)						
QP	150k	50.02	66.00	-15.98	10.02	Line	-	40.00	0.05	0.08	9.91						
AV	150k	39.32	56.00	-16.68	10.02	Line	-	29.30	0.05	0.08	9.91						
QP	186k	44.63	64.20	-19.57	10.05	Line	-	34.58	0.06	0.07	9.94						
AV	186k	35.86	54.20	-18.34	10.05	Line	-	25.81	0.06	0.07	9.94						
QP	213k	41.93	63.09	-21.16	10.07	Line	-	31.86	0.06	0.07	9.96						
AV	213k	33.79	53.09	-19.30	10.07	Line	-	23.72	0.06	0.07	9.96						
QP	249k	34.45	61.79	-27.34	10.10	Line	-	24.35	0.06	0.08	9.98						
AV	249k	26.53	51.79	-25.26	10.10	Line	-	16.43	0.06	0.08	9.98						
QP	370.5k	40.45	58.49	-18.04	10.17	Line	-	30.28	0.05	0.10	10.05						
AV	370.5k	29.46	48.49	-19.03	10.17	Line	-	19.29	0.05	0.10	10.05						
QP	496.5k	45.80	56.06	-10.26	10.21	Line	"Worst"	35.59	0.06	0.10	10.08						
AV	496.5k	33.65	46.06	-12.41	10.21	Line	-	23.44	0.06	0.10	10.08						

Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)						
QP	168k	43.83	65.06	-21.23	10.04	Neutral	-	33.79	0.08	0.08	9.93						
AV	168k	35.63	55.06	-19.43	10.04	Neutral	-	25.59	0.08	0.08	9.93						
QP	339k	36.69	59.23	-22.54	10.14	Neutral	-	26.55	0.08	0.09	10.03						
AV	339k	26.41	49.23	-22.82	10.14	Neutral	-	16.27	0.08	0.09	10.03						
QP	393k	40.20	58.01	-17.81	10.18	Neutral	-	30.02	0.08	0.10	10.06						
AV	393k	29.48	48.01	-18.53	10.18	Neutral	-	19.30	0.08	0.10	10.06						
QP	496.5k	45.51	56.06	-10.55	10.19	Neutral	"Worst"	35.32	0.08	0.10	10.08						
AV	496.5k	33.91	46.06	-12.15	10.19	Neutral	-	23.72	0.08	0.10	10.08						
QP	519k	44.51	56.00	-11.49	10.20	Neutral	-	34.31	0.08	0.10	10.09						
AV	519k	33.17	46.00	-12.83	10.20	Neutral	-	22.97	0.08	0.10	10.09						
QP	654k	29.27	56.00	-26.73	10.21	Neutral	-	19.06	0.09	0.09	10.11						
AV	654k	20.00	46.00	-26.00	10.21	Neutral	-	9.79	0.09	0.09	10.11						
QP	2.27M	25.61	56.00	-30.39	10.01	Neutral	-	15.60	0.12	0.14	9.94						
AV	2.27M	18.77	46.00	-27.23	10.01	Neutral	-	8.76	0.12	0.14	9.94						




Radiated Emissions below 1GHz

Appendix B

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	PK	30M	36.96	40.00	-3.04	Vertical

Mode 1



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB/m)	CL (dB)	PA (dB)		
PK	30M	36.96	40.00	-3.04	-19.12	3	Vertical	57	1.00	"Worst"	56.08	24.35	0.96	44.43		
PK	54.25M	34.27	40.00	-5.73	-30.21	3	Vertical	70	2.00	-	64.48	13.15	1.33	44.69		
PK	82.38M	36.93	40.00	-3.07	-29.81	3	Vertical	341	3.00	-	66.74	13.20	1.62	44.63		
PK	186.17M	34.97	43.50	-8.53	-27.08	3	Vertical	258	1.00	-	62.05	14.98	2.43	44.49		
PK	710.94M	39.15	46.00	-6.85	-14.09	3	Vertical	116	2.00	-	53.24	25.18	4.54	43.81		
PK	743.92M	38.97	46.00	-7.03	-13.32	3	Vertical	146	1.25	-	52.29	25.74	4.65	43.71		

Mode 1



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB/m)	CL (dB)	PA (dB)		
QP	30M	36.91	40.00	-3.09	-19.12	3	Horizontal	309	1.00	"Worst"	56.03	24.35	0.96	44.43		
PK	81.41M	36.54	40.00	-3.46	-29.97	3	Horizontal	24	1.00	-	66.51	13.05	1.61	44.63		
PK	146.4M	37.51	43.50	-5.99	-25.91	3	Horizontal	34	1.00	-	63.42	16.59	2.16	44.66		
PK	207.51M	32.45	43.50	-11.05	-26.51	3	Horizontal	92	1.50	-	58.96	15.47	2.52	44.50		
PK	743.92M	36.40	46.00	-9.60	-13.32	3	Horizontal	64	1.25	-	49.72	25.74	4.65	43.71		
PK	915M	37.16	46.00	-8.84	-11.60	3	Horizontal	5	2.00	-	48.76	26.79	5.11	43.50		