RADIO TEST REPORT
FCC 47 CFR PART 15 SUBPART C

Test Standard	**FCC Part 15.247**
Product name	**iCareDx PSS-1**
Brand Name	**iCare Diagnostics**
Model No.	**PSS-1**
Test Result	**Pass**
Statements of Conformity	**Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.**

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.
The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:

Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 28, 2021	Initial Issue	ALL	Mita Wu

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Table of contents

1. GENERAL INFORMATION 4
1.1 EUT INFORMATION 4
1.2 EUT CHANNEL INFORMATION 5
1.3 ANTENNA INFORMATION 5
1.4 MEASUREMENT UNCERTAINTY 6
1.5 FACILITIES AND TEST LOCATION 7
1.6 INSTRUMENT CALIBRATION 7
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT 8
1.8 TEST METHODOLOGY AND APPLIED STANDARDS 8
2. TEST SUMMERY 9
3. DESCRIPTION OF TEST MODES 10
3.1 THE WORST MODE OF OPERATING CONDITION 10
3.2 THE WORST MODE OF MEASUREMENT 11
3.3 EUT DUTY CYCLE 12
4. TEST RESULT 13
4.1 AC POWER LINE CONDUCTED EMISSION 13
4.2 6DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%) 16
4.3 OUTPUT POWER MEASUREMENT 24
4.4 POWER SPECTRAL DENSITY 26
4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION 31
4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION 41
APPENDIX 1 - PHOTOGRAPHS OF EUT A-1

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	iCare Diagnostics International Co. Ltd. 15F., NO. 207-3, SEC. 3, BEIXIN RD., XINDIAN DIST., NEW TAIPEI CITY 231, Taiwan
Manufacturer	iCare Diagnostics International Co. Ltd. 4F., No. 53, Sec. 4, Zhongyang Rd., Tucheng Dist., New Taipei City 236, Taiwan
Equipment	iCareDx PSS-1
Model Name	PSS-1
Trade Name	iCare Diagnostics
Received Date	January 21, 2021
Date of Test	January 21 ~ January 25, 2021
Power Supply	Power from Adapter. Shenzhen SOY Technology Co.,Ltd / SOY-1200400-327 I/P: 100-240V~, 50/60Hz, 1.7A Max. O/P: 12.0Vdc, 4.0A, 48.0W

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20: 2412MHz ~ 2462MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM
Number of channel	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels

Remark:
Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	**Number of frequencies**	**Location in frequency range of operation**
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	PCBA Antenna
Antenna Gain	Gain: -2.38 dBi
Antenna connector	N/A

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:
1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Jerry Chang	-
Radiation	Jerry Chang	-
RF Conducted	Rick Lee	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Date**	**Calibration Due**
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Coaxial Cable	Woken	WC12	CC001	06/29/2020	06/28/2021
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	09/07/2020	09/06/2021
Power Meter	Anritsu	ML2487A	6K00003260	05/21/2020	05/20/2021
Power Seneor	Anritsu	MA2490A	032910	05/21/2020	05/20/2021
Software	N/A				

3M 966 Chamber Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2020	02/24/2021
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+327109/4	09/19/2020	09/18/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/06/2021	01/05/2022
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	09/30/2020	09/29/2021
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Remark: Each piece of equipment is scheduled for calibration once a year.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

AC Power Line Conducted Emission Test Room					
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Date**	**Calibration Due**
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2020	02/12/2021
Software	EZ-EMC(CCS-3A1-CE)				

Remark: Each piece of equipment is scheduled for calibration once a year.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

Support Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
1	NB	LENOVO	INVALID	N/A	N/A

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2. TEST SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d)	4.6	Radiation Band Edge	Pass
15.247(d)	4.6	Radiation Spurious Emission	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS0
Test Channel Frequencies	**IEEE 802.11b mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz **IEEE 802.11g mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz **IEEE 802.11n HT20 mode :** 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz
Operation Transmitter	IEEE 802.11b mode : 1T1R IEEE 802.11g mode : 1T1R IEEE 802.11n HT20 mode : 1T1R

Remark:
1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	**AC Power line conducted emission for line and neutral**
Power supply Mode	**Mode 1: EUT power by Adapter**
Worst Mode	☒ **Mode 1** ☐ **Mode 2** ☐ **Mode 3** ☐ **Mode 4**

Radiated Emission Measurement Below 1G	
Test Condition	**Radiated Emission Below 1G**
Power supply Mode	**Mode 1: EUT power by Adapter**
Worst Mode	☒ **Mode 1** ☐ **Mode 2** ☐ **Mode 3** ☐ **Mode 4**

Radiated Emission Measurement Above 1G	
Test Condition	**Radiated Emission Above 1G**
Power supply Mode	**Mode 1: EUT power by Adapter**
Worst Mode	☒ **Mode 1** ☐ **Mode 2** ☐ **Mode 3** ☐ **Mode 4**
Worst Position	☐ **Placed in fixed position.** ☒ **Placed in fixed position at X-Plane (E2-Plane)**

Remark:
1. The worst mode was record in this test report.
2. EUT pre-scanned in axis X and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3.3 EUT DUTY CYCLE

Temperature: 23.9℃ **Humidity:** 53% RH

Tested by: Rick Lee **Test date:** January 22, 2021

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	97.66%	0.10	0.12	1.00
802.11g	87.29%	0.59	0.74	1.00
802.11n HT20	93.05%	0.31	0.79	1.00

802.11b



802.11g



802.11n HT20



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a)(2),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Pass.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

Test Mode:	Mode 1	Temp/Hum	22.9(℃)/ 53%RH
Phase:	Line	Test Date	January 21, 2021
Test Voltage:	120Vac, 60Hz	Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (d uV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1820	29.58	20.99	10.21	39.79	31.20	64.39	54.39	-24.60	-23.19	Pass
0.2140	26.82	17.24	10.21	37.03	27.45	63.05	53.05	-26.02	-25.60	Pass
0.3940	27.69	19.36	10.22	37.91	29.58	57.98	47.98	-20.07	-18.40	Pass
0.4500	29.06	20.22	10.22	39.28	30.44	56.88	46.88	-17.60	-16.44	Pass
0.9580	24.30	17.76	10.24	34.54	28.00	56.00	46.00	-21.46	-18.00	Pass
23.9500	24.36	23.06	10.31	34.67	33.37	60.00	50.00	-25.33	-16.63	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	Mode 1	Temp/Hum	22.9(℃)/ 53%RH
Phase:	Neutral	Test Date	January 21, 2021
Test Voltage:	120Vac, 60Hz	Test Engineer	Jerry Chang



Frequency (MHz)	Quasi Peak reading dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1540	30.15	20.04	10.18	40.33	30.22	65.78	55.78	-25.45	-25.56	Pass
0.1820	29.21	20.48	10.19	39.40	30.67	64.39	54.39	-24.99	-23.72	Pass
0.2100	25.64	17.47	10.19	35.83	27.66	63.21	53.21	-27.38	-25.55	Pass
0.4340	31.26	23.81	10.19	41.45	34.00	57.18	47.18	-15.73	-13.18	Pass
0.9380	25.17	18.44	10.21	35.38	28.65	56.00	46.00	-20.62	-17.35	Pass
26.9420	25.23	24.77	10.59	35.82	35.36	60.00	50.00	-24.18	-14.64	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a)(2),

6 dB Bandwidth ：

Limit	Shall be at least 500kHz

Occupied Bandwidth(99%) ： For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.2.4 Test Result

Temperature: 23.9℃ **Humidity:** 53% RH

Tested by: Rick Lee **Test date:** January 22, 2021

Test mode: IEEE 802.11b mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	13.035	-	8.113	-	≥500
Mid	2437	12.899	-	8.574	-	
High	2462	12.838	-	8.097	-	

Test mode: IEEE 802.11g mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	17.285	-	16.42	-	≥500
Mid	2437	17.225	-	16.36	-	
High	2462	16.984	-	16.40	-	

Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz						
Channel	**Frequency (MHz)**	**Chain 0 OBW(99%) (MHz)**	**Chain 1 OBW(99%) (MHz)**	**Chain 0 6dB BW (MHz)**	**Chain 1 6dB BW (MHz)**	**6dB limit (kHz)**
Low	2412	18.188	-	17.65	-	≥500
Mid	2437	18.128	-	17.33	-	
High	2462	17.961	-	17.59	-	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

6dB BANDWIDTH

IEEE 802.11b mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11n HT20 mode- chain 0

Low CH



Mid CH



High CH



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

BANDWIDTH 99%

IEEE 802.11b mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11n HT20 mode- chain 0	
Low CH	**Mid CH**
	
igh CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b),

Peak output power：

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	☒ Antenna not exceed 6 dBi：30dBm ☐ Antenna with DG greater than 6 dBi： [Limit = 30 – (DG – 6)] ☐ Point-to-point operation：

Average output power：For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.3.4 Test Result

Temperature:	23.9℃	**Humidity:**	53% RH
Tested by:	Rick Lee	**Test date:**	January 22, 2021

Peak output power：

Wifi 2.4G							
Config	CH	Freq. (MHz)	power setting	PK Power (dBm)	PK Total Power (W)	DG (dBi)	Limit (dBm)
			Chain 0	Chain 0			
IEEE 802.11b Data rate: 1Mbps	Low	2412	16	19.91	0.0979	2.87	30
	Mid	2437	17	19.76	0.0946		
	High	2462	15	19.99	0.0998		
IEEE 802.11g Data rate: 6Mbps	Low	2412	14	24.30	0.2692		
	Mid	2437	15	24.60	0.2884		
	High	2462	14	24.47	0.2799		
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	13	23.70	0.2344		
	Mid	2437	14	23.77	0.2382		
	High	2462	13	23.61	0.2296		

Average output power：

Wifi 2.4G				
Config	CH	Freq. (MHz)	Power Setting	AV Power (dBm)
				Chain 0
IEEE 802.11b Data rate: 1Mbps	Low	2412	16	16.86
	Mid	2437	17	16.83
	High	2462	15	17.05
IEEE 802.11g Data rate: 6Mbps	Low	2412	14	15.22
	Mid	2437	15	14.44
	High	2462	14	15.38
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	13	13.65
	Mid	2437	14	13.42
	High	2462	13	13.14

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi：8dBm ☐ Antenna with DG greater than 6 dBi： [Limit = 8 – (DG – 6)] ☐ Point-to-point operation：

4.4.2 Test Procedure

Test method Refer as ANSI C63.10:2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.4.4 Test Result

Temperature: 23.9℃ **Humidity:** 53% RH

Tested by: Rick Lee **Test date:** January 22, 2021

Test mode: IEEE 802.11b mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PPSD (dBm)**	**Limit (dBm)**
Low	2412	-7.14	-	-7.14	8
Mid	2437	-6.45	-	-6.45	
High	2462	-5.57	-	-5.57	

Test mode: IEEE 802.11g mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PPSD (dBm)**	**Limit (dBm)**
Low	2412	-9.38	-	-9.38	8
Mid	2437	-10.56	-	-10.56	
High	2462	-10.72	-	-10.72	

Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz					
Channel	**Frequency (MHz)**	**Chain 0 PPSD (dBm)**	**Chain 1 PPSD (dBm)**	**Total PPSD (dBm)**	**Limit (dBm)**
Low	2412	-12.78	-	-12.78	8
Mid	2437	-12.91	-	-12.91	
High	2462	-13.33	-	-13.33	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

IEEE 802.11b mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode- chain 0

Low CH



Mid CH



High CH



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11n HT20 mode- chain 0	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d),

In any 100 kHz bandwidth outside the authorized frequency band,

Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as KDB 662911 D01, ANSI C63.10:2013.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.

2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.

3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. f the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup



4.5.4 Test Result

Temperature: 23.9℃ **Humidity:** 53% RH

Tested by: Rick Lee **Test date:** January 22, 2021

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

IEEE 802.11b mode Low CH chain 0	
Reference Level of PSD in 100kHz	**Band Edge**
	
Spurious Emission 30MHz-25GHz	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11b mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11b mode High CH chain 0	
Reference Level of PSD in 100kHz	**Band Edge**
	
Spurious Emission 30MHz-25GHz	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode Low CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11g mode High CH chain 0	
Reference Level of PSD in 100kHz	**Band Edge**
	
Spurious Emission 30MHz-25GHz	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11 n HT20 mode Low CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11 n HT20 mode Mid CH chain 0	
Reference Level of PSD in 100kHz	**Spurious Emission 30MHz-25GHz**
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

IEEE 802.11n HT20 mode High CH chain 0

Reference Level of PSD in 100kHz



Band Edge



Spurious Emission 30MHz-25GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency	Field Strength (microvolts/m)	Measurement Distance (metres)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6.2 Test Procedure

Test method Refer as KDB 662911 D01, ANSI C63.10:2013.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4. The SA setting following：

(1) Below 1G：RBW = 100kHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G：

(2.1) For Peak measurement：RBW = 1MHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement：RBW = 1MHz, VBW

˙If Duty Cycle ≥ 98%, VBW=10Hz.

˙If Duty Cycle < 98%, VBW=1/T.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6.3 Test Setup

9kHz ~ 30MHz



30MHz ~ 1GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1 GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6.4 Test Result

Band Edge Test Data

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	49.03	-1.14	47.89	74.00	-26.11
2390.00	Average	37.30	-1.14	36.16	54.00	-17.84

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	47.19	-1.14	46.05	74.00	-27.95
2390.00	Average	37.13	-1.14	35.99	54.00	-18.01

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	47.80	-0.80	47.00	74.00	-27.00
2483.50	Average	35.74	-0.80	34.94	54.00	-19.06

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	46.19	-0.80	45.39	74.00	-28.61
2483.50	Average	35.81	-0.80	35.01	54.00	-18.99

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	64.10	-1.14	62.96	74.00	-11.04
2390.00	Average	46.93	-1.14	45.79	54.00	-8.21

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	57.03	-1.14	55.89	74.00	-18.11
2390.00	Average	46.79	-1.14	45.65	54.00	-8.35

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	50.42	-0.80	49.62	74.00	-24.38
2483.50	Average	39.06	-0.80	38.26	54.00	-15.74

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	50.46	-0.80	49.66	74.00	-24.34
2483.50	Average	37.82	-0.80	37.02	54.00	-16.98

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	62.99	-1.14	61.85	74.00	-12.15
2390.00	Average	46.96	-1.14	45.82	54.00	-8.18

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11 n20 Low CH 2412MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	60.08	-1.14	58.94	74.00	-15.06
2390.00	Average	44.04	-1.14	42.90	54.00	-11.10

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	47.24	-0.80	46.44	74.00	-27.56
2483.50	Average	37.98	-0.80	37.18	54.00	-16.82

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n20 High CH 2462MHz	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Band Edge	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	49.10	-0.80	48.30	74.00	-25.70
2483.50	Average	37.32	-0.80	36.52	54.00	-17.48

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Below 1G Test Data

Test Mode	Mode 1	Temp/Hum	20.5(℃)/ 58%RH
Test Item	30MHz-1GHz	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
32.91	Peak	36.82	-4.48	32.34	40.00	-7.66
154.16	Peak	42.48	-10.32	32.16	43.50	-11.34
245.34	Peak	48.27	-10.77	37.50	46.00	-8.50
479.11	Peak	30.50	-3.39	27.11	46.00	-18.89
744.89	Peak	28.37	0.78	29.15	46.00	-16.85
959.26	Peak	32.11	3.76	35.87	46.00	-10.13

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	Mode 1	Temp/Hum	20.5(℃)/ 58%RH
Test Item	30MHz-1GHz	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
114.39	Peak	44.23	-9.66	34.57	43.50	-8.93
156.10	Peak	50.67	-10.32	40.35	43.50	-3.15
240.49	Peak	55.55	-10.75	44.80	46.00	-1.20
476.20	Peak	34.51	-3.45	31.06	46.00	-14.94
839.95	Peak	27.76	2.30	30.06	46.00	-15.94
959.26	Peak	32.74	3.76	36.50	46.00	-9.50

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	34.58	5.65	40.23	74.00	-33.77
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	34.15	5.65	39.80	74.00	-34.20
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	34.63	5.90	40.53	74.00	-33.47
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	34.25	5.90	40.15	74.00	-33.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	33.27	6.34	39.61	74.00	-34.39
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11b High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	33.12	6.34	39.46	74.00	-34.54
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	34.12	5.65	39.77	74.00	-34.23
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	34.05	5.65	39.70	74.00	-34.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	34.55	5.90	40.45	74.00	-33.55
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	33.81	5.90	39.71	74.00	-34.29
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	33.33	6.34	39.67	74.00	-34.33
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11g High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	33.86	6.34	40.20	74.00	-33.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	34.16	5.65	39.81	74.00	-34.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	33.55	5.65	39.20	74.00	-34.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	33.71	5.90	39.61	74.00	-34.39
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	33.38	5.90	39.28	74.00	-34.72
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	32.22	6.34	38.56	74.00	-35.44
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	20.5(℃)/ 58%RH
Test Item	Harmonic	Test Date	January 25, 2021
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	34.25	6.34	40.59	74.00	-33.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。