Test result plots shown as follows:

802.11a U-NII-1 Low channel



802.11a U-NII-1 Middle channel



802.11a U-NII-1 High channel



802.11n(HT20) U-NII-1 Low channel



802.11n(HT20) U-NII-1 Middle channel



802.11n(HT20) U-NII-1 High channel



802.11n(HT40) U-NII-1 Low channel



802.11n(HT40) U-NII-1 High channel



802.11ac(HT20) U-NII-1 Low channel



802.11ac(HT20) U-NII-1 Middle channel



802.11ac(HT20) U-NII-1 High channel



802.11ac(HT40) U-NII-1 Low channel



802.11n(HT40) U-NII-1 High channel



802.11ac(HT80) U-NII-1 Low channel



802.11a U-NII-3 Low channel



802.11a U-NII-3 Middle channel



802.11a U-NII-3 High channel



802.11n(HT20) U-NII-3 Low channel



802.11n(HT20) U-NII-3 Middle channel



802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



802.11ac(HT20) U-NII-3 Low channel



802.11ac(HT20) U-NII-3 Middle channel



802.11ac(HT20) U-NII-3 High channel



802.11ac(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



802.11ac(HT80) U-NII-3 Low channel



13 Power Spectral density

Test Requirement:	FCC CFR47 Part 15 Section 15.407(a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General U-NII Test Procedures New Rules v02r01, Section F
Test Limit:	≤11.00dBm/MHz for Operation in the U-NII-1(5150MHz-5250MHz)of mobile device ≤30.00dBm/500KHz for Operation in the U-NII-3(5725MHz-5850MHz)of device
Test Result:	PASS

13.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer:

U-NII-1

RBW = 1MHz, VBW ⩾3* RBW Sweep = auto; Detector Function = Peak. Trace = Max hold.

U-NII-3

RBW = 510KHz, VBW ⩾3* RBW Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

13.2 Test Result:

Band	Operation mode	Power Spectral Density (dBm/MHz)		
		Low	Middle	High
U-NII-1	802.11a	4.359	2.844	4.363
	802.11n(HT20)	3.135	4.648	3.333
	802.11n(HT40)	0.027	/	2.390
	802.11ac(HT20)	3.076	4.106	4.914
	802.11ac(HT40)	-0.032	/	1.904
	802.11ac(HT80)	-3.968	/	/
	Limit	≤11.00dBm/MHz		

Band	Operation mode	Power Spectral Density (dBm/MHz)		
		Low	Middle	High
U-NII-3	802.11a	-0.022	-0.862	-1.416
	802.11n(HT20)	2.166	1.154	0.860
	802.11n(HT40)	-3.238	/	-3.671
	802.11ac(HT20)	1.483	0.271	0.205
	802.11ac(HT40)	-2.973	/	-4.070
	802.11ac(HT80)	-6.255	/	/
	Limit	≤30.00dBm/500kHz		

* All transmit signals are completely uncorrelated with each other, Directional gain = G_{ANT} which is less than 6dBi. So the limit does not be reduced.

Test result plots shown as follows:

802.11a U-NII-1 Low channel



802.11a U-NII-1 Middle channel



802.11a U-NII-1 High channel



802.11n(HT20) U-NII-1 Low channel



802.11n(HT20) U-NII-1 Middle channel



802.11n(HT20) U-NII-1 High channel



802.11n(HT40) U-NII-1 Low channel



802.11n(HT40) U-NII-1 High channel



802.11ac(HT20) U-NII-1 Low channel



802.11ac(HT20) U-NII-1 Middle channel



802.11ac(HT20) U-NII-1 High channel



802.11ac(HT40) U-NII-1 Low channel



802.11n(HT40) U-NII-1 High channel



802.11ac(HT80) U-NII-1 Low channel



802.11a U-NII-3 Low channel



802.11a U-NII-3 Middle channel



802.11a U-NII-3 High channel



802.11n(HT20) U-NII-3 Low channel



802.11n(HT20) U-NII-3 Middle channel



802.11n(HT20) U-NII-3 High channel



802.11n(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



802.11ac(HT20) U-NII-3 Low channel



802.11ac(HT20) U-NII-3 Middle channel



802.11ac(HT20) U-NII-3 High channel



802.11ac(HT40) U-NII-3 Low channel



802.11n(HT40) U-NII-3 High channel



802.11ac(HT80) U-NII-3 Low channel



14 Frequency Stability

Test Requirement:	FCC CFR47 Part 15 Section 15.407(g)
Test Method:	ANSI C63.10:2013
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual or 20ppm.
Test Result:	PASS

14.1 Test Procedure:

1. The transmitter output (antenna port) was connected to the spectrum analyzer. EUT have transmitted absence of unmodulation signal and fixed channelise. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings. fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc × 106 ppm and the limit is less than ±20ppm The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.

2. Extreme temperature rule is -15°C~ 45°C.

14.2 Test Result:

U-NII-1 Test Frequency:5180MHz				
Temperature (℃)	Power Supply (VAC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	120	/	/	/
45		1807	2.1599	20
30		1800	2.1516	20
20		1806	2.1587	20
10		1800	2.1516	20
0		1803	2.1552	20
-10		1800	2.1516	20
-15		1809	2.1623	20
-30		/	/	/
20	108	1810	2.1635	20
20	132	1798	2.1492	20

U-NII-3 Test Frequency:5785MHz				
Temperature (℃)	Power Supply (VAC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	120	/	/	/
45		1919	2.2938	20
30		1911	2.2842	20
20		1915	2.2890	20
10		1923	2.2986	20
0		1907	2.2795	20
-10		1908	2.2807	20
-15		1914	2.2878	20
-30		/	/	/
20	108	1918	2.2926	20
20	132	1906	2.2783	20

15 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

This device uses of two antennas that uses a specified coupling to the intentional radiator. Antenna connectors complied with the requirement.



16 RF Exposure

Remark: refer to MPE test report: WTF21D01002802W003.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-DB21-Photos.

======End of Report======