



REPORT No.: SZ25090192S01

Annex F Test Position Consideration

Exposure Position	Wireless Interface	BT	2.4GHz WLAN ANT 1	5GHz WLAN ANT 1	5GHz WLAN ANT 1	5GHz WLAN ANT 1	5GHz WLAN ANT 2
	Calculated Frequency	2480MHz	2462MHz	5220MHz	5300MHz	5600MHz	5825MHz
	Maximum power (dBm)	11	19	19.5	19.5	19.5	19.5
	Maximum rated power(mW)	13.0	79.0	89.0	89.0	89.0	89.0
Bottom Face	Separation distance(mm)	5.0	5.0	5.0	5.0	5.0	5.0
	exclusion threshold	4.1	24.8	27.9	27.9	43.0	43.0
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	4.1	4.1	4.1	4.1	4.1	4.1
	exclusion threshold	4.1	24.8	27.9	27.9	43.0	43.0
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes
Edge 2	Separation distance(mm)	4.5	4.5	4.5	4.5	4.5	4.5
	exclusion threshold	4.1	24.8	27.9	27.9	43.0	43.0
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes
Edge 3	Separation distance(mm)	183.0	183.0	183.0	183.0	183.0	183.0
	exclusion threshold	1425.0	1426.0	1426.0	1426.0	1392.0	1392.0
	Testing required?	No	No	No	No	No	No
Edge 4	Separation distance(mm)	247.6	247.6	247.6	247.6	247.6	247.6
	exclusion threshold	2071.0	2071.0	2071.0	2071.0	2038.0	2038.0
	Testing required?	No	No	No	No	No	No