

RF Exposure Report

Project Number: 4926553**Proposal Number:** 06072022NG-1.1**Report Number:** 4926553EMC04**Revision Level:** 0**Client:** Airgo Systems, LLC**Equipment Under Test:** Large Vehicle Monitoring Telematics**Model Name:** AirBoxOne**Model Number:** Drov-ABO**FCC ID:** 2AYTU-EG91-NA-ABO**Contains FCC ID:** VPYLB1YM
2AKNO-VOLJN5179M16
SH6MDBT50Q
2ADWC-S76S**Applicable Standards:** 47 CFR §§ 2.1091

FCC KDB 447498 D01 General RF Exposure Guidance v06

FCC OET Bulletin 65

Report issued on: 12 June 2023**Result:** Compliant

FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01

Report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:
Brandon Osborn, EMC/RF Project Engineer**Reviewed by:**
Stephen Whalen, SAR/EMC Manager

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	CLIENT INFORMATION.....	3
1.2	TEST LABORATORY	3
1.3	GENERAL INFORMATION OF EUT	4
1.4	OPERATING MODES AND CONDITIONS	4
2	RF EXPOSURE.....	5
2.1	TEST RESULTS.....	5
2.2	TEST METHOD.....	5
2.3	SINGLE TRANSMISSION RF EXPOSURE LEVELS (mW/cm ²)	5
2.4	SIMULTANEOUS CONDITIONS	6
3	REVISION HISTORY	7

1 General Information

1.1 *Client Information*

Name: Airgo Systems, LLC.
Address: 8232 SW 23rd Place
City, State, Zip, Country: Oklahoma City, OK 73128, USA

1.2 *Test Laboratory*

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01

1.3 General Information of EUT

Type of Product: Large Vehicle Monitoring Telematics
Model Number: Drov-ABO
Serial Number: FCC 9083 (on label), 2017100031 (DC on pcb)
Module Models: EG91NA

Frequency Ranges: 699-716 MHz (LTE Band 12); 1710-1754 MHz (LTE Band 4)
777-787 MHz (LTE Band 13); 1850-1910 MHz (LTE Band 2)
824-849 MHz (LTE Band 5)
2412-2462 MHz (WLAN); 5180-5825 MHz (WLAN)
902.3-914.9 MHz (LoRa); 2405-2480 MHz (Zigbee)
2402-2480 MHz (Bluetooth)

Antenna Gain¹: FPC, 699-849 MHz – 3.5dBi*
FPC, 1710-1910 MHz – 6.0dBi*
FPC, 2412-2462 MHz – 2.5dBi*
FPC, 2402-2480 MHz – 1.0dBi*
FPC, 5180 – 5825 MHz – 3.5dBi*
FPC, 902.3-914.9 MHz – 0.0dBi

Max Conducted Output Power: LTE Band 2: 24.44 dBm*
LTE Band 4: 24.31 dBm*
LTE Band 5: 24.23 dBm*
LTE Band 12: 24.23 dBm*
LTE Band 13: 23.94 dBm*
Bluetooth BDR: 8.2 dBm*
Bluetooth LE: 8.2 dBm*
WLAN 2.4GHz: 28.13 dBm*
WLAN 5GHz U-NII-1: 14.9 dBm*
WLAN 5GHz U-NII-2A: 19.0 dBm*
WLAN 5GHz U-NII-2C: 18.9 dBm*
WLAN 5GHz U-NII-3: 20.0 dBm*
Zigbee 2.4GHz: 25.53 dBm*
LoRa 900MHz: 17.25 dBm*

**Data was not measured by SGS laboratory and therefore not responsible for accuracy. Data obtained via customer, specification sheet, previous regulatory filing or other.*

Note¹: Antenna and gain is not the original for each transmitter.

1.4 Operating Modes and Conditions

Maximum power levels were utilized for all calculations. Simultaneous transmission is possible with one LTE band, one WLAN band, Zigbee, LoRa and Bluetooth.

2 RF Exposure

2.1 Test Results

Test Description	Product Specific Standard	Test Result
RF Exposure	FCC Part 1.1310	Compliant

2.2 Test Method

The formula below calculates power density.

$$S = \frac{PG}{4\pi R^2} \quad \text{Or} \quad S = \frac{EIRP}{4\pi R^2}$$

Where;

S = Power density (mW/cm²)

P = Maximum sourced based average power delivered to antenna port (mW)

G = Maximum power gain of the antenna in the direction of interest relative to an isotropic radiator (dBi)

R = Distance between by-stander and antenna (cm)

EIRP = Equivalent (or effective) isotropically radiated power

2.3 Single transmission RF Exposure Levels (mW/cm²)

Band of Operation		Conducted Power w/tolerance dBm	Antenna Gain	Cable Loss	Average EIRP		Distance (R) cm	Power Density EIRP _{avg} /(4πR ²) mW/cm ²	FCC mW/cm ²	% of Limit	Verdict
Type	MHz				dBm	mW					
LTE Band 2	1850-1910	24.4	6.0	0.0	30.4	1107	20	0.220	1.00	22%	Pass
LTE Band 4	1710-1755	24.3	6.0	0.0	30.3	1076	20	0.214	1.00	21%	Pass
LTE Band 5	824-849	24.2	3.5	0.0	27.7	593	20	0.118	0.55	21%	Pass
LTE Band 12	699-716	24.2	3.5	0.0	27.7	593	20	0.118	0.47	25%	Pass
LTE Band 13	777-787	24.0	3.5	0.0	27.5	556	20	0.111	0.52	21%	Pass
WLAN 2.4	2412-2462	28.1	2.5	0.0	30.6	1156	20	0.230	1.00	23%	Pass
Bluetooth	2400-2483.5	8.2	1.0	0.0	9.2	8	20	0.002	1.00	0%	Pass
WLAN 5 GHz (UNII-1)	5180-5240	14.9	3.5	0.0	18.4	69	20	0.014	1.00	1%	Pass
WLAN 5 GHz (UNII-2)	5260-5700	19.0	3.5	0.0	22.5	178	20	0.035	1.00	4%	Pass
WLAN 5 GHz (UNII-3)	5745-5825	20.0	3.5	0.0	23.5	224	20	0.045	1.00	4%	Pass
LoRa	902.3-914.9	17.3	0.0	0.0	17.3	53	20	0.011	0.60	2%	Pass
Zigbee	2405-2480	25.5	1.0	0.0	26.5	450	20	0.089	1.00	9%	Pass
Bluetooth LE	2402-2480	8.2	1.0	0.0	9.2	8	20	0.002	1.00	0%	Pass

2.4 Simultaneous Conditions

Simultaneous transmissions are evaluated using the equation and highest results from each technology.

$$\frac{S_1}{S_1 \text{ Limit}} + \frac{S_2}{S_2 \text{ Limit}} + \dots + \frac{S_n}{S_n \text{ Limit}} \leq 1.0$$

Calculation

LTE Band 12 = 25%

WLAN 2.4 = 23 %

Zigbee = 9%

LoRa = 2%

BLE = 0%

Bluetooth BDR = 0%

Total Simultaneous = 59% which is < 100% - Compliant

3 Revision History

Revision Level	Description of changes	Revision Date
0	Initial Release	01 May 2023
1	Updated distance to 20cm	12 June 2023