DFS TEST REPORT

Part 15 Subpart E 15.407

Equipment under test	LOAA Analyzer
Model name	On-Point
FCC ID	2AYU4LOAA-ONPOINT
Applicant	OPTOLANE Technologies, Inc.
Manufacturer	OPTOLANE Technologies, Inc.
Date of test(s)	2021.02.08 ~ 2021.03.05
Date of issue	2021.03.10

Issued to

OPTOLANE Technologies, Inc.

6F, 20, Pangyoyeok-ro 241 beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13494, S.Korea
Tel: +82-31-881-9647/ Fax: -

Issued by

KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, Kore
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Jun-Su Jeong Test engineer	Young-Jin Lee Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Revision history

Revision	Date of issue	Test report No.	Description
-	2021.03.10	KES-RF1-21T0023	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 5
1.3. Accessory information 5
1.4. Software and Firmware description 5
1.5. Device modifications 5
1.6. Frequency/channel operations 6
2. Summary of tests 7
3. DFS (Dynamic Frequency Selection) test description 8
3.1. Applicability 8
3.2. Requirements 9
3.3. DFS Detection Thresholds 10
3.4. Parameters of DFS Test Signals 11
4. Test results 12
4.1. DFS (Dynamic Frequency Selection) 12
4.1.1 Radar waveform 13
4.1.2 LAN Traffic 14
4.1.3 Channel move time & aggregate channel closing transmission time 15
4.1.4 Non-occupancy period 17
Appendix A. 18

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1. General information

Applicant:	OPTOLANE Technologies, Inc.
Applicant address:	6F, 20, Pangyoyeok-ro 241 beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13494, S.Korea
Test site:	KES Co., Ltd.
Test site address:	3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
Rule part(s):	15.407
FCC ID:	2AYU4LOAA-ONPOINT
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	LOAA Analyzer	
Frequency range		2 402 ㎒ ~ 2 480 ㎒ (BDR/EDR)
		2 412 ㎒ ~ 2 462 ㎒ (11b/g/n_HT20)
		2 422 ㎒ ~ 2 452 ㎒ (11n_HT40)
	UNII-1	5 180 ㎒ ~ 5 240 ㎒ (11a/n_HT20/ac_VHT20)
		5 190 ㎒ ~ 5 230 ㎒ (11n_HT40/ac_VHT40)
		5 210 ㎒ (11ac_VHT80)
	UNII-2A	5 260 ㎒ ~ 5 320 ㎒ (11a/n_HT20/ac_VHT20)
		5 270 ㎒ ~ 5 310 ㎒ (11n_HT40/ac_VHT40)
		5 290 ㎒ (11ac_VHT80)
	UNII-2C	5 500 ㎒ ~ 5 700 ㎒ (11a/n_HT20/ac_VHT20)
		5 510 ㎒ ~ 5 670 ㎒ (11n_HT40/ac_VHT40)
		5 530 ㎒ ~ 5 610 ㎒ (11ac_VHT80)
	UNII-3	5 745 ㎒ ~ 5 825 ㎒ (11a/n_HT20/ac_VHT20)
		5 755 ㎒ ~ 5 795 ㎒ (11n_HT40/ac_VHT40)
		5 775 ㎒ (11ac_VHT80)
Model:	On-Point	
Modulation technique	WIFI : DSSS, OFDM	
	BT : GFSK, π/4DQPSK, 8DPSK	
Antenna specification	2.4 ㎓_ WIFI&BT // Dipole Antenna & 3.18 ㏈i	
	5 ㎓_UNII 1 // Dipole Antenna & 3.52 ㏈i	
	5 ㎓_UNII 2A // Dipole Antenna & 4.35 ㏈i	
	5 ㎓_UNII 2C // Dipole Antenna & 4.25 ㏈i	
	5 ㎓_UNII 3 // Dipole Antenna & 3.14 ㏈i	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Power source	AC 220 V
Number of channels	2 402 ㎒ ~ 2 480 ㎒ (BDR/EDR) : 79ch 2 412 ㎒ ~ 2 462 ㎒ (11b/g/n_HT20) : 11ch 2 422 ㎒ ~ 2 452 ㎒ (11n_HT40) : 7ch 5 180 ㎒ ~ 5 240 ㎒ (11a/n_HT20/ac_VHT20) : 4ch 5 190 ㎒ ~ 5 230 ㎒ (11n_HT40/ac_VHT40) : 2ch 5 210 ㎒ (11ac_VHT80) : 1ch 5 260 ㎒ ~ 5 320 ㎒ (11a/n_HT20/ac_VHT20) : 4ch 5 270 ㎒ ~ 5 310 ㎒ (11n_HT40/ac_VHT40) : 2ch **5 290 ㎒ (11ac_VHT80) : 1ch** 5 500 ㎒ ~ 5 700 ㎒ (11a/n_HT20/ac_VHT20) : 11ch 5 510 ㎒ ~ 5 670 ㎒ (11n_HT40/ac_VHT40) : 5ch **5 530 ㎒ ~ 5 610 ㎒ (11ac_VHT80) : 2ch** 5 745 ㎒ ~ 5 825 ㎒ (11a/n_HT20/ac_VHT20) : 5ch 5 755 ㎒ ~ 5 795 ㎒ (11n_HT40/ac_VHT40) : 2ch 5 775 ㎒ (11ac_VHT80) : 1ch

1.2. Test configuration

The **OPTOLANE Technologies, Inc. LOAA Analyzer FCC ID: 2AYU4LOAA-ONPOINT** was tested per the guidance of KDB 905462 D02 v02, D03 v01r02.

1.3. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.4. Software and Firmware description

The software and firmware installed in the EUT is version 3.0.0

1.5. Device modifications

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.6. Frequency/channel operations

UNII-1

Ch.	Frequency (㎒)
36	5 180
44	5 220
48	5 240

UNII-2A

Ch.	Frequency (㎒)
52	5 260
56	5 280
64	5 320

UNII-2C

Ch.	Frequency (㎒)
100	5 500
120	5 600
140	5 700

UNII-3

Ch.	Frequency (㎒)
149	5 745
157	5 785
165	5 825

Table 1.7-1. 802.11ac_VHT20 mode

UNII-1

Ch.	Frequency (㎒)
38	5 190
46	5 230

UNII-2A

Ch.	Frequency (㎒)
54	5 270
62	5 310

UNII-2C

Ch.	Frequency (㎒)
102	5 510
118	5 590
134	5 670

UNII-3

Ch.	Frequency (㎒)
151	5 755
159	5 795

Table 1.7-2. 802.11ac_VHT40 mode

UNII-1

Ch.	Frequency (㎒)
42	5 210

UNII-2A

Ch.	Frequency (㎒)
58	5 290

UNII-2C

Ch.	Frequency (㎒)
106	5 530
122	5 610

UNII-3

Ch.	Frequency (㎒)
155	5 775

Table 1.7-3. 802.11ac_VHT80 mode

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2. Summary of tests

Reference	Parameter	Test results
15.407(h)(iii)(iv)	Channel Move Time	Pass
	Channel Closing Transmission Time	Pass
	Non-Occupancy Period	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3. DFS (Dynamic Frequency Selection) test description

3.1. Applicability

The following table from KDB 905462 D02 v02 lists the applicable requirements for the DFS testing.
The device evaluated in this report is considered a client device without radar detection capability.

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2.1. DFS Applicability

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required
Non-Occupancy Period	NA/Yes	Yes

Additional requirements for devices with multiple	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 2.2. DFS Applicability During normal operation

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.2. Requirements

KDB 905462 D02 v02 the following are the requirements for Client Devices:

a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements. The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.
e) The client test frequency must be monitored to ensure no transmission of any type has occurred for 30 minutes. Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy period test. For devices that shutdown (rather than moving channels), no beacons should appear

Parameter	**Value**
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an Aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note3.
Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. **Note 2:** The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (and aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. **Note 3:** During the U-NII Detection Bandwidth detection test, radar type 0 should the used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 2.3. DFS Response Requirement Values

3.3. DFS Detection Thresholds

The DFS detection thresholds are defined for Master devices and Client Devices with In-service monitoring. These detection Thresholds are listed in the following table.

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP< 200 milliwatt and Power spectral density < 10 dBm/㎒	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. **Note 2:** Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS respons. **Note 3:** EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01	

Table 2.4. DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.4. Parameters of DFS Test Signals

As the EUT is a Client Device with no Radar Detection only Zero type radar pulse is required for the testing.
Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (µsec)	PRI (µsec)	Number of Pulses	Minimum Percentage of Successful Detection	Mnimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup: {(1/360)*(19*10^6 PRI µsec)}	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 µsec, with a minimum increment of 1 µsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

Table 2.5. Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (µsec)	Chirp Width (MHz)	PRI (µsec)	Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 2.6. Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (µsec)	PRI (µsec)	Pulses Per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

Table 2.7. Frequency Hopping Radar Test Waveform

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

4. Test results

4.1. DFS (Dynamic Frequency Selection)

Test setup



Figure 1: Conducted Test Setup for DFS

Test procedure

KDB 905462 D02 v02 describes a radiated test setup and a conducted test setup. The conducted test setup was used for this testing. Figure 1 shows the typical test setup.

1. One frequency will be chosen from the Operating Channels of the UUT within the 5250 ~5350 ㎒ or 5470 ~5725 ㎒ bands.
2. The Client Device (EUT) is setup per the diagram in Firure1 and communications between the Master device and the Client is established.
3. An MPEG or data file that is typical for the device is streamed from the Master to the Client to properly load the network.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

4.1.1 Radar waveform

Mode: 802.11ac_VHT80 (Band2A)

Operating frequency: 5 290 ㎒



Mode: 802.11ac_VHT80 (Band2C)

Operating frequency: 5 530 ㎒



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

4.1.2 LAN Traffic

Mode: 802.11ac_VHT80 (Band2A)

Operating frequency: 5 290 ㎒



Mode: 802.11ac_VHT80 (Band2C)

Operating frequency: 5 530 ㎒



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

4.1.3 Channel move time & aggregate channel closing transmission time

Mode: 802.11ac_VHT80 (Band2A)

Operating frequency: 5 290 ㎒



Channel closing transmission time calculated	Test results
Sweep time[S] sec	10
Sampling bins[B]	32001
Number of sampling bins in 10 sec[N]	10
Closing transmission time [C] ms	0.312

Channel move time (s)	Limit
0.750	≤ 10 s

Note:
Dwell = S/B;
Where **dwell** is the dwell time per spectrum analyzer sampling bin, **S** is the sweep time and **B** is the number of spectrum analyzer sampling bins.

An upper bound of the aggregate duration of the channel closing transmission time is calculated by:
C = N × Dwell;
Where **C** is the closing time, **N** is the number of spectrum analyzer sampling bins showing a U-NII transmission and dwell is the dwell time per bin.

Dwell = [S] / [B] = 10 / 32001 = 0.000312
Closing Transmission Time[C] = [N] × [Dwell] = 10 × 0.000312 = 0.00312 s = 3.12 ms

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode: 802.11ac_VHT80 (Band2C)

Operating frequency: 5 530 ㎒



Channel closing transmission time calculated	Test results
Sweep time[S] sec	10
Sampling bins[B]	32001
Number of sampling bins in 10 sec[N]	10
Closing transmission time [C] ms	0.312

Channel move time (s)	Limit
1.127	≤ 10 s

Note:
Dwell = S/B;
Where **dwell** is the dwell time per spectrum analyzer sampling bin, **S** is the sweep time and **B** is the number of spectrum analyzer sampling bins.

An upper bound of the aggregate duration of the channel closing transmission time is calculated by:
C = N × Dwell;
Where **C** is the closing time, **N** is the number of spectrum analyzer sampling bins showing a U-NII transmission and dwell is the dwell time per bin.

Dwell = [S] / [B] = 10 / 32001 = 0.000312
Closing Transmission Time[C] = [N] × [Dwell] = 10 × 0.000312 = 0.00312 s = 3.12 ms

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

4.1.4 Non-occupancy period

Mode: 802.11ac_VHT80 (Band2A)

Operating frequency: 5 290 ㎒



Mode: 802.11ac_VHT80 (Band2C)

Operating frequency: 5 530 ㎒



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Appendix A.
Measurement equipment

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV40	101002	1 year	2021.07.02
Vector Signal Generator	R&S	SMBV100A	256397	1 year	2021.06.22
AC POWER SOURCE/ ANALYZER	HP	6813A	3729A00754	1 year	2022.01.15
Attenuator	HP	8495B	2814A14772	1 year	2022.01.15
Attenuator	WEINSCHEL	200099	8969	1 year	2022.01.15
Attenuator	WEINSCHEL	200099	9011	1 year	2022.01.14
Attenuator	KEYSIGHT	8493C 10dB	82506	1 year	2022.01.15
Attenuator	HP	8494B	MY42143296	1 year	2022.01.15
Attenuator	HP	8494B	2630A12857	1 year	2022.01.15
Splitter	MINI-CIRCUITS	ZFSC-2-10G+	F679501347-1	1 year	2021.06.23
Splitter	MINI-CIRCUITS	ZFSC-2-10G+	F679501347-2	1 year	2021.06.23

Peripheral devices

Device	Manufacturer	Model No.	Serial No.	Note.
Access Point (Master)	Cisco system Inc.	AIR-RM3000AC-A-K9	-	FCC ID: LDK102086
Notebook Computer	LG	LG15U47	701QCPY564416	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr