



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

TEST REPORT

Report No.: CQASZ20221101969E-01
Applicant: Shenzhen Deepsea Innovation Technology Co., Ltd.
Address of Applicant: Room 1901, Jinqizhigu Building, Tangling Road, Nanshan District, Shenzhen, CN
Equipment Under Test (EUT):
Product: Atom SE
Model No.: DSDR04B, DSDR04C, DSDR04D, DSDR02D
Test Model No.: DSDR04B
Brand Name: N/A
FCC ID: 2AYUO-DSDR04B
Standards: 47 CFR Part 15, Subpart C
ANSI C63.10: 2013
KDB 558074 D01 15.247 Meas Guidance v05r02
KDB 662911 D01 Multiple Transmitter Output v02r01
Date of Receipt: 2022-11-22
Date of Test: 2022-11-22 to 2022-12-06
Date of Issue: 2023-01-30
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20221101969E-01	Rev.01	Initial report	2023-01-30

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
4.4 TEST ENVIRONMENT AND MODE	7
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 TEST LOCATION	8
4.7 TEST FACILITY	8
4.8 STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
4.9 DEVIATION FROM STANDARDS	9
4.10 ABNORMALITIES FROM STANDARD CONDITIONS	9
4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
4.12 EQUIPMENTS LIST	10
5 TEST RESULTS AND MEASUREMENT DATA	11
5.1 ANTENNA REQUIREMENT	11
5.2 CONDUCTED EMISSIONS	12
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	18
5.4 6DB OCCUPY BANDWIDTH	22
<i>Test Graphs</i>	30
OCCUPIED CHANNEL BANDWIDTH	40
<i>Test Graphs</i>	40
5.5 POWER SPECTRAL DENSITY	45
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	59
5.7 RF CONDUCTED SPURIOUS EMISSIONS	67
5.8 RADIATED SPURIOUS EMISSIONS	96
5.8.1 Radiated emission below 1GHz	99
5.8.2 Transmitter emission above 1GHz	103
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	107
6 PHOTOGRAPHS - EUT TEST SETUP	115
6.1 RADIATED EMISSION	115
6.2 CONDUCTED EMISSION	116
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	117

4 General Information

4.1 Client Information

Applicant:	Shenzhen Deepsea Innovation Technology Co., Ltd.
Address of Applicant:	Room 1901, Jinqizhigu Building, Tangling Road, Nanshan District, Shenzhen, CN
Manufacturer:	Shenzhen Deepsea excellence technology Co.,Ltd
Address of Manufacturer:	5th Floor, Building 7, Hongfa High-tech Park, Keji 4th Road, Shiyan Street, Baoan District, Shenzhen
Factory:	Shenzhen Deepsea excellence technology Co.,Ltd
Address of Factory:	5th Floor, Building 7, Hongfa High-tech Park, Keji 4th Road, Shiyan Street, Baoan District, Shenzhen

4.2 General Description of EUT

Product Name:	Atom SE
Model No.:	DSDR04B, DSDR04C, DSDR04D, DSDR02D
Test Model No.:	DSDR04B
Trade Mark:	N/A
Software Version:	V1.2.7
Hardware Version:	V06
Power Supply:	Li-ion battery DC 7.2V 2500mAh, Charge by DC 5V for adapter
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz;

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☒ Mobile ☐ Portable
Test Software of EUT:	MobaXterm_Installer_v22.2
Antenna Type:	FPC antenna
Antenna Gain:	Ant 1: 2.5dBi; Ant2: 2.5dBi (provided by the applicant)

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):


Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.



4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.9 Deviation from Standards

None.

4.10 Abnormalities from Standard Conditions

None.

4.11 Other Information Requested by the Customer

None.

4.12 Equipments List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2022/09/09	2023/09/08
Spectrum analyzer	R&S	FSU26	CQA-038	2022/09/09	2023/09/08
Spectrum analyzer	R&S	FSU40	CQA-075	2022/09/09	2023/09/08
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2022/09/09	2023/09/08
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2022/09/09	2023/09/08
Preamplifier	EMCI	EMC184055SE	CQA-089	2022/09/09	2023/09/08
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/09/16	2024/09/15
Bilog Antenna	R&S	HL562	CQA-011	2021/09/16	2024/09/15
Horn Antenna	R&S	HF906	CQA-012	2021/09/16	2024/09/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/09/16	2024/09/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2022/09/09	2023/09/08
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2022/09/09	2023/09/08
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2022/09/09	2023/09/08
Antenna Connector	CQA	RFC-01	CQA-080	2022/09/09	2023/09/08
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2022/09/09	2023/09/08
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2022/09/09	2023/09/08
Power meter	R&S	NRVD	CQA-029	2022/09/09	2023/09/08
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2022/09/09	2023/09/08
EMI Test Receiver	R&S	ESR7	CQA-005	2022/09/09	2023/09/08
LISN	R&S	ENV216	CQA-003	2022/09/09	2023/09/08
Coaxial cable	CQA	N/A	CQA-C009	2022/09/09	2023/09/08
DC power	KEYSIGHT	E3631A	CQA-028	2022/09/09	2023/09/08

Test software:


	Manufacturer	Software brand
Radiated Emissions test software	Tonscend	JS1120-3
Conducted Emissions test software	Audix	e3
RF Conducted test software	Audix	e3

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is FPC antenna. Ant 1: 2.5 dBi; Ant2: 2.5 dBi (provided by the applicant)	

5.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and		

	highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Ant 1

Measurement Data

Live Line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.18	22.57	9.54	32.21	54.49	-22.28	Average	Line
2	0.18	27.97	9.54	37.61	64.49	-26.88	QP	Line
3	0.27	22.15	9.43	31.68	51.27	-19.59	Average	Line
4	0.27	27.14	9.43	36.67	61.27	-24.60	QP	Line
5	0.59	21.54	9.60	31.33	46.00	-14.67	Average	Line
6	0.59	27.84	9.60	37.63	56.00	-18.37	QP	Line
7	1.38	19.28	10.48	29.88	46.00	-16.12	Average	Line
8	1.38	24.47	10.48	35.07	56.00	-20.93	QP	Line
9	2.10	17.78	11.40	29.33	46.00	-16.67	Average	Line
10	2.10	23.65	11.40	35.20	56.00	-20.80	QP	Line
11	16.94	24.28	9.60	34.05	50.00	-15.95	Average	Line
12	16.94	39.39	9.60	49.16	60.00	-10.84	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT.
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:



	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.29	21.87	9.39	31.36	50.52	-19.16	Average	Neutral
2	0.29	27.00	9.39	36.49	60.52	-24.03	QP	Neutral
3	0.61	22.76	9.60	32.57	46.00	-13.43	Average	Neutral
4	0.61	28.36	9.60	38.17	56.00	-17.83	QP	Neutral
5	0.79	21.69	9.60	31.53	46.00	-14.47	Average	Neutral
6	0.79	27.68	9.60	37.52	56.00	-18.48	QP	Neutral
7	1.21	21.90	9.60	31.61	46.00	-14.39	Average	Neutral
8	1.21	27.18	9.60	36.89	56.00	-19.11	QP	Neutral
9	1.98	20.26	9.60	30.01	46.00	-15.99	Average	Neutral
10	1.98	25.46	9.60	35.21	56.00	-20.79	QP	Neutral
11	16.46	26.17	9.60	35.93	50.00	-14.07	Average	Neutral
12	16.46	46.17	9.60	55.93	60.00	-4.07	Peak	Neutral
13	16.46	36.31	9.60	46.07	60.00	-13.93	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT.
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Ant 2

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.285	20.88	9.49	30.37	50.67	-20.30	Average	Line
2	0.285	25.98	9.49	35.47	60.67	-25.20	QP	Line
3	0.435	19.52	9.51	29.03	47.16	-18.13	Average	Line
4	0.435	24.65	9.51	34.16	57.16	-23.00	QP	Line
5	0.635	19.40	9.77	29.17	46.00	-16.83	Average	Line
6	0.635	24.17	9.77	33.94	56.00	-22.06	QP	Line
7	0.785	19.38	9.77	29.15	46.00	-16.85	Average	Line
8	0.785	24.18	9.77	33.95	56.00	-22.05	QP	Line
9	1.235	19.68	9.52	29.20	46.00	-16.80	Average	Line
10	1.235	24.68	9.52	34.20	56.00	-21.80	QP	Line
11 PP	1.390	20.99	9.53	30.52	46.00	-15.48	Average	Line
12 QP	1.390	26.30	9.53	35.83	56.00	-20.17	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT.
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.180	21.73	9.64	31.37	54.49	-23.12	Average	Neutral
2	0.180	27.29	9.64	36.93	64.49	-27.56	QP	Neutral
3	0.315	20.46	9.50	29.96	49.84	-19.88	Average	Neutral
4	0.315	25.44	9.50	34.94	59.84	-24.90	QP	Neutral
5	0.450	19.50	9.65	29.15	46.88	-17.73	Average	Neutral
6	0.450	24.45	9.65	34.10	56.88	-22.78	QP	Neutral
7	0.555	19.02	9.76	28.78	46.00	-17.22	Average	Neutral
8 QP	0.555	24.45	9.76	34.21	56.00	-21.79	QP	Neutral
9	0.625	19.04	9.83	28.87	46.00	-17.13	Average	Neutral
10	0.625	24.15	9.83	33.98	56.00	-22.02	QP	Neutral
11 PP	0.715	19.22	9.89	29.11	46.00	-16.89	Average	Neutral
12	0.715	24.03	9.89	33.92	56.00	-22.08	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT.
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Measurement Data

Ant 1

802.11b mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	10.93	10.97	30.00	Pass
Middle	12.05	12.09	30.00	Pass
Highest	10.78	10.82	30.00	Pass
802.11g mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	8.75	8.98	30.00	Pass
Middle	9.77	10.00	30.00	Pass
Highest	7.99	8.22	30.00	Pass
802.11n(HT20)mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	7.06	7.28	30.00	Pass
Middle	8.29	8.51	30.00	Pass
Highest	7.66	7.88	30.00	Pass
Remark:				
1. Average Output Power was for reference only				
2. Average Output Power had added duty cycle factor				


Ant 2

802.11b mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	6.86	6.89	30.00	Pass
Middle	7.59	7.62	30.00	Pass
Highest	6.77	6.80	30.00	Pass
802.11g mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	4.63	4.84	30.00	Pass
Middle	5.48	5.69	30.00	Pass
Highest	4.65	4.86	30.00	Pass
802.11n(HT20)mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	3.98	4.18	30.00	Pass
Middle	4.73	4.93	30.00	Pass
Highest	3.84	4.04	30.00	Pass
Remark:				
1. Average Output Power was for reference only				
2. Average Output Power had added duty cycle factor				

Ant 1+Ant 2

802.11n(HT20)mode				
Test channel	Measured Average Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)	Result
Lowest	9.17	9.40	30.00	Pass
Middle	9.88	10.11	30.00	Pass
Highest	9.17	9.40	30.00	Pass
Remark: 1. Average Output Power was for reference only 2. Average Output Power had added duty cycle factor 3. The EUT supports MIMO and transmit signals are correlated with each other, then Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ dBi = 5.41 dBi < 6dBi				

5.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass

Measurement Data

Ant 1


802.11b mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	8.160	14.186	≥500	Pass
Middle	8.160	13.467	≥500	Pass
Highest	8.120	13.027	≥500	Pass
802.11g mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	16.440	16.663	≥500	Pass
Middle	13.840	16.424	≥500	Pass
Highest	14.520	16.344	≥500	Pass
802.11n(HT20) mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	16.960	17.742	≥500	Pass
Middle	13.600	17.383	≥500	Pass
Highest	13.640	17.343	≥500	Pass
Remark:				
1. 99% OBW was for reference only				

Ant 2


802.11b mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	10.160	13.866	≥500	Pass
Middle	9.200	13.227	≥500	Pass
Highest	9.360	12.827	≥500	Pass
802.11g mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	16.040	16.583	≥500	Pass
Middle	16.400	16.424	≥500	Pass
Highest	16.400	16.224	≥500	Pass
802.11n(HT20) mode				
Test channel	6dB Occupy Bandwidth (MHz)	99% OBW [MHz]	Limit (kHz)	Result
Lowest	14.760	17.702	≥500	Pass
Middle	16.120	17.383	≥500	Pass
Highest	17.680	17.383	≥500	Pass
Remark:				
1. 99% OBW was for reference only				

Test plot as follows:

Ant1




11B Ant1_2462




Date: 3 DEC.2022 01:59:32

11G Ant1_2412




Date: 3 DEC.2022 02:01:32

11G_Ant1_2437




Date: 3 DEC.2022 02:03:24

11G_Ant1_2462




Date: 3 DEC.2022 02:06:59

11N20SISO_Ant1_2412




Date: 3 DEC.2022 02:15:21


11N20SISO_Ant1_2437




Date: 3 DEC.2022 02:18:30



Occupied Channel Bandwidth Test Graphs




11B Ant1_2462




Date: 3 DEC.2022 01:59:43

11G Ant1_2412



Date: 3 DEC.2022 02:01:44

11G_Ant1_2437




Date: 3 DEC.2022 02:03:35

11G_Ant1_2462



Date: 3 DEC.2022 02:07:10

11N20SISO_Ant1_2412



Date: 3 DEC.2022 02:15:33


11N20SISO_Ant1_2437




Date: 3 DEC.2022 02:18:41



Ant2




11B_Ant2_2462




Date: 1.DEC.2022 02:36:59

11G_Ant2_2412




Date: 1.DEC.2022 03:01:24

11G_Ant2_2437




Date: 1.DEC.2022 03:04:43

11G_Ant2_2462




Date: 1.DEC.2022 03:07:32

11N20SISO_Ant2_2412




Date: 1.DEC.2022 03:10:44

11N20SISO_Ant2_2437




Date: 1.DEC.2022 03:14:16




Occupied Channel Bandwidth

Test Graphs




11B_Ant2_2462



Date: 1.DEC.2022 02:37:10

11G_Ant2_2412



Date: 1.DEC.2022 03:01:36

11G_Ant2_2437




Date: 1 DEC.2022 03:04:54

11G_Ant2_2462




Date: 1 DEC.2022 03:07:43

11N20SISO_Ant2_2412



Date: 1 DEC 2022 03:10:55


11N20SISO_Ant2_2437



Date: 1 DEC 2022 03:14:27



5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). Only the worst case is recorded in the report.
Limit:	$\leq 8.00\text{dBm}/3\text{kHz}$
Test Results:	Pass

Measurement Data

Ant1

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-17.1	≤8.00	Pass
Middle	-15.92	≤8.00	Pass
Highest	-13.69	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-23.28	≤8.00	Pass
Middle	-21.24	≤8.00	Pass
Highest	-22.57	≤8.00	Pass
802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-25.56	≤8.00	Pass
Middle	-23.69	≤8.00	Pass
Highest	-23.42	≤8.00	Pass

Ant2

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-21.19	≤8.00	Pass
Middle	-19.88	≤8.00	Pass
Highest	-21.07	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-26.97	≤8.00	Pass
Middle	-25.36	≤8.00	Pass
Highest	-26.51	≤8.00	Pass
802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-28.6	≤8.00	Pass
Middle	-27.13	≤8.00	Pass
Highest	-27.34	≤8.00	Pass


Ant1+Ant2

802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-23.81	≤8.00	Pass
Middle	-22.07	≤8.00	Pass
Highest	-21.94	≤8.00	Pass


Note: The EUT supports MIMO and transmit signals are correlated with each other, then

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ dBi = 5.41 dBi < 6dBi

Ant1



11B_Ant1_2462



11G_Ant1_2412

